



FCC TEST REPORT

REPORT NO.: RF990914D03

MODEL NO.: RMTP-S1H1, HWMP1

FCC ID: YSXRMTP-S1H1-01

RECEIVED: Sep. 14, 2010

TESTED: Sep. 15 ~ 20, 2010

ISSUED: Oct. 1, 2010

APPLICANT: SUYIN Optronics Corp

ADDRESS: No.377, Fude 1st RD., Xizhi City, Taipei County
221, Taiwan

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.)
Ltd., Taoyuan Branch

LAB LOCATION: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang,
Taipei Hsien, 244 Taiwan

This test report consists of 23 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by TAF or any government agencies. The test results in the report only apply to the tested sample.





Table of Contents

1. CERTIFICATION	3
2. SUMMARY OF TEST RESULTS	4
2.1 MEASUREMENT UNCERTAINTY	4
3. GENERAL INFORMATION	5
3.1 GENERAL DESCRIPTION OF EUT	5
3.2 DESCRIPTION OF TEST MODES	6
3.2.1 CONFIGURATION OF SYSTEM UNDER TEST	6
3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	7
3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS	8
3.4 DESCRIPTION OF SUPPORT UNITS	8
4. TEST TYPES AND RESULTS	9
4.1 CONDUCTED EMISSION MEASUREMENT	9
4.2 RADIATED EMISSION MEASUREMENT	9
4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	9
4.2.2 TEST INSTRUMENTS	10
4.2.3 TEST PROCEDURES	11
4.2.4 DEVIATION FROM TEST STANDARD	11
4.2.5 TEST SETUP	12
4.2.6 EUT OPERATING CONDITIONS	12
4.2.7 TEST RESULTS	13
4.3 BAND EDGES MEASUREMENT	18
4.3.1 LIMITS OF BAND EDGES MEASUREMENT	18
4.3.2 TEST INSTRUMENTS	18
4.3.3 TEST PROCEDURE	18
4.3.4 DEVIATION FROM TEST STANDARD	18
4.3.5 EUT OPERATING CONDITION	18
4.3.6 TEST RESULTS	18
5. PHOTOGRAPHS OF THE TEST CONFIGURATION	21
6. INFORMATION ON THE TESTING LABORATORIES	22
7. APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	23



A D T

1. CERTIFICATION

PRODUCT: RMTP
MODEL NO.: RMTP-S1H1 (**BRAND NAME:** SUYIN)
HWMP1 (**BRAND NAME:** HAWKING)
APPLICANT: SUYIN Optronics Corp
TESTED: Sep. 15 ~ 20, 2010
TEST ITEM: ENGINEERING SAMPLE
STANDARDS: FCC Part 15, Subpart C (Section 15.249)
ANSI C63.4-2003

The above equipment (Model: RMTP-S1H1) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Annie Chang , **DATE:** Oct. 1, 2010
(Annie Chang / Senior Specialist)

**TECHNICAL
ACCEPTANCE :** Jamison Chan , **DATE:** Oct. 1, 2010
Responsible for RF
(Jamison Chan / Supervisor)

APPROVED BY : Ken Liu , **DATE:** Oct. 1, 2010
(Ken Liu / Manager)



A D T

2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C (Section 15.249)			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.207	Conducted Emission Test	N/A	Power supply is 4.2Vdc from battery
15.209 15.249 15.249 (d)	Radiated Emission Test Band Edge Measurement Limit: 50dB less than the peak value of fundamental frequency or meet radiated emission limit in section 12.209	PASS	Minimum passing margin is -9.5dB at 2390.00MHz

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Frequency	Uncertainty
Radiated emissions	30MHz ~ 1GHz	3.67 dB
	Above 1GHz	2.89 dB



3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

EUT	RMTP
MODEL NO.	RMTP-S1H1, HWMP1
FCC ID	YSXRMTP-S1H1-01
POWER SUPPLY	4.2Vdc from battery
MODULATION TYPE	GFSK
OPERATING FREQUENCY	2402.5MHz ~ 2475MHz
NUMBER OF CHANNEL	30
ANTENNA TYPE	Printed antenna with -7.77dBi gain
ANTENNA CONNECTOR	N/A
DATA CABLE	N/A
I/O PORTS	N/A
ASSOCIATED DEVICES	N/A

NOTE:

1. The EUT is a transceiver.
2. The EUT has several models, which are identical to each other except for their brand name differences only, as the following:

Brand Name	Model No.	Differentiation
SUYIN	RMTP-S1H1	
HAWKING	HWMP1	Marketing differentiation

During the test, model: **RMTP-S1H1** was selected as the representative one and therefore only its test data was recorded in this report.

3. The above EUT information was declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.



3.2 DESCRIPTION OF TEST MODES

30 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
1	2402.5	9	2422.5	17	2442.5	25	2462.5
2	2405.0	10	2425.0	18	2445.0	26	2465.0
3	2407.5	11	2427.5	19	2447.5	27	2467.5
4	2410.0	12	2430.0	20	2450.0	28	2470.0
5	2412.5	13	2432.5	21	2452.5	29	2472.5
6	2415.0	14	2435.0	22	2455.0	30	2475.0
7	2417.5	15	2437.5	23	2457.5		
8	2420.0	16	2440.0	24	2460.0		

3.2.1 CONFIGURATION OF SYSTEM UNDER TEST

EUT

(Powered from battery)

Test Table



A D T

3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT configure mode	Applicable to				Description
	PLC	RE<1G	RE \geq 1G	BM	
-	Note	✓	✓	✓	-

Where PLC: Power Line Conducted Emission

RE<1G RE: Radiated Emission below 1GHz

RE \geq 1G: Radiated Emission above 1GHz

BM: Bandedge Measurement

Note: No need to concern of Conducted Emission due to the EUT is powered by battery.

RADIATED EMISSION TEST (BELOW 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
1 to 30	1	GFSK

RADIATED EMISSION TEST (ABOVE 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
1 to 30	1, 16, 30	GFSK

BANDEDGE MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
1 to 30	1, 30	GFSK

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE<1G	28deg. C, 67% RH, 1011hPa	4.2Vdc	Chad Lee
RE \geq 1G	28deg. C, 67% RH, 1008hPa	4.2Vdc	Chad Lee
BM	26deg. C, 72% RH, 1008hPa	4.2Vdc	Nick Chen



A D T

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (Section 15.249)

ANSI C63.4-2003

All test items have been performed and recorded as per the above standards.

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together without any necessary accessory or support unit.



4. TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

N/A

4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209, 15.249 as following:

15.209 Limit		
Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

15.249 Limit		
Fundamental Frequency	Field Strength of Fundamental (millivolts/meter)	Field Strength of Harmonics (microvolts/meter)
902 ~ 928 MHz	50	500
2400 ~ 2483.5 MHz	50	500
5725 ~ 5875 MHz	50	500
24 ~ 24.25 GHz	250	2500

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB_{UV}/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



A D T

4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
HP Preamplifier	8447D	2432A03504	May 06, 2010	May 05, 2011
HP Preamplifier	8449B	3008A01924	Jul. 14, 2010	Jul. 13, 2011
HP Preamplifier	8449B	3008A01292	Jul. 14, 2010	Jul. 13, 2011
ROHDE & SCHWARZ TEST RECEIVER	ESU26	100005	Jun. 10, 2010	Jun. 09, 2011
Schwarzbeck Antenna	VULB 9168	137	Apr. 29, 2010	Apr. 28, 2011
Schwarzbeck Antenna	VHBA 9123	480	Apr. 29, 2010	Apr. 28, 2011
ADT. Turn Table	TT100	0306	NA	NA
ADT. Tower	AT100	0306	NA	NA
Software	ADT_Radiated_V 7.6.15.9.2	NA	NA	NA
SUHNER RF cable	SF104-26.5	CABLE-CH6-17m -01	Aug. 20, 2010	Aug. 19, 2011
ROHDE & SCHWARZ Spectrum Analyzer	FSP 40	100036	Apr. 06, 2010	Apr. 05, 2011
EMCO Horn Antenna	3115	6714	Oct. 26, 2009	Oct. 25, 2010
EMCO Horn Antenna	3115	9312-4192	Apr. 23, 2010	Apr. 22, 2011

NOTE:

1. The calibration interval of the above test instruments is 12/24 months. And the calibrations are traceable to NML/ROC and NIST/USA.
2. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
3. The test was performed in Chamber No. 6.
4. The Industry Canada Reference No. IC 7450E-6.
5. The FCC Site Registration No. is 447212.



A D T

4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak method or average method as specified and then reported in data sheet.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS

Set the EUT under transmission condition continuously at specific channel frequency.



A D T

4.2.7 TEST RESULTS

ABOVE 1GHz DATA

EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL		Channel 1		FREQUENCY RANGE 1 ~ 25GHz
INPUT POWER		4.2Vdc		DETECTOR FUNCTION Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS		28deg. C, 67%RH 1008 hPa		TESTED BY Chad Lee

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	59.1 PK	74.0	-14.9	1.16 H	148	27.16	31.89
2	2390.00	44.5 AV	54.0	-9.5	1.16 H	148	12.59	31.89
3	2400.00	45.0 PK	74.0	-29.0	1.16 H	148	13.06	31.93
4	2400.00	19.0 AV	54.0	-35.0	1.16 H	148	-12.94	31.93
5	*2402.50	94.5 PK	114.0	-19.5	1.16 H	148	62.57	31.94
6	*2402.50	68.5 AV	94.0	-25.5	1.16 H	148	36.57	31.94
7	4805.00	58.6 PK	74.0	-15.4	1.09 H	318	19.51	39.07
8	4805.00	32.6 AV	54.0	-21.4	1.09 H	318	-6.49	39.07

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	58.4 PK	74.0	-15.6	1.29 V	198	26.52	31.89
2	2390.00	44.0 AV	54.0	-10.0	1.29 V	198	12.12	31.89
3	2400.00	36.9 PK	74.0	-37.1	1.29 V	198	4.93	31.93
4	2400.00	10.9 AV	54.0	-43.1	1.29 V	198	-21.07	31.93
5	*2402.50	86.4 PK	114.0	-27.6	1.29 V	198	54.44	31.94
6	*2402.50	60.4 AV	94.0	-33.6	1.29 V	198	28.44	31.94
7	4805.00	60.4 PK	74.0	-13.6	1.00 V	100	21.29	39.07
8	4805.00	34.4 AV	54.0	-19.6	1.00 V	100	-4.71	39.07

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “*”: Fundamental frequency
6. The average value of fundamental frequency is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula:

$$20 \log (\text{Duty cycle}) = 20 \log (0.4 \text{ ms} / 7.996 \text{ ms}) = -26.0 \text{ dB}$$
Please see page 16 for plotted duty.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL		FREQUENCY RANGE		1 ~ 25GHz
INPUT POWER		DETECTOR FUNCTION		Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS		TESTED BY		Chad Lee

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2440.00	91.6 PK	114.0	-22.4	1.18 H	207	59.54	32.07
2	*2440.00	65.6 AV	94.0	-28.4	1.18 H	207	33.54	32.07
3	4880.00	57.5 PK	74.0	-16.5	1.00 H	10	18.09	39.41
4	4880.00	31.5 AV	54.0	-22.5	1.00 H	10	-7.91	39.41
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2440.00	88.3 PK	114.0	-25.7	1.01 V	273	56.21	32.07
2	*2440.00	62.3 AV	94.0	-31.7	1.01 V	273	30.21	32.07
3	4880.00	59.7 PK	74.0	-14.3	1.15 V	101	20.29	39.41
4	4880.00	33.7 AV	54.0	-20.3	1.15 V	101	-5.71	39.41

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “*”: Fundamental frequency
 6. The average value of fundamental frequency is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula:
 $20 \log (\text{Duty cycle}) = 20 \log (0.4 \text{ ms} / 7.996 \text{ ms}) = -26.0 \text{ dB}$
 Please see page 16 for plotted duty.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 30	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	4.2Vdc	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	28deg. C, 67%RH 1008 hPa	TESTED BY	Chad Lee

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2475.00	90.8 PK	114.0	-23.2	1.00 H	110	58.65	32.19
2	*2475.00	64.8 AV	94.0	-29.2	1.00 H	110	32.65	32.19
3	2483.50	40.7 PK	74.0	-33.3	1.00 H	110	8.52	32.21
4	2483.50	14.7 AV	54.0	-39.3	1.00 H	110	-17.48	32.21
5	4950.00	52.8 PK	74.0	-21.2	1.00 H	344	13.16	39.63
6	4950.00	26.8 AV	54.0	-27.2	1.00 H	344	-12.84	39.63

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2475.00	83.0 PK	114.0	-31.0	1.26 V	204	50.79	32.19
2	*2475.00	57.0 AV	94.0	-37.0	1.26 V	204	24.78	32.19
3	2483.50	32.9 PK	74.0	-41.1	1.26 V	204	0.65	32.21
4	2483.50	6.9 AV	54.0	-47.1	1.26 V	204	-25.35	32.21
5	4950.00	55.9 PK	74.0	-18.1	1.00 V	103	16.30	39.63
6	4950.00	29.9 AV	54.0	-24.1	1.00 V	103	-9.70	39.63


REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “*”: Fundamental frequency
6. The average value of fundamental frequency is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula:

$$20 \log (\text{Duty cycle}) = 20 \log (0.4 \text{ ms} / 7.996 \text{ ms}) = -26.0 \text{ dB}$$
Please see page 16 for plotted duty.



A D T





A D T

BELOW 1GHz WORST-CASE DATA

EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL		Channel 1		FREQUENCY RANGE Below 1000MHz
INPUT POWER		4.2Vdc		DETECTOR FUNCTION Quasi-Peak
ENVIRONMENTAL CONDITIONS		28deg. C, 67%RH 1011 hPa		TESTED BY Chad Lee

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	752.84	25.0 QP	46.0	-21.0	1.51 H	295	-0.54	25.57
2	810.35	25.3 QP	46.0	-20.7	1.23 H	358	-1.12	26.42
3	844.55	26.0 QP	46.0	-20.0	2.02 H	208	-1.03	27.05
4	852.32	26.2 QP	46.0	-19.8	1.55 H	340	-0.98	27.18
5	894.29	27.9 QP	46.0	-18.2	1.98 H	91	0.03	27.82
6	956.47	28.0 QP	46.0	-18.0	1.52 H	127	-0.63	28.65
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	774.60	25.2 QP	46.0	-20.8	2.02 V	301	-0.70	25.87
2	791.70	25.4 QP	46.0	-20.6	1.41 V	223	-0.68	26.11
3	844.55	26.5 QP	46.0	-19.5	1.50 V	76	-0.52	27.05
4	860.10	27.3 QP	46.0	-18.7	1.59 V	10	-0.03	27.30
5	895.85	27.3 QP	46.0	-18.7	1.63 V	157	-0.55	27.85
6	917.61	27.6 QP	46.0	-18.4	1.24 V	76	-0.57	28.15

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



4.3 BAND EDGES MEASUREMENT

4.3.1 LIMITS OF BAND EDGES MEASUREMENT

Below -50dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.3.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSP 40	100036	Apr. 06, 2010	Apr. 05, 2011

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. Set both RBW and VBW of spectrum analyzer to 100 kHz and 300 kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

The spectrum plots are attached on the following pages.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation

4.3.5 EUT OPERATING CONDITION



Same as Item 4.2.6

4.3.6 TEST RESULTS

The spectrum plots are attached on the following 4 images. D1 line indicates the highest level, and D2 line indicates the 50dB offset below D1. It shows compliance with the requirement in part 15.249(d).





A D T





A D T





A D T

5. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



A D T

6. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site: www.adt.com.tw/index.5/phtml. If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:

Tel: 886-2-26052180
Fax: 886-2-26051924

Hsin Chu EMC/RF Lab:

Tel: 886-3-5935343
Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety Telecom Lab:

Tel: 886-3-3183232
Fax: 886-3-3185050

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.



A D T

7. APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---