

FCC 47 CFR PART 15 SUBPART C TEST REPORT

For

Applicant: Technical Pro

Address: 140 58th. Suite 5G BOX 85 Brooklyn, NY 11220

Product Name: BLUETOOTH AUDIO RECEIVER

Model Name: BLUEMINI

Brand Name: technical pro

FCC ID: YT6BLUEMINI

Report No.: MTE/DAL/D12070897

Date of Issue: Jul. 10, 2012

Issued by: Most Technology Service Co., Ltd.

Address: No.5, 2nd Langshan Road, North District, Hi-tech Industrial Park,

Nanshan, Shenzhen, Guangdong, China

Tel: 86-755-8617 0306

Fax: 86-755-8617 0310

The report consists 31 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by MOST. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver.

TABLE OF CONTENTS

1. VERIFICATION OF CONFORMITY	3
2. GENERAL INFORMATION	4
2.1 Product Information	4
2.2 OBJECTIVE	5
2.2 TEST STANDARDS AND RESULTS	5
2.3 ENVIRONMENTAL CONDITIONS	5
2.5 MEASUREMENT UNCERTAINTY	5
3. TEST METHODOLOGY	6
3.1TEST FACILITY	6
3.2 Test Conditions	6
3.3 Channel List	7
3.4 Description of Test Modes	7
3.5 Table of Parameters of Text Software Setting	8
3.6 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS	9
4. SETUP OF EQUIPMENT UNDER TEST	10
4.1 SUPPORT EQUIPMENT	10
4.2 TEST EQUIPMENT LIST	11
5. 47 CFR Part 15C 15.249 Requirements	12
5.1 SPURIOUS EMISSION TEST	12
5.1.1 REQUIREMENT	12
5.1.2 TEST DESCRIPTION	13
5.1.3 TEST DESCRIPTION	14
5.1.4 TEST RESULT	14
5.2 BAND EDGE	21
5.2.1 REQUIREMENT	21
5.2.2 TEST DESCRIPTION	21
5.2.3TEST RESULT	21
5.3 LINE CONDUCTED EMISSION TEST	24
5.3.1. LIMITS OF LINE CONDUCTED EMISSION TEST	24
5.3.2. BLOCK DIAGRAM OF TEST SETUP	24
5.3.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	25
5.3.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST	25
5.3.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST	
5.4 20 dB Bandwidth	28
5.4.1 Definition	
5.4.2 Block Diagram Of Test Setup	
5.4.3 Test Result	28
APPENDIX 1	30
PHOTOGRAPHS OF TEST SETUP	30

1. VERIFICATION OF CONFORMITY

Equipment Under Test: BLUETOOTH AUDIO RECEIVER

Brand Name: technical pro

Model Number: BLUEMINI

Series Model Number: N/A

Difference description: N/A

FCC ID: YT6BLUEMINI
Applicant: Technical Pro

140 58th. Suite 5G BOX 85 Brooklyn, NY 11220

Manufacturer: Guangzhou Zhengsheng Electronic Co., Ltd.

No.369, Junhe Erheng Road, Junhe Street, Baiyun District, Guangzhou,

China

Technical Standards: 47 CFR Part 15 Subpart C

File Number: MTE/DAL/D12070897

Approved by (+ signature):

Date of test: Jul. 06, 2012

Deviation:NoneCondition of Test Sample:NormalTest Result:PASS

The above equipment was tested by MOST for compliance with the requirements set forth in FCC rules and the Technical Standards mentioned above. This said equipment in the configuration described in this report shows the maximum emission levels emanating from equipment and the level of the immunity endurance of the equipment are within the compliance requirements.

The test results of this report relate only to the tested sample identified in this report.

Prepared by (+ signature):

Dona Liu

Jul. 09, 2012

Review by (+ signature):

Elva Wong

Jul. 10, 2012

APPROVED

APPROVED

Yvette Zhou(Manager) Jul. 10, 2012

2. GENERAL INFORMATION

2.1 Product Information

Z.1 1 Toduct Illioillation	
Product	BLUETOOTH AUDIO RECEIVER
Trade Name	technical pro
Model Number	BLUEMINI
Series Number:	N/A
Description Differences:	N/A
Power Supply	DC 5V by USB Port
Frequency Range	2402MHz -2480MHz
Modulation Type:	GFSK, Pi/4-DQPSK, 8-DPSK
Modulation Technique:	FHSS
Antenna Type:	Internal Fixed
Antenna Gain:	4.0 dBi
Channel Spacing:	1MHz
Channel Number	40
Temperature Range	-10°C ~ 80°C

NOTE:

1. For a more detailed features description about the EUT, please refer to User's Manual.

FCC ID: YT6BLUEMINI Report No.:MTE/DAL/D12070897

2.2 OBJECTIVE

Perform FCC Part 15 Subpart C tests for FCC Marking.

2.2 TEST STANDARDS AND RESULTS

Test items and the results are as bellow:

No.	Section	Description	Result	Date of Test
1	15.249(a)	Spurious Emission	PASS	May 02, 2012
2	15.249(a)	Band Edge	PASS	May 02, 2012
3	15.207	Power Line Conducted Emission Test	PASS	May 02, 2012
4	15.249(a)	20dB Bandwidth	PASS	May 02, 2012

Note: 1. The test result judgment is decided by the limit of measurement standard

2. The information of measurement uncertainty is available upon the customer's request.

2.3 ENVIRONMENTAL CONDITIONS

During the measurement the environmental conditions were within the listed ranges:

Temperature: 15-35°CHumidity: 30-60 %

- Atmospheric pressure: 86-106 kPa

2.5 MEASUREMENT UNCERTAINTY

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

The report uncertainty of measurement y±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2,Providing a level of confidence of approximately 95%

- Uncertainty of Conducted Emission, Uc = ±1.8dB
- Uncertainty of Radiated Emission, Uc = ±3.2dB

FCC ID: YT6BLUEMINI Report No.:MTE/DAL/D12070897

3. TEST METHODOLOGY

3.1TEST FACILITY

Test Site: Most Technology Service Co.,ltd

Location: No.5, Langshan 2nd Rd., North Hi-Tech Industrial park, Nanshan, Shenzhen,

Guangdong, China

Description: There is one 3m semi-anechoic an area test sites and two line conducted labs for final

test. The Open Area Test Sites and the Line Conducted labs are constructed and calibrated to meet the FCC requirements in documents ANSI C63.4:2009 and CISPR

16 requirements.

The FCC Registration Number is 490827.

The IC Registration Number is 46405-7103.

The CNAS Registration Number is CNAS L3573.

Site Filing: The site description is on file with the Federal Communications

Commission, 7435 Oakland Mills Road, Columbia, MD 21046.

Instrument Tolerance: All measuring equipment is in accord with ANSI C63.4:2009 and CISPR 16

requirements that meet industry regulatory agency and accreditation agency

requirement.

Ground Plane: Two conductive reference ground planes were used during the Line Conducted

Emission, one in vertical and the other in horizontal. The dimensions of these ground planes are as below. The vertical ground plane was placed distancing 40 cm to the rear of the wooden test table on where the EUT and the support equipment were placed during test. The horizontal ground plane projected 50 cm beyond the footprint of the EUT system and distanced 80 cm to the wooden test table. For Radiated Emission Test, one horizontal conductive ground plane extended at least 1m beyond the periphery of the EUT and the largest measuring antenna, and covered the entire

area between the EUT and the antenna.

3.2 Test Conditions

The EUT has been tested under normal operating (TX) and standby (RX) condition.

The field strength of radiation emission was measured in the following position: EUT stand-up position (Y axis), lie-down position (X, Z axis).

The following data show only with the worst case setup.

The worst case of Y axis was reported.

Based on client request, all normal using modes of the normal function were tested but only the worst test data of the worst mode is reported by this report.

3.3 Channel List

	Cha	nnel List for GFS	SK, Pi/4-DQPSK, 8-D	PSK Mode	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2402MHz	28	2429MHz	55	2456MHz
02	2403MHz	29	2430MHz	56	2457MHz
03	2404MHz	30	2431MHz	57	2458MHz
04	2405MHz	31	2432MHz	58	2459MHz
05	2406MHz	32	2433MHz	59	2460MHz
06	2407MHz	33	2434MHz	60	2461MHz
07	2408MHz	34	2435MHz	61	2462MHz
08	2409MHz	35	2436MHz	62	2463MHz
09	2410MHz	36	2437MHz	63	2464MHz
10	2411MHz	37	2438MHz	64	2465MHz
11	2412MHz	38	2439MHz	65	2466MHz
12	2413MHz	39	2440MHz	66	2467MHz
13	2414MHz	40	2441MHz	67	2468MHz
14	2415MHz	41	2442MHz	68	2469MHz
15	2416MHz	42	2443MHz	69	2470MHz
16	2417MHz	43	2444MHz	70	2471MHz
17	2418MHz	44	2445MHz	71	2472MHz
18	2419MHz	45	2446MHz	72	2473MHz
19	2420MHz	46	2447MHz	73	2474MHz
20	2421MHz	47	2448MHz	74	2475MHz
21	2422MHz	48	2449MHz	75	2476MHz
22	2423MHz	49	2450MHz	76	2477MHz
23	2424MHz	50	2451MHz	77	2478MHz
24	2425MHz	51	2452MHz	78	2479MHz
25	2426MHz	52	2453MHz	79	2480MHz
26	2427MHz	53	2454MHz		
27	2428MHz	54	2455MHz		

3.4 Description of Test Modes

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level, Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively

Pre-test Mode	Description
Mode 1	GFSK CH01/CH41/CH79
Mode 2 Pi/4-DQPSK CH01/CH41/CH79	
Mode 3	8-DPSK CH01/CH41/CH79

Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The measurements are performed at all bit rate of transmitter, the worst data was reported.

3.5 Table of Parameters of Text Software Setting

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level, the RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of Bluetooth.

Test software Version	Test program:N/A		
GFSK Mode	2402MHz	2442MHz	2480MHz
Pi/4-DQPSK	2402MHz	2442MHz	2480MHz
8-DPSK	2402MHz	2442MHz	2480MHz

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4:2009, Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.4:2009.

3.6 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110 10.495 - 0.505 2.1735 - 2.1905 4.125 - 4.128 4.17725 - 4.17775 4.20725 - 4.20775 6.215 - 6.218 6.26775 - 6.26825 6.31175 - 6.31225 8.291 - 8.294 8.362 - 8.366 8.37625 - 8.38675 8.41425 - 8.41475 12.29 - 12.293 12.51975 - 12.52025 12.57675 - 12.57725	16.42 - 16.423 16.69475 - 16.69525 16.80425 - 16.80475 25.5 - 25.67 37.5 - 38.25 73 - 74.6 74.8 - 75.2 108 - 121.94 123 - 138 149.9 - 150.05 156.52475 - 156.52525 156.7 - 156.9 162.0125 - 167.17 167.72 - 173.2 240 - 285 322 - 335.4	399.9 - 410 608 - 614 960 - 1240 1300 - 1427 1435 - 1626.5 1645.5 - 1646.5 1660 - 1710 1718.8 - 1722.2 2200 - 2300 2310 - 2390 2483.5 - 2500 2655 - 2900 3260 - 3267 3332 - 3339 3345.8 - 3358 3600 - 4400	4.5 - 5.15 5.35 - 5.46 7.25 - 7.75 8.025 - 8.5 9.0 - 9.2 9.3 - 9.5 10.6 - 12.7 13.25 - 13.4 14.47 - 14.5 15.35 - 16.2 17.7 - 21.4 22.01 - 23.12 23.6 - 24.0 31.2 - 31.8 36.43 - 36.5
13.36 - 13.41			()

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

(b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

² Above 38.6

4. SETUP OF EQUIPMENT UNDER TEST

4.1 SUPPORT EQUIPMENT

Device Type	Manufacturer	Model	Series No.	Data Cable	Power Cord

Remark:

All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4.2 TEST EQUIPMENT LIST

Instrumentation: The following list contains equipment used at Most for testing. The equipment conforms to the CISPR 16-1 / ANSI C63.2 Specifications for Electromagnetic Interference and Field Strength Instrumentation from 10 kHz to 1.0 GHz or above.

No.	Equipment	Manufacturer	Model No.	S/N	Calculator date	Calculator Interval
1	Test Receiver	Rohde & Schwarz	ESCI	100492	2012/03/14	1 Year
2	L.I.S.N.	Rohde & Schwarz	ENV216	100093	2012/03/14	1 Year
3	Coaxial Switch	Anritsu Corp	MP59B	6200283933	2012/03/14	1 Year
4	Terminator	Hubersuhner	50Ω	No.1	2012/03/14	1 Year
5	RF Cable	SchwarzBeck	N/A	No.1	2012/03/14	1 Year
6	Test Receiver	Rohde & Schwarz	ESPI	101202	2012/03/14	1 Year
7	Bilog Antenna	SCHWARZBECK	BBHA9120D	D69250	2012/03/14	1 Year
8	Cable	Resenberger	N/A	NO.1	2012/03/14	1 Year
9	Cable	SchwarzBeck	N/A	NO.2	2012/03/14	1 Year
10	Cable	SchwarzBeck	N/A	NO.3	2012/03/14	1 Year
11	DC Power Filter	DuoJi	DL2×30B	N/A	2012/03/14	1 Year
12	Single Phase Power Line Filter	DuoJi	FNF 202B30	N/A	2012/03/14	1 Year
13	3 Phase Power Line Filter	DuoJi	FNF 402B30	N/A	2012/03/14	1 Year
14	Test Receiver	Rohde & Schwarz	ESCI	100492	2012/03/14	1 Year
15	Absorbing Clamp	Luthi	MDS21	3635	2012/03/14	1 Year
16	Coaxial Switch	Anritsu Corp	MP59B	6200283933	2012/03/14	1 Year
17	AC Power Source	Kikusui	AC40MA	LM003232	2012/03/14	1 Year
18	Test Analyzer	Kikusui	KHA1000	LM003720	2012/03/14	1 Year
19	Line Impendence Network	Kikusui	LIN40MA- PCR-L	LM002352	2012/03/14	1 Year
20	ESD Tester	Kikusui	KES4021	LM003537	2012/03/14	1 Year
21	EMCPRO System	EM Test	UCS-500-M4	V0648102026	2012/03/14	1 Year
22	Signal Generator	IFR	2032	203002/100	2012/03/14	1 Year
23	Amplifier	A&R	150W1000	301584	2012/03/14	1 Year
24	CDN	FCC	FCC-801-M2-25	47	2012/03/14	1 Year
25	CDN	FCC	FCC-801-M3-25	107	2012/03/14	1 Year
26	EM Injection Clamp	FCC	F-203I-23mm	403	2012/03/14	1 Year
27	RF Cable	MIYAZAKI	N/A	No.1/No.2	2012/03/14	1 Year
28	Universal Radio Communication Tester	ROHDE&SCHWARZ	CMU200	0304789	2012/03/14	1 Year
29	Telecommunication Antenna	European Antennas	PSA 75301R/170	0304213	2012/03/14	1 Year
30	Telecommunication Test Equipment	R&S	CMU200	N/A	2012/03/14	1 Year
31	8 Loop Antenna	ARA	PLA-1030/B	1029	2012/02/19	1 Year

NOTE: Equipments listed above have been calibrated and are in the period of validation.

5. 47 CFR Part 15C 15.249 Requirements 5.1 SPURIOUS EMISSION TEST 5.1.1 REQUIREMENT

According to FCC section 15.249(a):

FCC ID: YT6BLUEMINI

Except as provided in paragraph (a) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency (MHz)	Field Strength of Fundamental (mV/m)	Field Strength of Harmonics (μV/m)
902-928	50	500
2400-2483.5	50	500
5725-5875	50	500
24000-24250	250	2500

According to FCC section 15.109 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Remark: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.


In the above emission table, the tighter limit applies at the band edges.

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3


5.1.2 TEST DESCRIPTION

Test Setup:


From 9KHz to 30MHz:



Below 1GHz:



Above 1GHz:



5.1.3 TEST DESCRIPTION

- 1. The EUT is placed on a turntable, which is 0.8m above ground plane.
- 2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
- 3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- 4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 6. Set the spectrum analyzer in the following setting as:

Below 1GHz: RBW=100 kHz / VBW=300 kHz / Sweep=AUTO

Above 1GHz:(a) PEAK: RBW=VBW=1MHz / Sweep=AUTO

(b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO

7. Repeat above procedures until the measurements for all frequencies are complete.

5.1.4 TEST RESULT

The Bluetooth model was carried out for GFSK, Pi/4-DQPSK and 8-DPSK modulation types, GFSK Low channel modulation type was the worst case condition, The test data was shown on the summary data page.

From 9 KHz to 30MHz:

Freq. (MHz)	Ant. Pol H/V	Peak Reading	AV Reading	Ant. / CL CF	Actu	Actual Fs		AV Limit	AV Margin
		(dBuV)	(dBuV)	(dB)	Peak	AV	(dBuV/m)	(dBuV/m)	(dB)
					(dBuV/m)	(dBuV/m)			
N/A	Н								>20
N/A	V								>20

-Note: No test data was detected in below 30MHz.


Below 1GHz



Address:No.5,Langshan 2nd Rd., North Hi-Tech Industrial park Guangdong, China

Tel: 0755-86170306 Fax: 0755-86170310

Radiated Emission Measurement



Site site MOST 3M Limit: FCC Part15 B 3M Radiation

Power: DC 5V Adapter AC 120V/60Hz

Polarization: Horizontal

Temperature: 26

EUT: BLUETOOTH AUDIO RECEIVER

Distance:

Humidity: 61 %

M/N: BLUEMINI

Mode: Running

Note:

No.	Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBu∨	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	71.7100	21.28	11.68	32.96	40.00	-7.04	QР			
2		191.9900	13.91	16.70	30.61	43.50	-12.89	QP			
3		215.2700	17.18	16.12	33.30	43.50	-10.20	QP			
4		288.0200	12.85	19.42	32.27	46.00	-13.73	QP			
5		527.6100	7.79	22.08	29.87	46.00	-16.13	QP			
6		576.1100	8.46	22.82	31.28	46.00	-14.72	QΡ			

Engineer Signature:

Sky

^{*:}Maximum data x:Over limit !:over margin



Address:No.5,Langshan 2nd Rd., North Hi-Tech Industrial park Guangdong ,China Tel: 0755-86170306 Fax: 0755-86170310

Radiated Emission Measurement File:BLUEMINI Date: 2012-7-5 Time: 14:06:59 dBuV/m 70.0 Limit: 60 50 40 30 20 10 0 -10.0

515.00

Site site MOST 3M

Limit: FCC Part15 B 3M Radiation

127.00

321.00

418.00

EUT: BLUETOOTH AUDIO RECEIVER

M/N: BLUEMINI Mode: Running

Note:

Polarization: Vertical

709.00

Power: DC 5V Adapter AC 120V/60Hz

612.00

Temperature: 26 Humidity: 61 %

1000.00 MHz

Distance:

806.00

No.	Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBu∨	dB	dBu∀/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	30.0000	7.86	24.80	32.66	40.00	-7.34	QР			
2		71.7100	18.56	11.68	30.24	40.00	-9.76	QP			
3		191.9900	13.41	16.70	30.11	43.50	-13.39	QP			
4		384.0500	9.29	18.18	27.47	46.00	-18.53	QP			
5		544.1000	5.80	22.28	28.08	46.00	-17.92	QP			
6		738.1000	5.84	25.37	31.21	46.00	-14.79	QP			

Engineer Signature:

Sky

^{*:}Maximum data x:Over limit : 1:over margin

Above 1 GHz

Operation Mode: GFSK Mode/CH Low Test Date: Jul. 06, 2012

Temperature: 20°C **Tested by:** Habby Guo

Humidity: 70 % RH **Polarity:** Ver. / Hor.

Freq.	Ant. Pol	Peak	AV	Ant. / CL	Actu	al Fs	Peak	AV	AV
(MHz)	H/V	Reading	Reading	CF			Limit	Limit	Margin
		(dBuV)	(dBuV)	(dB)	Peak	AV	(dBuV/m)	(dBuV/m)	(dB)
					(dBuV/m)	(dBuV/m)			
2402.0	Н	94.36	70.51	9.07	103.43	79.58	114.00	94.00	-14.42
1612.5	Н	54.29	33.58	6.05	60.34	39.63	74.00	54.00	-14.37
4815.0	Н	47.98	25.06	17.05	65.04	42.11	74.00	54.00	-11.89
N/A									>20
2402.0	V	93.27	68.49	9.07	102.34	77.56	114.00	94.00	-16.44
1612.5	V	52.41	31.08	6.05	58.46	38.13	74.00	54.00	-15.87
4815.0	V	46.86	26.15	17.05	64.91	49.20	74.00	54.00	-10.80
N/A	V								

Notes:

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4. Spectrum setting:
 - a. Peak Setting 1GHz 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = auto.
 - b. AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = auto

FCC ID: YT6BLUEMINI Report No.:MTE/DAL/D12070897

Operation Mode:GFSK Mode/CH MidTest Date:Jul. 06, 2012Temperature:20°CTested by:Habby Guo

Humidity: 70 % RH **Polarity:** Ver. / Hor.

Freq.	Ant. Pol	Peak	AV	Ant. / CL	Actu	al Fs	Peak	AV	AV
(MHz)	H/V	Reading	Reading	CF			Limit	Limit	Margin
		(dBuV)	(dBuV)	(dB)	Peak	AV	(dBuV/m)	(dBuV/m)	(dB)
					(dBuV/m)	(dBuV/m)			
2441.0	Н	92.64	71.45	9.07	101.71	80.52	114.00	94.00	-13.48
1612.5	Н	52.78	30.49	6.05	58.83	36.54	74.00	54.00	-17.46
4815.0	Н	45.62	24.02	17.05	62.67	41.07	74.00	54.00	-12.93
N/A									>20
2441.0	>	91.82	69.27	9.07	100.89	78.34	114.00	94.00	-15.66
1612.5	V	50.10	32.95	6.05	56.15	39.00	74.00	54.00	-15.00
4815.0	V	43.35	27.84	17.05	60.40	44.89	74.00	54.00	-9.11
N/A	V								>20

Notes:

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4. Spectrum setting:
 - a. Peak Setting 1GHz 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = auto.
 - b. AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = auto.

Operation Mode:GFSK Mode/CH HighTest Date:Jul. 06, 2012Temperature:20°CTested by:Habby GuoHumidity:70 % RHPolarity:Ver. / Hor.

Freq.	Ant. Pol	Peak	AV	Ant. / CL	Actu	al Fs	Peak	AV	AV
(MHz)	H/V	Reading	Reading	CF			Limit	Limit	Margin
		(dBuV)	(dBuV)	(dB)	Peak	AV	(dBuV/m)	(dBuV/m)	(dB)
					(dBuV/m)	(dBuV/m)			
2480.0	Н	90.04	68.72	9.07	99.11	77.79	114.00	94.00	-16.21
1612.5	Н	49.62	28.16	6.05	55.67	34.21	74.00	54.00	-19.79
4815.0	Н	41.34	19.46	17.05	61.39	37.51	74.00	54.00	-16.49
N/A									>20
2480.0	V	89.58	67.82	9.07	98.65	76.89	114.00	94.00	-17.11
1612.5	V	48.27	27.51	6.05	54.32	33.56	74.00	54.00	-20.44
4815.0	V	47.82	26.81	17.05	64.87	43.86	74.00	54.00	-10.14
N/A	V								>20


Notes:

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4. Spectrum setting:
 - a. Peak Setting 1GHz 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = auto.
 - b. AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = auto.

5.2 BAND EDGE 5.2.1 REQUIREMENT

According to FCC section 15.249(a), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.2.2 TEST DESCRIPTION




5.2.3TEST RESULT


The EUT operates at hopping-off test mode. The lowest and highest channels are tested to verify the band edge emissions.

				Test Result Highest Emission (dBuv/m)				
Test	Mode	Channel Marked Frequency	Limit (dBuv/m)	Ver	tical	Horizontal		
		, ,		Peak	Average	Peak	Average	
	Low	2390MHz		59.02	36.25	69.77	45.45	
Pluotooth	Channel	2400MHz	74(Peak)	66.86	46.38	59.22	43.78	
Bluetooth	High	2483.5MHz	54(Average)	69.77	48.75	60.56	40.69	
	Channel	2500MHz		67.69	49.08	60.29	45.47	


Test Plot:




(CH Low, Horizontal)



(CH Low, Vertical)



(CH High, Horizontal)



(CH High, Vertical)

5.3 LINE CONDUCTED EMISSION TEST


5.3.1. LIMITS OF LINE CONDUCTED EMISSION TEST

Fraguency	Maximum RF	Line Voltage
Frequency	Q.P.(dBuV)	Average(dBuV)
150kHz-500kHz	66-56	56-46
500kHz-5MHz	56	46
5MHz-30MHz	60	50

^{**}Note: 1. the lower limit shall apply at the transition frequency.

2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz

5.3.2. BLOCK DIAGRAM OF TEST SETUP



5.3.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

- The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per FCC Part 15 (see Test Facility for the dimensions of the ground plane used). When the EUT is floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2) Support equipment, if needed, was placed as per FCC Part 15.

FCC ID: YT6BLUEMINI

- 3) All I/O cables were positioned to simulate typical actual usage as per FCC Part 15.
- 4) The EUT through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5) All support equipments received power from a second LISN supplying power of AC 120V/60Hz, if any.
- 6) The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7) Analyzer / Receiver scanned from 150 kHz to 30 MHz for emissions in each of the test modes.
- 8) During the above scans, the emissions were maximized by cable manipulation.

5.3.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

EUT and support equipment was set up on the test bench as per step 9 of the preliminary test.

A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.

The test data of the worst case condition(s) was reported on the Summary Data page.

The Bluetooth model was carried out for GFSK, Pi/4-DQPSK and 8-DPSK modulation types, GFSK Low channel modulation type was the worst case condition, The test data was shown on the summary data page.


Humidity: 60 %

5.3.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST



Address:No.5,Langshan 2nd Rd., North Hi-Tech Industrial park Guangdong ,China

Tel: 0755-86170306 Fax: 0755-86170310



Power: DC 5V Adapter AC 120V/60Hz

Site site #1

Limit: FCC Part15 B Class B QP

EUT: BLUETOOTH AUDIO RECEIVER

M/N: BLUEMINI Mode: Running

Note:

No. Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
	MHz	dBu∀	dB	dBu∀	dBu∀	dB	Detector	Comment
1	0.1940	37.34	11.64	48.98	63.86	-14.88	QP	
2 *	0.2740	37.20	11.51	48.71	61.00	-12.29	QP	
3	0.5580	30.23	10.00	40.23	56.00	-15.77	QР	
4	0.8860	28.60	10.00	38.60	56.00	-17.40	QР	
5	1.5180	26.56	9.48	36.04	56.00	-19.96	QP	
6	3.4220	20.92	10.42	31.34	56.00	-24.66	QР	


Engineer Signature: Allen

^{*:}Maximum data x:Over limit !:over margin



Address:No.5,Langshan 2nd Rd., North Hi-Tech Industrial park Guangdong ,China

Tel: 0755-86170306 Fax: 0755-86170310



Power: DC 5V Adapter AC 120V/60Hz

Humidity: 60 %

Limit: FCC Part15 B Class B QP

EUT: BLUETOOTH AUDIO RECEIVER

M/N: BLUEMINI Mode: Running

Note:

No. Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
	MHz	dBu∨	dB	dBu∀	dBu∀	dB	Detector	Comment
1	0.1860	38.23	11.16	49.39	64.21	-14.82	QP	
2 *	0.3620	34.06	10.92	44.98	58.68	-13.70	QР	
3	0.7260	28.56	10.00	38.56	56.00	-17.44	QР	
4	1.5260	26.96	9.47	36.43	56.00	-19.57	QP	
5	3.4420	20.83	10.44	31.27	56.00	-24.73	QP	
6	5.6340	14.65	11.62	26.27	60.00	-33.73	QP	

Engineer Signature: Allen

^{*:}Maximum data x:Over limit !:over margin


5.4 20 dB Bandwidth

5.4.1 Definition

Intentional radiators operating under the alternative provisions to the general emission limits, as Contained in §15.217 through 15.257 and in sub-part E of this part, must be designed to ensure that the 20 dB Bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific Rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.


5.4.2 Block Diagram Of Test Setup

The EUT is powered by the Battery, is coupled to the Spectrum Analyzer (SA) through the Attenuator/DC Block. The path loss as the factor is calibrated to correct the reading. During the measurement, the EUT is activated and is set to operate at maximum power. The RF load attached to the EUT antenna terminal is 500hm.




5.4.3 Test Result


The Bluetooth model was carried out for GFSK, Pi/4-DQPSK and 8-DPSK modulation types, GFSK modulation type was the worst case condition, The test data was shown on the summary data page:



CH Low



CH MID



CH High

APPENDIX 1 PHOTOGRAPHS OF TEST SETUP

FCC ID: YT6BLUEMINI

SPURIOUS EMISSION TEST SETUP



-----END OF REPORT-----