

# Appendix C. Co-location

FCC ID: YUATLDPV00A1 Page No. : C1 of C18



### 1. Test Mode for Co-located

Investigation has been done on all the possible configurations for searching the worst cases.

The following table is a list of the test modes shown in this test report.

Mod		GSM850	LTE	WLAN	LAN	WAN	SIM (Bottom)	Adapter
362	1	• Link	-	● 2.4GHz	•	•	•	• Adapter 2
odel: E3	2	• Link	-	• 5GHz	•	•	•	• Adapter 2
Module model: E362	3	-	• Link	● 2.4GHz	•	•	•	• Adapter 2
Мос	4	-	• Link	• 5GHz	•	•	•	• Adapter 2
	5	• Link	-	• 2.4GHz	•	•	•	• Adapter 2
Module model: E371	6	• Link	-	• 5GHz	•	•	•	• Adapter 2
lodule ma E371	7	-	• Link	● 2.4GHz	•	•	•	• Adapter 2
$\geq$	8	-	• Link	• 5GHz	•	•	•	• Adapter 2

Note: After evaluating, Adapter 2 has been evaluated to be the worst case.

Consequently, measurement for Co-located test will follow this same test mode.

FCC ID: YUATLDPV00A1 Page No. : C2 of C18






## 2. Results of Radiated Emissions for Co-located


Temperature	23°C	Humidity	63%
Test Engineer	Satoshi Yang	Test Mode	Mode 1

#### Horizontal




	Freq	Level	Limi t Line	Over Limit	Read Level					T/Pos	A/Pos	Pol/Phase
-	MHz	$\overline{dBuV/m}$	$\overline{dBuV/m}$	——dB	- dBuV	——dB	——dB	dB/m		deg	Cm	
3 a	1673.89 1674.00 2511.03 2511.08	25.84 27.57	54.00 54.00	-28.16 -26.43	31.86 31.49	2.40 2.98	34.96 34.65	27.75	Average Average	274 274 258 258	100 107	HORIZONTAL HORIZONTAL HORIZONTAL HORIZONTAL

FCC ID: YUATLDPV00A1 Page No. : C3 of C18








	Freq	Level		Over Limit						T/Pos	A/Pos	Pol/Phase
-	MHz	$\overline{dBuV/m}$	$\overline{\mathtt{dBuV/m}}$	dB	dBu∀	dВ	——dB	dB/m		deg	Cm	
3р	1673.86 1673.94 2510.88 2510.95	26.20 51.19	54.00 74.00	-27.80 -22.81	32.22 55.11	2.40 2.98	34.96 34.65	26.54 27.75	Average Peak	24 24 38 38	100 100	VERTICAL VERTICAL VERTICAL VERTICAL

FCC ID: YUATLDPV00A1 Page No. : C4 of C18




Temperature	23 <b>°C</b>	Humidity	63%
Test Engineer	Satoshi Yang	Test Mode	Mode 2




	Freq	Level	Limit Line	Over Limit						T/Pos	A/Pos	Pol/Phase
-	MHz	$\overline{dBuV/m}$	$\overline{\mathtt{dBuV/m}}$	——dB	dBu∀	——dB	dB	dB/m		deg	Cm	
3 p	1673.91 1674.12 2510.82 2510.91	43.69 45.15	74.00 74.00	-30.31 -28.85	49.71 49.07	2.40 2.98	34.96 34.65	26.54 27.75	Peak Peak	275 275 285 285	100 100	HORIZONTAL HORIZONTAL HORIZONTAL HORIZONTAL

FCC ID: YUATLDPV00A1 Page No. : C5 of C18








	Freq	Level		Over Limit					Remark	T/Pos	A/Pos	Pol/Phase
-	MHz	$\overline{\mathtt{dBuV/m}}$	$\overline{\mathtt{dBuV/m}}$	——dB	dBu∀	dВ	——dB	dB/m		deg	Cm	
3 р	1674.05 1674.11 2510.82 2510.99	46.93 51.52	74.00 74.00	-27.07 -22.48	52.95 55.44	2.40 2.98	34.96 34.65	26.54 27.75	Peak Peak	22 22 37 37	100 100	VERTICAL VERTICAL VERTICAL VERTICAL

FCC ID: YUATLDPV00A1 Page No. : C6 of C18




Temperature	23 <b>°C</b>	Humidity	63%
Test Engineer	Satoshi Yang	Test Mode	Mode 3




	Freq	Level		Over Limit					Remark	T/Pos	A/Pos	Pol/Phase
-	MHz	$\overline{dBuV/m}$	$\overline{dBuV/m}$	——dB	-dBuV	——dB	dB	dB/m		deg	Cm	
1 p 2 a 3	3200.00 3200.03 3599.96 3600.19	36.38 29.66	54.00 54.00	-17.62 -24.34	38.25 30.13	3.38 3.63	34.81 34.69	29.56 30.59	Average Average	123 123 354 354	123 100	HORIZONTAL HORIZONTAL HORIZONTAL HORIZONTAL

FCC ID: YUATLDPV00A1 Page No. : C7 of C18








	Freq	Level	Limit Line	Over Limit	Read Level					T/Pos	A/Pos Pol/P	hase
-	MHz	$\overline{\mathtt{dBuV/m}}$	$\overline{\mathtt{dBuV/m}}$	dB	dBu∀	——dB	——dB	dB/m		deg	Cm	
2 p	3200.03 3200.07 3599.98 3599.99	45.56 43.28	74.00 74.00	-28.44 -30.72	47.43 43.75	3.38 3.63	34.81 34.69	29.56 30.59	Peak Peak	250 250 4 4	100 VERTI 100 VERTI 100 VERTI 100 VERTI	CAL CAL

FCC ID: YUATLDPV00A1 Page No. : C8 of C18




Temperature	23°C	Humidity	63%
Test Engineer	Satoshi Yang	Test Mode	Mode 4




	Freq	Level	Limit Line	Over Limit	Read Level					T/Pos	A/Pos	Pol/Phase
-	MHz	$\overline{\mathtt{dBuV/m}}$	$\overline{\mathtt{dBuV/m}}$	——dB	dBu∀	dB	——dB	dB/m		deg	Cm	
	3199.84 3200.06 3599.54 3599.96	33.74 42.68	54.00 74.00	-20.26 -31.32	35.61 43.15	3.38 3.63	34.81 34.69	30.59	Average Peak	263 263 130 130	126 100	HORIZONTAL HORIZONTAL HORIZONTAL HORIZONTAL

FCC ID: YUATLDPV00A1 Page No. : C9 of C18










	Freq	Level		Over Limit					Remark	T/Pos	A/Pos	Pol/Phase
_	MHz	$\overline{\mathtt{dBuV/m}}$	$\overline{\mathtt{dBuV/m}}$	dB	dBuV	dB	——dB	dB/m		deg	Cm	
1 a 2 p 3	3200.04 3200.20 3600.00 3600.03	46.15 44.46	74.00 74.00	-27.85 -29.54	48.02 44.93	3.38 3.63	34.81 34.69	29.56 30.59	Peak	70 70 282 282	100 100	VERTICAL VERTICAL VERTICAL VERTICAL

FCC ID: YUATLDPV00A1 Page No. : C10 of C18




Temperature	25.6 <b>℃</b>	Humidity	56%
Test Engineer	Jim Huang	Test Mode	Mode 5




	_			0∨er						A/Pos	-	
	Freq	Level	Line	Limit	Level	Loss	Factor	Factor	Remark			Pol/Phase
	MHz	dBu∀/m	dBu∀/m	dB	dBu∨	dB	dB/m	dB		cm	deg	
1	2129.65	42.02	54.00	-11.98	47.44	2.08	27.60	35.10	Average	100	216	HORIZONTAL
2	2129.65	45.06	74.00	-28.94	50.48	2.08	27.60	35.10	Peak	100	216	HORIZONTAL
3	3200.04	36.97	54.00	-17.03	39.69	2.64	30.00	35.36	Average	158	257	HORIZONTAL
4	3200.18	43.62	74.00	-30.38	46.34	2.64	30.00	35.36	Peak	158	257	HORIZONTAL

FCC ID: YUATLDPV00A1 Page No. : C11 of C18








			Limit	0∨er	Read	CableA	ntenna	Preamp		A/Pos	T/Pos	
	Freq	Level	Line	Limit	Level	Loss	Factor	Factor	Remark		Pol/Phase	
	MHz	dBu\√/m	dBu∀/m	dB	dBu∀	dB	dB/m	dB		cm	deg	
1	2129.81	44.73	54.00	-9.27	50.15	2.08	27.60	35.10	Average	100	102 VERTICAL	
2	2129.88	47.16	74.00	-26.84	52.58	2.08	27.60	35.10	Peak	100	102 VERTICAL	
3	3200.04	40.09	54.00	-13.91	42.81	2.64	30.00	35.36	Average	100	9 VERTICAL	
4	3200.04	45.51	74.00	-28.49	48.23	2.64	30.00	35.36	Peak	100	9 VERTICAL	

FCC ID: YUATLDPV00A1 Page No. : C12 of C18




Temperature	25.6 <b>℃</b>	Humidity	56%
Test Engineer	Jim Huang	Test Mode	Mode 6



			Limit	0∨er	Read	CableA	ntenna	Preamp		A/Pos	T/Pos	
	Freq	Level	Line	Limit	Level	Loss	Factor	Factor	Remark			Pol/Phase
	MHz	dBu∀/m	dBu∀/m	dB	dBu∖∕	dB	dB/m	dB		cm	deg	
1	1807.78	43.10	54.00	-10.90	49.89	1.91	26.57	35.27	Average	112	180	HORIZONTAL
2	1807.78	42.95	74.00	-31.05	49.74	1.91	26.57	35.27	Peak	112	180	HORIZONTAL
3	2130.28	45.80	74.00	-28.20	51.22	2.08	27.60	35.10	Peak	100	217	HORIZONTAL
4	2130.34	42.38	54.00	-11.62	47.80	2.08	27.60	35.10	Average	100	217	HORIZONTAL

FCC ID: YUATLDPV00A1 Page No. : C13 of C18






			Limit	0∨er	Read	Cable/	\nt enna	Preamp		A/Pos	T/Pos	
	Freq	Level	Line	Limit	Level	Loss	Factor	Factor	Remark			Pol/Phase
	MHz	dBu√/m	dBu∀/m	dB	dBu∀	dB	dB/m	dB		cm	deg	
1	1807.72	43.07	74.00	-30.93	49.86	1.91	26.57	35.27	Peak	135	243	VERTICAL
2	1807.82	42.03	54.00	-11.97	48.82	1.91	26.57	35.27	Average	135	243	VERTICAL
3	2130.26	47.74	74.00	-26.26	53.16	2.08	27.60	35.10	Peak	100	102	VERTICAL
4	2130.29	45.27	54.00	-8.73	50.69	2.08	27.60	35.10	Average	100	102	VERTICAL

FCC ID: YUATLDPV00A1 Page No. : C14 of C18




Temperature	24.5° <b>C</b>	Humidity	57%
Test Engineer	Kenneth Huang	Test Mode	Mode 7




Freq	Level		Over Limit						A/Pos	T/Pos Pol/Phase
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg
1375.00 1375.00								_	122 122	176 HORIZONTAL 176 HORIZONTAL

FCC ID: YUATLDPV00A1 Page No. : C15 of C18








	Freq	Level		Over Limit						A/Pos	T/Pos Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBu√	dB	dB/m	dB		cm	deg
1	1375.00	36.74	54.00	-17.26	43.36	2.95	25.17	34.74	Average	100	301 VERTICAL
2	1375.00	41.51	74.00	-32.49	48.13	2.95	25.17	34.74	Peak	100	301 VERTICAL

FCC ID: YUATLDPV00A1 Page No. : C16 of C18




Temperature	24.5° <b>C</b>	Humidity	57%
Test Engineer	Kenneth Huang	Test Mode	Mode 8




Freq	Level		Over Limit					A/Pos		l/Phase
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
13 <b>75.00</b> 13 <b>75.00</b>								 100 100		RIZONTAL

FCC ID: YUATLDPV00A1 Page No. : C17 of C18







Freq	Level	Limit Line	Over Limit					A/Pos		Pol/Phase
MHz	dBuV/m	dBuV/m	——dB	dBuV	dB	dB/m	——dB	 cm	deg	
1375.00 1375.00								100 100		VERTICAL VERTICAL

FCC ID: YUATLDPV00A1 Page No. : C18 of C18