

Radio Frequency Exposure

LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

EUT Specification

EUT	RX-357x ZigBee Module				
Frequency band (Operating)	 ✓ WLAN: 2.405GHz ~ 2.480GHz ✓ WLAN: 5.725GHz ~ 5.850GHz ✓ Bluetooth: 2.402GHz ~ 2.480 GHz 				
Device category	☐ Portable (<20cm separation)☑ Mobile (>20cm separation)				
Exposure classification	☐ Occupational/Controlled exposure (S = 5mW/cm²) ☐ General Population/Uncontrolled exposure (S=1mW/cm²)				
Antenna diversity	 Single antenna Multiple antennas □ Tx diversity □ Rx diversity □ Tx/Rx diversity 				
Max. output power	O-QPSK: 7.88 dBm (6.1 mW)				
Antenna gain (Max)	3.74 dBi				
Evaluation applied					

Remark:

- 1. The maximum output power is 7.88 dBm (6.1 mW) at 2405 MHz (with numeric 3.74 antenna gain.)
- 2. DTS device is not subject to routine RF evaluation; MPE estimate is used to justify the compliance.
- For mobile or fixed location transmitters, no SAR consideration applied. The maximum power density is 1.0 mW/cm² even if the calculation indicates that the power density would be larger.

Cerpass Technology Corp.

Tel: 886-2-2655-8100 Fax: 886-2-2655-8200 Page No. : 1 of 3

FCC ID : YUDRX357X

Issued date : Oct. 29, 2013

Report No.: TEFA1308091

TEST RESULTS

No non-compliance noted.

Calculation

Given

$$E = \frac{\sqrt{30 \times P \times G}}{d} \quad \& \quad S = \frac{E^2}{3770}$$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = *Distance in meters*

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770d^2}$$

Changing to units of mW and cm, using:

$$P(mW) = P(W) / 1000$$
 and $d(cm) = d(m) / 100$

Yields

$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2}$$
 Equation 1

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

 $S = Power density in mW / cm^2$

Cerpass Technology Corp.

Tel: 886-2-2655-8100 Fax: 886-2-2655-8200 Page No. : 2 of 3

Issued date : Oct. 29, 2013

Report No.: TEFA1308091

FCC ID : YUDRX357X



Maximum Permissible Exposure

Modulation Mode	Frequency band (MHz)	Max. Conducted output power(dBm)	Antenna gain (dBi)	Distance (cm)	Power density (mW/cm2)	Limit (mW/cm2)
O-QPSK	2405-2480	7.88	3.74	20	0.003	1

NOTE:

Total (Chain0+Chain1), the formula of calculated the MPE is:

CPD1 / LPD1 + CPD2 / LPD2 +etc. < 1

CPD = Calculation power density

LPD = Limit of power density

Cerpass Technology Corp. Issued date : Oct. 29, 2013

Tel: 886-2-2655-8100 Fax: 886-2-2655-8200 Page No. : 3 of 3

FCC ID : YUDRX357X

Report No.: TEFA1308091