

## Compliance with 47 CFR 2.1091, 1.1310, and 15.247(i)

The EUT provides wireless audio connectivity for TV, radio, etc. It is seeking authorization under FCC 15.247 in the 2400 - 2483.5 MHz band. The EUT will only be used with a separation distance of 20 centimeters or greater between the antenna and the body of the user or nearby persons and can therefore be considered a mobile transmitter per 47 CFR 2.1091(b). The antenna is a PIFA antenna that is permanently attached to the unit. The antenna has a gain of 1.7 dBi.

The maximum peak radiated power is 29.7 mW (EIRP) for FCC ID: YUKFOX4345666870. Since the transmit frequency is greater than 1.5 GHz, and the output power is less than 3 W ERP, the EUT is categorically excluded from routine environmental evaluation per 47 CFR 2.1091(c).

The MPE estimates are as follows:

Table 1 in 47 CFR 1.1310 defines the maximum permissible exposure (MPE) for the general population as 1 mW/cm<sup>2</sup>. The exposure level at a 20 cm distance from the EUT's transmitting antenna is calculated using the general equation:

$$S = (PG)/4\pi R^2$$

Where: S = power density (mW/cm<sup>2</sup>)

P = power input to the antenna (mW)

G = numeric power gain relative to an isotropic radiator

R = distance to the center of the radiation of the antenna (20 cm = limit for MPE estimates)

PG = EIRP

Solving for S, the maximum power density 20 cm from the transmitting antenna is summarized in the following table:

MPE Estimate								
FCC ID: YUKFOX4345666870								
Antenna Type	Antenna Manufacturer	Antenna Part No.	Transmit Frequency (MHz)	Max Peak Radiated Output Power - EIRP (mW)	Antenna Gain (dBi)	Minimum Antenna Cable Loss (dB)	Power Density @ 20 cm (mW/cm <sup>2</sup> )	General Population Exposure Limit from 1.1310 (mW/cm <sup>2</sup> )
PIFA	SYNIC	Rib PIFA	2400	29.7	1.7	0	0.006	1

The power density does not exceed 0.006 mW/cm<sup>2</sup> at 20 cm; therefore, the exposure condition is compliant with FCC rules.