

FCC Test Report

FCC ID : YUW-301F
Equipment : Mobile Phone
Model No. : 301F
Brand Name : FUJITSU
Applicant : Fujitsu Mobile Communications Ltd.
Address : 1-1, Kamikodanaka 4-chome, Nakahara-ku,
Kawasaki 211-8588, Japan
Standard : 47 CFR FCC Part 24 Subpart E
Received Date : Sep. 13, 2013
Tested Date : Sep. 24 ~ Sep. 25, 2013

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Approved & Reviewed by:



Gary Chang / Manager



Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Local Support Equipment List	7
1.3	Test Setup Chart	7
1.4	The Equipment List	8
1.5	Test Standards	9
1.6	Measurement Uncertainty	9
2	TEST CONFIGURATION.....	10
2.1	Testing Condition and Location Information.....	10
2.2	The Worst Test Modes and Channel Details	10
3	TEST RESULTS.....	11
3.1	Equivalent Isotropically Radiated Power	11
3.2	Radiated Emissions.....	14
3.3	Conducted Emissions.....	18
3.4	Band Edge	20
3.5	Occupied Bandwidth	22
3.6	Peak to Average Ratio	24
3.7	Frequency Stability	26
4	TEST LABORATORY INFORMATION	28

Release Record

Report No.	Version	Description	Issued Date
FG391306	Rev. 01	Initial issue	Nov. 01, 2013

Summary of Test Results

FCC Rules	Test Items	Measured	Result
2.1046 / 24.232(c)	Equivalent Isotropically Radiated Power	Power[dBm]: 31.33	Pass
2.1053 / 24.238(a)	Radiated Emissions	Meet the requirement of limit	Pass
2.1051 / 24.238(a)	Conducted Emissions	Meet the requirement of limit	Pass
2.1051 / 24.238(a)	Band Edge	Meet the requirement of limit	Pass
2.1049 / 24.238(a)	Occupied Bandwidth	Meet the requirement of limit	Pass
24.232(d)	Peak to average ratio	Meet the requirement of limit	Pass
2.1055 / 24.235	Frequency Stability	Meet the requirement of limit	Pass

1 General Description

1.1 Information

1.1.1 Specification of the Equipment under Test (EUT)

Operating band(MHz)	GSM: 1850.2-1909.8
Modulation	GSM / GPRS: GMSK
Multislot class	33
IMEI Code	357613050017374 & 357613050017366
H/W Version	V2.1.0
S/W Version	R25.1e

1.1.2 Maximum ERP, Frequency Tolerance and Emission Designator

System	Modulation	Maximum EIRP(W)	Frequency Tolerance (ppm)	Emission Designator
GSM 1900	GMSK	1.358	0.012	247KGXW

1.1.3 Antenna Details

Ant. No.	Type	Gain (dBi)	Connector	Remark
1	$\lambda/4$ Monopole	1.5	---	---

1.1.4 EUT Operational Condition

Supply Voltage	<input checked="" type="checkbox"/> AC mains	<input checked="" type="checkbox"/> DC	
Type of DC Source	<input type="checkbox"/> Internal DC supply	<input checked="" type="checkbox"/> External DC adapter	<input checked="" type="checkbox"/> Battery
Operational Voltage	<input checked="" type="checkbox"/> V _{nom} (3.9 V)	<input checked="" type="checkbox"/> V _{max} (4.29 V)	<input checked="" type="checkbox"/> V _{min} (3.51 V)

1.1.5 Accessories

Accessories		
No.	Equipment	Description
1	Battery	Brand Name: Fujitsu limited Model Name: CA54310-0053 Power Rating: O/P: 3.75Vdc, 2600mA
2	Cradle	Brand Name: SOFTBANK MOBILE Corp. Model Name: CA50601-1881 Power Rating: O/P: 12.0Vdc, 1.5A
3	Adapter for cradle	Brand Name: SOFTBANK MOBILE Corp. Model Name: TA08017-B330 I/P: 100-240Vac, 1000mA O/P: 12.0Vdc, 3000mA DC 1.1m non-shielded cable with one core AC 0.9m non-shielded cable without core

1.1.6 Operating Channel List



GSM & GPRS		
	Channel	Frequency (MHz)
Low	512	1850.2
Middle	661	1880.0
High	810	1909.8

1.2 Local Support Equipment List

Support Equipment List						
No.	Equipment	Brand	Model	S/N	FCC ID	Signal cable / Length (m)
1	Adapter	NTT docomo	AC Adaptor 04	---	---	1m non-shielded with 2 cores
2	Earphone	Apple	MD827FE/A	---	---	1.2m non-shielded w/o core

Note: Item 1 was provided by client.

1.3 Test Setup Chart



1.4 The Equipment List

Test Item	Radiated Emission				
Test Site	966 chamber1 / (03CH01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
3m semi-anechoic chamber	CHAMPRO	SAC-03	03CH01-WS	Jan. 04, 2013	Jan. 03, 2014
Spectrum Analyzer	R&S	FSV40	101498	Jan. 24, 2013	Jan. 23, 2014
Receiver	R&S	ESR3	101658	Jan. 28, 2013	Jan. 27, 2014
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-522	Jan. 11, 2013	Jan. 10, 2014
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1096	Feb. 18, 2013	Feb. 17, 2014
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Jan. 14, 2013	Jan. 13, 2014
Amplifier	Burgeon	BPA-530	100219	Nov. 28, 2012	Nov. 27, 2013
Amplifier	Agilent	83017A	MY39501308	Dec. 18, 2012	Dec. 17, 2013
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16014/4	Dec. 25, 2012	Dec. 24, 2013
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16019/4	Dec. 25, 2012	Dec. 24, 2013
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16139/4	Dec. 25, 2012	Dec. 24, 2013
RF Cable-R03m	Woken	CFD400NL-LW	CFD400NL-001	Dec. 25, 2012	Dec. 24, 2013
RF Cable-R10m	Woken	CFD400NL-LW	CFD400NL-002	Dec. 25, 2012	Dec. 24, 2013
Radio Communication Analyzer	Anritsu	MT8820C	6201240341	Mar. 13, 2013	Mar. 12, 2014
control	EM Electronics	EM1000	60612	N/A	N/A

Note: Calibration Interval of instruments listed above is one year.

Loop Antenna	R&S	HFH2-Z2	100330	Nov. 15, 2012	Nov. 14, 2014
Amplifier	MITEQ	AMF-6F-260400	9121372	Apr. 19, 2013	Apr. 18, 2015

Note: Calibration Interval of instruments listed above is two year.

Test Item	RF Conducted				
Test Site	(TH01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV 40	101063	Feb. 18, 2013	Feb. 17, 2014
TEMP&HUMIDITY CHAMBER	GIANT FORCE	GCT-225-40-SP-SD	MAF1212-002	Nov. 29, 2012	Nov. 28, 2013
Signal Generator	R&S	SMB100A	175727	Jan. 14, 2013	Jan. 13, 2014
Radio Communication Analyzer	Anritsu	MT8820C	6201240341	Mar. 13, 2013	Mar. 12, 2014

Note: Calibration Interval of instruments listed above is one year.

1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards.

47 CFR FCC Part 24 Subpart E

ANSI C63.43-2003

ANSI / TIA / EIA-603-C -2004

Note: The EUT has been tested and complied with FCC part 15B requirement. FCC Part 15B test results are issued to another report.

1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Uncertainty	
Parameters	Uncertainty
Bandwidth	±40.246 Hz
Conducted power	±0.552 dB
Frequency error	±40.246 Hz
Temperature	±0.3 °C
Conducted emission	±2.946 dB
AC conducted emission	±2.43 dB
Radiated emission	±2.49 dB

2 Test Configuration

2.1 Testing Condition and Location Information

Test Item	Test Site	Ambient Condition	Tested By
RF conducted	TH01-WS	22°C / 63%	Brad Wu
Radiated Emissions	03CH01-WS	24°C / 64%	Haru Yang

➤ FCC site registration No.: 657002

➤ IC site registration No.: 10807A-1

2.2 The Worst Test Modes and Channel Details

Test item	Mode	Test Channel	Test Configuration
E.I.R.P	GSM	512, 661, 810	1
Radiated Emissions < 1GHz	GSM	661	1, 2
Radiated Emissions > 1GHz	GSM	512, 661, 810	1
Conducted Emissions	GSM	512, 661, 810	1
Band Edge	GSM	512, 810	1
Occupied Bandwidth	GSM	512, 661, 810	1
Frequency Stability	GSM	661	1

NOTE:

1. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **Z-plane** results were found as the worst case and were shown in this report.
2. The EUT had been tested by following test configurations for radiated emission below 1GHz.
 - 1) Configuration 1 : Adapter mode
 - 2) Configuration 2 : Cradle mode
3. Adapter and cradle mode had been pretested for radiated emission above 1GHz and found that the adapter mode was the worst case and was selected for final test.

3 Test Results

3.1 Equivalent Isotropically Radiated Power

3.1.1 Limit of Equivalent Isotropically Radiated Power

Mobile and portable stations are limited to 2 watts EIRP.

3.1.2 Test Procedures


1. The EUT links up with simulator and is set to maximum output power level at low / middle / high channel. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at a height of 0.8 m test table above the ground plane.
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.
4. After finding the max radiated emission, substitution method will be used for getting effective radiated power. EUT will be removed and substitution antenna will be placed at same position. Signal generator will output CW signal to substitution antenna through a RF cable. Rotate turntable and move antenna to find maximum radiated emission. Adjust output power of signal generator to let the maximum radiated emission is same as step 3. Record the output power level.
5. $E.I.R.P = \text{output power of step 4} + \text{gain of substitution antenna} - \text{cable loss of RF cable}$.

For Conducted power measurement


1. The EUT links up with simulator and is set to maximum output power level at low / middle / high channel.
2. Measure the output power of low / middle / high channel of the EUT

3.1.3 Test Setup

Equivalent Isotropically Radiated Power Measurement



Conducted Power Measurement



3.1.4 Test Result of Conducted Power (dBm)

Band	GSM1900		
Channel	512	661	810
Frequency (MHz)	1850.2	1880	1909.8
GSM	30.86	30.72	30.98
GPRS 8 (GMSK, 1 slot)	30.76	30.70	30.97
GPRS 10 (GMSK, 2 slots)	27.70	27.66	27.95
GPRS 11 (GMSK, 3 slots)	26.01	25.94	26.12
GPRS 12 (GMSK, 4 slots)	24.76	24.71	24.85

3.1.5 Test Result of Equivalent Isotropically Radiated Power (dBm)

Mode	GSM							
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Vaule (dBm)	Correction Factor (dB)	
512	1850.2	29.91	33	-3.09	-11.25	25.29	4.62	
661	1880.0	29.57	33	-3.43	-12.03	25.01	4.56	
810	1909.8	31.33	33	-1.67	-10.21	26.83	4.50	

Note: EIRP = S.G Power value + Correction factor

3.2 Radiated Emissions

3.2.1 Limit of Radiated Emissions


The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB equal to -13dBm.

3.2.2 Test Procedures


1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at a height of 0.8 m test table above the ground plane.
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.
4. After finding the max radiated emission, substitution method will be used for getting effective radiated power. EUT will be removed and substitution antenna will be placed at same position. Signal generator will output CW signal to substitution antenna through a RF cable. Rotate turntable and move antenna to find maximum radiated emission. Adjust output power of signal generator to let the maximum radiated emission is same as step 3. Record the output power level.
5. E.I.R.P = output power of step 4 + gain of substitution antenna – cable loss of RF cable.

3.2.3 Test Setup

Radiated Emissions below 1 GHz



Radiated Emissions above 1 GHz



3.2.4 Test Result of Radiated Emissions below 1GHz

Mode	GSM, Channel : 810 (Adapter mode)						
Frequency (MHz)	Antenna Polarity	E.I.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Vaule (dBm)	Correction Factor (dB)
167.74	H	-54.63	-13	-41.63	-46.19	-56.51	1.88
233.7	H	-59.83	-13	-46.83	-49.9	-65.54	5.71
307.42	H	-59.07	-13	-46.07	-51.69	-64.64	5.57
363.68	H	-58.73	-13	-45.73	-51.85	-64.27	5.54
592.6	H	-61.4	-13	-48.4	-58.64	-65.8	4.4
701.24	H	-59.55	-13	-46.55	-58.17	-63.8	4.25
95.96	V	-42.12	-13	-29.12	-32.7	-42.59	0.47
165.8	V	-52.5	-13	-39.5	-49.81	-54.09	1.59
261.83	V	-43.44	-13	-30.44	-36.07	-49.03	5.59
411.21	V	-47.94	-13	-34.94	-44.46	-53.31	5.37
508.21	V	-46.69	-13	-33.69	-44.64	-51.83	5.14
801.15	V	-55.76	-13	-42.76	-57.41	-59.6	3.84

Note: EIRP = S.G Power value + Correction factor

Mode	GSM, Channel : 810 (Cradle mode)						
Frequency (MHz)	Antenna Polarity	E.I.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Vaule (dBm)	Correction Factor (dB)
38.73	H	-52.15	-13	-39.15	-48.41	-40.53	-11.62
88.2	H	-43.45	-13	-30.45	-30.36	-43.69	0.24
164.83	H	-53.66	-13	-40.66	-45.37	-55.1	1.44
232.73	H	-58.14	-13	-45.14	-48.16	-63.86	5.72
363.68	H	-57.76	-13	-44.76	-50.88	-63.3	5.54
701.24	H	-58.97	-13	-45.97	-57.59	-63.22	4.25
39.7	V	-44.62	-13	-31.62	-36.09	-33.07	-11.55
87.23	V	-36.23	-13	-23.23	-25.76	-36.39	0.16
107.6	V	-47.23	-13	-34.23	-39.24	-47.58	0.35
390.84	V	-49.11	-13	-36.11	-44.97	-54.6	5.49
634.31	V	-51.66	-13	-38.66	-51.44	-55.97	4.31
801.15	V	-55.04	-13	-42.04	-56.69	-58.88	3.84

Note: EIRP = S.G Power value + Correction factor

3.2.5 Test Result of Radiated Emissions above 1GHz

Mode	GSM , Channel : 512						
Frequency (MHz)	Antenna Polarity	E.I.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Vaule (dBm)	Correction Factor (dB)
3700.40	H	-45.06	-13	-32.06	-57.12	-50.38	5.32
5550.60	H	-42.69	-13	-29.69	-60.63	-47.21	4.52
7400.80	H	-29.87	-13	-16.87	-51.87	-32.67	2.80
3700.40	V	-34.22	-13	-21.22	-46.36	-39.54	5.32
5550.60	V	-34.2	-13	-21.2	-50.9	-38.72	4.52
7400.80	V	-28.59	-13	-15.59	-48.37	-31.39	2.80

Mode	GSM , Channel : 661						
Frequency (MHz)	Antenna Polarity	E.I.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Vaule (dBm)	Correction Factor (dB)
3760.00	H	-45.03	-13	-32.03	-57.49	-50.28	5.25
5640.00	H	-43.49	-13	-30.49	-61.4	-47.85	4.36
7520.00	H	-30.72	-13	-17.72	-52.09	-33.26	2.54
3760.00	V	-34.55	-13	-21.55	-46.89	-39.8	5.25
5640.00	V	-34.71	-13	-21.71	-51.64	-39.07	4.36
7520.00	V	-28.76	-13	-15.76	-48.12	-31.3	2.54

Mode	GSM , Channel : 810						
Frequency (MHz)	Antenna Polarity.	E.I.R.P (dBm)	Limit (dBm)	Margin (dB)	S.A Reading (dBm)	S.G Power Vaule (dBm)	Correction Factor (dB)
3819.60	H	-44.9	-13	-31.9	-57.66	-50.08	5.18
5729.40	H	-42.83	-13	-29.83	-60.98	-46.99	4.16
7639.20	H	-31.38	-13	-18.38	-52.28	-33.8	2.42
3819.60	V	-34.77	-13	-21.77	-47.31	-39.95	5.18
5729.40	V	-33.23	-13	-20.23	-50.44	-37.39	4.16
7639.20	V	-29.06	-13	-16.06	-48.11	-31.48	2.42

Note: EIRP = S.G Power value + Correction factor

3.3 Conducted Emissions


3.3.1 Limit of Conducted Emissions

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB equal to -13dBm.




3.3.2 Test Procedures

1. Lowest, middle and highest operating channels are tested for this item.
2. Scan frequency range is from 30MHz~19.1GHz.
3. Set RBW = 1MHz, VBW = 3MHz, detector = Peak, sweep time = auto.
4. Record the max trace value and capture the test plot of each sub frequency band.

3.3.3 Test Setup



3.3.4 Test Result of Conducted Emissions

Mode	GSM	
Channel	512	Channel 661
	 <p>Spectrum Ref Level 34.30 dBm Offset 24.30 dB RBW 1 MHz Att 20 dB SWT 300 ms VBW 3 MHz Mode Sweep 1Pk View</p> <p>30 dBm 20 dBm 10 dBm 0 dBm -10 dBm -20 dBm -30 dBm -40 dBm -50 dBm -60 dBm</p> <p>Start 30.0 MHz 32001 pts Stop 19.1 GHz</p> <p>Date: 24.SEP.2013 22:23:39</p>	 <p>Spectrum Ref Level 34.30 dBm Offset 24.30 dB RBW 1 MHz Att 20 dB SWT 300 ms VBW 3 MHz Mode Sweep 1Pk View</p> <p>30 dBm 20 dBm 10 dBm 0 dBm -10 dBm -20 dBm -30 dBm -40 dBm -50 dBm -60 dBm</p> <p>Start 30.0 MHz 32001 pts Stop 19.1 GHz</p> <p>Date: 24.SEP.2013 22:23:02</p>
Channel	810	
	 <p>Spectrum Ref Level 34.30 dBm Offset 24.30 dB RBW 1 MHz Att 20 dB SWT 300 ms VBW 3 MHz Mode Sweep 1Pk View</p> <p>30 dBm 20 dBm 10 dBm 0 dBm -10 dBm -20 dBm -30 dBm -40 dBm -50 dBm -60 dBm</p> <p>Start 30.0 MHz 32001 pts Stop 19.1 GHz</p> <p>Date: 24.SEP.2013 22:25:32</p>	

3.4 Band Edge


3.4.1 Limit of Band Edge

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB equal to -13dBm.


3.4.2 Test Procedures

1. Lowest and highest operating channels are tested for this item.
2. The center frequency of spectrum analyzer will be set to 1850 and 1910 MHz.
3. Set RBW =10kHz, VBW = 30 kHz, span = 1 MHz, detector = RMS, sweep time = auto.
4. Record the max trace value and capture the test plot.

3.4.3 Test Setup



3.4.4 Test Result of Band Edge




3.5 Occupied Bandwidth

3.5.1 Test Procedures


1. Set resolution bandwidth (RBW) = 10 kHz, Video bandwidth = 30kHz.
2. Detector = Sample, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Using occupied bandwidth measurement function of spectrum analyzer to measure occupied bandwidth.

3.5.2 Test Setup



3.5.3 Test Result of Occupied Bandwidth

MODE	Channel	Frequency (MHz)	OBW (kHz)	26dB bandwidth(kHz)
GSM	512	1850.2	243.13	318.4
GSM	661	1880.0	247.47	318.4
GSM	810	1909.8	244.57	321.3



3.6 Peak to Average Ratio


3.6.1 Limit of Peak to Average Ratio

Peak-to-average ratio (PAR) of the transmission may not exceed 13 dB

3.6.2 Test Procedures


1. Set RBW=1MHz, RBW=3MHz, Peak detector in Trace 1
2. Set RBW=1MHz, RBW=3MHz, RMs detector in Trace 2
3. Trigger function is enabled for measuring singal at burst on time. Measure the difference between trace1 and trace 2.

3.6.3 Test Setup



3.6.4 Test Result of Peak to Average ratio

MODE	Channel	Frequency (MHz)	Peak to Average ratio (dB)
GSM	512	1850.2	0.01
GSM	661	1880.0	0.01
GSM	810	1909.8	0.01



3.7 Frequency Stability


3.7.1 Limit of Frequency Stability

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

3.7.2 Test Procedures

1. EUT was placed at temperature chamber and connected to an external power supply.
2. Temperature and voltage condition shall be tested to confirm frequency stability.
3. Temperature range is from -30~55°C and voltage range is from lowest to highest working voltage.
4. Tem Link up EUT and simulator. Confirm frequency drift value of simulator and record it.

3.7.3 Test Setup



3.7.4 Test Result of Frequency Stability

Temperature (°C)	Voltage (dc)	Frequency Drift (ppm)	Limit (ppm)
55	3.9	0.003	2.5
50	3.9	0.004	2.5
40	3.9	0.005	2.5
30	3.9	0.006	2.5
20	3.9	0.007	2.5
10	3.9	0.009	2.5
0	3.9	0.010	2.5
-10	3.9	0.010	2.5
-20	3.9	0.011	2.5
-30	3.9	0.012	2.5
20	4.29	0.008	2.5
20	3.51	0.010	2.5

4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp, it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan Hsiang. Location map can be found on our website <http://www.icertifi.com.tw>.

Linkou

Tel: 886-2-2601-1640
No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City, Taiwan, R.O.C.

Kwei Shan

Tel: 886-3-271-8666
No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666
Fax: 886-3-318-0155
Email: ICC_Service@icertifi.com.tw

==END==