

FCC TEST REPORT (BLUETOOTH LE4.0)

REPORT NO.: RF120405C14-7

MODEL NO.: FJI13

FCC ID: YUW-FJI13

RECEIVED: Apr. 05, 2012

TESTED: May 08 ~ May 15, 2012

ISSUED: Jun. 01, 2012

APPLICANT: Fujitsu Mobile Communications Ltd.

ADDRESS: 1-1, Kamikodanaka 4-chome, Nakahara-ku,

Kawasaki 211-8588, Japan

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.)

Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist., New

Taipei City, Taiwan (R.O.C)

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei

Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



Table of Contents

RELE	ASE CONTROL RECORD	
1.	CERTIFICATION	5
2.	SUMMARY OF TEST RESULTS	6
2.1	MEASUREMENT UNCERTAINTY	6
3.	GENERAL INFORMATION	7
3.1	GENERAL DESCRIPTION OF EUT	7
3.2	DESCRIPTION OF TEST MODES	8
3.2.1	TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	9
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS	
3.4	DESCRIPTION OF SUPPORT UNITS	11
3.4.1	CONFIGURATION OF SYSTEM UNDER TEST	
4.	TEST TYPES AND RESULTS	
4.1	RADIATED EMISSION AND BANDEDGE MEASUREMENT	12
4.1.1	LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT	
4.1.2	TEST INSTRUMENTS	12
4.1.3	TEST PROCEDURES	12
4.1.4	DEVIATION FROM TEST STANDARD	
4.1.5	TEST SETUP	12
4.1.6	EUT OPERATING CONDITIONS	
4.1.7	TEST RESULTS	13
4.2	CONDUCTED EMISSION MEASUREMENT	
4.2.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	21
4.2.2		
4.2.3	TEST PROCEDURES	
4.2.4	DEVIATION FROM TEST STANDARD	21
4.2.5	TEST SETUP	21
4.2.6	EUT OPERATING CONDITIONS	
4.2.7		
4.3	6DB BANDWIDTH MEASUREMENT	24
4.3.1	LIMITS OF 6DB BANDWIDTH MEASUREMENT	24
4.3.2		
4.3.3	TEST INSTRUMENTS	24
4.3.4	TEST PROCEDURE	24
4.3.5	DEVIATION FROM TEST STANDARD	24
4.3.6	EUT OPERATING CONDITIONS	24
4.3.7	TEST RESULTS	25
4.4	CONDUCTED OUTPUT POWER	
4.4.1	LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT	26
4.4.2	TEST SETUP	26



4.4.3	TEST INSTRUMENTS	.26
4.4.4	TEST PROCEDURES	.26
4.4.5	DEVIATION FROM TEST STANDARD	.26
4.4.6	EUT OPERATING CONDITIONS	.26
4.4.7	TEST RESULTS	.26
4.5	POWER SPECTRAL DENSITY MEASUREMENT	.27
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	.27
4.5.2	TEST SETUP	.27
4.5.3	TEST INSTRUMENTS	.27
4.5.4	TEST PROCEDURE	.27
4.5.5	DEVIATION FROM TEST STANDARD	.27
4.5.6	EUT OPERATING CONDITION	.27
4.5.7	TEST RESULTS	.27
4.6	CONDUCTED OUT OF BAND EMISSION MEASUREMENT	.28
4.6.1	LIMITS OF OUT OF BAND EMISSION MEASUREMENT	
4.6.2	TEST SETUP	.28
4.6.3	TEST INSTRUMENTS	
4.6.4	TEST PROCEDURE	.28
4.6.5	DEVIATION FROM TEST STANDARD	
4.6.6	EUT OPERATING CONDITION	.29
4.6.7	TEST RESULTS	.29
4.6.8	TEST RESULTS	.30
5.	PHOTOGRAPHS OF THE TEST CONFIGURATION	.31
6.	INFORMATION ON THE TESTING LABORATORIES	.32
7.	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGE	S
TO TH	HE EUT BY THE LAB	.33



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF120405C14-7	Original release	Jun. 01, 2012

Report No.: RF120425C14-7 4 of 33 Report Format Version 5.0.0



1. CERTIFICATION

PRODUCT: CDMA FJI13

MODEL: FJI13

BRAND: Fujitsu Mobile Communications Ltd.

APPLICANT: Fujitsu Mobile Communications Ltd.

TESTED: May 08 ~ May 15, 2012

TEST SAMPLE: Production Unit

STANDARDS: FCC Part 15, Subpart C (Section 15.247)

ANSI C63.10-2009

The above equipment (Model: FJI13) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch,** and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY: Jun. 01, 2012

Ivonne Wu / Senior Specialist

APPROVED BY: Jun. 01, 2012

Gary Chang / Technical Manager



2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247) (Bluetooth LE 4.0)							
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK				
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -12.63dB at 1.38672MHz.				
15.247(d) 15.209	Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -2.06dB at 7440.00MHz.				
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.				
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.				
15.247(b)	Conducted power	PASS	Meet the requirement of limit.				
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.				
15.203	Antenna Requirement	PASS	No antenna connector is used.				

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY		
Conducted emissions	9kHz~30MHz	2.44 dB		
	30MHz ~ 200MHz	2.93 dB		
Radiated emissions	200MHz ~1000MHz	2.95 dB		
Radiated emissions	1GHz ~ 18GHz	2.26 dB		
	18GHz ~ 40GHz	1.94 dB		

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

EUT	CDMA FJI13		
MODEL NO.	FJI13		
POWER SUPPLY	5.0Vdc (adapter)		
POWER SUPPLY	3.7Vdc (Li-ion batte	ry)	
MODULATION TYPE	Bluetooth LE 4.0	GFSK	
TRANSFER RATE	Bluetooth LE 4.0 1Mbps		
OPERATING FREQUENCY	2402 ~ 2480MHz		
NUMBER OF CHANNEL	Bluetooth LE 4.0 40		
CHANNEL SPACING	Bluetooth LE 4.0	2MHz	
OUTPUT POWER	Bluetooth LE 4.0 0.007W		
ANTENNA TYPE	Dipole antenna with -3.2dBi gain		
ANTENNA CONNECTOR	NA		
DATA CABLE	NA		
I/O PORTS	Refer to user's manual		
ACCESSORY DEVICES	Refer to Note as be	low	

NOTE:

1. The EUT contains following accessory and components.

ITEM	BRAND	MODEL	SPECIFICATION
Battery	Panasonic	FJI13UAA	Rating: 3.7Vdc, 1800mAh Type: Li-ion
LCD Panel	TMD	LT046MDY0000	
Camera 1	SONY	IU091F-Z	
Camera 2	SAMSUNG	S5K6AAFX13	
WLAN/BT Module	TI	WL1283	
WiMAX Module	Broadcom	BCSM350	

2. The following accessory is for support unit only.

ITEM	BRAND	MODEL	SPECIFICATION
Adapter	HOSHIDEN	ΙΟΣΟΔΡΙΔ	Input: 100-240Vac, 220mA Output: 5Vdc, 600mA

3. The above EUT information is declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.



3.2 DESCRIPTION OF TEST MODES

For Bluetooth LE 4.0:

40 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480



3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

FOR Bluetooth LE 4.0:

EUT		APPLICA	ABLE TO		
CONFIGURE MODE	RE≥1G	RE<1G	PLC	APCM	DESCRIPTION
-	V	\checkmark	V	\checkmark	-

Where RE≥1G: Radiated Emission above 1GHz RE<1G: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission APCM: Antenna Port Conducted Measurement

NOTE: 1. The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **X-plane**.

2. "-"means no effect.

RADIATED EMISSION TEST (ABOVE 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE	AVAILABLE	TESTED	MODULATION	DATA RATE (Mbps)
MODE	CHANNEL	CHANNEL	TYPE	
-	0 to 39	0, 19, 39	GFSK	1.0

RADIATED EMISSION TEST (BELOW 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE	AVAILABLE	TESTED	MODULATION	DATA RATE (Mbps)
MODE	CHANNEL	CHANNEL	TYPE	
-	0 to 39	19	GFSK	1.0

POWER LINE CONDUCTED EMISSION TEST:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
	0 to 39	19	GFSK	1.0

Report No.: RF120425C14-7 9 of 33 Report Format Version 5.0.0



ANTENNA PORT CONDUCTED MEASUREMENT:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE	AVAILABLE	TESTED	MODULATION	DATA RATE (Mbps)
MODE	CHANNEL	CHANNEL	TYPE	
-	0 to 39	0, 19, 39	GFSK	1.0

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE≥1G	25deg. C, 65%RH	120Vac, 60Hz	Kay Wu
RE<1G	25deg. C, 65%RH	120Vac, 60Hz	Kay Wu
PLC	22deg. C, 56%RH	120Vac, 60Hz	Skys Huang
APCM	25deg. C, 65%RH	120Vac, 60Hz	Phoenix Chen

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)
ANSI C63.10-2009
558074 D01 DTS Meas Guidance v01


All test items have been performed and recorded as per the above standards.



3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units.

3.4.1 CONFIGURATION OF SYSTEM UNDER TEST





4. TEST TYPES AND RESULTS

4.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT

4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT Same as 4.1.1.

4.1.2 TEST INSTRUMENTS

Same as 4.1.2.

4.1.3 TEST PROCEDURES

Same as 4.1.3.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation.

4.1.5 TEST SETUP

Same as 4.1.5.

4.1.6 EUT OPERATING CONDITIONS

Same as 4.1.6.




4.1.7 TEST RESULTS

ABOVE 1GHz DATA



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch



Site : 966 Chamber 5 Condition : FCC CLASS-B 3m ANT_18G~40G_HF HORIZONTAL

Brand/Model: FJI13

Remark : BT4.0 TX CH00 Tested by : Kay Wu

Temprature : 25℃ Humidity : 65% Plane : X


	Freq	Level	Read Level			Antenna Factor			A/Pos	T/Pos	Remark
(S <u>*</u>	MHz	dBuV/m	dBuV	dBuV/m	dB	dB/m	dB	dB	cm	deg	<u> </u>
1	2368.00	44.51	50.00	54.00	-9.49	27.16	4.85	37.50	129	60	Average
2	2368.00	56.53	62.02	74.00	-17.47	27.16	4.85	37.50	129	60	Peak
3 pp	2402.00	99.42	104.81			27.26	4.87	37.52	129	60	Average
4 pk	2402.00	100.80	106.19			27.26	4.87	37.52	129	60	Peak
5	2486.00	45.03	49.93	54.00	-8.97	27.50	4.92	37.32	129	60	Average
6	2486.00	56.24	61.14	74.00	-17.76	27.50	4.92	37.32	129	60	Peak
7!	7206.00	48.20	54.83	54.00	-5.80	35.97	9.57	52.17	127	14	Average
8	7206.00	54.05	60.68	74.00	-19.95	35.97	9.57	52.17	127	14	Peak



25000



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch



Frequency (MHz)

Site : 966 Chamber 5

4000.

6000.

Condition : FCC CLASS-B 3m ANT_18G~40G_HF VERTICAL

Brand/Model: FJI13

: BT4.0 TX CH00 Remark

Tested by : Kay Wu Temprature : 25℃ Humidity : 65% Plane

		-,							4 (0	T (D	
	Freq	Level	Read Level			Factor		Preamp Factor	A/Pos	1/Pos	Remark
<u> </u>	MHz	dBuV/m	dBuV	dBuV/m	dB	dB/m	dB	dB	Cm	deg	# <u></u>
1	2380.00	44.48	49.92	54.00	-9.52	27.21	4.85	37.50	100	194	Average
2	2380.00	56.30	61.74	74.00	-17.70	27.21	4.85	37.50	100	194	Peak
3 pp	2402.00	91.85	97.24			27.26	4.87	37.52	100	194	Average
4 pk	2402.00	93.42	98.81			27.26	4.87	37.52	100	194	Peak
5	2500.00	45.20	49.96	54.00	-8.80	27.55	4.94	37.25	100	194	Average
6	2500.00	55.49	60.25	74.00	-18.51	27.55	4.94	37.25	100	194	Peak
7!	7206.00	48.19	54.82	54.00	-5.81	35.97	9.57	52.17	130	306	Average
8	7206.00	54.35	60.98	74.00	-19.65	35.97	9.57	52.17	130	306	Peak




25000



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

8000. 10000. 12000. 14000. 16000. 18000. 20000. 22000.

Frequency (MHz)



Site : 966 Chamber 5

4000.

6000.

Condition : FCC CLASS-B 3m ANT_18G~40G_HF HORIZONTAL

Brand/Model: FJI13

10

1000

Remark : BT4.0 TX CH19


Tested by : Kay Wu Temprature : 25°C Humidity : 65% Plane : X

	Freq	Level	Read Level			Antenna Factor		Preamp Factor	A/Pos	T/Pos	Remark
<u> </u>	MHz	dBuV/m	dBuV	dBuV/m	dB	dB/m	dB	dB		deg	P
1	2332.00	44.38	50.00	54.00	-9.62	27.06	4.79	37.47	125	62	Average
2	2332.00	55.88	61.50	74.00	-18.12	27.06	4.79	37.47	125	62	Peak
3 pp	2440.00	98.17	103.34			27.40	4.89	37.46	125	62	Average
4 pk	2440.00	99.36	104.53			27.40	4.89	37.46	125	62	Peak
5	2488.00	45.27	50.12	54.00	-8.73	27.55	4.92	37.32	125	62	Average
6	2488.00	55.96	60.81	74.00	-18.04	27.55	4.92	37.32	125	62	Peak
7	7320.00	47.46	53.34	54.00	-6.54	36.26	9.63	51.77	131	13	Average
8	7320.00	54.70	60.58	74.00	-19.30	36.26	9.63	51.77	131	13	Peak





Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch



Frequency (MHz)

Site : 966 Chamber 5

Condition : FCC CLASS-B 3m ANT_18G~40G_HF VERTICAL

Brand/Model: FJI13

Remark : BT4.0 TX CH19

Tested by : Kay Wu Temprature : 25℃ Humidity : 65% Plane

			Read	Limit	Over	Antenna	Cable	Preamp	A/Pos	T/Pos	
	Freq	Level	Level	Line		Factor		1.5	197	950	Remark
25 <u>-</u>	MHz	dBuV/m	dBuV	dBuV/m	dB	dB/m	dB	dB	cm	deg	<u> </u>
1	2360.00	44.39	49.90	54.00	-9.61	27.16	4.82	37.49	119	195	Average
2	2360.00	55.06	60.57	74.00	-18.94	27.16	4.82	37.49	119	195	Peak
3 pp	2440.00	88.66	93.83			27.40	4.89	37.46	119	195	Average
4 pk	2440.00	90.11	95.28			27.40	4.89	37.46	119	195	Peak
5	2494.00	45.17	49.93	54.00	-8.83	27.55	4.94	37.25	119	195	Average
6	2494.00	55.75	60.51	74.00	-18.25	27.55	4.94	37.25	119	195	Peak
7!	7320.00	48.25	54.13	54.00	-5.75	36.26	9.63	51.77	100	383	Average
8	7320.00	54.97	60.85	74.00	-19.03	36.26	9.63	51.77	100		Peak




25000



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

8000. 10000. 12000. 14000. 16000. 18000. 20000. 22000.

Frequency (MHz)



Site : 966 Chamber 5

4000.

6000.

Condition : FCC CLASS-B 3m ANT_18G~40G_HF HORIZONTAL

Brand/Model: FJI13

10

1000

Remark : BT4.0 TX CH39


Tested by : Kay Wu Temprature : 25°C Humidity : 65% Plane : X

	Freq	Level	Read Level	Limit Line		Antenna Factor		Preamp Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dBuV	dBuV/m	dB	dB/m	dB	dB	cm	deg	() <u>-</u>
1	2358.00	44.59	50.10	54.00	-9.41	27.16	4.82	37.49	123	58	Average
2	2358.00	56.81	62.32	74.00	-17.19	27.16	4.82	37.49	123	58	Peak
3 pp	2480.00	99.77	104.67			27.50	4.92	37.32	123	58	Average
4 pk	2480.00	101.46	106.36			27.50	4.92	37.32	123	58	Peak
5	2484.00	45.23	50.13	54.00	-8.77	27.50	4.92	37.32	123	58	Average
6!	7440.00	49.77	54.89	54.00	-4.23	36.55	9.71	51.38	106	29	Average
7	7440.00	54.16	59.28	74.00	-19.84	36.55	9.71	51.38	106	29	Peak





Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch



Frequency (MHz)

Site : 966 Chamber 5

Condition : FCC CLASS-B 3m ANT_18G~40G_HF VERTICAL

Brand/Model: FJI13

Remark : BT4.0 TX CH39

Tested by : Kay Wu Temprature : 25°C Humidity : 65% Plane : X


		•	355 A	0.8556 2300	325	20 00	N287220	75 <u>2</u> 5	5,6353	925925	
	Freq	Level	Read Level			Antenna Factor		Preamp Factor	A/Pos	T/Pos	Remark
<u> </u>	MHz	dBuV/m	dBuV	dBuV/m	dB	dB/m	dB	dB	cm	deg	
1	2350.00	44.61	50.17	54.00	-9.39	27.11	4.82	37.49	100	357	Average
2	2350.00	56.80	62.36	74.00	-17.20	27.11	4.82	37.49	100	357	Peak
3 pp	2480.00	89.41	94.31			27.50	4.92	37.32	100	357	Average
4 pk	2480.00	90.64	95.54			27.50	4.92	37.32	100	357	Peak
5	2500.00	45.44	50.20	54.00	-8.56	27.55	4.94	37.25	100	357	Average
6	2500.00	56.52	61.28	74.00	-17.48	27.55	4.94	37.25	100	357	Peak
7!	7440.00	51.94	57.06	54.00	-2.06	36.55	9.71	51.38	101	343	Average
8	7440.00	58.40	63.52	74.00	-15.60	36.55	9.71	51.38	101	343	Peak



BELOW 1GHz WORST-CASE DATA



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch



Site : 966 Chamber 5 Condition : FCC CLASS-B 3m ANT_30M~1G_LF HORIZONTAL


Brand/Model: FJI13 Remark : BT4.0 TX LF Tested by : Kay Wu Temprature : 25℃ Humidity : 65% Plane : X

	Freq	Level	Read Level			Antenna Factor		100	A/Pos	T/Pos	Remark
8	MHz	dBuV/m	dBuV	dBuV/m	dB	dB/m	dB	dB	Cm	deg	
1	137.73	31.58	49.78	43.50	-11.92	12.21	1.28	31.69	100	212	Peak
2	198.48	29.87	50.61	43.50	-13.63	9.43	1.59	31.76	100	258	Peak
3 pp	246.54	40.81	59.55	46.00	-5.19	11.32	1.82	31.88	100	221	Peak
4	369.30	29.52	44.53	46.00	-16.48	14.61	2.30	31.92	100	266	Peak
5	406.40	32.96	47.09	46.00	-13.04	15.46	2.45	32.04	100	41	Peak
6	475.70	29.05	41.39	46.00	-16.95	16.83	2.70	31.87	100	199	Peak





Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch



Site : 966 Chamber 5

Condition : FCC CLASS-B 3m ANT_30M~1G_LF VERTICAL

Brand/Model: FJI13
Remark : BT4.0 TX LF
Tested by : Kay Wu
Temprature : 25℃
Humidity : 65%
Plane : X

	Freq	Level	Read Level			Antenna Factor			A/Pos	T/Pos	Remark
12 <u>5</u>	MHz	dBuV/m	dBuV	dBuV/m	dB	dB/m	dB	dB	Cm	deg	
1 pp	39.72	29.29	46.09	40.00	-10.71	13.54	0.65	30.99	100	174	Peak
2	138.81	26.96	45.06	43.50	-16.54	12.27	1.29	31.66	100	132	Peak
3	247.08	29.42	48.14	46.00	-16.58	11.36	1.82	31.90	100	227	Peak
4	410.60	26.64	40.63	46.00	-19.36	15.54	2.46	31.99	212	221	Peak
5	482.00	30.13	42.28	46.00	-15.87	16.96	2.72	31.83	123	21	Peak
6	497.40	29.59	41.21	46.00	-16.41	17.27	2.77	31.66	102	285	Peak



4.2 CONDUCTED EMISSION MEASUREMENT

4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

Same as 4.2.1.

4.2.2 TEST INSTRUMENTS

Same as 4.2.2.

4.2.3 TEST PROCEDURES

Same as 4.2.3.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

4.2.5 TEST SETUP

Same as 4.2.5.

4.2.6 EUT OPERATING CONDITIONS

Same as 4.2.6.



4.2.7 TEST RESULTS


CONDUCTED WORST CASE DATA:

PHASE	Line 1	6dB BANDWIDTH	9kHz
-------	--------	---------------	------

	Freq. Corr.		Reading Value		Emission Level		Limit		Margin	
No	rreq.	Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16562	0.27	47.90	29.03	48.17	29.30	65.18	55.18	-17.01	-25.88
2	0.35703	0.29	39.43	27.68	39.72	27.97	58.80	48.80	-19.08	-20.83
3	0.62656	0.30	38.46	24.71	38.76	25.01	56.00	46.00	-17.24	-20.99
4	1.38672	0.33	43.04	23.76	43.37	24.09	56.00	46.00	-12.63	-21.91
5	2.49219	0.39	38.51	22.36	38.90	22.75	56.00	46.00	-17.10	-23.25
6	22.68359	0.70	27.04	11.61	27.74	12.31	60.00	50.00	-32.26	-37.69

REMARKS:

- 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
- 2. The emission levels of other frequencies were very low against the limit.
- 3. Margin value = Emission level Limit value
- 4. Correction factor = Insertion loss + Cable loss
- 5. Emission Level = Correction Factor + Reading Value.






PHASE Line 2	6dB BANDWIDTH	9kHz
--------------	---------------	------

	Eroa	Corr.			Emission Level		Limit		Margin	
No	Freq.	Factor			[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16172	0.29	47.42	27.38	47.71	27.67	65.38	55.38	-17.67	-27.71
2	0.24766	0.29	37.16	25.41	37.45	25.70	61.84	51.84	-24.38	-26.13
3	0.62266	0.31	38.01	24.78	38.32	25.09	56.00	46.00	-17.68	-20.91
4	1.39453	0.35	42.94	23.48	43.29	23.83	56.00	46.00	-12.71	-22.17
5	2.24219	0.40	38.03	22.52	38.43	22.92	56.00	46.00	-17.57	-23.08
6	22.92969	0.83	24.84	14.98	25.67	15.81	60.00	50.00	-34.33	-34.19

REMARKS:

- 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
- 2. The emission levels of other frequencies were very low against the limit.
- 3. Margin value = Emission level Limit value
- 4. Correction factor = Insertion loss + Cable loss
- 5. Emission Level = Correction Factor + Reading Value.






4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST SETUP



4.3.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.3.4 TEST PROCEDURE

- 1. Set resolution bandwidth (RBW) = approximately 1% of the emission bandwidth
- 2. Set the video bandwidth (VBW) \geq 3 x RBW, Detector = Peak.
- 3. Trace mode = max hold.
- 4. Sweep = auto couple.
- 5. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

4.3.5 DEVIATION FROM TEST STANDARD

No deviation.

4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



4.3.7 TEST RESULTS

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL	
0	2402	0.668	0.5	PASS	
19	2440	0.664	0.5	PASS	
39	2480	0.668	0.5	PASS	




4.4 CONDUCTED OUTPUT POWER

4.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz: 1 Watt (30dBm)

4.4.2 TEST SETUP



4.4.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.4.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the peak power level.

4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6.

4.4.7 TEST RESULTS

CHANNEL	FREQUENCY (MHz)	PEAK POWER (W)	PEAK POWER (dBm)	LIMIT (dBm)	PASS/FAIL
0	2402	0.006	7.65	30	PASS
19	2440	0.007	8.22	30	PASS
39	2480	0.006	7.58	30	PASS




4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST SETUP



4.5.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.5.4 TEST PROCEDURE

- a. Set the RBW = 100 kHz, VBW =300 kHz, Detector = peak.
- b. Sweep time = auto couple, Trace mode = max hold, allow trace to fully stabilize.
- c. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.
- d. Scale the observed power level to an equivalent value in 3 kHz by adjusting (reducing) the measured power by a bandwidth correction factor (BWCF) where BWCF = 10log(3 kHz/100kHz)

4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

4.5.6 EUT OPERATING CONDITION

Same as Item 4.3.6

4.5.7 TEST RESULTS

Channel	FREQ. (MHz)	PSD (dBm/100kHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
0	2402	6.45	-8.75	8	PASS
19	2440	7.17	-8.03	8	PASS
39	2480	6.48	-8.72	8	PASS



4.6 CONDUCTED OUT OF BAND EMISSION MEASUREMENT

4.6.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 TEST SETUP



4.6.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.6.4 TEST PROCEDURE

MEASUREMENT PROCEDURE REF

- 1. Set the RBW = 100 kHz.
- 2. Set the VBW ≥ 300 kHz.
- 3. Detector = peak.
- 4. Sweep time = auto couple.
- 5. Trace mode = max hold.
- 6. Allow trace to fully stabilize.
- 7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.



MEASUREMENT PROCEDURE OOBE

- 1. Set RBW = 100 kHz.
- 2. Set VBW ≥ 300 kHz.
- 3. Set span to encompass the spectrum to be examined
- 4. Detector = peak.
- 5. Trace Mode = max hold.
- 6. Sweep = auto couple.

4.6.5 DEVIATION FROM TEST STANDARD

No deviation.

4.6.6 EUT OPERATING CONDITION


Same as Item 4.3.6

4.6.7 TEST RESULTS

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.



4.6.8 TEST RESULTS





5. PHOTOGRAPHS OF THE TEST CONFIGURATION
Please refer to the attached file (Test Setup Photo).



6. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab: Hsin Chu EMC/RF Lab: Tel: 886-2-26052180 Tel: 886-3-5935343

Fax: 886-2-26051924 Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety Telecom Lab:

Tel: 886-3-3183232 Fax: 886-3-3185050

Email: service.adt@tw.bureauveritas.com

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.



7. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No modifications were made to the EUT by the lab during the test.

--- END ---