

# FCC TEST REPORT (BLUETOOTH LE4.0)

**REPORT NO.:** RF120716C28-4

**MODEL NO.:** FJL21

FCC ID: YUW-FJL21

**RECEIVED:** Jul. 16, 2012

**TESTED:** Aug. 08 ~ Aug. 24, 2012

**ISSUED:** Aug. 27, 2012

APPLICANT: Fujitsu Mobile Communications Ltd.

ADDRESS: 1-1, Kamikodanaka 4-chome, Nakahara-ku,

Kawasaki 211-8588, Japan

**ISSUED BY:** Bureau Veritas Consumer Products Services (H.K.)

Ltd., Taoyuan Branch

**LAB ADDRESS:** No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist., New

Taipei City, Taiwan (R.O.C.)

**TEST LOCATION:** No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei

Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



# **Table of Contents**

RELE	ASE CONTROL RECORD	4
1.	CERTIFICATION	
2.	SUMMARY OF TEST RESULTS	6
2.1	MEASUREMENT UNCERTAINTY	6
3.	GENERAL INFORMATION	
3.1	GENERAL DESCRIPTION OF EUT	7
3.2	DESCRIPTION OF TEST MODES	8
3.2.1	TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	9
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS	10
3.4	DESCRIPTION OF SUPPORT UNITS	
3.4.1	CONFIGURATION OF SYSTEM UNDER TEST	11
4.	TEST TYPES AND RESULTS	
4.1	RADIATED EMISSION AND BANDEDGE MEASUREMENT	12
4.1.1	LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT	12
4.1.2	TEST INSTRUMENTS	13
4.1.3	TEST PROCEDURES	
4.1.4	DEVIATION FROM TEST STANDARD	14
4.1.5	TEST SETUP	15
4.1.6	EUT OPERATING CONDITIONS	15
4.1.7	TEST RESULTS	
4.2	CONDUCTED EMISSION MEASUREMENT	20
4.2.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	20
4.2.2	TEST INSTRUMENTS	
4.2.3	TEST PROCEDURES	21
4.2.4	DEVIATION FROM TEST STANDARD	
4.2.5	TEST SETUP	
4.2.6	EUT OPERATING CONDITIONS	22
4.2.7	TEST RESULTS	
4.3	6dB BANDWIDTH MEASUREMENT	
4.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT	
4.3.2	TEST SETUP	
4.3.3	TEST INSTRUMENTS	
4.3.4	TEST PROCEDURE	
4.3.5	DEVIATION FROM TEST STANDARD	
4.3.6		
	TEST RESULTS	26
4.4	CONDUCTED OUTPUT POWER	
	LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT	
	TEST SETUP	
4.4.3	TEST INSTRUMENTS	
4.4.4	TEST PROCEDURES	
4.4.5	DEVIATION FROM TEST STANDARD	
4.4.6	EUT OPERATING CONDITIONS	
4.4.7	TEST RESULTS	
4.5	POWER SPECTRAL DENSITY MEASUREMENT	
	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	
4.5.2	TEST SETUP	28



4.5.3	TEST INSTRUMENTS	28
4.5.4	TEST PROCEDURE	28
4.5.5	DEVIATION FROM TEST STANDARD	28
4.5.6	EUT OPERATING CONDITION	28
4.5.7	TEST RESULTS	28
4.6	CONDUCTED OUT OF BAND EMISSION MEASUREMENT	29
4.6.1	LIMITS OF OUT OF BAND EMISSION MEASUREMENT	29
4.6.2	TEST SETUP	29
4.6.3	TEST INSTRUMENTS	29
4.6.4	TEST PROCEDURE	29
4.6.5	DEVIATION FROM TEST STANDARD	30
4.6.6	EUT OPERATING CONDITION	30
4.6.7	TEST RESULTS	30
4.6.8	TEST RESULTS	31
5.	PHOTOGRAPHS OF THE TEST CONFIGURATION	32
6.	INFORMATION ON THE TESTING LABORATORIES	33
7.	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGE	
	TO THE EUT BY THE LAB	34



# **RELEASE CONTROL RECORD**

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF120716C28-4	Original release	Aug. 27, 2012

Report No.: RF120716C28-4 4 of 34 Report Format Version 5.0.0



# 1. CERTIFICATION

**PRODUCT:** CDMA FJL21

**MODEL NO.:** FJL21

**BRAND:** Fujitsu Mobile Communications Ltd.

APPLICANT: Fujitsu Mobile Communications Ltd.

**TESTED:** Aug. 08 ~ Aug. 24, 2012

**TEST SAMPLE:** ENGINEERING SAMPLE

STANDARDS: FCC Part 15, Subpart C (Section 15.247)

ANSI C63.10-2009

The above equipment (Model: FJL21) has been tested by Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY: Andrea Hsia / Specialist

, **DATE** : \_\_Aug. 27, 2012 APPROVED BY



# 2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)							
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK				
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -15.57dB at 1.32031MHz.				
15.247(d) 15.209	Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -3.0dB at 175.5MHz.				
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.				
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.				
15.247(b)	Conducted power	PASS	Meet the requirement of limit.				
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.				
15.203	Antenna Requirement	PASS	No antenna connector is used.				

#### 2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY	
Conducted emissions	9kHz~30MHz	2.44 dB	
	30MHz ~ 200MHz	3.19 dB	
Radiated emissions	200MHz ~1000MHz	3.21 dB	
Radiated emissions	1GHz ~ 18GHz	2.26 dB	
	18GHz ~ 40GHz	1.94 dB	

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



# 3. GENERAL INFORMATION 3.1 GENERAL DESCRIPTION OF EUT

EUT	CDMA FJL21
MODEL NO.	FJL21
POWER SUPPLY	5.0Vdc (adapter)
	3.7Vdc (Li-ion battery)
MODULATION TYPE	GFSK
TRANSFER RATE	1Mbps
OPERATING FREQUENCY	2402 ~ 2480MHz
NUMBER OF CHANNEL	40
CHANNEL SPACING	2MHz
OUTPUT POWER	0.521mW
ANTENNA TYPE	$\lambda$ /4 Monopole antenna with -5.35dBi gain
ANTENNA CONNECTOR	NA
DATA CABLE	NA
I/O PORTS	Refer to user's manual
ACCESSORY DEVICES	Battery

#### NOTE:

1. The EUT consumes power from the following internal Li-ion battery.

BATTERY					
BRAND	SANYO				
MODEL	FJI13UAA				
RATING	3.7Vdc, 1800mAh, 6.7Wh				

2. The following accessories are for support units only.

PRODUCT	BRAND	MODEL	DESCRIPTION
Adapter	HOSHIDEN	0204PTA	I/P: 100-240Vac, 220mA O/P: 5.0Vdc, 600mA
USB cable	NA	NA	0.9m non-shielded cable without core

- 3. SW version is R23.5e.
- 4. HW version is V2.1.0.
- 5. IMEI Code: 353038050006124, 353038050006132.
- 6. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.



# 3.2 DESCRIPTION OF TEST MODES

40 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480



#### 3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT		APPLICA	ABLE TO		
CONFIGURE MODE	RE≥1G	RE<1G	PLC	APCM	DESCRIPTION
-	$\checkmark$	$\checkmark$	$\checkmark$	√	-

Where RE≥1G: Radiated Emission above 1GHz PLC: Power Line Conducted Emission RE<1G: Radiated Emission below 1GHz APCM: Antenna Port Conducted Measurement

**NOTE:** The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **Z-plane**.

# **RADIATED EMISSION TEST (ABOVE 1GHz):**

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture) and packet type.

Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	PACKET TYPE
0 to 39	0, 19, 39	GFSK	1.0

#### **RADIATED EMISSION TEST (BELOW 1GHz):**

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture) and packet type.

Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	PACKET TYPE
0 to 39	19	GFSK	1.0

#### **POWER LINE CONDUCTED EMISSION TEST:**

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture) and packet type.

Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	PACKET TYPE	
0 to 39	19	GFSK	1.0	

#### ANTENNA PORT CONDUCTED MEASUREMENT:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	PACKET TYPE
0 to 39	0, 19, 39	GFSK	1.0

Report No.: RF120716C28-4 9 of 34 Report Format Version 5.0.0



#### **TEST CONDITION:**

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE≥1G	27deg. C, 70%RH	120Vac, 60Hz	Alan Wu
RE<1G	25deg. C, 65%RH	120Vac, 60Hz	Sun Lin
PLC	25deg. C, 65%RH	120Vac, 60Hz	David Huang
APCM	25deg. C, 65%RH	120Vac, 60Hz	Phoenix Chen

# 3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)
ANSI C63.10-2009
558074 D01 DTS Meas Guidance v01

All test items have been performed and recorded as per the above standards.



# 3.4 DESCRIPTION OF SUPPORT UNITS


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	EARPHONE	PHILIPS	SBC HL150	NA	NA

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	1.8m audio cable.

**NOTE:** All power cords of the above support units are non shielded (1.8m).

# 3.4.1 CONFIGURATION OF SYSTEM UNDER TEST



Kept in a remote area



# 4. TEST TYPES AND RESULTS

# 4.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT

#### 4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

#### NOTE:

- 1. The lower limit shall apply at the transition frequencies.
- 2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
- 3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



# 4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESI7	838496/016	Jan. 03, 2012	Jan. 02, 2013
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	100115	Sep. 05, 2011	Sep. 04, 2012
BILOG Antenna SCHWARZBECK	VULB9168	9168-155	Apr. 06, 2012	Apr. 05, 2013
HORN Antenna SCHWARZBECK	BBHA 9120D	9120D-408	Jan. 05, 2012	Jan. 04, 2013
HORN Antenna SCHWARZBECK	BBHA 9170	148	Jul. 11, 2012	Jul. 10, 2013
Loop Antenna	HFH2-Z2	100070	Jan. 31, 2012	Jan. 30, 2014
Preamplifier Agilent	8449B	3008A01961	Oct. 29, 2011	Oct. 28, 2012
Preamplifier Agilent	8447D	2944A10738	Oct. 29, 2011	Oct. 28, 2012
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	309220/4	Nov. 03, 2011	Nov. 02, 2012
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	250724/4	Nov. 03, 2011	Nov. 02, 2012
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	295012/4	Nov. 03, 2011	Nov. 02, 2012
Software ADT	ADT_Radiated_ V7.6.15.9.2	NA	NA	NA
Antenna Tower inn-co GmbH	MA 4000	010303	NA	NA
Antenna Tower Controller inn-co GmbH	CO2000	019303	NA	NA
Turn Table ADT	TT100.	TT93021704	NA	NA
Turn Table Controller ADT	SC100.	SC93021704	NA	NA
Antenna Tower &Turn Table Controller MF	MF-7802	NA	NA	NA
BLUETOOTH TESTER	CBT	100870	Jan. 26, 2012	Jan. 25, 2013
High Speed Peak Power Meter	ML2495A	0842014	Apr. 28, 2012	Apr. 27, 2013
Power Sensor	MA2411B	0738404	Apr. 28, 2012	Apr. 27, 2013

- NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
  - 2. The calibration interval of the loop antenna is 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
  - 3. The test was performed in HwaYa Chamber 4.
  - 4. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
  - 5. The FCC Site Registration No. is 460141.
  - 6. The IC Site Registration No. is IC7450F-4.



#### 4.1.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

#### NOTE:


- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
- 2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
- 3. All modes of operation were investigated and the worst-case emissions are reported.

#### 4.1.4 DEVIATION FROM TEST STANDARD

No deviation.



# 4.1.5 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

# 4.1.6 EUT OPERATING CONDITIONS

- a. Placed the EUT on a testing table.
- b. Use the software to control the EUT under transmission condition continuously at specific channel frequency.



# 4.1.7 TEST RESULTS

#### **ABOVE 1GHz DATA**

EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz	
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)	
ENVIRONMENTAL CONDITIONS	24deg. C, 66%RH	TESTED BY	Alan Wu	

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M							
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	56.1 PK	74.0	-17.9	1.12 H	128	24.10	32.00
2	2390.00	44.6 AV	54.0	-9.4	1.12 H	128	12.60	32.00
3	*2402.00	83.6 PK			1.12 H	128	51.60	32.00
4	*2402.00	82.1 AV			1.12 H	128	50.10	32.00
5	4804.00	44.7 PK	74.0	-29.3	1.24 H	130	6.40	38.30
6	4804.00	33.0 AV	54.0	-21.0	1.24 H	130	-5.30	38.30
		ANTENNA	A POLARIT	Y & TEST DI	STANCE: V	ERTICAL A	T 3 M	
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	55.2 PK	74.0	-18.8	1.25 V	122	23.20	32.00
2	2390.00	43.8 AV	54.0	-10.2	1.25 V	122	11.80	32.00
3	*2402.00	84.8 PK			1.25 V	122	52.80	32.00
4	*2402.00	83.5 AV			1.25 V	122	51.50	32.00
5	4804.00	45.0 PK	74.0	-29.0	1.24 V	280	6.70	38.30
6	4804.00	32.7 AV	54.0	-21.3	1.24 V	280	-5.60	38.30

- 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
- 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission level Limit value.
- 5. " \* ": Fundamental frequency.



EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL	Channel 19	FREQUENCY RANGE	1 ~ 25GHz	
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)	
ENVIRONMENTAL CONDITIONS	24deg. C, 66%RH	TESTED BY	Alan Wu	

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)	
1	*2440.00	85.0 PK			1.10 H	114	52.90	32.10	
2	*2440.00	83.0 AV			1.10 H	114	50.90	32.10	
3	4880.00	43.5 PK	74.0	-30.5	1.17 H	174	5.00	38.50	
4	4880.00	32.3 AV	54.0	-21.7	1.17 H	174	-6.20	38.50	
5	7320.00	52.5 PK	74.0	-21.5	1.06 H	109	8.10	44.40	
6	7320.00	39.2 AV	54.0	-14.8	1.06 H	109	-5.20	44.40	
		ANTENNA	POLARITY	/ & TEST DI	STANCE: V	ERTICAL A	T 3 M		
NO.	EMISSION LIMIT ANTENNA TABLE RAW VALUE CORRECTIO								
1	*2440.00	87.5 PK			1.03 V	228	55.40	32.10	
2	*2440.00	85.6 AV			1.03 V	228	53.50	32.10	
3	4880.00	44.7 PK	74.0	-29.3	1.05 V	126	6.20	38.50	
4	4880.00	32.8 AV	54.0	-21.2	1.05 V	126	-5.70	38.50	
5	7320.00	52.2 PK	74.0	-21.8	1.16 V	222	7.80	44.40	
U	7020.00	02.2110	7 7.0	21.0	1.10				

- 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
- 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission level Limit value.
- 5. " \* ": Fundamental frequency.



EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL	Channel 39	FREQUENCY RANGE	1 ~ 25GHz	
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)	
ENVIRONMENTAL CONDITIONS	24deg. C, 66%RH	TESTED BY	Alan Wu	

		ANTENNA	POLARITY	& TEST DIS	TANCE: HO	RIZONTAL	AT 3 M	
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	85.1 PK			1.06 H	121	52.80	32.30
2	*2480.00	84.2 AV			1.06 H	121	51.90	32.30
3	2483.50	55.9 PK	74.0	-18.1	1.06 H	121	23.60	32.30
4	2483.50	44.8 AV	54.0	-9.2	1.06 H	121	12.50	32.30
5	4960.00	45.1 PK	74.0	-28.9	1.17 H	259	6.70	38.40
6	4960.00	34.0 AV	54.0	-20.0	1.17 H	259	-4.40	38.40
		ANTENNA	POLARITY	/ & TEST DI	STANCE: V	ERTICAL A	T 3 M	
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	87.2 PK			1.04 V	217	54.90	32.30
2	*2480.00	86.4 AV			1.04 V	217	54.10	32.30
3	2483.50	56.1 PK	74.0	-17.9	1.04 V	217	23.80	32.30
4	2483.50	44.7 AV	54.0	-9.3	1.04 V	217	12.40	32.30
5	4960.00	43.0 PK	74.0	-31.0	1.16 V	249	4.60	38.40
6	4960.00	31.9 AV	54.0	-22.1	1.16 V	249	-6.50	38.40

- 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
- 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission level Limit value.
- 5. " \* ": Fundamental frequency.



#### **BELOW 1GHz WORST-CASE DATA**

<b>EUT TEST CONDITION</b>		MEASUREMENT DETAIL		
CHANNEL	Channel 19	FREQUENCY RANGE	Below 1000MHz	
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak	
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Sun Lin	

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M									
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)		
1	175.50	40.5 QP	43.5	-3.0	1.50 H	97	27.30	13.20		
2	189.08	39.9 QP	43.5	-3.6	1.00 H	266	27.90	12.00		
3	255.04	30.6 QP	46.0	-15.4	1.00 H	132	17.40	13.20		
4	336.52	29.2 QP	46.0	-16.8	1.00 H	133	13.40	15.80		
5	544.10	27.0 QP	46.0	-19.0	1.00 H	44	5.90	21.10		
6	871.96	30.3 QP	46.0	-15.7	1.00 H	315	4.30	26.00		
		ANTENNA	POLARITY	/ & TEST DI	STANCE: V	ERTICAL A	T 3 M			
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)		
1	30.00	29.8 QP	40.0	-10.2	1.00 V	291	17.90	11.90		
2	191.02	31.2 QP	43.5	-12.3	2.00 V	183	19.30	11.90		
3	348.16	27.1 QP	46.0	-18.9	1.25 V	331	11.00	16.10		
4	367.56	27.4 QP	46.0	-18.6	1.00 V	0	10.80	16.60		
5	871.96	33.7 QP	46.0	-12.3	1.25 V	17	7.70	26.00		
6	959.26	33.1 QP	46.0	-12.9	1.25 V	152	6.40	26.70		

- 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
- 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission level Limit value.



#### 4.2 CONDUCTED EMISSION MEASUREMENT

# 4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED	LIMIT (dBµV)
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

**NOTE**: 1. The lower limit shall apply at the transition frequencies.

- 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
- 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

#### 4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCS30	100289	Nov. 19, 2011	Nov. 18, 2012
RF signal cable Woken	5D-FB	Cable-HYCO2-01	Dec. 29, 2011	Dec. 28, 2012
LISN ROHDE & SCHWARZ (EUT)	ESH2-Z5	100100	Dec. 30, 2011	Dec. 29, 2012
LISN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100311	Jul. 06, 2012	Jul. 05, 2013
Software ADT	BV ADT_Cond_ V7.3.7.3	NA	NA	NA

**NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

- 2. The test was performed in HwaYa Shielded Room 2.
- 3. The VCCI Site Registration No. is C-2047.



#### 4.2.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit 20dB) was not recorded.


**NOTE:** All modes of operation were investigated and the worst-case emissions are reported.

# 4.2.4 DEVIATION FROM TEST STANDARD

No deviation.



# 4.2.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

# 4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6.




# 4.2.7 TEST RESULTS

#### **CONDUCTED WORST CASE DATA:**

PHASE	Line 1	6dB BANDWIDTH	9kHz
-------	--------	---------------	------

Eron		Corr.	Readin	g Value	Emissic	n Level	Lir	nit	Mar	gin
No	Freq.	Factor	[dB	(uV)]	[dB	(uV)]	[dB	(uV)]	(d	B)
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16953	0.15	48.54	31.99	48.69	32.14	64.98	54.98	-16.29	-22.84
2	0.35703	0.17	39.64	29.17	39.81	29.34	58.80	48.80	-18.99	-19.46
3	0.90781	0.19	39.88	28.03	40.07	28.22	56.00	46.00	-15.93	-17.78
4	1.62500	0.23	38.55	22.14	38.78	22.37	56.00	46.00	-17.22	-23.63
5	2.91797	0.30	38.65	23.95	38.95	24.25	56.00	46.00	-17.05	-21.75
6	23.04297	0.60	23.51	10.19	24.11	10.79	60.00	50.00	-35.89	-39.21

- 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
- 2. The emission levels of other frequencies were very low against the limit.
- 3. Margin value = Emission level Limit value
- 4. Correction factor = Insertion loss + Cable loss
- 5. Emission Level = Correction Factor + Reading Value.






PHASE	Line 2	6dB BANDWIDTH	9kHz
FHASE	LITIE Z	OUB BANDWIDTH	SKI IZ

	Eroa	Corr.	Readin	g Value	Emissio	n Level	Lir	nit	Mai	rgin
No	Freq.	Factor	[dB	(uV)]	[dB	(uV)]	[dB	(uV)]	(d	B)
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16953	0.13	48.41	31.79	48.54	31.92	64.98	54.98	-16.44	-23.06
2	0.36094	0.16	39.50	30.97	39.66	31.13	58.71	48.71	-19.05	-17.58
3	0.89219	0.18	38.66	22.76	38.84	22.94	56.00	46.00	-17.16	-23.06
4	1.32031	0.21	40.22	23.02	40.43	23.23	56.00	46.00	-15.57	-22.77
5	2.82813	0.30	38.38	22.50	38.68	22.80	56.00	46.00	-17.32	-23.20
6	21.95313	0.69	24.51	10.49	25.20	11.18	60.00	50.00	-34.80	-38.82

- 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
- 2. The emission levels of other frequencies were very low against the limit.
- 3. Margin value = Emission level Limit value
- 4. Correction factor = Insertion loss + Cable loss
- 5. Emission Level = Correction Factor + Reading Value.






#### 4.3 6dB BANDWIDTH MEASUREMENT

#### 4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

#### 4.3.2 TEST SETUP



#### 4.3.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

### 4.3.4 TEST PROCEDURE

- 1. Set resolution bandwidth (RBW) = approximately 1% of the emission bandwidth
- 2. Set the video bandwidth (VBW)  $\geq$  3 x RBW, Detector = Peak.
- 3. Trace mode = max hold.
- 4. Sweep = auto couple.
- 5. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

#### 4.3.5 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



# 4.3.7 TEST RESULTS

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (kHz)	MINIMUM LIMIT (MHz)	PASS / FAIL	
0	2402	657.090	0.5	PASS	
19	2440	656.800	0.5	PASS	
39	2480	656.940	0.5	PASS	




#### 4.4 CONDUCTED OUTPUT POWER

#### 4.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz: 1 Watt (30dBm)

#### 4.4.2 TEST SETUP



#### 4.4.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

#### 4.4.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the peak power level.

#### 4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6.

# 4.4.7 TEST RESULTS

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS/FAIL
0	2402	0.515	-2.88	30	PASS
19	2440	0.521	-2.83	30	PASS
39	2480	0.516	-2.87	30	PASS




#### 4.5 POWER SPECTRAL DENSITY MEASUREMENT

#### 4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

#### 4.5.2 TEST SETUP



#### 4.5.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

#### 4.5.4 TEST PROCEDURE

- a. Set the RBW = 100 kHz, VBW =300 kHz, Detector = peak.
- b. Sweep time = auto couple, Trace mode = max hold, allow trace to fully stabilize.
- c. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.
- d. Scale the observed power level to an equivalent value in 3 kHz by adjusting (reducing) the measured power by a bandwidth correction factor (BWCF) where BWCF = 10log(3 kHz/100kHz)

#### 4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.5.6 EUT OPERATING CONDITION

Same as Item 4.3.6

#### 4.5.7 TEST RESULTS

Channel	FREQ. (MHz)	PSD (dBm/100kHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
0	2402	-7.07	-22.30	8	PASS
19	2440	-7.06	-22.29	8	PASS
39	2480	-7.37	-22.60	8	PASS

Report No.: RF120716C28-4 28 of 34 Report Format Version 5.0.0



#### 4.6 CONDUCTED OUT OF BAND EMISSION MEASUREMENT

#### 4.6.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

#### 4.6.2 TEST SETUP



#### 4.6.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

# 4.6.4 TEST PROCEDURE

#### **MEASUREMENT PROCEDURE REF**

- 1. Set the RBW = 100 kHz.
- 2. Set the VBW ≥ 300 kHz.
- 3. Detector = peak.
- 4. Sweep time = auto couple.
- 5. Trace mode = max hold.
- 6. Allow trace to fully stabilize.
- 7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.



#### **MEASUREMENT PROCEDURE OOBE**

- 1. Set RBW = 100 kHz.
- 2. Set VBW ≥ 300 kHz.
- 3. Set span to encompass the spectrum to be examined
- 4. Detector = peak.
- 5. Trace Mode = max hold.
- 6. Sweep = auto couple.

#### 4.6.5 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.6.6 EUT OPERATING CONDITION


Same as Item 4.3.6

# 4.6.7 TEST RESULTS

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.



# 4.6.8 TEST RESULTS





5. PHOTOGRAPHS OF THE TEST CONFIGURATION
Please refer to the attached file (Test Setup Photo).



# 6. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

 Linko EMC/RF Lab:
 Hsin Chu EMC/RF Lab:

 Tel: 886-2-26052180
 Tel: 886-3-5935343

 Fax: 886-2-26051924
 Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety Telecom Lab:

Tel: 886-3-3183232 Fax: 886-3-3270892

Email: <a href="mailto:service.adt@tw.bureauveritas.com">service.adt@tw.bureauveritas.com</a>

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.



# 7. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No modifications were made to the EUT by the lab during the test.

--- END ---