



## **RF Exposure Considerations for FCC ID: YVELB1DX**

The FCC requires that the calculated MPE be equal to or less than a given limit dependent on frequency at a distance of 20 cm from a device to the body of a user.

The following FCC Rule Parts and procedures are applicable:

Part 1.1310 – Radiofrequency radiation exposure limits

Part 2.1091 – Radiofrequency radiation exposure evaluation: mobile devices

KDB447498 D01 v06

Mobile and Portable Devices RF Exposure Procedures and Equipment Authorisation Policies

### **MPE CALCULATIONS**

The MPE calculation used to calculate the safe operating distance for the user.

$$S = EIRP/4 \pi R^2$$

**Where**

S = Power density

EIRP = Effective Isotropic Radiated Power (EIRP = P x G)

P = Conducted Transmitter Power

G = Antenna Gain (relative to an isotropic radiator)

R = distance to the centre of radiation of the antenna (safe operating distance)

### **For BT**

Values:

Transmitter frequency range = 2402MHz to 2480MHz

P = 14dBm average max (0.025mW)

G = 2.0dBi (x1.58)

R = 20cm



### Power Density Requirement

From table 1 (b) - Limits for General Population/ Uncontrolled Exposure of FCC Rule Part 1.1310 for 2400MHz

$$S = 1.0 \text{ mW/cm}^2$$

### Calculation:

$$S = \text{EIRP} / 4 \pi R^2$$

$$S = 0.025 \times 1.58 / (12.56 \times 20^2)$$

$$S = 0.034 / (5024)$$

ie:

$$S < 1.0 \text{ mW/cm}^2$$

### For BT LE

#### Values:

Transmitter frequency range = 2402MHz to 2480MHz

P = 10dBm average max (0.010mW)

G = 2.0dBi (x1.58)

R = 20cm

### Power Density Requirement

From table 1 (b) - Limits for General Population/ Uncontrolled Exposure of FCC Rule Part 1.1310 for 2400MHz

$$S = 1.0 \text{ mW/cm}^2$$

### Calculation:

$$S = \text{EIRP} / 4 \pi R^2$$

$$S = 0.01 \times 1.58 / (12.56 \times 20^2)$$

$$S = 0.016 / (5024)$$

ie:

$$S < 1.0 \text{ mW/cm}^2$$



### For WIFI

#### Values:

Transmitter frequency range = 2412MHz to 2462MHz

P = 19dBm average max (0.079mW)

G = 2.0dBi (x1.58)

R = 20cm

### Power Density Requirement

From table 1 (b) - Limits for General Population/ Uncontrolled Exposure of FCC Rule Part 1.1310 for 2400MHz

**S = 1.0 mW/cm<sup>2</sup>**

#### Calculation:

$$S = \text{EIRP}/4 \pi R^2$$

$$S = 0.079 \times 1.58/(12.56 \times 20^2)$$

$$S = 0.125/(5024)$$

ie:

$$\mathbf{S < 1.0 \text{ mW/cm}^2}$$

### Conclusion

The required 20cm RF exposure limits for General Population/ Uncontrolled Exposure will not be exceeded for the using antennas having a maximum gain of 2.0dBi.