FCC Test Report

Report No.: AGC11581009SZ12-2F1

TEST NAME : FCC Part 15

FCC ID : YVP-S1

PRODUCT DESIGNATION: Phone Slide Keyboard Case

BRAND NAME : N/A

TEST MODEL : S1

CLIENT SHENZHEN CTECH SCIENCE & TECHNOLOGY DEVELOPMENT CO.,

LTD

DATE OF ISSUE : Nov.09, 2010

STANDARD(S) : FCC Part 15 Rules

Attestation of Global Compliance Co., Ltd.

CAUTION: This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.

Page 1 of 55

VERIFICATION OF COMPLIANCE

Applicant:	SHENZHEN CTECH SCIENCE & TECHNOLOGY DEVELOPMENT CO., LTD
Address	10G. Baihe yindu, Longgang District, Shenzhen, China
Manufacturer Name:	FLAGSHIP INDUSTRIAL DESIGN CO., LTD
Address:	A-302.Shennan Garden, Kexing Road, Nanshan District, Shenzhen, China
Product Description:	Phone Slide Keyboard Case
Brand Name:	N/A
Model Number:	S1,S2,S3,S4,S5,S6,S7,S8,S9
Model Difference	Product appearance is different, The PCB is same
FCC ID	YVP-S1
Report Number:	AGC11581009SZ12-2F1
Date of Test:	Nov. 01, 2010 to Nov.09, 2010

WE HEREBY CERTIFY THAT:

The above equipment was tested by Shenzhen Attestation of Global Compliance Science & Technology Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2003) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC Rules Part 15.247.

Checked By:

Jekey Zhang

Jekey Zhang

Nov.09, 2010

Authorized By

King Zhang

Nov.09, 2010

TABLE OF CONTENTS

1. GENERAL INFORMATION	4
1.1PRODUCT DESCRIPTION	4
1.2TABLE OF CARRIER FREQUENCYS	
1.3 RECEIVER INPUT BANDWIDTH AND BEHAVIOUR FOR REPEATED SINGLE	4
1.4 RELATED SUBMITTAL(S) / GRANT (S)	4
1.5TEST METHODOLOGY	
1.6TEST FACILITY	
1.7SPECIAL ACCESSORIES	
1.8EQUIPMENT MODIFICATIONS	
2. SYSTEM TEST CONFIGURATION	6
2.1 CONFIGURATION OF TESTED SYSTEM	6
2.2 EQUIPMENT USED IN TESTED SYSTEM	6
3. SUMMARY OF TEST RESULTS	7
4. DESCRIPTION OF TEST MODES	7
5. CONDUCTION EMISSIONS	8
5.1 MEASUREMENT PROCEDURE:	8
5.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	
5.3 MEASUREMENT EQUIPMENT USED:	
5.4 LIMITS AND MEASUREMENT RESULT:	9
6.MAXIMUM OUTPUT POWER	12
6.1 MEASUREMENT PROCEDURE:	12
6.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	12
6.3 MEASUREMENT EQUIPMENT USED:	15
6.4 LIMITS AND MEASUREMENT RESULT:	16
7.20 DB BANDWIDTH	19
7.1 MEASUREMENT PROCEDURE	19
7.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	19
7.3 MEASUREMENT EQUIPMENT USED:	
7.4 LIMITS AND MEASUREMENT RESULTS:	19
8.MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY (N/A)	23
8.1 MEASUREMENT PROCEDURE:	
8.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	
8.3 MEASUREMENT EQUIPMENT USED:	
8.4 LIMITS AND MEASUREMENT RESULT:	23

Page	3	of	55

9.OUT OF BAND EMISSION	24
9.1 MEASUREMENT PROCEDURE:	24
9.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	24
9.3 MEASUREMENT EQUIPMENT USED:	24
9.4 LIMITS AND MEASUREMENT RESULT:	24
10. NUMBER OF HOPPING FREQUENCY	40
10.1 MEASUREMENT PROCEDURE	40
10.2 TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)	40
10.3 MEASUREMENT EQUIPMENT USED	
10.4 LIMITS AND MEASUREMENT RESULT:	40
11. TIME OF OCCUPANCY (DWELL TIME)	42
11.1 MEASUREMENT PROCEDURE	42
11.2 TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)	42
11.3 MEASUREMENT EQUIPMENT USED	42
11.4 LIMITS AND MEASUREMENT RESULT	42
12. FREQUENCY SEPARATION	48
12.1 MEASUREMENT PROCEDURE	48
12.2 TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)	48
12.3 MEASUREMENT EQUIPMENT USED	48
12.4 LIMITS AND MEASUREMENT RESULT	
APPENDIX I	52
PHOTOGRAPHS OF THE EUT	52
PPENDIX II	55
PHOTOGRAPHS OF THE TEST SETUP	55

Page 4 of 55

1. GENERAL INFORMATION

1.1 PRODUCT DESCRIPTION

The EUT is a **Phone Slide Keyboard Case**; It is short range, lower power. And it is designed by way of utilizing the FHSS technology to achieve the system operation.

A major technical description of EUT is described as following:

Operation Frequency	2.402 GHz to 2.480GHz
Output Power	2.25 dBm
Modulation	GFSK
Number of channels	79
Antenna Designation	Integrated Antenna
Power Supply	Internal Lion Composite Battery DC 3.7~4.2V by battery It's only Charged from PC

1.2 TABLE OF CARRIER FREQUENCYS

Frequency Band	Channel Number	Frequency				
	0	2402MHZ				
	1	2403MHZ				
	:	:				
	38	2440 MHZ				
2400~2483.5MHZ	39	2441 MHZ				
	40	2442 MHZ				
	:	:				
	77	2479 MHZ				
	78	2480 MHZ				

1.3 RECEIVER INPUT BANDWIDTH AND BEHAVIOUR FOR REPEATED SINGLE OR MULTIPLE PACKETS

The input bandwidth of the receiver is 1MHz,In every connection one Bluetooth device is the master and the other one is slave. The master determines the hopping sequence. The slave follows this sequence. Both devices shift between RX and TX time slot according to the clock of the master.

Additionally the type of connection(e.g. single of multislot packet) is set up at the beginning of the connection. The master adapts its hopping frequency and its TX/RX timing according to the packet type of the connection. Also the slave of the connection will use these settings.

Repeating of a packet has no influence on the hopping sequence. The hopping sequence generated by the master of the connection will be followed in any case. That means, a repeated packet will not be send on the same frequency, it is send on the next frequency of the hopping sequence.

1.4 RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for FCC ID: YVP-S1 filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

Page 5 of 55

1.5 TEST METHODOLOGY

Both conducted and radiated testing were performed according to the procedures in ANSI C63.4 (2003). Radiated testing was performed at an antenna to EUT distance 3 meters.

1.6 TEST FACILITY

All measurement facilities used to collect the measurement data are located at Attestation of Global Compliance Co., Ltd.

1F, No.2 Building, Huafeng No.1 Technical, Industrial Park, Sanwei, Xixiang, Baoan District,

Shenzhen, China

The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4: 2003. FCC register No.: 259865

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with preselectors and quasi-peak detectors are used to perform radiated measurements.

1.7 SPECIAL ACCESSORIES

Not available for this EUT intended for grant.

1.8 EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

Page 6 of 55

2. SYSTEM TEST CONFIGURATION 2.1 CONFIGURATION OF TESTED SYSTEM

EUT

2.2 EQUIPMENT USED IN TESTED SYSTEM

Item	Equipment	Equipment Mfr/Brand Model/Type N		FCC ID		
1						

Page 7 of 55

3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.207	Conduction Emission	Compliant
§15.209	Radiated Emission	Compliant
§15.247	Maximum Output Power	Compliant
§15.247	20 dB Bandwidth	Compliant
§15.247	Band Edges	Compliant
§15.247	Spurious Emission	Compliant
§15.247	Frequency Separation	Compliant
§15.247	Number of Hopping Frequency	Compliant
§15.247	Time of Occupancy	Compliant

4. DESCRIPTION OF TEST MODES

- 1. The EUT has been set to operate continuously on the lowest, the middle and the highest operation frequency individually.
- 2. The EUT stays in continuous transmitting mode on the operation frequency being set.


Page 8 of 55

5. CONDUCTION EMISSIONS

5.1 MEASUREMENT PROCEDURE:

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system; a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4.
- 2. Support equipment, if needed, was placed as per ANSI C63.4.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- 4. The EUT received DC3.7V through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5. All support equipments received AC power from a second LISN, if any.
- 6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.

5.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)



5.3 MEASUREMENT EQUIPMENT USED:

Conducted Emission Test Site										
Name of Equipment	Cal. Date									
Test Receiver	Rohde & Schwarz	ESCS30	828985/018	05/29/2011						
LISN	Rohde & Schwarz	ESH2-Z5	834549/005	05/29/2011						
LISN	Rohde & Schwarz	ESH2-Z5	834549/005	05/29/2011						
50 Ω Coaxial Switch	Anritsu	MP59B	M20531	05/29/2011						

Page 9 of 55

5.4 LIMITS AND MEASUREMENT RESULT:

LIMITS OF LINE CONDUCTED EMISSION TEST

Fraguency	Maximum RF Line Voltage						
Frequency	Q.P.(dBuV)	Average(dBuV)					
150kHz~500kHz	66-56	56-46					
500kHz~5MHz	56	46					
5MHz~30MHz	60	50					

^{1**}Note: 1. The lower limit shall apply at the transition frequency.

MEASURING INSTRUMENT AND SETTING

The following table is the setting of receiver.

Receiver Parameter	Setting
Attenuation	10dB
Start Frequency	0.15MHz
Stop Frequency	30MHz
6dB bandwidth	9KHz for QP
IF bandwidth	9KHz for AV

^{2.} The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz

Page 10 of 55


TEST RESULT AT CHARGE MODE:

Operation Mode: CHARGE(connected to PC) Test Date: Nov.10, 2010

Temperature: 25°C Tested by: Jekey Zhang

Humidity: 55 % RH Polarity: --

TEST RESULT OF LINE -L CONDUCTED EMISSION TEST




Site: Conduction Phase: L1 Temperature: 26
Limit: FCC PART15 Class B Conduction(QP) Power:AC120V/60Hz Humidity: 60 %

EUT: M/N: S1 Mode: Note:

No.	Freq.	Reading_Level (dBuV)		Correct Factor	Measurement (dBuV)		I				Limit Margin (dBuV) (dB)		P/F	Comment
	(MHz)	Peak	QP	AVG	dB	Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.3620	33.48		31.69	10.27	43.75		41.96	58.68	48.68	-14.93	-6.72	Р	
2	0.4500	32.51		31.28	10.29	42.80		41.57	56.87	46.87	-14.07	-5.30	Р	
3	1.6420	35.19		30.41	11.16	46.35		41.57	56.00	46.00	-9.65	-4.43	Р	
4	2.9420	28.95		21.23	11.53	40.48		32.76	56.00	46.00	-15.52	-13.24	Р	
5	4.4820	31.66		26.46	11.98	43.64		38.44	56.00	46.00	-12.36	-7.56	Р	
6	11.7100	20.88		10.18	13.69	34.57		23.87	60.00	50.00	-25.43	-26.13	Р	

Page 11 of 55

TEST RESULT OF LINE -N CONDUCTED EMISSION TEST



Site: Conduction Phase: N Temperature: 26
Limit: FCC PART15 Class B Conduction(QP) Power:AC120V/60Hz Humidity: 60 %

EUT: M/N: S1 Mode: Note:

No.	No. Freq.		3		Correct Factor	Measurement (dBuV)				Margin (dB)		P/F	Comment	
(MHz)	Peak	QP	AVG	dB	Peak	QP	AVG	QP	AVG	QP	AVG			
1	0.4500	32.03		27.11	10.29	42.32		37.40	56.87	46.87	-14.55	-9.47	Р	
2	0.9740	31.17		27.62	10.82	41.99		38.44	56.00	46.00	-14.01	-7.56	Р	
3	1.7060	34.83		26.21	11.19	46.02		37.40	56.00	46.00	-9.98	-8.60	Р	
4	2.7139	30.71		25.16	11.47	42.18		36.63	56.00	46.00	-13.82	-9.37	Р	
5	4.3140	28.57		21.12	11.94	40.51		33.06	56.00	46.00	-15.49	-12.94	Р	

Page 12 of 55

6. MAXIMUM OUTPUT POWER

6.1 MEASUREMENT PROCEDURE:


CONDUCTED METHOD

- 1. The EUT was placed on a turn table which is 0.8m above ground plane.
- 2. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 3. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 4. Set SPA Centre Frequency = Operation Frequency, RBW= 1 MHz, VBW= 1 MHz.
- 5. Set SPA Trace 1 Max hold, then View.

RADIATED METHOD According to ANSI C63.4:2003


6.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

CONDUCTED METHOD




RADIATED EMISSION TEST SETUP

RADIATED MISSION TEST SETUP BELOW 30MHz




Page 13 of 55

RADIATED MISSION TEST SETUP 30MHz-1000MHz




RADIATED MISSION TEST SETUP ABOVE 1000MHz




EIRP TEST SETUP


TEST SETUP BELOW 1GHZ




Report No.: AGC11581009SZ12-2F1 Page 14 of 55



TEST SETUP ABOVE 1GHZ





Report No.: AGC11581009SZ12-2F1 Page 15 of 55

6.3 MEASUREMENT EQUIPMENT USED:

Description	Manufacturer	Model	SERIAL NUMBER	Cal. Date	Cal. Due
Spectrum Analyzer	Rohde & Schwarz	FSEM30	849720/019	05/29/2010	05/29/2011
Amplifier	H.P.	8449B	3008A00277	05/29/2010	05/29/2011
Horn Antenna	Sunol Sciences	DRH-118	A052604	05/29/2010	05/29/2011
Horn Antenna	A.H. Systems Inc.	SAS-574		05/29/2010	05/29/2011
EMI Test Receiver	Rohde & Schwarz	ESCI	100028	05/29/2010	05/29/2011
Amplifier	H.P.	HP8447E	1937A01046	05/29/2010	05/29/2011
Broadband Antenna	Sunol Sciences	JB1	A040904-2	05/29/2010	05/29/2011
LOOP ANTENNA	R&S	HM525		05/29/2010	05/29/2011

Page 16 of 55

6.4 LIMITS AND MEASUREMENT RESULT:


Operation Mode: RF MODE Test Date: Nov.08, 2010

Temperature: 25°C Tested by: Jekey Zhang

Humidity: 55 % RH


Channel	Frequency Reading (MHZ) (dBm)		Limit (dBm)	Result
0	2402	2.25	30	Pass
39	2441	2.14	30	Pass
78	2480	1.62	30	Pass

TEST PLOT OF BOTTOM CHANNEL:




Report No.: AGC11581009SZ12-2F1 Page 17 of 55

TEST PLOT OF MIDDLE CHANNEL:



Report No.: AGC11581009SZ12-2F1 Page 18 of 55

TEST PLOT OF TOP CHANNEL:



Page 19 of 55

7. 20 DB BANDWIDTH

7.1 MEASUREMENT PROCEDURE

- 1. The EUT was placed on a turn table which is 0.8m above ground plane.
- 2. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 3, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set SPA Centre Frequency = Operation Frequency, RBW= 100 KHz, VBW= 100 KHz.
- 4. Set SPA Trace 1 Max hold, then View.

7.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The Same as described in Section 6.2

7.3 MEASUREMENT EQUIPMENT USED:

The same as described in Section 6.3


7.4 LIMITS AND MEASUREMENT RESULTS:

Operation Mode: RF MODE Test Date: Nov.08, 2010
Temperature: 25°C Tested by: Jekey Zhang


Humidity: 55 % RH Polarity: --

LIM	IITS AND MEASUREN	IENT RESULT					
Applicable Limits		Measurement Result					
Applicable Littlis	Test Da	ta (MHz)	Criteria				
	Bottom Channel	1.232	PASS				
	Middle Channel	1.228	PASS				
	Top Channel	1.224	PASS				


TEST PLOT OF BANDWIDTH FOR BOTTOM CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



TEST PLOT OF BANDWIDTH FOR TOP CHANNEL




Page 23 of 55

8. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY (N/A)

8.1 MEASUREMENT PROCEDURE:

- (1). The EUT was placed on a turn table which is 0.8m above ground plane.
- (2). Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- (3), Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- (4). Set SPA Centre Frequency = Operation Frequency, RBW= 3 KHz, VBW= 10 KHz., Sweep time= Auto
- (5). Set SPA Trace 1 Max hold, then View.

8.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)



8.3 MEASUREMENT EQUIPMENT USED:

	SHIELDING ROOM								
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.				
Spectrum Analyzer	Agilent	E4440A	US41421290	04/16/2010	04/15/2011				

8.4 LIMITS AND MEASUREMENT RESULT:

LIMITS	AND MEASUREMEN	NT RESULT				
Applicable Limite		Measurement Result				
Applicable Limits	Test Data (di	Criteria				
	Bottom Channel					
8 dBm / 3KHz	Middle Channel					
	Top Channel					

Page 24 of 55

9. OUT OF BAND EMISSION

9.1 MEASUREMENT PROCEDURE:

- 1. The EUT was placed on a turn table which is 0.8m above ground plane.
- 2. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 3, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set SPA Centre Frequency = Operation Frequency, RBW= 100 KHz, VBW= 100 KHz.
- 4. Set SPA Trace 1 Max hold, then View.

9.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The Same as described in section 6.2

- 1. Conducted test setup
- 2. Radiated Emission test Setup below 1Ghz and Above 1GHz

9.3 MEASUREMENT EQUIPMENT USED:

The Same as described in section 6.3

9.4 LIMITS AND MEASUREMENT RESULT:


LIMITS AND MEASUREMENT RESULT								
Applicable Limits	Measurement R	esult						
Applicable Limits	Test Data	Criteria						
In any 100 KHz Bandwidth Outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produce by the intentional radiator shall be at least 20 dB below that in 100KHz bandwidth within the band that contains the highest	At least -20dBc than the limit Specified on the BOTTOM Channel	PASS						
level of the desired power. In addition, radiation emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in§15.209(a))	At least -20dBc than the limit Specified on the TOP Channel	PASS						

Page 25 of 55


Humidity: 55 % RH Test Date: Nov.09, 2010

Temperature: 25°C Tested by: Mary Liu

TEST PLOT OF BAND ELDG FOR BOTTOM CHANNEL



TEST PLOT OF BAND ELDG FOR TOP CHANNEL



Page 27 of 55

RADIATED EMISSSION

MEASUREMENT PROCEDURE

- Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

Page 28 of 55

The following table is the setting of spectrum analyzer and receiver.'

Spectrum Parameter	Setting
Start Frequency	1GHz
Stop Frequency	26.5GHz
RB/VB(Emission in restricted band)	1MHz/1MHz for Peark, 1MHz/10Hz for Average
RB/VB(Emission in non-restricted band)	1MHz/1MHz for peak

Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP

TEST SET-UP

The Same as described in section 6.2

Page 29 of 55

TEST RESULT OF RADIATED EMISSION TEST (9KHz ~30MHz)

Distance 3m Test Date: Nov.09, 2010

Temperature: 25°C Tested by: Jekey Zhang

Humidity: 55 % RH

Operation Mode: CHARGE MODE CHARGE(connected to PC)

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
0.83	30.2	49.2	-19.0	PASS
4.32	29.4	49.5	-20.1	PASS
10.56	28.6	49.5	-20.9	PASS
				PASS

Operation Mode: BT MODE (channel 39)

ion meder by med	/			
Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
0.92	31.4	48.3	-16.9	PASS
5.42	27.5	49.5	-22.0	PASS
14.56	29.8	49.5	-19.7	PASS
				PASS

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = 20 log (specific distance / test distance) (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

Page 30 of 55

TEST RESULT OF RADIATED EMISSION TEST (30MHZ-1GHZ)

Operation Mode:

CHARGE MODE (connected to PC)

Test Date:

Nov.08, 2010

Temperature:

25°C


Tested by:

Mary Liu

Humidity:

55 % RH


Horizontal:



	Freq	Freq	Freq	Freq	Freq	Freq	Freq	Freq	Freq	Level	Over Limit			Antenna Factor			Ant Pos	Table Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/n	dB	dB -	cm	deg									
1	147.180	29.97	-20.13	43.50	39.01	10.72	1.65	29.01			Peak								
2	228.450	29.30	-16.70	46.00	44.13	10.94	1.98	27.74			Peak								
3	299.460	31.88	-14.12	46.00	44.93	12.31	2.24	27.60			Peak								
4	332.900	31.98	-14.02	46.00	44.02	13.45	2.35	27.83	100	198	Peals								
5	906.200	27.98	-19.02	46.00	29.15	23.66	3.96	20.79			Peak								
6	957.300	28.70	-17.30	46.00	28.44	24.96	3.98	28.69			Peak								

Report No.: AGC11581009SZ12-2F1 Page 31 of 55

Vertical:



			Over	Linit	Read	intenna	Cable	Preamp	Ant	Table			
	-	Freq	Freq	Level	Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Remark
		dEuV/m	dB	dBuV/n	dBuV	dB/n	dB	dB -	cm	deg	-		
1	69.690	24.70	-15.30	40.00	46.15	5.62	1.19	28.25			Peak		
2	77.250	25.15	-14.85	40.00	45.48	6.67	1.25	28.25	100	169	Peak		
3	225.210	28.22	-17.78	46.00	43.36	10.65	1.97	27.75	7		Peak		
4	332.900	25.43	-20.57	46.00	37.47	13.45	2.35	27.83			Peak		
5	491.800	25.57	-20.43	46.00	34.91	16.81	2.79	28.94			Peak		
6	937.000	29.07	-16.93	46.00	29.37	24.45	3.98	28.73			Peak		

Page 32 of 55

Operation Mode: BT MODE(channel 39)

Test Date:

Oct.10, 2010

Temperature:

25°C


Tested by:

Mary Liu

Humidity:

55 % RH


Horizontal



					Over	Linit	Readintenna		Cable Preamp		Ant Pos	Table Pos deg	
	Freq	Level	Limit	Line	:	Factor dB/n	Loss	Factor	Remark				
	MHz	dBuV/m	dB					dB -					
1	228.450	31.09	-14.91	46.00	45.92	10.94	1.98	27.74	100	125	Peak		
2	264.090	28.26	-17.74	46.00	41.33	12.50	2.10	27.67			Peak		
3	Z99.460	30.36	-15.64	46.00	43.41	1Z.31	Z. Z4	Z7.60			Peak		
4	332.900	30.84	-15.16	46.00	42.88	13.45	2.35	27.83	903286	500	Peak		
5	881.000	27.78	-18.22	46.00	29.87	22.80	3.92	28.82			Peak		
6	945.400	27.87	-18.13	46.00	27.93	24.67	3.98	28.71			Peak		

Page 33 of 55

Vertical



	Freq	Level	Over Limit			ntenna Factor		Preamp Factor	Ant Pos		Remark
	MHz	dEuV/m	dB	dBuY/n	dBuV	dB/n	dB	dB -	cm	deg	
1	78.060	26.83	-13.17	40.00	47.02	6.80	1.26	28.24	100	136	Peak
2	228.450	26.82	-19.18	46.00	41.65	10.94	1.98	27.74			Peak
3	Z99.460	Z6.01	-19.99	46.00	39.06	1Z.31	Z. Z4	Z7.60			Peak
4	724.200	24.74	-21.26	46.00	30.20	20.07	3.53	29.05			Peak
5	867.000	26.02	-19.98	46.00	28.65	22.30	3.90	28.83	00.00		Peak
6	932.100	20.53	-17.47	46.00	28.97	24.32	3.97	29.74	222	2.22	Peak

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).


Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Page 34 of 55

TEST RESULT OF RADIATED EMISSION TEST(1GHZ-10TH HARMONIC)

Operation Mode:	channel 0	Test Date:	Oct.10, 2010
Temperature:	25°C	Tested by:	Mary Liu
Humidity:	55 % RH		


Horizontal



	Freq		Over	Linit	Read	lntenna	Cable	Preamp	Ant	Table	
		Level	Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Remark
	MHz	dBuV/m	dB	dBuV/n	dBuV	dB/n	dB	dB -	cm	deg	-
1	2389.420	34.66	-19.34	54.00	32.16	32.54	3.74	33.78	160	101	Average
2	2389.420	46.99	-27.01	74.00	44.49	32.54	3.74	33.78	100	.0	Peak
3 X	2402.000	82.26			79.76	32.54	3.74	33.78	160	101	Average
4 X	2402.000	95.07			92.57	32.54	3.74	33.78	100	0	Peak
5	2486.000	33.12	-20.88	54.00	30.49	32.59	3.84	33.80	160	101	Average
6	2486.000	45.26	-28.74	74.00	42.63	32.59	3.84	33.80	100	.0	Peak
7	6942.000	54.41	-19.59	74.00	44.61	36.00	6.34	32.54	100	0	Peak
8	6942.000	43.60	-10.40	\$4.00	33.90	36.00	6.34	32.54	100	188	Average

Report No.: AGC11581009SZ12-2F1 Page 35 of 55

Vertical




			Over	Linit	Read	intenna	Cable	Preamp	Ant	Table	
	Freq	Level	Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Remark
	MHz	dBuV/m	dB	dBuV/n	dBuV	dB/n	dB	dB -	cm	deg	-
1	2349.140	33.08	-20.92	54.00	30.65	32.51	3.59	33.77	101	68	Average
2	2349.140	50.33	-23.67	74.00	47.90	32.51	3.69	33.77	100	0	Peak
3 @	2402.000	83.87			81.37	32.54	3.74	33.78	101	68	Average
4 X	2402.000	96.69			94.19	32.54	3.74	33.78	100	0	Peak
5	2492.000	33.10	-20.90	54.00	30.46	32.60	3.84	33.80	101	68	Average
6	2492.000	44.76	-29.24	74.00	42.12	32.60	3.84	33.80	100	0	Peak
7	6957.000	54.81	-19.19	74.00	44.99	36.00	6.34	32.52	100	0	Peak
8	6957,000	43.86	-10.14	54.00	34.04	36.00	6.34	32.52	100	181	Average

Report No.: AGC11581009SZ12-2F1 Page 36 of 55

Operation Mode:	channel 39	Test Date:	Oct.10, 2010
Temperature:	25°C	Tested by:	Mary Liu
Humidity:	55 % RH		


Horizontal



			Over	Linit	Read	intenna	Cable	Preamp	Ant	Table	
	Freq	Level	Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Remark
	MHz	dBuV/m	dB	dBuV/n	dBuV	dB/n	dB	dB -	cm	deg	-
1	2324.000	45.21	-28.79	74.00	42.82	32.50	3.66	33.77	100	0	Peak
2	2324.000	32.80	-21.20	54.00	30.41	32.50	3.56	33.77	156	98	Average
3 @	2441.000	96.07			93.50	32.57	3.79	33.79	100	0	Peak
4 0	2441.000	84.27			81.70	32.57	3.79	33.79	156	98	Average
5	2486.000	33.35	-20.65	54.00	30.72	32.59	3.84	33.80	156	98	Average
6	2486.000	46.12	-27.88	74.00	43.49	32.59	3.84	33.80	100	0	Peak
7	8721.000	54.76	-19.24	74.00	45.73	36.47	7.13	34.58	100	0	Peak
8 @	8721.000	44.70	-9.30	54.00	35.67	36.47	7.13	34.58	100	147	Average

Report No.: AGC11581009SZ12-2F1 Page 37 of 55

Vertical




			Over	Linit	Read	intenna	Cable	Preamp	Ant	Table	
	Freq	Level	Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Remark
	MHz	dBuV/m	419	dBuV/n	dBuV	dB/n	419	dB -	□ m	deg	-
Ĺ	2388.000	47.54	-26.46	74.00	45.04	32.54	3.74	33.78	100	0	Peak
2	2388.000	32.96	-21.04	54.00	30.46	32.54	3.74	33.78	100	308	Average
3 @	2441.000	97.40			94.83	32.57	3.79	33.79	100	0	Peak
4 @	2441.000	84.36			81.79	32.57	3.79	33.79	100	308	Average
5	2494.000	33.30	-20.70	54.00	30.66	32.60	3.84	33.80	100	308	Average
6	2494.000	49.62	-24.38	74.00	46.98	32.60	3.84	33.80	100	0	Peak
7	6906.000	54.22	-19.78	74.00	44.45	36.00	6.33	32.56	100	0	Peak
8 0	6906.000	43.45	-10.55	54.00	33.68	36.00	6.33	32.56	100	168	Average

Report No.: AGC11581009SZ12-2F1 Page 38 of 55

Operation Mode:	channel 78	Test Date:	Oct.10, 2010
Temperature:	25°C	Tested by:	Mary Liu
Humidity:	55 % RH		


Horizontal



			Over	Linit	Read	intenna	Cable	Dreamp	Ant	Table	
	Freq	Level	Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Remark
	MHZ	dEuV/m	dB	dBuV/m	dBuV	dB/n	dB	dB -	cm	deg	-
1	2340.000	46.00	-28.00	74.00	43.57	32.51	3.69	33.77	100	0	Peak
2	2340.000	32.71	-21.29	54.00	30.28	32.51	3.69	33.77	102	94	Average
3 X	2480.000	96.13			93.50	32.59	3.84	33.80	100	0	Peak
4 X	2480.000	82.79			80.16	32.59	3.84	33.80	102	94	Average
5	2483.500	63.73	-10.27	74.00	61.10	32.59	3.84	33.80	100	0	Peak
6 1	2483.500	50.60	-3.40	54.00	47.97	32.59	3.84	33.80	102	94	Average
7	7050.000	54.81	-19.19	74.00	45.06	36.00	6.38	32.63	100	0	Pesk
8	7050.000	44.06	-9.94	54.00	34.31	36.00	6.38	32.63	100	102	Average

Report No.: AGC11581009SZ12-2F1 Page 39 of 55

Vertical



	Freq	and the second s				J. 71451071075	Ant Pos		Remark		
	MHz	dBuV/m		dBuV/n	dBuV	dB/n			c m	deg	-
1	2318.000	45.00	-29.00	74.00	42.61	32.50	3.66	33.77	100	0	Peak
2	2318.000	32.80	-21.20	54.00	30.41	32.50	3.56	33.77	150	99	Average
3 X	2480.000	97.55			94.92	32.59	3.84	33.80	100	0	Peak
4 @	Z480.000	84.75			8Z.1Z	3Z.59	3.84	33.80	150	99	Average
5	2493.500	65.00	-9.00	74.00	62.37	32.59	3.84	33.80	100	0	Peak
6!	2483.500	51.31	-2.69	54.00	48.68	32.59	3.84	33.80	150	99	Average
7	7998.000	54.80	-19.20	74.00	45.45	36.20	6.76	33.61	100	0	Dealt
8	7998.000	44.45	-9.55	54.00	35.10	36.20	5.76	33.61	100	146	Average

Page 40 of 55

10. NUMBER OF HOPPING FREQUENCY

10.1 MEASUREMENT PROCEDURE

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum analyzer.
- 3. Set the spectrum analyzer Start = 2.4GHz Stop = 2.4835GHz, span=20MHz
- 4. Set the Spectrum Analyzer as RBW = VBW = 510KHz

10.2 TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)

Same as described in section 6.2

1. Conducted Method.

10.3 MEASUREMENT EQUIPMENT USED

The Same as described in section 6.3


10.4 LIMITS AND MEASUREMENT RESULT:

TOTAL NO. OF	LIMIT (NO. OF CH)	MEASUREMENT (NO. OF CH)	RESULT
HOPPING CHANNEL	>=15	79	PASS

Page 41 of 55

Humidity:	55 % RH	Test Date:	Nov.08, 2010
Temperature:	25°C	Tested by:	Jekey Zhang

NUMBER OF HOPPING CHANNEL PLOT ON CHANNEL 0~78



Page 42 of 55

11. TIME OF OCCUPANCY (DWELL TIME)

11.1 MEASUREMENT PROCEDURE

- 1. Place the EUT on the table and set it in transmitting mode
- 2. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum analyzer
- 3. Set center frequency of spectrum analyzer = Operating frequency
- 4. Set the spectrum analyzer as RBW, VBW=1MHz, Span = 0 Hz,

11.2 TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)

Same as described in section 6.2

Conducted Method

11.3 MEASUREMENT EQUIPMENT USED

The same as described in section 6.3

11.4 LIMITS AND MEASUREMENT RESULT

	BOTTOM CHANNEL						
Mode	Frequency	Spectrum Reading	Test Result	Limit	Pass / Fail		
Mode	(MHz)	(uS)	(mS)	(mS)	Fass / Fall		
DH1	2402	370	118.40	400	Pass		
DH3	2402	1627	260.32	400	Pass		
DH5	2402	2870	306.13	400	Pass		
		MIDDLE	CHANNEL				
	Frequency	Spectrum Reading	Test Result	Limit	D / E		
Mode	(MHz)	(uS)	(mS)	(mS)	Pass / Fail		
DH1	2441	373.3	119.46	400	Pass		
DH3	2441	1627	260.32	400	Pass		
DH5	2441	2860	305.07	400	Pass		
		TOP (CHANNEL				
	Frequency	Spectrum Reading	Test Result	Limit	D / E		
Mode	(MHz)	(uS)	(mS)	(mS)	Pass / Fail		
DH1	2480	370	118.40	400	Pass		
DH3	2480	1627	260.32	400	Pass		
DH5	2480	2860	305.07	400	Pass		


A Period Time = 79*0.4=31.6 S


DH1 Time Slot: Reading * (1600/2)*31.6/79 DH3 Time Slot: Reading * (1600/4)*31.6/79 DH5 Time Slot: Reading * (1600/6)*31.6/79

Page 43 of 55

Humidity:	55 % RH	Test Date:	Nov.08, 2010
Temperature:	25°C	Tested by:	Sky liu
Configurations	DH1, DH3, DH5		


TEST PLOT DH1 MODE BOTTOM CHANNEL






Report No.: AGC11581009SZ12-2F1 Page 44 of 55

TEST PLOT DH5 MODE BOTTOM CHANNEL




TEST PLOT DH1 MODE MIDDLE CHANNEL




Report No.: AGC11581009SZ12-2F1 Page 45 of 55

TEST PLOT DH3 MODE MIDDLE CHANNEL




TEST PLOT DH5 MODE MIDDLE CHANNEL




Report No.: AGC11581009SZ12-2F1 Page 46 of 55

TEST PLOT DH1 MODE TOP CHANNEL




TEST PLOT DH3 MODE TOP CHANNEL



Report No.: AGC11581009SZ12-2F1 Page 47 of 55

TEST PLOT DH5 MODE TOP CHANNEL



Page 48 of 55

12. FREQUENCY SEPARATION 12.1 MEASUREMENT PROCEDURE

- 1. Place the EUT on the table and set it in transmitting mode
- 2. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum analyzer
- 3. Set center frequency of spectrum analyzer = Middele of Operating frequency
- 4. Set the spectrum analyzer as RBW, VBW=100KHz, Span = 5 MHz,

12.2 TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)

Same as described in section 6.2

12.3 MEASUREMENT EQUIPMENT USED

The same as described in section 6.3


12.4 LIMITS AND MEASUREMENT RESULT

CHANNEL	CHANNEL SEPARATION	LIMIT	RESULT
OI WATALE	KHz	KHz	
CH00-CH01	1000		Pass
CH39-CH40	1000	>=25 KHz or 2/3 20 dB BW	F 055
CH77-CH78	1000		


Page 49 of 55

Humidity:	55 % RH	Test Date:	Nov.08, 2010		
Temperature:	25°C	Tested by:	Jekey Zhang		
Configurations	Channel 0-1, channel39-40, channel78-79				


TEST PLOT FOR FREQUENCY SEPARATION -CHANNEL0-1



TEST PLOT FOR FREQUENCY SEPARATION -CHANNEL39-40



TEST PLOT FOR FREQUENCY SEPARATION -CHANNEL77-78



Page 52 of 55

APPENDIX I PHOTOGRAPHS OF THE EUT

TOP VIEW OF SAMPLE



BACK VIEW OF SAMPLE




Report No.: AGC11581009SZ12-2F1 Page 53 of 55






Report No.: AGC11581009SZ12-2F1 Page 54 of 55

INTERNAL PHOTO OF SAMPLE - 1



INTERNAL PHOTO OF SAMPLE - 2




Report No.: AGC11581009SZ12-2F1 Page 55 of 55

PPENDIX II

PHOTOGRAPHS OF THE TEST SETUP CONDUCTED EMISSION TEST



RADIATED EMISSION TEST SETUP



----END OF REPORT----