

FCC RADIO TEST REPORT FCC ID: YVV-AEEF1000001

Product: Unmanned Aircraft Systems (Unmanned Aircraft)

Trade Name: AEE

Model Name: F100

Serial Model: F100A,F100B,F100C,F100J,F100G,F100I, F100S,F110,F115,AF100,AF110,AF115

Report No.: NTEK-2014NT1008522F

Prepared for

SHENZHEN AEE TECHNOLOGY CO.,LTD.

AEE Hi-Tech Park, Tangtou Crossroads, Shiyan Town, Bao'an District, Shenzhen, China 518000

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park, Sanwei Community,Xixiang Street Bao'an District, Shenzhen P.R. China

Tel.: +86-0755-61156588 Fax.: +86-0755-61156599 Website:www.ntek.org.cn

Applicant's name: SHENZHEN AEE TECHNOLOGY CO.,LTD.



TEST RESULT CERTIFICATION

Report No.: NTEK-2014NT1008522F

Address:	AEE Hi-Tech Park, Tangtou Crossroads, Shiyan Town, Bao'an District, Shenzhen, China 518000			
Manufacture's Name:	SHENZHEN AEE TECHNOLOGY CO.,LTD.			
Address:	AEE Hi-Tech Park,Tangtou Crossroads, Shiyan Town,Bao'an District,Shenzhen, China 518000			
Product description				
Product name:	Unmanned Aircraft Systems (Unmanned Aircraft)			
Model and/or type reference :	F100			
Serial Model:	F100A,F100B,F100C,F100J,F100G,F100I, F100S,F110,F115,AF100,AF110,AF115			
Rating(s):	DC 22.2V			
Standards:	FCC Part15.249: 01 Oct. 2014			
Test procedure	. ANSI C63.4-2003			
	as been tested by NTEK, and the test results show that the in compliance with the FCC requirements. And it is applicable only in the report.			
•	iced except in full, without the written approval of NTEK, this vised by NTEK, personal only, and shall be noted in the revision of			
Date (s) of performance of tests	: 08 Oct. 2014 ~ 28 Nov 2014			
Date of Issue	: 28 Nov 2014			
Test Result	Pass			
Testing Engine	eer : Donny Yuang Denny Huang			
Technical Mar	nager: Brown Lu)			
Authorized Sig	gnatory: (Bill Yao)			



Table of Contents	Page
1 . SUMMARY OF TEST RESULTS	4
1.1 TEST FACILITY	5
1.2 MEASUREMENT UNCERTAINTY	5
	_
2 . GENERAL INFORMATION	6
2.1 GENERAL DESCRIPTION OF EUT	6
2.2 DESCRIPTION OF TEST MODES	8
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTE	
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	10
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	11
3 . ANTENNA REQUIREMENT	12
3.1 STANDARD REQUIREMENT	12
3.2 EUT ANTENNA	12
3.3 CONDUCTED EMISSION MEASUREMENT	13
3.3.1 POWER LINE CONDUCTED EMISSION LIMITS	13
3.3.2 TEST PROCEDURE	14
3.3.3 DEVIATION FROM TEST STANDARD 3.3.4 TEST SETUP	14 14
3.2.5 TEST RESULT	15
3.4 RADIATED EMISSION MEASUREMENT	16
3.4.1 RADIATED EMISSION LIMITS	16
3.4.2 TEST PROCEDURE	17
3.4.3 DEVIATION FROM TEST STANDARD 3.4.4 TEST SETUP	17
3.4.4 TEST SETUP 3.4.5 TEST RESULTS (BLOW 30MHZ)	18 20
3.4.6 TEST RESULTS (BETWEEN 30 – 1000 MHZ)	21
3.4.7 TEST RESULTS (ABOVE 1000 MHZ)	23
3.4.8 TEST RESULTS (RESTRICTED BANDS REQUIREMENTS)	25
4 . BANDWIDTH TEST	27
4.1 TEST PROCEDURE	27
4.2 DEVIATION FROM STANDARD	27
4.3 TEST SETUP 4.4 TEST RESULTS	27 28
5 . EUT TEST PHOTO APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	29



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15, Subpart C (15.249)					
Standard Section	Test Item	Judgment	Remark		
15.207	Conducted Emission	N/A			
15.203	Antenna Requirement	Pass			
15.249	Radiated Spurious Emission	Pass			
15.205	Band Edge Emission	Pass			
15.249	Occupied Bandwidth	Pass			



1.1 TEST FACILITY

NTEK Testing Technology Co., Ltd

Add.: 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District,

Shenzhen P.R. China.

FCC FRN Registration No.:238937; IC Registration No.:9270A-1

CNAS Registration No.:L5516

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $\mathbf{y} \pm \mathbf{U}$, where expended uncertainty \mathbf{U} is based on a standard uncertainty multiplied by a coverage factor of $\mathbf{k=2}$, providing a level of confidence of approximately 95 % $^{\circ}$

No.	Item	Uncertainty
1	Conducted Emission Test	±1.38dB
2	RF power,conducted	±0.16dB
3	Spurious emissions,conducted	±0.21dB
4	All emissions,radiated(<1G)	±4.68dB
5	All emissions,radiated(>1G)	±4.89dB
6	Temperature	±0.5°C
7	Humidity	±2%



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	Unmanned Aircraft Systems (Unmanned Aircraft)			
Trade Name	AEE			
Model Name	F100			
Serial Model	F100A,F100B,F100C,F	100J,F100G,F100I,		
	F100S,F110,F115,AF10	00,AF110,AF115		
Model Difference	All the model are the sa	me circuit and RF module,		
Weder Billerende	except the model name	and colour.		
	The EUT is a Unmanned Aircraft Systems (Unmanned Aircraft)			
	Operation Frequency:	915MHz		
	Modulation Type:	FSK		
	Antenna Designation:	External Antenna		
Product Description	Antenna Gain(Peak)	5.5 dBi		
	Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.			
Channel List	Please refer to the Note 2.			
Adapter	N/A			
Battery	DC 22.2V, 20000mAh			

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



2.

·		
Channel	Frequency (MHz)	
01	915	

3

Table for Filed Antenna

F	\nt	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
	1	N/A	N/A	External Antenna	N/A	5.5	Antenna

•



2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	TX

For Conducted Emission		
Final Test Mode Description		
N/A	TX	

For Radiated Emission		
Final Test Mode	Description	
Mode 1	TX	

Note:

(1) The measurements are performed at the highest, middle, lowest available channels.

(2) The EUT use new battery.



2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED			
E-1 EUT			

•



2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Unmanned Aircraft Systems (Unmanned Aircraft)	AEE	F100	N/A	EUT

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- For detachable type I/O cable should be specified the length in cm in <code>[Length]</code> column. (2)



2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

· · · ·	ation rest equipme	114			
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	Agilent	E4407B	160400005	Jul. 06. 2015
2	Test Receiver	R&S	ESPI	101318	Jul. 06. 2015
3	Bilog Antenna	TESEQ	CBL6111D	31216	Jul. 06. 2015
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	Jul. 06. 2015
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	Jul. 06. 2015
6	Horn Antenna	EM	EM-AH-10180	2011071402	Jul. 06. 2015
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	Jul. 06. 2015
8	Amplifier	EM	EM-30180	060538	Jul. 06. 2015
9	Loop Antenna	ARA	PLA-1030/B	1029	Jul. 06. 2015
10	Power Meter	R&S	NRVS	100696	Jul. 06. 2015

Conduction Test equipment

COIN	Conduction Test equipment					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until	
1	Test Receiver	R&S	ESCI	101160	Jul. 06. 2015	
2	LISN	R&S	ENV216	101313	Jul. 06. 2015	
3	LISN	EMCO	3816/2	00042990	Jul. 06. 2015	
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	Jul. 06. 2015	
5	Passive Voltage Probe	R&S	ESH2-Z3	100196	Jul. 06. 2015	
6	Absorbing clamp	R&S	MOS-21	100423	Jul. 06. 2015	



3. ANTENNA REQUIREMENT

3.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

3.2 EUT ANTENNA

The EUT antenna is p	ermanent attached ar	itenna. It comply	v with the	standard re	auirement.
----------------------	----------------------	-------------------	------------	-------------	------------

L



3.3 CONDUCTED EMISSION MEASUREMENT

3.3.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

	Class A (dBuV)		Class B (dBuV)		Standard
FREQUENCY (MHz)	Quasi-peak	Average	Quasi-peak	Average	Standard
0.15 -0.5			66 - 56 *	56 - 46 *	CISPR
0.50 -5.0			56.00	46.00	CISPR
5.0 -30.0			60.00	50.00	CISPR

0.15 -0.5		66 - 56 *	56 - 46 *	LP002.
0.50 -5.0		56.00	46.00	LP002.
5.0 -30.0		60.00	50.00	LP002.

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz




3.3.2 TEST PROCEDURE

- a. The EUT was placed 0.4 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item -EUT Test Photos.

3.3.3 DEVIATION FROM TEST STANDARD


No deviation

3.3.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes





3.2.5 TEST RESULT

	Unmanned Aircraft Systems (Unmanned Aircraft)	Model Name. :	F100		
Temperature:	26 ℃	Relative Humidity:	54%		
Pressure:	1010hPa	Phase :	N/A		
Test Voltage :	N/A	Test Mode:	N/A		

•



- Sgr to all a support of the same and the s

3.4 RADIATED EMISSION MEASUREMENT

3.4.1 Radiated Emission Limits (FCC 15.209)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
Frequency (MHz)	Limit (dBuV)	
30~88	40	3
88~216	43.5	3
216~960	46	3
960 -10000	54.00	3
*902 - 928	94.00	3

Note:

- (1) The tighter limit applies at the band edges.
- (2) Emission level (dBuV/m)=20log Emission level (uV/m).
- (3) *Note: This is the limit for the fundamental frequency.

LIMITS OF RADIATED EMISSION MEASUREMENT (FCC 15.249)

Frequency of Emission (MHz)	Field Strength of fundamental ((millivolts /meter)	Field Strength of Harmonics (microvolts/meter)
902-928	50	500

Notes:

(1) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1MHz / 1MHz for Peak

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP



3.4.2 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3m meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos. Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
	Peak	1 MHz	1 MHz
Above 1000	Peak	1 MHz	10 Hz


3.4.3 DEVIATION FROM TEST STANDARD

No deviation




3.4.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz




(B) Radiated Emission Test-Up Frequency 30MHz~1GHz









Page 19 of 29

•



3.4.5 TEST RESULTS (BLOW 30MHz)

EUT:	Unmanned Aircraft Systems (Unmanned Aircraft)	Model Name. :	F100
Temperature :	20 ℃	Relative Humidtity:	48%
Pressure:	1010 hPa	Test Voltage :	
Test Mode :	TX	Polarization :	

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
				PASS
				PASS

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor =20 log (specific distance/test distance)(dB); Limit line = specific limits(dBuv) + distance extrapolation factor.




3.4.6 TEST RESULTS (BETWEEN 30 – 1000 MHZ)

	Unmanned Aircraft Systems (Unmanned Aircraft)	Model Name :	F100
Temperature :	20 ℃	Relative Humidity:	48%
Pressure :	1010 hPa	Test Voltage :	DC 22.2V
Test Mode :	TX 915MHz	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Domork
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Remark
55.0274	10.62	9.26	19.88	40.00	-20.12	QP
216.024	23.63	11.86	35.49	46.00	-10.51	QP
270.3748	28.25	13.82	42.07	46.00	-3.93	QP
354.1831	23.75	16.41	40.16	46.00	-5.84	QP
482.2156	22.19	19.94	42.13	46.00	-3.87	QP
915.0000	60.20	27.10	87.30	94.00	-6.7	QP

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.



.




	Unmanned Aircraft Systems (Unmanned Aircraft)	Model Name :	F100
Temperature :	20 ℃	Relative Humidity:	48%
Pressure :	1010 hPa	Test Voltage :	DC 22.2V
Test Mode :	TX 915MHz	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Domork
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Remark
55.4147	24.02	9.14	33.16	40.00	-6.84	QP
107.5100	20.67	9.71	30.38	43.50	-13.12	QP
151.5971	28.68	10.42	39.10	43.50	-4.40	QP
204.2375	20.87	11.07	31.94	43.50	-11.56	QP
517.2480	20.96	20.65	41.61	46.00	-4.39	QP
915.0000	59.80	27.10	86.90	94.00	-7.1	QP

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.



.




3.4.7 TEST RESULTS (ABOVE 1000 MHZ)

	Unmanned Aircraft Systems (Unmanned Aircraft)	Model Name :	F100
Temperature :	20 ℃	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 22.2V
Test Mode :	TX 915MHz	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Domark
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Remark
1821.145	71.54	-14.32	57.22	74	-16.78	peak
1821.145	62.87	-14.32	48.55	54	-5.45	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.





EUI.	Unmanned Aircraft Systems (Unmanned Aircraft)	Model Name :	F100
Temperature :	20 ℃	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 22.2V
Test Mode :	TX 915MHz	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Remark
1821.096	62.92	-14.32	48.6	74	-25.4	peak
1821.096	50.21	-14.32	35.89	54	-18.11	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




3.4.8 TEST RESULTS (RESTRICTED BANDS REQUIREMENTS)

	Unmanned Aircraft Systems (Unmanned Aircraft)	Model Name :	F100
Temperature :	20 ℃	Relative Humidity:	48%
Pressure :	1010 hPa	Test Voltage :	DC 22.2V
Test Mode :	TX 915MHz	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Remark
915.0000	63.60	23.30	86.90	114.0	-27.10	QP

Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.






		-	
	Unmanned Aircraft Systems (Unmanned Aircraft)	Model Name :	F100
Temperature:	20 ℃	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 22.2V
Test Mode :	TX 915MHz	Polarization :	Horizontal

Page 26 of 29

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Domark
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Remark
915.0000	64.60	23.30	87.90	114.0	-26.10	QP

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.





4. BANDWIDTH TEST

4.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below, b. Spectrum Setting : RBW= 100KHz, VBW≧RBW, Sweep time = Auto.

4.2 DEVIATION FROM STANDARD

No deviation.

4.3 TEST SETUP


EUT	SPECTRUM
	ANALYZER




4.4 TEST RESULTS

	Unmanned Aircraft Systems (Unmanned Aircraft)	Model Name :	F100
Temperature :	26 ℃	Relative Humidity:	53%
Pressure:	1020 hPa	Test Power :	DC 22.2V
Test Mode :	TX 915MHz		

Test Channel	Frequency	20 dBc Bandwidth
103t Orianner	(MHz)	(MHz)
CH1	915	0.478



•





5. EUT TEST PHOTO





