## 1.1 RF Exposure Evaluation

#### **1.1.1** Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)	
(A) Limits for Occupational/Controlled Exposures					
0.3–3.0 614 1.63 *(100) 6					
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6	
30–300	61.4	0.163	1.0	6	
300–1500			f/300	6	
1500–100,000			5	6	
(B) Limits for General Population/Uncontrolled Exposure					
0.3–1.34	614	1.63	*(100)	30	
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30	
30–300	27.5	0.073	0.2	30	
300–1500			f/1500	30	
1500–100,000			1.0	30	

f = frequency in MHz

Friis Formula

Friis transmission formula:  $Pd = (Pout*G)/(4*pi*r^2)$ 

Where

Pd = power density in mW/cm<sup>2</sup>

**Pout** = output power to antenna in mW

**G** = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm2. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

### **1.1.2** Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

# **1.1.3** Test Result of RF Exposure Evaluation

## 802.11b

Channel	Output power to	Power Density at R=20cm	Limit (mW/cm <sup>2</sup> )	Result
	antenna (mW)	(mW/cm <sup>2</sup> )		
Lowest	143.55	0.045261519	1.0	Pass
Middle	146.89	0.046315796	1.0	Pass
Highest	109.14	0.034413523	1.0	Pass

802.11g

Channel	Output power to	Power Density at R=20cm	Limit (mW/cm <sup>2</sup> )	Result
	antenna (mW)	(mW/cm <sup>2</sup> )		
Lowest	180.30	0.056849825	1.0	Pass
Middle	142.89	0.045053562	1.0	Pass
Highest	118.85	0.037473920	1.0	Pass

802.11n(H20)

Channel	Output power to	Power Density at R=20cm	Limit (mW/cm <sup>2</sup> )	Result
	antenna (mW)	(mW/cm <sup>2</sup> )		
Lowest	299.23	0.094347225	1.0	Pass
Middle	241.55	0.076160385	1.0	Pass
Highest	215.28	0.067878014	1.0	Pass

802.11n(H40)

Channel	Output power to	Power Density at R=20cm	Limit (mW/cm <sup>2</sup> )	Result
	antenna (mW)	(mW/cm <sup>2</sup> )		
Lowest	147.91	0.046636841	1.0	Pass
Middle	126.77	0.039969538	1.0	Pass
Highest	109.90	0.034652066	1.0	Pass

Remark: antenna gain=1.58dBi