RF Exposure evaluation

According to KDB 447498 D01 General RF Exposure Guidance v05 The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by: [(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] • [\sqrt{f} (GHz)] \leq 3.0 for 1-g SAR and \leq 7.5 for 10-g extremity SAR, where

 $\ensuremath{\text{f}}\xspace(\text{GHz})$ is the RF channel transmit frequency in GHz Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

```
eirp = pt x gt = (EXd)^2/30

where:

pt = transmitter output power in watts,

gt = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m, --- 10^{((dBuV/m)/20)}/10^6

d = measurement distance in meters (m)---3m

So pt = (EXd)^2/30 x gt

Ant gain 3dBi ;so Ant numeric gain=1.995

Field strength = 98.87 dBuV/m @3m

So EIRP={ [10^{(98.87 /20)}/10^6 x3]^2/30x1.995 }x1000 mW = 1.16 mW

So ( 1.16 mW/5mm)x \sqrt{2.441} GHz = 0.4 <3
```

Then SAR evaluation is not required