

Test Report

Report No. : CQASZ20190900050EX-01

Applicant: Chervon(China)Trading Co.,Ltd

Address of Applicant: No.99 Tianyuan West Road, Jiangning Economic & Technical Development Zone, nanjing, jiangsu, China

Manufacturer: Chervon(China)Trading Co.,Ltd

Address of Manufacturer: No.99 Tianyuan West Road, Jiangning Economic & Technical Development Zone, nanjing, jiangsu, China

Equipment Under Test (EUT):

Product: Bluetooth speaker

All models: 5026, RO5026MNT ("M,N,T" may be hyphen or blank or 0~9 or A~Z letter)

Test Model No.: 5026

Brand Name: SKIL

FCC ID: YWK5026

Standards: 47 CFR Part 15, Subpart C Section 15.247

Date of Test: 2019-09-05 to 2019-09-17

Date of Issue: 2019-09-18

Test Result : **PASS***

Tested By:

Tom Chen

(Tom Chen)

Reviewed By:

Aaron Ma

(Aaron Ma)

Approved By:

Jack Ai

(Jack Ai)



* In the configuration tested, the EUT complied with the standards specified above.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

1. Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20190900050EX-01	Rev.01	Initial report	2019-09-18

2. Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 (2013)	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 (2013)	N/A
Conducted Peak Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(1)	ANSI C63.10 (2013)	PASS
20dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Carrier Frequencies Separation	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Hopping Channel Number	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Dwell Time	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Pseudorandom Frequency Hopping Sequence	47 CFR Part 15, Subpart C Section 15.247(b)(4)&TCB Exclusion List (7 July 2002)	ANSI C63.10 (2013)	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 (2013)	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 (2013)	PASS
Radiated Spurious emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 (2013)	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 (2013)	PASS

N/A: Not Applicable

3. Contents

	Page
COVER PAGE.....	1
1. VERSION.....	2
2. TEST SUMMARY.....	3
3. CONTENTS.....	4
4. GENERAL INFORMATION.....	5
4.1 CLIENT INFORMATION.....	5
4.2 GENERAL DESCRIPTION OF EUT.....	5
4.4 TEST ENVIRONMENT.....	8
4.5 DESCRIPTION OF SUPPORT UNITS.....	8
4.6 STATEMENT OF THE MEASUREMENT UNCERTAINTY.....	9
4.7 TEST FACILITY.....	10
4.9 DEVIATION FROM STANDARDS.....	10
4.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	10
4.11 EQUIPMENT LIST.....	11
5. TEST RESULTS AND MEASUREMENT DATA.....	12
5.1. ANTENNA REQUIREMENT.....	12
5.2. CONDUCTED EMISSIONS.....	13
5.3. CONDUCTED PEAK OUTPUT POWER.....	14
5.4. 20DB OCCUPY BANDWIDTH.....	18
5.5. FREQUENCIES SEPARATION.....	21
5.6. HOPPING CHANNEL NUMBER.....	24
5.7. DWELL TIME.....	26
5.8. BAND-EDGE FOR RF CONDUCTED EMISSIONS.....	29
5.9. SPURIOUS RF CONDUCTED EMISSIONS.....	33
5.10. OTHER REQUIREMENTS FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM.....	41
5.11. RADIATED SPURIOUS EMISSION & RESTRICTED BANDS.....	43
5.11.1. Radiated Emission below 1GHz.....	46
5.11.2. Transmitter Emission above 1GHz.....	48
6. PHOTOGRAPHS - EUT TEST SETUP.....	50
7. PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS.....	52

4. General Information

4.1 Client Information

Applicant:	Chervon(China)Trading Co.,Ltd
Address of Applicant:	No.99 Tianyuan West Road, Jiangning Economic & Technical Development Zone, nanjing, jiangsu, China
Manufacturer:	Chervon(China)Trading Co.,Ltd
Address of Manufacturer:	No.99 Tianyuan West Road, Jiangning Economic & Technical Development Zone, nanjing, jiangsu, China

4.2 General Description of EUT

Product Name:	Bluetooth speaker
Test Model No.:	5026
Trade Mark:	SKIL
EUT Supports Radios application:	Bluetooth EDR+BDR

4.3 Product Specification subjective to this standard

Radio function:	Bluetooth V4.2
Operation Frequency:	2402-2480MHz
Hardware Version:	V1.0
Software Version:	V2.4
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, $\pi/4$ DQPSK
Transfer Rate:	1Mbps/2Mbps
Number of Channel:	79
Hopping Channel Type:	Adaptive Frequency Hopping systems
Test Power Grade:	Power level: 7
Test Software of EUT:	V2.4 (For details, refer to the software interface on page 7.)
Product Type:	☐ Mobile ☒ Portable ☐ Fix Location
Antenna Type:	PCB Antenna
Antenna Gain:	0dBi
EUT Power Supply:	DC 12V from battery

Note:

There are many products, Only 5026 the model was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above models, with difference being color of appearance and model name.

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	20	2422MHz	40	2442MHz	60	2462MHz
1	2403MHz	21	2423MHz	41	2443MHz	61	2463MHz
2	2404MHz	22	2424MHz	42	2444MHz	62	2464MHz
3	2405MHz	23	2425MHz	43	2445MHz	63	2465MHz
4	2406MHz	24	2426MHz	44	2446MHz	64	2466MHz
5	2407MHz	25	2427MHz	45	2447MHz	65	2467MHz
6	2408MHz	26	2428MHz	46	2448MHz	66	2468MHz
7	2409MHz	27	2429MHz	47	2449MHz	67	2469MHz
8	2410MHz	28	2430MHz	48	2450MHz	68	2470MHz
9	2411MHz	29	2431MHz	49	2451MHz	69	2471MHz
10	2412MHz	30	2432MHz	50	2452MHz	70	2472MHz
11	2413MHz	31	2433MHz	51	2453MHz	71	2473MHz
12	2414MHz	32	2434MHz	52	2454MHz	72	2474MHz
13	2415MHz	33	2435MHz	53	2455MHz	73	2475MHz
14	2416MHz	34	2436MHz	54	2456MHz	74	2476MHz
15	2417MHz	35	2437MHz	55	2457MHz	75	2477MHz
16	2418MHz	36	2438MHz	56	2458MHz	76	2478MHz
17	2419MHz	37	2439MHz	57	2459MHz	77	2479MHz
18	2420MHz	38	2440MHz	58	2460MHz	78	2480MHz
19	2421MHz	39	2441MHz	59	2461MHz		

Note:In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel

see below:

Channel	Frequency
The Lowest channel	2402MHz
The Middle channel	2441MHz
The Highest channel	2480MHz

FCCAssist 1.5

Parameter

MODE TX

Channel 0 Packet type 2-DH5 Data Types Pn9

Transmit Power 7 Hopping OFF Serial Port COM2

Send configuration

2019-09-17_16:54:29
Channel: 78 Data Types: Pn9
Transmit Power : 7 Packet type: 1-DH5
Send configuration information successfully

2019-09-17_16:57:16
Channel: 77 Data Types: Pn9
Transmit Power : 7 Packet type: 1-DH5
Send configuration information successfully

2019-09-17_16:57:35
Channel: 0 Data Types: Pn9
Transmit Power : 7 Packet type: 2-DH5
Send configuration information successfully

Description:

1 \ Channel: range 0-78, corresponding frequency 2.402GHz-2.480GHZ

2 \ Transmit Power range 0-10, 0 is the minimum, maximum 10

4.4 Test Environment

Operating Environment:	
Radiated Emission	
Temperature:	25.1 °C
Humidity:	51 % RH
Atmospheric Pressure:	992mbar
RF item test (RF test room)	
Temperature:	25.7 °C
Humidity:	56 % RH
Atmospheric Pressure:	992mbar
Test Mode:	Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT.

4.5 Description of Support Units

The EUT has been tested with associated equipment below.

Description	Manufacturer	Model No.	Remark	FCC certification
/	/	/	/	/
/	/	/	/	/

4.6 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate.

The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities.

The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the **Shenzhen Huaxia Testing Technology Co., Ltd.** quality system acc. to DIN EN ISO/IEC 17025.

Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CQA laboratory is reported:

No.	Item	Uncertainty	Notes
1	Radiated Emission (Below 1GHz)	5.12dB	(1)
2	Radiated Emission (Above 1GHz)	4.60dB	(1)
3	Conducted Disturbance (0.15~30MHz)	3.34dB	(1)
4	Radio Frequency	3×10^{-8}	(1)
5	Duty cycle	0.6 %.	(1)
6	Occupied Bandwidth	1.1%	(1)
7	RF conducted power	0.86dB	(1)
8	RF power density	0.74	(1)
9	Conducted Spurious emissions	0.86dB	(1)
10	Temperature test	0.8°C	(1)
11	Humidity test	2.0%	(1)
12	Supply voltages	0.5 %.	(1)
13	Frequency Error	5.5 Hz	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

4.7 Test Facility

Shenzhen Huaxia Testing Technology Co., Ltd,

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

The test facility is recognized, certified, or accredited by the following organizations:

- **IC Registration No.: 22984-1**

The 3m Semi-anechoic chamber of Shenzhen Huaxia Testing Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L5785)**

CNAS has accredited Shenzhen Huaxia Testing Technology Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 4742.01)**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 4742.01.

- **FCC Registration No.: 522263**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.:522263

4.9 Deviation from Standards

None.

4.10 Other Information Requested by the Customer

None.

4.11 Equipment List


Test Equipment	Manufacturer	Model No.	Instrument No.	Calibration Date	Calibration Due Date
EMI Test Receiver	R&S	ESR7	CQA-005	2018/9/26	2019/9/25
Spectrum analyzer	R&S	FSU26	CQA-038	2018/10/28	2018/10/27
Spectrum analyzer	keysight	N9020A	CQA-105	2018/10/28	2019/10/27
Preamplifier	MITEQ	AFS4-00010300-18-10P-4	CQA-035	2018/9/26	2019/9/25
Preamplifier	MITEQ	AMF-6D-02001800-29-20P	CQA-036	2018/11/2	2019/11/1
Loop antenna	Schwarzbeck	FMZB1516	CQA-087	2018/10/28	2020/10/27
Bilog Antenna	R&S	HL562	CQA-011	2018/9/26	2020/9/25
Horn Antenna	R&S	HF906	CQA-012	2018/9/26	2020/9/25
Horn Antenna	Schwarzbeck	BBHA 9170	CQA-088	2018/9/26	2020/9/25
Coaxial Cable (Above 1GHz)	CQA	N/A	C019	2018/9/26	2019/9/25
Coaxial Cable (Below 1GHz)	CQA	N/A	C020	2018/9/26	2019/9/25
Antenna Connector	CQA	RFC-01	CQA-080	2018/9/26	2019/9/25
RF cable(9KHz~40GHz)	CQA	RF-01	CQA-079	2018/9/26	2019/9/25
Power divider	MIDWEST	PWD-2533-02-SMA-79	CQA-067	2018/9/26	2019/9/25
EMI Test Receiver	R&S	ESPI3	CQA-013	2018/9/26	2019/9/25
LISN	R&S	ENV216	CQA-003	2018/11/5	2019/11/4
Coaxial cable	CQA	N/A	CQA-C009	2018/9/26	2019/9/25

Note:


The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

5. Test results and Measurement Data

5.1. Antenna Requirement


Standard requirement:	47 CFR Part 15C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.	
EUT Antenna:	PCB ANTENNA  The antenna is integral antenna. The best case gain of the antenna is 0dBi.

5.2. Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207		
Test Method:	ANSI C63.10: 2013		
Test Frequency Range:	150kHz to 30MHz		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test Procedure:	1) The mains terminal disturbance voltage test was conducted in a shielded room. 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.		
Test Setup:			
Test Mode:	N/A		
Test Results:	N/A		

Not application to this device


5.3. Conducted Peak Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (b)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Limit:	21dBm
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type. Only the worst case is recorded in the report.
Test Results:	Pass

Measurement Data


GFSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	3.731	21.00	Pass
Middle	3.473	21.00	Pass
Highest	3.241	21.00	Pass
$\pi/4$ DQPSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	4.309	21.00	Pass
Middle	4.058	21.00	Pass
Highest	3.834	21.00	Pass

Test plot as follows:



$\pi/4$DQPSK/LCH		
$\pi/4$DQPSK/MCH		
$\pi/4$DQPSK/HCH		


5.4. 20dB Occupy Bandwidth




Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Limit:	NA
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type. Only the worst case is recorded in the report.
Test Results:	Pass

Measurement Data


Test channel	20dB Occupy Bandwidth (MHz)		
	GFSK	$\pi/4$ DQPSK	/
Lowest	0.887	1.325	/
Middle	0.886	1.317	/
Highest	0.884	1.282	/

Test plot as follows:

Graphs		
GFSK/LCH	 Keylight Spectrum Analyzer - Occupied BW Center Freq 2.402000000 GHz Center Freq: 2.402000000 GHz Trig: Free Run Avg/Hold: 100/100 Radio Std: None Radio Device: BTS #IF Gain: Low #Atten: 30 dB Ref 10.00 dBm 15 dB/div Log Center 2.402 GHz #Res BW 20 kHz #VBW 62 kHz Span 2 MHz Sweep 4.8 ms Occupied Bandwidth 841.54 kHz Total Power 10.0 dBm Transmit Freq Error -27.105 kHz % of OBW Power 99.00 % x dB Bandwidth 887.4 kHz x dB -20.00 dB Frequency Center Freq 2.402000000 GHz CF Step 200.000 kHz Man Freq Offset 0 Hz Auto STATUS	
GFSK/MCH	 Keylight Spectrum Analyzer - Occupied BW Center Freq 2.441000000 GHz Center Freq: 2.441000000 GHz Trig: Free Run Avg/Hold: 100/100 Radio Std: None Radio Device: BTS #IF Gain: Low #Atten: 30 dB Ref 10.00 dBm 10 dB/div Log Center 2.441 GHz #Res BW 20 kHz #VBW 62 kHz Span 2 MHz Sweep 4.8 ms Occupied Bandwidth 825.85 kHz Total Power 10.1 dBm Transmit Freq Error -30.207 kHz % of OBW Power 99.00 % x dB Bandwidth 886.4 kHz x dB -20.00 dB Frequency Center Freq 2.441000000 GHz CF Step 200.000 kHz Man Freq Offset 0 Hz Auto STATUS	
GFSK/HCH	 Keylight Spectrum Analyzer - Occupied BW Center Freq 2.480000000 GHz Center Freq: 2.480000000 GHz Trig: Free Run Avg/Hold: 100/100 Radio Std: None Radio Device: BTS #IF Gain: Low #Atten: 30 dB Ref 5.00 dBm 10 dB/div Log Center 2.48 GHz #Res BW 20 kHz #VBW 62 kHz Span 2 MHz Sweep 4.8 ms Occupied Bandwidth 826.50 kHz Total Power 9.84 dBm Transmit Freq Error -30.944 kHz % of OBW Power 99.00 % x dB Bandwidth 883.5 kHz x dB -20.00 dB Frequency Center Freq 2.480000000 GHz CF Step 200.000 kHz Man Freq Offset 0 Hz Auto STATUS	


$\pi/4$DQPSK/LCH	 Center Freq 2.40200000 GHz Center Freq 2.40200000 GHz Trig: Free Run Avg/Hold: 100/100 Radio Std: None Radio Device: BTS Ref -10.00 dBm Center 2.402 GHz #Res BW 20 kHz #VBW 62 kHz Span 2 MHz Sweep 4.8 ms Occupied Bandwidth 1.1949 MHz Total Power 9.48 dBm Transmit Freq Error -25.584 kHz % of OBW Power 99.00 % x dB Bandwidth 1.325 MHz x dB -20.00 dB Frequency Center Freq 2.40200000 GHz CF Step 200.000 kHz Auto Freq Offset 0 Hz	
$\pi/4$DQPSK/MCH	 Center Freq 2.44100000 GHz Center Freq 2.44100000 GHz Trig: Free Run Avg/Hold: 100/100 Radio Std: None Radio Device: BTS Ref 5.00 dBm Center 2.441 GHz #Res BW 20 kHz #VBW 62 kHz Span 2 MHz Sweep 4.8 ms Occupied Bandwidth 1.1952 MHz Total Power 9.26 dBm Transmit Freq Error -24.926 kHz % of OBW Power 99.00 % x dB Bandwidth 1.317 MHz x dB -20.00 dB Frequency Center Freq 2.44100000 GHz CF Step 200.000 kHz Auto Freq Offset 0 Hz	
$\pi/4$DQPSK/HCH	 Center Freq 2.48000000 GHz Center Freq 2.48000000 GHz Trig: Free Run Avg/Hold: 100/100 Radio Std: None Radio Device: BTS Ref 0.00 dBm Center 2.48 GHz #Res BW 20 kHz #VBW 62 kHz Span 2 MHz Sweep 4.8 ms Occupied Bandwidth 1.1848 MHz Total Power 9.15 dBm Transmit Freq Error -26.361 kHz % of OBW Power 99.00 % x dB Bandwidth 1.282 MHz x dB -20.00 dB Frequency Center Freq 2.48000000 GHz CF Step 200.000 kHz Auto Freq Offset 0 Hz	

5.5. Frequencies Separation

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Limit:	2/3 of the 20dB bandwidth
	Remark: the transmission power is less than 0.125W.
Exploratory Test Mode:	Hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type. Only the worst case is recorded in the report.
Test Results:	Pass


Modulation	Channel	Channel Separation (MHz)	Limit(MHz)	Result
GFSK	CH00	1.003	25KHz or 2/3*20dB bandwidth	Pass
	CH01			
	CH39	1.009		
	CH40			
	CH77	0.996		
	CH78			
pi/4DQPSK	CH00	1.000	25KHz or 2/3*20dB bandwidth	Pass
	CH01			
	CH39	1.322		
	CH40			
	CH77	0.999		
	CH78			

Test plot as follows:



$\pi/4$DQPSK / LCH	
$\pi/4$DQPSK / MCH	
$\pi/4$DQPSK / HCH	


5.6. Hopping Channel Number

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Limit:	At least 15 channels
Exploratory Test Mode:	hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type. Only the worst case is recorded in the report.
Test Results:	Pass


Measurement Data

Mode	Hopping channel numbers	Limit
GFSK	79	≥ 15
$\pi/4$ DQPSK	79	≥ 15

Test plot as follows:



5.7. Dwell Time

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Test Mode:	Only the worst case is recorded in the report.
Limit:	0.4 Second
Test Results:	Pass

Measurement Data

Mode	Packet	Channel	Burst Width [ms/hop/ch]	Dwell Time[ms]	Limit (ms)
GFSK	DH1	MCH	0.373	119.520	≤400
GFSK	DH3	MCH	1.629	260.640	≤400
GFSK	DH5	MCH	2.876	306.805	≤400
π/4DQPSK	2DH1	MCH	0.384	123.040	≤400
π/4DQPSK	2DH3	MCH	1.634	261.440	≤400
π/4DQPSK	2DH5	MCH	2.878	306.965	≤400

Remark:


The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$

DH1/2DH1/3DH1 Dwell time = Burst Width(ms)*(1600/ (2*79))*31.6

DH3/2DH3/3DH3 Dwell time = Burst Width (ms)*(1600/ (4*79))*31.6


DH5/2DH5/3DH5 Dwell time = Burst Width (ms)*(1600/ (6*79))*31.6

Test plot as follows:



$\pi/4$ DQPSK_2DH1/MCH	Keylight Spectrum Analyzer - Swept SA Center Freq 2.441000000 GHz Ref Offset 1 dB Ref 20.00 dBm Mkr3 1.751 ms 6.13 dBm Center 2.441000000 GHz Res BW 1.0 MHz #VBW 3.0 MHz Sweep 4.000 ms (8001 pts) <table><tr><th>MNPR</th><th>MODE</th><th>TRIG</th><th>SCL</th><th>X</th><th>Y</th><th>FUNCTION</th><th>FUNCTION WIDTH</th><th>FUNCTION VALUE</th></tr><tr><td>1</td><td>N</td><td>1</td><td>t</td><td>500.5 us</td><td>5.57 dBm</td><td></td><td></td><td></td></tr><tr><td>2</td><td>N</td><td>1</td><td>t</td><td>885.0 us</td><td>3.97 dBm</td><td></td><td></td><td></td></tr><tr><td>3</td><td>N</td><td>1</td><td>t</td><td>1.751 ms</td><td>6.13 dBm</td><td></td><td></td><td></td></tr></table> File <temp.png> saved Frequency Auto Tune Center Freq 2.441000000 GHz Start Freq 2.441000000 GHz Stop Freq 2.441000000 GHz CF Step 1.000000 MHz Auto Freq Offset 0 Hz Scale Type Log	MNPR	MODE	TRIG	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	t	500.5 us	5.57 dBm				2	N	1	t	885.0 us	3.97 dBm				3	N	1	t	1.751 ms	6.13 dBm			
MNPR	MODE	TRIG	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																													
1	N	1	t	500.5 us	5.57 dBm																																
2	N	1	t	885.0 us	3.97 dBm																																
3	N	1	t	1.751 ms	6.13 dBm																																
$\pi/4$ DQPSK_2DH3/MCH	Keylight Spectrum Analyzer - Swept SA Center Freq 2.441000000 GHz Ref Offset 1 dB Ref 20.00 dBm Mkr3 3.946 ms 6.22 dBm Center 2.441000000 GHz Res BW 1.0 MHz #VBW 3.0 MHz Sweep 8.000 ms (8001 pts) <table><tr><th>MNPR</th><th>MODE</th><th>TRIG</th><th>SCL</th><th>X</th><th>Y</th><th>FUNCTION</th><th>FUNCTION WIDTH</th><th>FUNCTION VALUE</th></tr><tr><td>1</td><td>N</td><td>1</td><td>t</td><td>197.0 us</td><td>6.29 dBm</td><td></td><td></td><td></td></tr><tr><td>2</td><td>N</td><td>1</td><td>t</td><td>1.831 ms</td><td>6.20 dBm</td><td></td><td></td><td></td></tr><tr><td>3</td><td>N</td><td>1</td><td>t</td><td>3.946 ms</td><td>6.22 dBm</td><td></td><td></td><td></td></tr></table> File <temp.png> saved Frequency Auto Tune Center Freq 2.441000000 GHz Start Freq 2.441000000 GHz Stop Freq 2.441000000 GHz CF Step 1.000000 MHz Auto Freq Offset 0 Hz Scale Type Log	MNPR	MODE	TRIG	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	t	197.0 us	6.29 dBm				2	N	1	t	1.831 ms	6.20 dBm				3	N	1	t	3.946 ms	6.22 dBm			
MNPR	MODE	TRIG	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																													
1	N	1	t	197.0 us	6.29 dBm																																
2	N	1	t	1.831 ms	6.20 dBm																																
3	N	1	t	3.946 ms	6.22 dBm																																
$\pi/4$ DQPSK_2DH5/MCH	Keylight Spectrum Analyzer - Swept SA Center Freq 2.441000000 GHz Ref Offset 1 dB Ref 20.00 dBm Mkr3 6.911 ms 6.30 dBm Center 2.441000000 GHz Res BW 1.0 MHz #VBW 3.0 MHz Sweep 10.13 ms (8001 pts) <table><tr><th>MNPR</th><th>MODE</th><th>TRIG</th><th>SCL</th><th>X</th><th>Y</th><th>FUNCTION</th><th>FUNCTION WIDTH</th><th>FUNCTION VALUE</th></tr><tr><td>1</td><td>N</td><td>1</td><td>t</td><td>661.2 us</td><td>6.31 dBm</td><td></td><td></td><td></td></tr><tr><td>2</td><td>N</td><td>1</td><td>t</td><td>3.839 ms</td><td>6.65 dBm</td><td></td><td></td><td></td></tr><tr><td>3</td><td>N</td><td>1</td><td>t</td><td>6.911 ms</td><td>6.30 dBm</td><td></td><td></td><td></td></tr></table> File <temp.png> saved Frequency Auto Tune Center Freq 2.441000000 GHz Start Freq 2.441000000 GHz Stop Freq 2.441000000 GHz CF Step 1.000000 MHz Auto Freq Offset 0 Hz Scale Type Log	MNPR	MODE	TRIG	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	t	661.2 us	6.31 dBm				2	N	1	t	3.839 ms	6.65 dBm				3	N	1	t	6.911 ms	6.30 dBm			
MNPR	MODE	TRIG	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																													
1	N	1	t	661.2 us	6.31 dBm																																
2	N	1	t	3.839 ms	6.65 dBm																																
3	N	1	t	6.911 ms	6.30 dBm																																


5.8. Band-edge for RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10:2013
Test Setup:	 Remark: $Offset = \text{cable loss} + \text{attenuation factor}$.
Limit:	In any 100kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Exploratory Test Mode:	Hopping and Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type. Only the worst case is recorded in the report.
Test Results:	Pass


Test plot as follows:

Graphs


GFSK/LCH/No Hop




GFSK/LCH/Hop




GFSK/HCH/No Hop



GFSK/HCH/Hop	Keylight Spectrum Analyzer - Swept SA Center Freq 2.483500000 GHz 10 dB/div Ref 20.00 dBm Start 2.45350 GHz #Res BW 100 kHz Stop 2.51350 GHz #VBW 300 kHz Sweep 5.867 ms (2001 pts) <table><thead><tr><th>MNR</th><th>MODE</th><th>TRIG</th><th>SCL</th><th>X</th><th>Y</th><th>FUNCTION</th><th>FUNCTION WIDTH</th><th>FUNCTION VALUE</th></tr></thead><tbody><tr><td>1</td><td>N</td><td>1</td><td>f</td><td>2.483 50 GHz</td><td>-49.216 dBm</td><td></td><td></td><td></td></tr><tr><td>2</td><td>N</td><td>1</td><td>f</td><td>2.500 00 GHz</td><td>-59.170 dBm</td><td></td><td></td><td></td></tr><tr><td>3</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>4</td><td>N</td><td>1</td><td>f</td><td>2.457 82 GHz</td><td>3.250 dBm</td><td></td><td></td><td></td></tr><tr><td>5</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>6</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>7</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>8</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>9</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>10</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>11</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></tbody></table> Frequency Auto Tune Center Freq 2.483500000 GHz Start Freq 2.453500000 GHz Stop Freq 2.513500000 GHz CF Step 6.000000 MHz Man Freq Offset 0 Hz Scale Type Log Lin	MNR	MODE	TRIG	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	2.483 50 GHz	-49.216 dBm				2	N	1	f	2.500 00 GHz	-59.170 dBm				3									4	N	1	f	2.457 82 GHz	3.250 dBm				5									6									7									8									9									10									11								
MNR	MODE	TRIG	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																																																																																																					
1	N	1	f	2.483 50 GHz	-49.216 dBm																																																																																																								
2	N	1	f	2.500 00 GHz	-59.170 dBm																																																																																																								
3																																																																																																													
4	N	1	f	2.457 82 GHz	3.250 dBm																																																																																																								
5																																																																																																													
6																																																																																																													
7																																																																																																													
8																																																																																																													
9																																																																																																													
10																																																																																																													
11																																																																																																													
$\pi/4$ DQPSK/LCH/No Hop	Keylight Spectrum Analyzer - Swept SA Center Freq 2.356750000 GHz 10 dB/div Ref 20.00 dBm Start 2.31000 GHz #Res BW 100 kHz Stop 2.40350 GHz #VBW 300 kHz Sweep 9.067 ms (2001 pts) <table><thead><tr><th>MNR</th><th>MODE</th><th>TRIG</th><th>SCL</th><th>X</th><th>Y</th><th>FUNCTION</th><th>FUNCTION WIDTH</th><th>FUNCTION VALUE</th></tr></thead><tbody><tr><td>1</td><td>N</td><td>1</td><td>f</td><td>2.390 00 GHz</td><td>-51.778 dBm</td><td></td><td></td><td></td></tr><tr><td>2</td><td>N</td><td>1</td><td>f</td><td>2.400 00 GHz</td><td>-37.718 dBm</td><td></td><td></td><td></td></tr><tr><td>3</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>4</td><td>N</td><td>1</td><td>f</td><td>2.401 77 GHz</td><td>0.139 dBm</td><td></td><td></td><td></td></tr><tr><td>5</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>6</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>7</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>8</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>9</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>10</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>11</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></tbody></table> Frequency Auto Tune Center Freq 2.356750000 GHz Start Freq 2.310000000 GHz Stop Freq 2.403500000 GHz CF Step 9.350000 MHz Man Freq Offset 0 Hz Scale Type Log Lin	MNR	MODE	TRIG	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	2.390 00 GHz	-51.778 dBm				2	N	1	f	2.400 00 GHz	-37.718 dBm				3									4	N	1	f	2.401 77 GHz	0.139 dBm				5									6									7									8									9									10									11								
MNR	MODE	TRIG	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																																																																																																					
1	N	1	f	2.390 00 GHz	-51.778 dBm																																																																																																								
2	N	1	f	2.400 00 GHz	-37.718 dBm																																																																																																								
3																																																																																																													
4	N	1	f	2.401 77 GHz	0.139 dBm																																																																																																								
5																																																																																																													
6																																																																																																													
7																																																																																																													
8																																																																																																													
9																																																																																																													
10																																																																																																													
11																																																																																																													
$\pi/4$ DQPSK/LCH/Hop	Keylight Spectrum Analyzer - Swept SA Center Freq 2.400000000 GHz 10 dB/div Ref 20.00 dBm Start 2.37000 GHz #Res BW 100 kHz Stop 2.43000 GHz #VBW 300 kHz Sweep 5.867 ms (2001 pts) <table><thead><tr><th>MNR</th><th>MODE</th><th>TRIG</th><th>SCL</th><th>X</th><th>Y</th><th>FUNCTION</th><th>FUNCTION WIDTH</th><th>FUNCTION VALUE</th></tr></thead><tbody><tr><td>1</td><td>N</td><td>1</td><td>f</td><td>2.390 00 GHz</td><td>-59.609 dBm</td><td></td><td></td><td></td></tr><tr><td>2</td><td>N</td><td>1</td><td>f</td><td>2.400 00 GHz</td><td>-40.061 dBm</td><td></td><td></td><td></td></tr><tr><td>3</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>4</td><td>N</td><td>1</td><td>f</td><td>2.413 83 GHz</td><td>3.332 dBm</td><td></td><td></td><td></td></tr><tr><td>5</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>6</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>7</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>8</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>9</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>10</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>11</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></tbody></table> Frequency Auto Tune Center Freq 2.400000000 GHz Start Freq 2.370000000 GHz Stop Freq 2.430000000 GHz CF Step 6.000000 MHz Man Freq Offset 0 Hz Scale Type Log Lin	MNR	MODE	TRIG	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	2.390 00 GHz	-59.609 dBm				2	N	1	f	2.400 00 GHz	-40.061 dBm				3									4	N	1	f	2.413 83 GHz	3.332 dBm				5									6									7									8									9									10									11								
MNR	MODE	TRIG	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																																																																																																					
1	N	1	f	2.390 00 GHz	-59.609 dBm																																																																																																								
2	N	1	f	2.400 00 GHz	-40.061 dBm																																																																																																								
3																																																																																																													
4	N	1	f	2.413 83 GHz	3.332 dBm																																																																																																								
5																																																																																																													
6																																																																																																													
7																																																																																																													
8																																																																																																													
9																																																																																																													
10																																																																																																													
11																																																																																																													



5.9. Spurious RF Conducted Emissions


Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10:2013
Test Setup:	 <i>Remark: Offset=cable loss+ attenuation factor.</i>
Limit:	In any 100kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type.
Test Results:	Pass

GFSK LCH_Graphs


Reference



30MHz-10GHz



10GHz-26.5GHz




GFSK_MCH_Graphs


Reference



30MHz-10GHz



10GHz-26.5GHz




GFSK HCH Graphs


Reference





30MHz-10GHz




10GHz-26.5GHz





$\pi/4$ DQPSK LCH_Graphs

Reference	 Keysight Spectrum Analyzer - Swept SA Center Freq 2.40200000 GHz Ref 20.00 dBm Mkr1 2.402 000 00 GHz 1.438 dBm Center 2.402000 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 1.067 ms (8001 pts) Span 2.000 MHz Frequency Auto Tune Center Freq 2.402000000 GHz Start Freq 2.401000000 GHz Stop Freq 2.403000000 GHz CF Step 200.000 kHz Man Freq Offset 0 Hz Scale Type Log
30MHz-10GHz	 Keysight Spectrum Analyzer - Swept SA Start Freq 30.0000000 MHz Ref 20.00 dBm Mkr1 2.397 9 GHz -35.931 dBm Start 0.030 GHz #Res BW 100 kHz #VBW 300 kHz Stop 10.000 GHz #Sweep 500.0 ms (20001 pts) Frequency Auto Tune Center Freq 5.015000000 GHz Start Freq 30.000000 MHz Stop Freq 10.000000000 GHz CF Step 997.000000 MHz Man Freq Offset 0 Hz Scale Type Log
10GHz-26.5GHz	 Keysight Spectrum Analyzer - Swept SA Start Freq 10.000000000 GHz Ref 20.00 dBm Mkr1 24.963 2 GHz -41.403 dBm Start 10.000 GHz #Res BW 100 kHz #VBW 300 kHz Stop 26.000 GHz #Sweep 500.0 ms (20001 pts) Frequency Auto Tune Center Freq 18.000000000 GHz Start Freq 10.000000000 GHz Stop Freq 26.000000000 GHz CF Step 1.600000000 GHz Man Freq Offset 0 Hz Scale Type Log



$\pi/4$ DQPSK HCH_Graphs

Reference	 Keysight Spectrum Analyzer - Swept SA Center Freq 2.480000000 GHz Ref 20.00 dBm Mkr1 2.480 000 00 GHz 1.924 dBm Center 2.480000 GHz #Res BW 100 kHz #VBW 300 kHz Span 2.000 MHz Sweep 1.067 ms (8001 pts) Frequency Auto Tune Center Freq 2.480000000 GHz Start Freq 2.479000000 GHz Stop Freq 2.481000000 GHz CF Step 200.000 kHz Man Freq Offset 0 Hz Scale Type Log																																																																																																												
30MHz-10GHz	 Keysight Spectrum Analyzer - Swept SA Start Freq 30.000000 MHz Ref 20.00 dBm Mkr1 4.960 2 GHz -36.005 dBm Stop 10.000 GHz #Res BW 100 kHz #VBW 300 kHz #Sweep 500.0 ms (20001 pts) <table><thead><tr><th>MNPR</th><th>MODE</th><th>TRIG</th><th>SCL</th><th>X</th><th>Y</th><th>FUNCTION</th><th>FUNCTION WIDTH</th><th>FUNCTION VALUE</th></tr></thead><tbody><tr><td>1</td><td>N</td><td>1</td><td>f</td><td>4.960 2 GHz</td><td>-36.005 dBm</td><td></td><td></td><td></td></tr><tr><td>2</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>3</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>4</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>5</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>6</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>7</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>8</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>9</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>10</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>11</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></tbody></table> Frequency Auto Tune Center Freq 5.015000000 GHz Start Freq 30.000000 MHz Stop Freq 10.000000000 GHz CF Step 997.000000 MHz Man Freq Offset 0 Hz Scale Type Log	MNPR	MODE	TRIG	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	4.960 2 GHz	-36.005 dBm				2									3									4									5									6									7									8									9									10									11								
MNPR	MODE	TRIG	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																																																																																																					
1	N	1	f	4.960 2 GHz	-36.005 dBm																																																																																																								
2																																																																																																													
3																																																																																																													
4																																																																																																													
5																																																																																																													
6																																																																																																													
7																																																																																																													
8																																																																																																													
9																																																																																																													
10																																																																																																													
11																																																																																																													
10GHz-26.5GHz	 Keysight Spectrum Analyzer - Swept SA Start Freq 10.000000000 GHz Ref 20.00 dBm Mkr1 24.968 0 GHz -42.140 dBm Stop 26.000 GHz #Res BW 100 kHz #VBW 300 kHz #Sweep 500.0 ms (20001 pts) <table><thead><tr><th>MNPR</th><th>MODE</th><th>TRIG</th><th>SCL</th><th>X</th><th>Y</th><th>FUNCTION</th><th>FUNCTION WIDTH</th><th>FUNCTION VALUE</th></tr></thead><tbody><tr><td>1</td><td>N</td><td>1</td><td>f</td><td>24.968 0 GHz</td><td>-42.140 dBm</td><td></td><td></td><td></td></tr><tr><td>2</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>3</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>4</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>5</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>6</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>7</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>8</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>9</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>10</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>11</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></tbody></table> Frequency Auto Tune Center Freq 18.000000000 GHz Start Freq 10.000000000 GHz Stop Freq 26.000000000 GHz CF Step 1.600000000 GHz Man Freq Offset 0 Hz Scale Type Log	MNPR	MODE	TRIG	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	24.968 0 GHz	-42.140 dBm				2									3									4									5									6									7									8									9									10									11								
MNPR	MODE	TRIG	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																																																																																																					
1	N	1	f	24.968 0 GHz	-42.140 dBm																																																																																																								
2																																																																																																													
3																																																																																																													
4																																																																																																													
5																																																																																																													
6																																																																																																													
7																																																																																																													
8																																																																																																													
9																																																																																																													
10																																																																																																													
11																																																																																																													

Remark: Pre test 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report. Per FCC Part 15.33 (a) and 15.31 (o) ,The amplitude of spurious emissions from intentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this part.

5.10. Other requirements Frequency Hopping Spread Spectrum System

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1), (h) requirement:
The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals. Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section. The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.	
Compliance for section 15.247(a)(1)	
According to Bluetooth Core Specification, the pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones. • Number of shift register stages: 9 • Length of pseudo-random sequence: $2^9 - 1 = 511$ bits • Longest sequence of zeros: 8 (non-inverted signal) <i>Linear Feedback Shift Register for Generation of the PRBS sequence</i> An example of Pseudorandom Frequency Hopping Sequence as follow: Each frequency used equally on the average by each transmitter. According to Bluetooth Core Specification, Bluetooth receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any Bluetooth transmitters and shift frequencies in synchronization with the transmitted signals.	
Compliance for section 15.247(g)	
According to Bluetooth Core Specification, the Bluetooth system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.	
Compliance for section 15.247(h)	

According to Bluetooth Core specification, the Bluetooth system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels.

According to the Bluetooth Core specification, the Bluetooth system is designed not have the ability to coordinated with other FHSS System in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitter.

5.11.Radiated Spurious Emission & Restricted bands

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10: 2013				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Peak	100 kHz	300kHz	Peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.					

Test Setup:




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

Test Procedure:


- a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
 2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
 Note: For the radiated emission test above 1GHz:
 Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

	d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel (2402MHz),the middle channel (2441MHz),the Highest channel (2480MHz) h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. i. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Non-hopping transmitting mode with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case. For below 1GHz part, through pre-scan, the worst case is the lowest channel. Only the worst case is recorded in the report.
Test Results:	Pass

5.11.1. Radiated Emission below 1GHz

30MHz~1GHz

Test mode: Transmitting Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		33.7986	26.02	-8.07	17.95	40.00	-22.05	QP		
2		43.5057	32.42	-15.28	17.14	40.00	-22.86	QP		
3	*	51.6616	38.10	-18.73	19.37	40.00	-20.63	QP		
4		64.2074	33.73	-18.81	14.92	40.00	-25.08	QP		
5		230.9068	35.84	-13.83	22.01	46.00	-23.99	QP		
6		601.4265	28.51	-4.86	23.65	46.00	-22.35	QP		

Remark:


The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Factor= Antenna Factor + Cable Factor – Preamplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.

Test mode:	Transmitting	Horizontal
------------	--------------	------------



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1	30.2111	23.32	-3.68	19.64	40.00	-20.36	QP		
2	34.6385	27.93	-7.47	20.46	40.00	-19.54	QP		
3	48.3318	34.33	-16.99	17.34	40.00	-22.66	QP		
4	* 57.5939	39.54	-18.88	20.66	40.00	-19.34	QP		
5	230.0985	33.36	-13.77	19.59	46.00	-26.41	QP		
6	360.4476	32.32	-9.57	22.75	46.00	-23.25	QP		

Remark:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Factor= Antenna Factor + Cable Factor – Preamplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.

5.11.2. Transmitter Emission above 1GHz

mode:		GFSK(DH5)		Test channel:		Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
2390	54.02	-9.2	44.82	74	-29.18	Peak	H
2400	51.45	-9.39	42.06	74	-31.94	Peak	H
4804	51.63	-4.33	47.30	74	-26.70	Peak	H
7206	48.26	1.01	49.27	74	-24.73	Peak	H
2390	54.02	-9.2	44.82	74	-29.18	Peak	V
2400	51.28	-9.39	41.89	74	-32.11	Peak	V
4804	50.80	-4.33	46.47	74	-27.53	Peak	V
7206	50.00	1.01	51.01	74	-22.99	Peak	V

mode:		GFSK(DH5)		Test channel:		Middle	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
4882	54.77	-4.11	50.66	74	-23.34	Peak	H
7323	51.53	1.51	53.04	74	-19.96	Peak	H
4882	52.23	-4.11	48.12	74	-25.88	Peak	V
7323	49.58	1.51	51.09	74	-22.91	Peak	V

mode:		GFSK(DH5)		Test channel:		Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
2483.5	54.67	-9.29	45.38	74	-28.62	Peak	H
4960	52.88	-4.04	48.84	74	-25.16	Peak	H
7440	51.36	1.57	52.93	74	-21.07	Peak	H
2483.5	53.63	-9.29	44.34	74	-29.66	Peak	V
4960	52.45	-4.04	48.41	74	-25.59	Peak	V
7440	51.83	1.57	53.40	74	-20.60	Peak	V

mode:		$\pi/4$ DQPSK (2DH5)		Test channel:		Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)		H/V
2390	53.89	-9.2	44.69	74	-29.31	Peak	H
2400	51.70	-9.39	42.31	74	-31.69	Peak	H
4804	51.50	-4.33	47.17	74	-26.83	Peak	H
7206	48.91	1.01	49.92	74	-24.08	Peak	H
2390	53.69	-9.2	44.49	74	-29.51	Peak	V
2400	51.91	-9.39	42.52	74	-31.48	Peak	V
4804	51.83	-4.33	47.50	74	-26.50	Peak	V
7206	49.90	1.01	50.91	74	-23.09	Peak	V

mode:		$\pi/4$ DQPSK (2DH5)		Test channel:		Middle	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)		H/V
4882	54.23	-4.11	50.12	74	-23.88	peak	H
7323	52.22	1.51	53.73	74	-20.27	peak	H
4882	51.60	-4.11	47.49	74	-26.51	peak	V
7323	49.51	1.51	51.02	74	-22.98	peak	V

mode:		$\pi/4$ DQPSK (2DH5)		Test channel:		Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)		H/V
2483.5	54.72	-9.29	45.43	74	-28.57	Peak	H
4960	51.62	-4.04	47.58	74	-26.42	Peak	H
7440	50.76	1.57	52.33	74	-21.67	Peak	H
2483.5	53.49	-9.29	44.20	74	-29.80	Peak	V
4960	51.10	-4.04	47.06	74	-26.94	Peak	V
7440	51.58	1.57	53.15	74	-20.85	Peak	V

Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 2) Scan from 9kHz to 25GHz, the disturbance above 10GHz and below 30MHz was very low. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.


6. Photographs - EUT Test Setup

Radiated Emission

Below 30MHz



30MHz~1GHz




Above 1GHz




7. Photographs - EUT Constructional Details



External photos

















Internal photos









The End