FCC ID: YWX-ES-AIO-02 Report No.: T131205L01-RP1-1

APPENDIX I MAXIMUM PERMISSIBLE EXPOSURE

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate theen vironment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

| Frequency Range (MHz) | Electric Field Strength (V/m) | | | Average Time | | | | |
|---|----------------------------------|--|--------|--------------|--|--|--|--|
| (A) Limits for Occupational / Control Exposures | | | | | | | | |
| 300-1,500 | F/300 | | F/300 | 6 | | | | |
| 1,500-100,000 | | | 5 | 6 | | | | |
| (B) Limits for General Population / Uncontrol Exposures | | | | | | | | |
| 300-1,500 | | | F/1500 | 6 | | | | |
| 1,500-100,000 | | | 1 | 30 | | | | |

CALCULATIONS

Given
$$E = \frac{\sqrt{30 \times P \times G}}{d} \& S = \frac{E^2}{3770}$$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = *Power density in milliwatts / square centimeter*

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770 d^2}$$

Changing to units of mW and cm, using:

$$P(mW) = P(W) / 1000$$
 and $d(cm) = d(m) / 100$

Yields

$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm2

FCC ID: YWX-ES-AIO-02 Report No.: T131205L01-RP1-1

<u>LIMIT</u>

Power Density Limit, S=1.0mW/cm²

TEST RESULTS

| Mode | Chain | Antenna Gain (dBi) | Minimum separation distance (cm) | Output Power (dBm) | Numeric antenna gain (mW) | Power Density Limit (mW/cm²) | Power Density at 20cm (mW/cm ²) |
|--------|-------|--------------------------|---|--------------------------|------------------------------------|---------------------------------------|--|
| GFSK | 2 | 2.0 | 20 | 4.17 | 1.58 | 1.00 | 0.000824 |
| 8-DPSK | 2 | 2.0 | 20 | 5.94 | 1.58 | 1.00 | 0.001238 |

Remark: For mobile or fixed location transmitters, the maximum power density is 1.0 mW/cm² even if the calculation indicates that the power density would be larger.