

Beijing Euro Card Standards Technical Services Co., Ltd.

Ray Stone Palm


Model: ZZB-2

November 18, 2010
Report No.: 1003026
(This report supersedes NONE)



Modifications made to the product : None

This Test Report is Issued Under the Authority of:

| | |
|---|--|
|  |  |
| Andy Hao Compliance Engineer | Jackson Chen Technical Manager |

This test report may be reproduced in full only.
Test result presented in this test report is applicable to the representative sample only.

RF Test Report
TO: FCC 15.247:2009

SIEMIC, INC.
Accessing global markets



Laboratory Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to [testing](#) and [certification](#), SIEMIC provides initial design reviews and [compliance management](#) through out a project. Our extensive experience with [China](#), [Asia Pacific](#), [North America](#), [European](#), and [international](#) compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the [global markets](#).

Accreditations for Conformity Assessment

| Country/Region | Accreditation Body | Scope |
|----------------|------------------------|------------------------------------|
| USA | FCC, A2LA | EMC , RF/Wireless , Telecom |
| Canada | IC, A2LA, NIST | EMC, RF/Wireless , Telecom |
| Taiwan | BSMI , NCC , NIST | EMC, RF, Telecom , Safety |
| Hong Kong | OFTA , NIST | RF/Wireless , Telecom |
| Australia | NATA, NIST | EMC, RF, Telecom , Safety |
| Korea | KCC/RRA, NIST | EMI, EMS, RF , Telecom, Safety |
| Japan | VCCI, JATE, TELEC, RFT | EMI, RF/Wireless, Telecom |
| Mexico | NOM, COFETEL, Caniety | Safety, EMC , RF/Wireless, Telecom |
| Europe | A2LA, NIST | EMC, RF, Telecom , Safety |

Accreditations for Product Certifications

| Country | Accreditation Body | Scope |
|-----------|--------------------|--------------------|
| USA | FCC TCB, NIST | EMC , RF , Telecom |
| Canada | IC FCB , NIST | EMC , RF , Telecom |
| Singapore | iDA, NIST | EMC , RF , Telecom |



Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 3 of 66
www.siemic.com.cn

This page has been left blank intentionally.



SIEMIC, INC.

Accessing global markets

Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 4 of 66
www.siemic.com.cn

CONTENTS

| | | |
|---|---|----|
| 1 | EXECUTIVE SUMMARY & EUT INFORMATION | 5 |
| 2 | TECHNICAL DETAILS | 6 |
| 3 | MODIFICATION | 7 |
| 4 | TEST SUMMARY | 8 |
| 5 | MEASUREMENTS, EXAMINATION AND DERIVED RESULTS | 9 |
| | ANNEX A. TEST INSTRUMENT & METHOD | 39 |
| | ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS..... | 43 |
| | ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT..... | 44 |
| | ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PART LIST | 48 |
| | ANNEX E. SIEMIC ACCREDITATION CERTIFICATES..... | 49 |



1 Executive Summary & EUT information

The purpose of this test programme was to demonstrate compliance of the Beijing Euro Card Standards Technical Services Co., Ltd., Ray Stone Palm, and model: ZZB-2 against the current Stipulated Standards. The Ray Stone Palm has demonstrated compliance with the FCC 15.247:2009.

EUT Information

| | |
|---|--|
| EUT Description | Ray Stone Palm compliance with IEEE 802.11/b/g, communicate with other WLAN device |
| Model No | ZZB-2 |
| Input Power | DC 7.4-8.4A |
| Classification Per Stipulated Test Standard | Spread Spectrum System/Device |



Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 6 of 66
www.siemic.com.cn

2 TECHNICAL DETAILS

| | |
|---------------------------------|--|
| Purpose | Compliance testing of WIFI Module with stipulated standard |
| Applicant / Client | Beijing Euro Card Standards Technical Services Co., Ltd. Beijing Haidian District, two miles west of Building 1, Building B, Unit 303 |
| Manufacturer | Beijing E-world Technology Co., Ltd. Shi Lei North Third Ring Road, Dongcheng District, nine-story World Trade Center |
| Laboratory performing the tests | SIEMIC Nanjing (China) Laboratories NO.2-1, Longcang Dadao, Yuhua Economic Development Zone, Nanjing, China Tel: +86(25)86730128/86730129 Fax: +86(25)86730127 Email: info@siemic.com |
| Test report reference number | 1003026 |
| Date EUT received | November 01, 2010 |
| Standard applied | FCC 15.247:2009 |
| Dates of test (from – to) | November 02~ November 18, 2010 |
| No of Units: | #2 |
| Equipment Category: | DTS |
| Trade Name: | Logic diagram |
| Model : | ZZB-2 |
| RF Operating Frequency (ies) | 2412MHz-2462MHz |
| Modulation : | GFSK |
| FCC ID: | YXWZZB-2 |



SIEMIC, INC.

Accessing global markets

Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 7 of 66
www.siemic.com.cn

3 MODIFICATION

NONE



4 TEST SUMMARY

The product was tested in accordance with the following specifications. All Testing has been performed according to below product classification:

Spread Spectrum System/Device

Test Results Summary

| Test Standard | Description | Pass / Fail |
|--|----------------------------------|-------------|
| CFR 47 Part 15.247: 2009 | | |
| 15.203 | Antenna Requirement | Pass |
| 15.205 | Restricted Band of Operation | Pass |
| 15.207(a) | Conducted Emissions Voltage | Pass |
| 15.247(a)(1) | Channel Separation | N/A |
| 15.247(a)(1) | Occupied Bandwidth | Pass |
| 15.247(a)(2) | 6dB Bandwidth | Pass |
| 15.247(a)(1) | Number of Hopping Channels | N/A |
| 15.247(a)(1) | Time of Occupancy | N/A |
| 15.247(b) | Output Power | Pass |
| 15.247(c) | Antenna Gain > 6 dBi | Pass |
| 15.247(d) | Conducted Spurious Emissions | Pass |
| 15.209; 15.247(d) | Radiated Spurious Emissions | Pass |
| 15.247(e) | Power Spectral Density | Pass |
| 15.247(f) | Hybrid System Requirement | N/A |
| 15.247(g) | Hopping Capability | N/A |
| 15.247(h) | Hopping Coordination Requirement | N/A |
| 15.247(i) | RF Exposure requirement | Pass |
| ANSI C63.4: 2003 | | |
| PS: Preliminary AC line and radiated emissions testing has been performed on all models, only worst case test result is presented in this test report. | | |



SIEMIC, INC.

Accessing global markets

Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 9 of 66
www.siemic.com.cn

5 MEASUREMENTS, EXAMINATION AND DERIVED RESULTS

5.1 Antenna Requirement

Requirement(s): 47 CFR §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Antenna requirement must meet at least one of the following:

- a) Antenna must be permanently attached to the device.
- b) Antenna must use a unique type of connector to attach to the device.
- c) Device must be professionally installed. Installer shall be responsible for ensuring that the correct antenna is employed with the device.

The antenna is integral antenna. Antenna maximum gain is 0 dBi.



5.2 Conducted Emissions Voltage

Requirement:

| Frequency of emission (MHz) | Conducted limit (dBμV) | |
|------------------------------------|--|----------------|
| | Quasi-peak | Average |
| 0.15–0.5 | 66 to 56* | 56 to 46* |
| 0.5–5 | 56 | 46 |
| 5–30 | 60 | 50 |

*Decreases with the logarithm of the frequency.

Procedures:


1. All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR and Average detectors, are reported. All other emissions were relatively insignificant.
2. A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
3. Conducted Emissions Measurement Uncertainty
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 9kHz – 30MHz (Average & Quasi-peak) is ± 3.5 dB.
4. Environmental Conditions Temperature 23°C
 Relative Humidity 50%
 Atmospheric Pressure 1019mbar
5. Test date : November 02~ November 18, 2010
Tested By : Andy Hao

**SIEMIC, INC.**

Accessing global markets

Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 11 of 66
www.siemic.com.cn

Neutral --Operating mode: transmitting**Test Data**


| Frequency (MHz) | Quasi Peak (dBuV) | Limit (dBuV) | Margin (dB) | Average (dBuV) | Limit (dBuV) | Margin (dB) | Factors (dB) |
|-----------------|-------------------|--------------|-------------|----------------|--------------|-------------|--------------|
| 1.05 | 35.34 | 56.00 | -20.66 | 33.75 | 46.00 | -12.25 | 10.17 |
| 1.25 | 35.77 | 56.00 | -20.23 | 33.98 | 46.00 | -12.02 | 10.18 |
| 0.77 | 35.25 | 56.00 | -20.75 | 33.72 | 46.00 | -12.28 | 10.16 |
| 0.56 | 35.04 | 56.00 | -20.96 | 33.62 | 46.00 | -12.38 | 10.17 |
| 1.53 | 33.64 | 56.00 | -22.36 | 31.95 | 46.00 | -14.05 | 10.19 |
| 1.74 | 33.98 | 56.00 | -22.02 | 32.61 | 46.00 | -13.39 | 10.20 |

**SIEMIC, INC.**

Accessing global markets

Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 12 of 66
www.siemic.com.cn

Line --Operating mode: transmitting**Test Data**

| Frequency (MHz) | Quasi Peak (dBuV) | Limit (dBuV) | Margin (dB) | Average (dBuV) | Limit (dBuV) | Margin (dB) | Factors (dB) |
|-----------------|-------------------|--------------|-------------|----------------|--------------|-------------|--------------|
| 0.21 | 40.97 | 63.34 | -22.37 | 39.34 | 53.34 | -14.00 | 10.28 |
| 1.25 | 35.96 | 56.00 | -20.04 | 34.16 | 46.00 | -11.84 | 10.17 |
| 3.07 | 34.63 | 56.00 | -21.37 | 31.17 | 46.00 | -14.83 | 10.22 |
| 3.00 | 31.16 | 56.00 | -24.84 | 23.51 | 46.00 | -22.49 | 10.20 |
| 1.05 | 35.52 | 56.00 | -20.48 | 33.91 | 46.00 | -12.09 | 10.16 |
| 0.84 | 34.08 | 56.00 | -21.92 | 32.49 | 46.00 | -13.51 | 10.16 |

5.3 6dB Occupied Bandwidth

1. Conducted Measurement

EUT was set for low, mid, high channel with modulated mode and highest RF output power. The spectrum analyzer was connected to the antenna terminal.

| | | | |
|----|--------------------------|----------------------|----------|
| 2. | Environmental Conditions | Temperature | 23°C |
| | | Relative Humidity | 50% |
| | | Atmospheric Pressure | 1019mbar |

3. Conducted Emissions Measurement Uncertainty

All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 40GHz is $\pm 1.5\text{dB}$.

4. Test date : November 02~ November 18, 2010

Tested By : Andy Hao

Requirement(s): 47 CFR § 15.247(a)(1)

Procedures: The 6dB Bandwidths were measured conducted using a spectrum analyzer at low, mid, and hi channels. 6dB Bandwidth Limit: $>500\text{kHz}$.

| Protocol | Channel | Channel Frequency (MHz) | 6dB Occupied Bandwidth Limit (MHz) | 6dB Channel Bandwidth (MHz) |
|----------|---------|-------------------------|------------------------------------|-----------------------------|
| 802.11b | Low | 2412 | 0.5 | 11.00 |
| 802.11b | Mid | 2437 | 0.5 | 9.92 |
| 802.11b | High | 2462 | 0.5 | 10.25 |
| 802.11g | Low | 2412 | 0.5 | 16.67 |
| 802.11g | Mid | 2437 | 0.5 | 16.67 |
| 802.11g | High | 2462 | 0.5 | 16.58 |




SIEMIC, INC.

Accessing global markets


Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 14 of 66
www.siemic.com.cn

Refer to the attached plots.



6dB Bandwidth – Low Channel (802.11b)



6dB Bandwidth – Mid Channel (802.11b)




SIEMIC, INC.


Accessing global markets

Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 15 of 66
www.siemic.com.cn



6dB Bandwidth – High Channel (802.11b)



6dB Bandwidth – Low Channel (802.11g)




SIEMIC, INC.


Accessing global markets

Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 16 of 66
www.siemic.com.cn



6dB Bandwidth – Mid Channel (802.11g)



6dB Bandwidth – High Channel (802.11g)



5.4 Power Spectral Density

1. Conducted Measurement

EUT was set for low, mid, high channel with modulated mode and highest RF output power. The spectrum analyzer was connected to the antenna terminal.

2. Environmental Conditions

| | |
|----------------------|----------|
| Temperature | 23°C |
| Relative Humidity | 50% |
| Atmospheric Pressure | 1019mbar |

3. Conducted Emissions Measurement Uncertainty

All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 40GHz is ± 1.5 dB.

4. Test date : November 02~ November 18, 2010

Tested By : Andy Hao

Requirement(s): 47 CFR § 15.247(e)

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3KHz band during any time interval of continuous transmission.

Procedures: The power spectral density measurement was taken conducted using a spectrum analyzer.

RBW=3KHz, VBW>RBW, Sweep time to SPAN/RBW(s).

The result:

| Protocol | Channel | Channel Frequency (MHz) | Peak Spectral Density Limit (dBm/3KHz) | Peak Spectral Density (dBm/3KHz) |
|----------|---------|-------------------------|--|----------------------------------|
| 802.11b | Low | 2412 | 8 | -12.17 |
| 802.11b | Mid | 2437 | 8 | -11.00 |
| 802.11b | High | 2462 | 8 | -11.83 |
| 802.11g | Low | 2412 | 8 | -20.83 |
| 802.11g | Mid | 2437 | 8 | -19.50 |
| 802.11g | High | 2462 | 8 | -20.33 |




SIEMIC, INC.

Accessing global markets


Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 18 of 66
www.siemic.com.cn

Refer to the attached plots.



PSD - Low Channel (802.11b)



PSD - Mid Channel (802.11b)




SIEMIC, INC.


Accessing global markets

Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 19 of 66
www.siemic.com.cn



PSD - High Channel (802.11b)



PSD - Low Channel (802.11g)




SIEMIC, INC.


Accessing global markets

Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 20 of 66
www.siemic.com.cn



PSD - Mid Channel (802.11g)



PSD - High Channel (802.11g)



5.5 Peak Output Power

1. Conducted Measurement

EUT was set for low, mid, high channel with modulated mode and highest RF output power. The spectrum analyzer was connected to the antenna terminal.

2. Conducted Emissions Measurement Uncertainty

All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 40GHz is ± 1.5 dB.

| | | | |
|----|--------------------------|----------------------|----------|
| 3. | Environmental Conditions | Temperature | 23°C |
| | | Relative Humidity | 50% |
| | | Atmospheric Pressure | 1019mbar |

4. Test date : November 02~ November 18, 2010

Tested By : Andy Hao

Standard Requirement: 47 CFR § 15.247(b)

Procedures: The peak output power was measured conducted using a spectrum analyzer at low, mid, and hi channels. Peak detector was set to measure the power output. The power is converted from watt to dBm, therefore, 1 watt = 30 dBm.

Test Result:

| Protocol | Channel | Channel Frequency (MHz) | Peak Output Power Limit (dBm) | Measured Output Power (dBm) |
|----------|---------|-------------------------|-------------------------------|-----------------------------|
| 802.11b | Low | 2412 | 30 | 12.80 |
| 802.11b | Mid | 2437 | 30 | 12.10 |
| 802.11b | High | 2462 | 30 | 12.50 |
| 802.11g | Low | 2412 | 30 | 8.90 |
| 802.11g | Mid | 2437 | 30 | 9.90 |
| 802.11g | High | 2462 | 30 | 9.70 |




SIEMIC, INC.

Accessing global markets


Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 22 of 66
www.siemic.com.cn

Refer to the attached plots.



Output Power Low Channel (802.11b)



Output Power Mid Channel (802.11b)




SIEMIC, INC.


Accessing global markets

Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009


Serial#: 1003026
Issue Date: November 18, 2010
Page 23 of 66
www.siemic.com.cn




Output Power High Channel (802.11b)



Output Power Low Channel (802.11g)



Output Power Mid Channel (802.11g)



Output Power High Channel (802.11g)



SIEMIC, INC.

Accessing global markets

Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 25 of 66
www.siemic.com.cn

5.6 Antenna Port Emission

1. Conducted Measurement
EUT was set for low, mid, high channel with modulated mode and highest RF output power.
The spectrum analyzer was connected to the antenna terminal.
2. Conducted Emissions Measurement Uncertainty
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 40GHz is ± 1.5 dB.
3. Environmental Conditions Temperature 23°C
 Relative Humidity 50%
 Atmospheric Pressure 1019mbar
4. Test date : November 02~ November 18, 2010
Tested By : Andy Hao

Standard Requirement: Radiated emission limits: In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the modulation products of the spreading sequence, the information sequence and the carrier frequency shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

Procedures: The conducted spurious emissions were measured conducted using a spectrum analyzer at low, mid, and hi channels. The limit was determined by attenuating 20 dB of the RF peak power output.

Test Result: Pass




SIEMIC, INC.


Accessing global markets

Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 26 of 66
www.siemic.com.cn



Antenna Port Emission Low Channel (802.11b)



Antenna Port Emission Mid Channel (802.11b)




SIEMIC, INC.


Accessing global markets

Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009


Serial#: 1003026
Issue Date: November 18, 2010
Page 27 of 66
www.siemic.com.cn




Antenna Port Emission High Channel (802.11b)



Antenna Port Emission Low Channel (802.11g)



Antenna Port Emission Mid Channel (802.11g)



Antenna Port Emission High Channel (802.11g)



5.7 Radiated Spurious Emission < 1GHz

1. All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR detectors, are reported. All other emissions were relatively insignificant.
2. A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
3. Radiated Emissions Measurement Uncertainty
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 1GHz & 1GHz above (3m & 10m) is +/-6dB.
4.

| Environmental Conditions | Temperature | 23°C |
|--------------------------|----------------------|----------|
| | Relative Humidity | 50% |
| | Atmospheric Pressure | 1019mbar |
5. Test date : November 02~ November 18, 2010
Tested By : Andy Hao

Standard Requirement: The emissions from the Low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges.

Test Result: Pass




SIEMIC, INC.

Accessing global markets

Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 30 of 66
www.siemic.com.cn

Operating mode: transmitting (802.11b Low channel)




Test Data

| Frequency (MHz) | Quasi Peak (dBuV/m) | Azimuth | Polarity(H /V) | Height (cm) | Factors (dB) | Limit (dBuV/m) | Margin (dB) |
|-----------------|---------------------|---------|----------------|-------------|--------------|----------------|-------------|
| 914.55 | 42.81 | 50.00 | V | 100.00 | -18.74 | 46.00 | -3.19 |
| 865.15 | 42.70 | 42.00 | V | 106.00 | -19.79 | 46.00 | -3.30 |
| 939.24 | 40.43 | 42.00 | H | 152.00 | -18.53 | 46.00 | -5.57 |
| 469.67 | 40.09 | 266.00 | V | 100.00 | -27.85 | 46.00 | -5.91 |
| 815.68 | 40.60 | 89.00 | H | 196.00 | -21.10 | 46.00 | -5.40 |
| 519.09 | 38.17 | 266.00 | V | 102.00 | -26.89 | 46.00 | -7.83 |



Operating mode: transmitting (802.11b Middle channel)



Test Data


| Frequency (MHz) | Quasi Peak (dBuV/m) | Azimuth | Polarity(H /V) | Height (cm) | Factors (dB) | Limit (dBuV/m) | Margin (dB) |
|-----------------|---------------------|---------|----------------|-------------|--------------|----------------|-------------|
| 865.15 | 42.63 | 41.00 | V | 102.00 | -20.26 | 46.00 | -3.37 |
| 914.61 | 41.96 | 50.00 | V | 100.00 | -19.15 | 46.00 | -4.04 |
| 469.65 | 28.43 | 325.00 | H | 99.00 | -28.15 | 46.00 | -17.57 |
| 898.30 | 21.98 | 341.00 | V | 207.00 | -19.31 | 46.00 | -24.02 |
| 939.20 | 39.46 | 359.00 | V | 141.00 | -18.97 | 46.00 | -6.54 |
| 519.05 | 38.32 | 271.00 | V | 101.00 | -27.23 | 46.00 | -7.68 |

**SIEMIC, INC.**

Accessing global markets

Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 32 of 66
www.siemic.com.cn

Operating mode: transmitting (802.11b High channel)**Test Data**


| Frequency (MHz) | Quasi Peak (dBuV/m) | Azimuth | Polarity(H /V) | Height (cm) | Factors (dB) | Limit (dBuV/m) | Margin (dB) |
|-----------------|---------------------|---------|----------------|-------------|--------------|----------------|-------------|
| 914.58 | 42.53 | 49.00 | H | 100.00 | -19.15 | 46.00 | -3.47 |
| 865.14 | 30.97 | 39.00 | V | 99.00 | -20.26 | 46.00 | -15.03 |
| 469.61 | 39.77 | 272.00 | V | 101.00 | -28.15 | 46.00 | -6.23 |
| 815.68 | 40.28 | 91.00 | V | 186.00 | -21.67 | 46.00 | -5.72 |
| 939.25 | 39.68 | 48.00 | V | 152.00 | -18.97 | 46.00 | -6.32 |
| 815.65 | 40.26 | 92.00 | V | 189.00 | -21.67 | 46.00 | -5.74 |

**SIEMIC, INC.**

Accessing global markets

Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009


Serial#: 1003026
Issue Date: November 18, 2010
Page 33 of 66
www.siemic.com.cn

Operating mode: transmitting (802.11g Low channel)**Test Data**

| Frequency (MHz) | Quasi Peak (dBuV/m) | Azimuth | Polarity(H /V) | Height (cm) | Factors (dB) | Limit (dBuV/m) | Margin (dB) |
|-----------------|---------------------|---------|----------------|-------------|--------------|----------------|-------------|
| 667.38 | 43.15 | 0.00 | H | 179.00 | -22.37 | 46.00 | -2.85 |
| 716.84 | 41.96 | 1.00 | V | 179.00 | -20.95 | 46.00 | -4.04 |
| 865.13 | 41.09 | 268.00 | H | 101.00 | -19.78 | 46.00 | -4.91 |
| 815.67 | 41.08 | 337.00 | V | 100.00 | -21.10 | 46.00 | -4.92 |
| 617.99 | 39.68 | 359.00 | V | 100.00 | -24.68 | 46.00 | -6.32 |
| 914.60 | 39.35 | 314.00 | H | 140.00 | -18.74 | 46.00 | -6.65 |



Operating mode: transmitting (802.11g Middle channel)



Test Data


| Frequency (MHz) | Quasi Peak (dBuV/m) | Azimuth | Polarity(H /V) | Height (cm) | Factors (dB) | Limit (dBuV/m) | Margin (dB) |
|-----------------|---------------------|---------|----------------|-------------|--------------|----------------|-------------|
| 667.37 | 42.32 | 5.00 | V | 173.00 | -22.80 | 46.00 | -3.68 |
| 716.81 | 34.88 | 16.00 | V | 99.00 | -21.39 | 46.00 | -11.12 |
| 864.99 | 40.92 | 260.00 | V | 100.00 | -20.26 | 46.00 | -5.08 |
| 815.65 | 39.81 | 342.00 | V | 153.00 | -21.67 | 46.00 | -6.19 |
| 815.60 | 39.59 | 340.00 | H | 150.00 | -21.67 | 46.00 | -6.41 |
| 914.45 | 40.08 | 318.00 | H | 146.00 | -19.15 | 46.00 | -5.92 |



Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 35 of 66
www.siemic.com.cn

Operating mode: transmitting (802.11g High channel)



Test Data

| Frequency (MHz) | Quasi Peak (dBuV/m) | Azimuth | Polarity(H /V) | Height (cm) | Factors (dB) | Limit (dBuV/m) | Margin (dB) |
|-----------------|---------------------|---------|----------------|-------------|--------------|----------------|-------------|
| 667.34 | 42.07 | 14.00 | V | 177.00 | -22.80 | 46.00 | -3.93 |
| 865.00 | 40.50 | 264.00 | V | 100.00 | -20.26 | 46.00 | -5.50 |
| 716.75 | 41.41 | 6.00 | V | 172.00 | -21.39 | 46.00 | -4.59 |
| 815.65 | 40.31 | 340.00 | V | 100.00 | -21.67 | 46.00 | -5.69 |
| 617.89 | 40.86 | 359.00 | H | 116.00 | -25.17 | 46.00 | -5.14 |
| 914.52 | 40.29 | 319.00 | V | 153.00 | -19.15 | 46.00 | -5.71 |



5.8 Radiated Spurious Emissions > 1GHz & Band Edge

1. All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR detectors, are reported. All other emissions were relatively insignificant.

2. A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.

3. Radiated Emissions Measurement Uncertainty
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 1GHz & 1GHz above (3m & 10m) is +/-6dB.

4. Environmental Conditions Temperature 23°C
 Relative Humidity 50%
 Atmospheric Pressure 1019mbar

5. Test date : November 02~ November 18, 2010
Tested By : Andy Hao

Standard Requirement: The emissions from the Low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges.

Test Result:

**SIEMIC, INC.**

Accessing global markets

Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 37 of 66
www.siemic.com.cn

Mode: 802.11b**@ 2412MHz @ 3 Meter**

| Frequency | Direction | Height | Polar | Cable loss | Amplifier | Corrected Reading | 15.247/15.209 | 15.247/15.209 | |
|-----------|-----------|--------|-------|------------|-----------|-------------------|----------------|---------------|----------|
| GHz | Degree | Meter | H / V | (dB) | (dB) | (dBuV/m) | Limit (dBuV/m) | Margin | Comments |
| 4.824 | 109.00 | 1.37 | v | 5.15 | 55.00 | 60.61 | 74.00 | -13.39 | Peak |
| 4.824 | 112.00 | 1.10 | h | 5.15 | 55.00 | 55.61 | 74.00 | -18.39 | Peak |
| 4.824 | 123.00 | 1.20 | v | 5.15 | 55.00 | 51.13 | 54.00 | -2.87 | Ave |
| 4.824 | 118.00 | 1.30 | h | 5.15 | 55.00 | 44.54 | 54.00 | -9.46 | Ave |

Emission was scanned up to 25GHz.

@ 2437MHz @ 3Meter

| Frequency | Direction | Height | Polar | Cable loss | Amplifier | Corrected Reading | 15.247/15.209 | 15.247/15.209 | |
|-----------|-----------|--------|-------|------------|-----------|-------------------|----------------|---------------|----------|
| GHz | Degree | Meter | H / V | (dB) | (dB) | (dBuV/m) | Limit (dBuV/m) | Margin | Comments |
| 4.874 | 81.00 | 1.10 | v | 5.16 | 55.00 | 43.77 | 74.00 | -30.23 | Peak |
| 4.874 | 75.00 | 1.00 | h | 5.16 | 55.00 | 46.82 | 74.00 | -27.18 | Peak |
| 4.874 | 71.00 | 1.10 | v | 5.16 | 55.00 | 35.89 | 54.00 | -18.11 | Ave |
| 4.874 | 86.00 | 1.30 | h | 5.16 | 55.00 | 37.78 | 54.00 | -16.22 | Ave |

Emission was scanned up to 25GHz.

@ 2462MHz @ 3Meter

| Frequency | Direction | Height | Polar | Cable loss | Amplifier | Corrected Reading | 15.247/15.209 | 15.247/15.209 | |
|-----------|-----------|--------|-------|------------|-----------|-------------------|----------------|---------------|----------|
| GHz | Degree | Meter | H / V | (dB) | (dB) | (dBuV/m) | Limit (dBuV/m) | Margin | Comments |
| 4.924 | 114.00 | 1.10 | v | 5.17 | 55.00 | 58.63 | 74.00 | -15.37 | Peak |
| 4.924 | 117.00 | 1.20 | h | 5.17 | 55.00 | 48.63 | 74.00 | -25.37 | Peak |
| 4.924 | 113.00 | 1.50 | v | 5.17 | 55.00 | 47.77 | 54.00 | -6.23 | Ave |
| 4.924 | 93.00 | 1.30 | h | 5.17 | 55.00 | 41.54 | 54.00 | -12.46 | Ave |

Emission was scanned up to 25GHz.

Mode: 802.11g**@ 2412MHz @ 3 Meter**

| Frequency | Direction | Height | Polar | Cable loss | Amplifier | Corrected Reading | 15.247/15.209 | 15.247/15.209 | |
|-----------|-----------|--------|-------|------------|-----------|-------------------|----------------|---------------|----------|
| GHz | Degree | Meter | H / V | (dB) | (dB) | (dBuV/m) | Limit (dBuV/m) | Margin | Comments |
| 4.824 | 115.00 | 1.37 | v | 5.15 | 55.00 | 54.77 | 74.00 | -16.23 | Peak |
| 4.824 | 125.00 | 1.40 | h | 5.15 | 55.00 | 51.22 | 74.00 | -22.78 | Peak |
| 4.824 | 123.00 | 1.10 | v | 5.15 | 55.00 | 36.78 | 54.00 | -17.22 | Ave |
| 4.824 | 95.00 | 1.20 | h | 5.15 | 55.00 | 37.12 | 54.00 | -16.88 | Ave |

Emission was scanned up to 25GHz.

**SIEMIC, INC.**

Accessing global markets

Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 38 of 66
www.siemic.com.cn

@ 2437MHz @ 3Meter

| Frequency | Direction | Height | Polar | Cable loss | Amplifier | Corrected Reading | 15.247/15.209 | 15.247/15.209 | |
|-----------|-----------|--------|-------|------------|-----------|-------------------|----------------|---------------|----------|
| GHz | Degree | Meter | H / V | (dB) | (dB) | (dBuV/m) | Limit (dBuV/m) | Margin | Comments |
| 4.874 | 111.00 | 1.10 | v | 5.16 | 55.00 | 48.33 | 74.00 | -25.67 | Peak |
| 4.874 | 134.00 | 1.00 | h | 5.16 | 55.00 | 43.45 | 74.00 | -30.55 | Peak |
| 4.874 | 129.00 | 1.10 | v | 5.16 | 55.00 | 39.55 | 54.00 | -14.45 | Ave |
| 4.874 | 128.00 | 1.30 | h | 5.16 | 55.00 | 39.12 | 54.00 | -14.88 | Ave |

Emission was scanned up to 25GHz.

@ 2462MHz @ 3Meter

| Frequency | Direction | Height | Polar | Cable loss | Amplifier | Corrected Reading | 15.247/15.209 | 15.247/15.209 | |
|-----------|-----------|--------|-------|------------|-----------|-------------------|----------------|---------------|----------|
| GHz | Degree | Meter | H / V | (dB) | (dB) | (dBuV/m) | Limit (dBuV/m) | Margin | Comments |
| 4.924 | 112.00 | 1.10 | v | 5.17 | 55.00 | 59.12 | 74.00 | -14.88 | Peak |
| 4.924 | 124.00 | 1.00 | h | 5.17 | 55.00 | 45.22 | 74.00 | -28.78 | Peak |
| 4.924 | 137.00 | 1.10 | v | 5.17 | 55.00 | 51.11 | 54.00 | -2.89 | Ave |
| 4.924 | 124.00 | 1.30 | h | 5.17 | 55.00 | 39.87 | 54.00 | -14.13 | Ave |

Emission was scanned up to 25GHz.

Band Edge

| Channel | Polarity | Detector | Frequency | Result | Limit | Margin |
|-------------|----------|----------|-----------|--------|-------|--------|
| Low Channel | V | Peak | 2400 | 36.56 | 74 | -37.44 |
| Low Channel | H | Peak | 2400 | 42.12 | 74 | -31.88 |
| Low Channel | V | Avg | 2400 | 24.12 | 54 | -29.88 |
| Low Channel | H | Avg | 2400 | 24.71 | 54 | -29.29 |

| Channel | Polarity | Detector | Frequency | Result | Limit | Margin |
|--------------|----------|----------|-----------|--------|-------|--------|
| High Channel | V | Peak | 2483.5 | 41.23 | 74 | -32.77 |
| High Channel | H | Peak | 2483.5 | 45.67 | 74 | -28.33 |
| High Channel | V | Avg | 2483.5 | 27.15 | 54 | -26.85 |
| High Channel | H | Avg | 2483.5 | 31.3 | 54 | -22.7 |



Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 39 of 66
www.siemic.com.cn

Annex A. TEST INSTRUMENT & METHOD

Annex A.i. TEST INSTRUMENTATION & GENERAL PROCEDURES

| Instrument | Manufacturer | Model | CAL Due Date |
|---------------------------------|-----------------|----------------------------|--------------|
| Spectrum Analyzer | HP | 8564 E | 2011.04.26 |
| EMI Receiver | Rohde & Schwarz | ESPI 3 | 2011.02.19 |
| Antenna (30MHz~2GHz) | Sunol Sciences | JB1 | 2011.02.19 |
| Horn Antenna (1-18GHz) | A-INFOMW | JXTXLB-10180 | 2011.02.19 |
| Horn Antenna (1-18GHz) | N/A | N/A | 2011.10.04 |
| Pre-Amplifier(0.01 ~ 1.3GHz) | HP | 8447F | 2011.04.24 |
| Pre-Amplifier(0.1 ~ 18GHz) | MITEQ | AMF-7D-00101800-30- 10P | 2011.03.05 |
| Horn Antenna (18~40GHz) | Com Power | AH-840 | 2011.05.21 |
| Microwave Pre-Amp (18~40GHz) | Com Power | PA-840 | 2011.05.21 |



Annex A.ii. CONDUCTED EMISSIONS TEST DESCRIPTION

Test Set-up

1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table, as shown in Annex B.
2. The power supply for the EUT was fed through a $50\Omega/50\mu\text{H}$ EUT LISN, connected to filtered mains.
3. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss coaxial cable.
4. All other supporting equipments were powered separately from another main supply.

Test Method

1. The EUT was switched on and allowed to warm up to its normal operating condition.
2. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver.
3. High peaks, relative to the limit line, were then selected.
4. The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 KHz. For FCC tests, only Quasi-peak measurements were made; while for CISPR/EN tests, both Quasi-peak and Average measurements were made.
5. Steps 2 to 4 were then repeated for the LIVE line (for AC mains) or DC line (for DC power).

Sample Calculation Example

At 20 MHz

limit = $250 \mu\text{V} = 47.96 \text{ dB}\mu\text{V}$

Transducer factor of LISN, pulse limiter & cable loss at 20 MHz = 11.20 dB

Q-P reading obtained directly from EMI Receiver = $40.00 \text{ dB}\mu\text{V}$
(Calibrated for system losses)

Therefore, Q-P margin = $47.96 - 40.00 = 7.96$

i.e. **7.96 dB below limit**



Annex A. iii RADIATED EMISSIONS TEST DESCRIPTION


EUT Characterisation

EUT characterisation, over the frequency range from 30MHz to 10th Harmonic, was done in order to minimise radiated emissions testing time while still maintaining high confidence in the test results.

The EUT was placed in the chamber, at a height of about 0.8m on a turntable. Its radiated emissions frequency profile was observed, using a spectrum analyzer /receiver with the appropriate broadband antenna placed 3m away from the EUT. Radiated emissions from the EUT were maximised by rotating the turntable manually, changing the antenna polarisation and manipulating the EUT cables while observing the frequency profile on the spectrum analyzer / receiver. Frequency points at which maximum emissions occurred, clock frequencies and operating frequencies were then noted for the formal radiated emissions test at the Open Area Test Site (OATS).

Test Set-up

1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m X 1.0m X 0.8m high, non-metallic table.
2. The filtered power supply for the EUT and supporting equipment were tapped from the appropriate power sockets located on the turntable.
3. The relevant broadband antenna was set at the required test distance away from the EUT and supporting equipment boundary.





Test Method

The following procedure was performed to determine the maximum emission axis of EUT:

1. With the receiving antenna is H polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
2. With the receiving antenna is V polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
3. Compare the results derived from above two steps. So, the axis of maximum emission from EUT was determined and the configuration was used to perform the final measurement.

Final Radiated Emission Measurement

1. Setup the configuration according to figure 1. Turn on EUT and make sure that it is in normal function.
2. For emission frequencies measured below 1 GHz, a pre-scan is performed in a shielded chamber to determine the accurate frequencies of higher emissions will be checked on a open test site. As the same purpose, for emission frequencies measured above 1 GHz, a pre-scan also be performed with a 1 meter measuring distance before final test.
3. For emission frequencies measured below and above 1 GHz, set the spectrum analyzer on a 100 kHz and 1 MHz resolution bandwidth respectively for each frequency measured in step 2.
4. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0° to 360° with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading.
5. Repeat step 4 until all frequencies need to be measured were complete.
6. Repeat step 5 with search antenna in vertical polarized orientations.

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

| Frequency Band (MHz) | Function | Resolution bandwidth | Video Bandwidth |
|----------------------|----------|----------------------|-----------------|
| 30 to 1000 | Peak | 100 kHz | 100 kHz |
| Above 1000 | Peak | 1 MHz | 1 MHz |
| | Average | 1 MHz | 10 Hz |

Sample Calculation Example

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. For the limit is employed average value, therefore the peak value can be transferred to average value by subtracting the duty factor. The basic equation with a sample calculation is as follows:

$$\text{Peak} = \text{Reading} + \text{Corrected Factor}$$

where

$$\text{Corr. Factor} = \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain (if any)}$$

And the average value is

$$\text{Average} = \text{Peak Value} + \text{Duty Factor or}$$

$$\text{Set RBW} = 1\text{MHz}, \text{VBW} = 10\text{Hz}.$$

Note :

If the measured frequencies are fall in the restricted frequency band, the limit employed must be quasi peak value when frequencies are below or equal to 1 GHz. And the measuring instrument is set to quasi peak detector function.



Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 43 of 66
www.siemic.com.cn

Annex B. EUT AND TEST SETUP PHOTOGRAPHS

Please see attachment



Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 44 of 66
www.siemic.com.cn

Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

EUT TEST CONDITIONS

Annex C. i. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

| Equipment Description (Including Brand Name) | Model & Serial Number | Cable Description (List Length, Type & Purpose) |
|---|-----------------------|--|
| Adapter | W&T-AD18W084200&N/A | Cable 1.5m |

Block Configuration Diagram for Radiated Emission




SIEMIC, INC.

Accessing global markets

Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 45 of 66
www.siemic.com.cn






SIEMIC, INC.

Accessing global markets

Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 46 of 66
www.siemic.com.cn

Block Configuration Diagram for Conducted Emission





Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 47 of 66
www.siemic.com.cn

Annex C.ii. EUT OPERATING CONDITIONS

The following is the description of how the EUT is exercised during testing.

| Test | Description Of Operation |
|-----------|--------------------------|
| Emissions | EUT is working normally. |



Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 48 of 66
www.siemic.com.cn

Annex D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PART LIST

Please see attachment



SIEMIC, INC.

Accessing global markets

Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 49 of 66
www.siemic.com.cn

Annex E. SIEMIC ACCREDITATION CERTIFICATES



THE AMERICAN ASSOCIATION FOR
LABORATORY ACCREDITATION

ACCREDITED LABORATORY

A2LA has accredited

SIEMIC LABORATORIES

San Jose, CA

for technical competence in the field of

Electrical Testing

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 *General Requirements for the Competence of Testing and Calibration Laboratories*. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated 18 June 2005).

Presented this 11th day of July 2008.



President
For the Accreditation Council
Certificate Number 2742.01
Valid to September 30, 2010



For the tests or types of tests to which this accreditation applies,
please refer to the laboratory's Electrical Scope of Accreditation.



THE AMERICAN ASSOCIATION FOR
LABORATORY ACCREDITATION

ACCREDITED PRODUCT CERTIFICATION BODY

A2LA has accredited


SIEMIC INC.

San Jose, CA

for technical competence as a
Product Certification Body

This product certification body is accredited in accordance with the recognized International Standard ISO/IEC Guide 65:1996 *General requirements for bodies operating product certification systems*. This accreditation demonstrates technical competence for a defined scope and the operation of a quality management system for a Telecommunications Certification Body (TCB) meeting FCC (U.S.), IDA (Singapore) and IC (Canada) requirements.

Presented this 9th day of January 2009.



President
For the Accreditation Council
Certificate Number: 2742.02
Valid to: September 30, 2010



For the product certification schemes to which this accreditation applies,
please refer to the certification body's Scope of Accreditation.



Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 50 of 66
www.siemic.com.cn

SCOPE OF ACCREDITATION TO ISO/IEC GUIDE 65:1996

SIEMIC INC.
2206 Ringwood Ave.
San Jose, CA 95131
Mr. Snell Leong (Authorized Representative) Phone: 408 526 1188
www.siemic.com

PRODUCT CERTIFICATION CONFORMITY ASSESSMENT BODY (CAB)

Valid to: September 30, 2010

Certificate Number: 2742.02

In recognition of the successful completion of the A2LA Certification Body Accreditation Program evaluation, including the US Federal Communications Commission (FCC), Industry Canada (IC) and Singapore (IDA) requirements for the indicated types of product certifications, accreditation is granted to this organization to perform the following product certification schemes:

Economy Scope

Federal Communication Commission - (FCC)

| | |
|------------------------------------|----------------|
| Unlicensed Radio Frequency Devices | A1, A2, A3, A4 |
| Licensed Radio Frequency Devices | B1, B2, B3, B4 |
| Telephone Terminal Equipment | C |

**Please refer to FCC TCB Program Roles and Responsibilities, v04, released February 14, 2008 detailing scopes, roles and responsibilities. <http://www.fcc.gov/oet/ea/FCC-Overview-TCB-Program.pdf>*

Industry Canada - (IC)

| | |
|-------|---|
| Radio | All Radio Standards Specifications (RSS) in Category I Equipment Standards List Radio |
|-------|---|

**Please refer to Industry Canada (IC) website at: http://www.ic.gc.ca/epic/site/smt-gst.nsf/en/h_sf01342e.html*

IDA – Singapore

| | |
|-------------------------------|---|
| Line Terminal Equipment | All Technical Specifications for Line Terminal Equipment – Table 1 of IDA MRA Recognition Scheme: 2008, Annex 2 |
| Radio-Communication Equipment | All Technical Specifications for Radio-Communication Equipment – Table 2 of IDA MRA Recognition Scheme: 2008, Annex 2 |

**Please refer to Info-Communication Development Authority (IDA) Singapore website at: http://www.ida.gov.sg/doc/Policies%20and%20Regulation/Policies_and_Regulation_Level2/20060609145118/MRA_RecScheme.pdf*



Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 51 of 66
www.siemic.com.cn

SIEMIC ACREDITATION DETAILS: FCC Test Site Registration No. 783147

FEDERAL COMMUNICATIONS COMMISSION
Laboratory Division
7435 Oakland Mills Road
Columbia, MD 21046

December 20, 2007

Registration Number: 783147

SIEMIC Laboratories
2206 Ringwood Avenue,
San Jose, CA 95131

Attention: Leslie Bai

Re: Measurement facility located at San Jose
3 & 10 meter site
Date of Renewal: December 20, 2007

Dear Sir or Madam:

Your request for renewal of the registration of the subject measurement facility has been received. The information submitted has been placed in your file and the registration has been renewed. The name of your organization will remain on the list of facilities whose measurement data will be accepted in conjunction with applications for Certification under Parts 15 or 18 of the Commission's Rules. Please note that the file must be updated for any changes made to the facility and the registration must be renewed at least every three years.

Measurement facilities that have indicated that they are available to the public to perform measurement services on a fee basis may be found on the FCC website www.fcc.gov under E-Filing, OET Equipment Authorization Electronic Filing, Test Firms.

Sincerely,

Phyllis Parrish
Industry Analyst



SIEMIC, INC.

Accessing global markets

Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 52 of 66
www.siemic.com.cn

SIEMIC ACREDITATION DETAILS: Industry of Canada CAB ID : US0160



UNITED STATES DEPARTMENT OF COMMERCE
National Institute of Standards and Technology
Gaithersburg, Maryland 20899

March 4, 2009

Mr. Leslie Bai
SIEMIC, Inc.
2206 Ringwood Avenue
San Jose, CA 95131

Dear Mr. Bai:

NIST is pleased to inform you that your laboratory has been recognized by Industry Canada (IC), under the Asia Pacific Economic Cooperation for Telecommunications Equipment Mutual Recognition Arrangement (APEC Tel MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA. The pertinent information about your laboratory's designation is as follows:

CAB Name: SIEMIC, Inc.
Physical Location: 2206 Ringwood Avenue, San Jose, CA 95131 USA
Identification No.: US0160
Recognized Scope: CS-03 Part I, II, V, VI, VII and VIII

You may submit test data to IC to verify that the equipment to be imported into Canada satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements.

Recognized CABs are listed on the NIST website at <http://ts.nist.gov/mra>. Please contact Ms. Ramona Saar at (301) 975-5521 or ramona.saar@nist.gov if you have any questions.

Sincerely,

David F. Alderman
Group Leader, Standards Coordination and Conformity Group
Standards Services Division

Enclosure

cc: CAB Program Manager



Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 53 of 66
www.siemic.com.cn

SIEMIC ACREDITATION DETAILS: Industry of Canada Test Site Registration No. 4842-1



May 23rd, 2008

OUR FILE: 46405-4842
Submission No: 126429

Siemic Inc.
2206 Ringwood Ave.
San Jose CA 95131
USA

Attention: Leslie Bai

Dear Sir/Madame:

The Bureau has received your application for the registration / renewal of a 3/10m OATS. Be advised that the information received was satisfactory to Industry Canada. The following number(s) is now associated to the site(s) for which registration / renewal was sought (**4842A-1**). Please reference the appropriate site number in the body of test reports containing measurements performed on the site. In addition, please be informed that the Bureau is now utilizing a **new site numbering scheme** in order to simplify the electronic filing process. Our goal is to reduce the number of secondary codes associated to one particular company. The following changes have been made to your record.

- Your primary code is: **4842**
- The company number associated to the site(s) located at the above address is: **4842A**
- The table below is a summary of the changes made to the unique site registration number(s):

| New Site Number | Obsolete Site Number | Description of Site | Expiry Date (YYYY-MM-DD) |
|-----------------|----------------------|---------------------|--------------------------|
| 4842A-1 | 4842-1 | 3m Chamber | 2010-05-23 |

Furthermore, to obtain or renew a unique site number, the applicant shall demonstrate that the site has been accredited to ANSI C63.4-2003 or later. A scope of accreditation indicating the accreditation by a recognized accreditation body to ANSI C63.4-2003 shall be accepted. Please indicate in a letter the previous assigned site number if applicable and the type of site (example: 3 meter OATS or 3 meter chamber). If the test facility is not accredited to ANSI C63.4-2003 or later, the test facility shall submit test data demonstrating full compliance with the ANSI standard. The Bureau will evaluate the filing to determine if recognition shall be granted.

The frequency for re-validation of the test site and the information that is required to be filed or retained by the testing party shall comply with the requirements established by the accrediting organization. However, in all cases, test site re-validation shall occur on an interval not to exceed two years. There is no fee or form associated with an OATS filing. OATS submissions are encouraged to be submitted electronically to the Bureau using the following URL;
http://strategis.ic.gc.ca/epic/internet/inceb-bhst.nsf/en/h_tt00052e.html.

If you have any questions, you may contact the Bureau by e-mail at certification.bureau@ic.gc.ca. Please reference our file and submission number above for all correspondence.

Yours sincerely,

S. Proulx
Test & Measurement Specialist
Certification and Engineering Bureau
3701 Carling Ave., Building 94
Ottawa, Ontario K2H 8S2



Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 54 of 66
www.siemic.com.cn

SIEMIC ACREDITATION DETAILS: FCC DOC CAB Recognition : US1109

FEDERAL COMMUNICATIONS COMMISSION

Laboratory Division
7435 Oakland Mills Road
Columbia, MD 21046

August 28, 2008

Siemic Laboratories
2206 Ringwood Ave.,
San Jose, CA 95131

Attention: Leslie Bai

Re: Accreditation of Siemic Laboratories
Designation Number: US1109
Test Firm Registration #: 540430

Dear Sir or Madam:

We have been notified by American Association for Laboratory Accreditation that Siemic Laboratories has been accredited as a Conformity Assessment Body (CAB).

At this time Siemic Laboratories is hereby designated to perform compliance testing on equipment subject to Declaration Of Conformity (DOC) and Certification under Parts 15 and 18 of the Commission's Rules.

This designation will expire upon expiration of the accreditation or notification of withdrawal of designation.

Sincerely,


George Tannahill
Electronics Engineer



Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 55 of 66
www.siemic.com.cn

SIEMIC ACREDITATION DETAILS: Australia CAB ID : US0160



UNITED STATES DEPARTMENT OF COMMERCE
National Institute of Standards and Technology
Gaithersburg, Maryland 20899

November 20, 2008

Mr. Leslie Bai
SIEMIC, Inc.
2206 Ringwood Avenue
San Jose, CA 95131

Dear Mr. Bai:

NIST is pleased to inform you that your laboratory has been recognized by the Australian Communications and Media Authority (ACMA) under the Asia Pacific Economic Cooperation for Telecommunications Equipment Mutual Recognition Arrangement (APEC Tel MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA. The pertinent information about your laboratory's designation is as follows:

CAB Name: Siemic, Inc.
Physical Location: 2206 Ringwood Avenue, San Jose, CA 95131
Identification No.: US0160
Recognized Scope: EMC: AS/NZS 4251.1 (until 5/31/2009), AS/NZS 4251.2 (until 5/31/2009), AS/NZS CISPR 11, AS/NZS CISPR 14.1, AS/NZS CISPR 22, AS/NZS 61000.6.3, AS/NZS 61000.6.4
Radiocommunications: AS/NZS 4281, AS/NZS 4268, AS/NZS 4280.1, AS/NZS 4280.2, AS/NZS 4295, AS/NZS 4582, AS/NZS 4583, AS/NZS 4769.1, AS/NZS 4769.2, AS/NZS 4770, AS/NZS 4771
Telecommunications: AS/ACIF S002:05, AS/ACIF S003:06, AS/ACIF S004:06, AS/ACIF S006:01, AS/ACIF S016:01, AS/ACIF S031:01, AS/ACIF S038:01, AS/ACIF S040:01, AS/ACIF S041:05, AS/ACIF S043.2:06, AS/NZS 60950.1

You may submit test data to ACMA to verify that the equipment to be imported into Australia satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements. Recognized CABs are listed on the NIST website at <http://ts.nist.gov/mra>. Please contact Ms. Ramona Saar, at (301) 975-5521 or ramona.saar@nist.gov if you have questions.

Sincerely,

David F. Alderman
Group Leader, Standards Coordination and Conformity Group
Standards Services Division

Enclosure

cc: Snell Leong, Siemic, Inc.; Ramona Saar, NIST

SIEMIC ACREDITATION DETAILS: Korea CAB ID: US0160



UNITED STATES DEPARTMENT OF COMMERCE
National Institute of Standards and Technology
 Gaithersburg, Maryland 20899

October 1, 2008

Mr. Leslie Bai
 SIEMIC, Inc.
 2206 Ringwood Avenue
 San Jose, CA 95131

Dear Mr. Bai:

NIST is pleased to inform you that your laboratory has been recognized by the Radio Research Agency (RRA) Korea Communications Commission (KCC) under the Asia Pacific Economic Cooperation for Telecommunications Equipment Mutual Recognition Arrangement (APEC Tel MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA. The pertinent information about your laboratory's designation is as follows:

CAB Name: SIEMIC, Inc.
 Physical Location: 2206 Ringwood Avenue, San Jose, CA 95131
 Identification No.: US0160
 Recognized Scope: **EMI:** KCC Notice 2008-39, RRL Notice 2008-3: CA Procedures for EMI
 KN22: Test Method for EMI
EMS: KCC Notice 2008-38, RRL Notice 2008-4: CA Procedures for EMS
 KN24, KN-61000-4-2, -4-3, -4-4, -4-5, -4-6, -4-8, -4-11: Test Method for EMS
Wireless: RRL Notice 2008-26, RRL Notice 2008-2, RRL Notice 2008-10,
 RRL Notice 2007-49, RRL Notice 2007-20, RRL Notice 2007-21,
 RRL Notice 2007-80, RRL Notice 2004-68
Wired: President Notice 20664, RRL Notice 2007-30,
 RRL Notice 2008-7 with attachments 1, 3, 5, 6
 President Notice 20664, RRL Notice 2008-7 with attachment 4

You may submit test data to RRA/KCC to verify that the equipment to be imported into Korea satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements.

Recognized CABs are listed on the NIST website at <http://ts.nist.gov/mra>. If you have any questions please contact Ramona Saar at (301) 975-5521 or ramona.saar@nist.gov.

Sincerely,

David F. Alderman
 Group Leader, Standards Coordination and Conformity Group
 Standards Services Division

Enclosure

cc: Ramona Saar



Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 57 of 66
www.siemic.com.cn

SIEMIC ACREDITATION DETAILS: Taiwan BSMI Accreditation No. SL2-IN-E-1130R



UNITED STATES DEPARTMENT OF COMMERCE
National Institute of Standards and Technology
Gaithersburg, Maryland 20889

May 3, 2006

Mr. Leslie Bai
SIEMIC Laboratories
2206 Ringwood Avenue
San Jose, CA 95131

Dear Mr. Bai:

I am pleased to inform you that your laboratory has been recognized by the Chinese Taipei's Bureau of Standards, Metrology, and Inspection (BSMI) under the Asia Pacific Economic Cooperation (APEC) Mutual Recognition Arrangement (MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA. You may submit test data to BSMI to verify that the equipment to be imported into Chinese Taipei satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements. The pertinent designation information is as follows:

- BSMI number: **SL2-IN-E-1130R** (Must be applied to the test reports)
- U.S. Identification No: **US0160**
- Scope of Designation: **CNS 13438**
- Authorized signatory: **Mr. Leslie Bai**

The names of all recognized CABs will be posted on the NIST website at <http://ts.nist.gov/mra>. If you have any questions, please contact Mr. Dhillon at 301-975-5521. We appreciate your continued interest in our international conformity assessment activities.

Sincerely,

David F. Alderman
Group Leader, Standards Coordination and Conformity Group

cc: Joginder Dhillon

NIST

SIEMIC ACREDITATION DETAILS: Taiwan NCC CAB ID: US0160



**UNITED STATES DEPARTMENT OF COMMERCE
National Institute of Standards and Technology
Gaithersburg, Maryland 20899**

November 25, 2008

Mr. Leslie Bai
SIEMIC, Inc.
2206 Ringwood Avenue
San Jose, CA 95131

Dear Mr. Bai:

NIST is pleased to inform you that your laboratory has been recognized by the National Communications Commission (NCC) for the requested scope expansion under the Asia Pacific Economic Cooperation for Telecommunications Equipment Mutual Recognition Arrangement (APEC Tel MRA). Your laboratory is designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I Procedures**, of the APEC Tel MRA. The pertinent information about your laboratory's designation is as follows:

CAB Name: SIEMIC, Inc.
Physical Location: 2206 Ringwood Avenue, San Jose, CA 95131
Identification No.: US0160
Current Scope: LP0002
Additional Scope: PSTN01, ADSL01, ID0002, IS6100 and CNS 14336

You may submit test data to NCC to verify that the equipment to be imported into China satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements.

Recognized CABs are listed on the NIST website at <http://ts.nist.gov/mra>. If you have any questions please contact Ramona Saar at (301) 975-5521 or ramona.saar@nist.gov.

Sincerely,

David F. Alderman
Group Leader, Standards Coordination and Conformity Group
Standards Services Division

Enclosure

cc: Ramona Saar

SIEMIC ACREDITATION DETAILS: Mexico NOM Recognition



CAMARA NACIONAL
DE LA INDUSTRIA
ELECTRONICA, DE
TELECOMUNICACIONES
E INFORMATICA

Laboratorio Valentín V. Rivero

México D.F. a 16 de octubre de 2006.

LESLIE BAI
DIRECTOR OF CERTIFICATION
SIEMIC LABORATORIES, INC.
ACCEESSING GLOBAL MARKETS
P R E S E N T E

En contestación a su escrito de fecha 5 de septiembre del año en curso, le comento que estamos muy interesados en su intención de firmar un Acuerdo de Reconocimiento Mutuo, para lo cual adjunto a este escrito encontrara el Acuerdo en idioma inglés y español preferido de los cuales le pido sea revisado y en su caso corregido, para que si esta de acuerdo poder firmarlo para mandarlo con las autoridades Mexicanas para su visto bueno y así poder ejercer dicho acuerdo.

Aprovecho este escrito para mencionarle que nuestro intermediano gestor será la empresa Isotel de México, S. A. de C. V., empresa que ha colaborado durante mucho tiempo con nosotros en lo relacionado a la evaluación de la conformidad y que cuenta con amplia experiencia en la gestoría de la certificación de cumplimiento con Normas Oficiales Mexicanas de producto en México.

Me despido de usted enviándole un cordial saludo y esperando sus comentarios al Acuerdo que nos ocupa.

Atentamente:

Ing. Faustino Sánchez González
Gerente Técnico del Laboratorio de
CANIETI



Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 60 of 66
www.siemic.com.cn

SIEMIC ACREDITATION DETAILS: Hong Kong OFTA CAB ID : US0160



UNITED STATES DEPARTMENT OF COMMERCE
National Institute of Standards and Technology
Gaithersburg, Maryland 20899

December 8, 2008

Mr. Leslie Bai
SIEMIC, Inc.
2206 Ringwood Avenue
San Jose, CA 95131

Dear Mr. Bai:

NIST is pleased to inform you that your laboratory has been recognized by the Office of the Telecommunications Authority (OFTA) under the Asia Pacific Economic Cooperation for Telecommunications Equipment Mutual Recognition Arrangement (APEC Tel MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I Procedures**, of the APEC Tel MRA. The pertinent information about your laboratory's designation is as follows:

CAB Name: SIEMIC, Inc.
Physical Location: 2206 Ringwood Avenue, San Jose, California 95131 USA
Identification No.: US0160
Recognized Scope: **Radio:** HKTA 1002, 1007, 1008, 1010, 1015, 1016, 1020, 1022, 1026, 1027, 1029, 1030, 1031, 1032, 1033, 1034, 1035, 1036, 1037, 1039, 1041, 1042, 1043, 1044, 1046, 1047, 1048, 1049, 1051
Telecom: HKTA 2011, 2012, 2013, 2014, 2017, 2018, 2022, 2024, 2026, 2027, 2028, 2029, 2030, 2031, 2032, 2033

You may submit test data to OFTA to verify that the equipment to be imported into Hong Kong satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements.

Recognized CABs are listed on the NIST website at <http://ts.nist.gov/mra>. If you have any questions please contact Ramona Saar at (301) 975-5521 or ramona.saar@nist.gov.

Sincerely,

David F. Alderman
Group Leader, Standards Coordination and Conformity Group
Standards Services Division

Enclosure

cc: Ramona Saar



Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 61 of 66
www.siemic.com.cn

SIEMIC ACREDITATION DETAILS: Australia ACMA CAB ID: US0160



UNITED STATES DEPARTMENT OF COMMERCE
National Institute of Standards and Technology
Gaithersburg, Maryland 20899

November 20, 2008

Mr. Leslie Bai
SIEMIC, Inc.
2206 Ringwood Avenue
San Jose, CA 95131

Dear Mr. Bai:

NIST is pleased to inform you that your laboratory has been recognized by the Australian Communications and Media Authority (ACMA) under the Asia Pacific Economic Cooperation for Telecommunications Equipment Mutual Recognition Arrangement (APEC Tel MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA. The pertinent information about your laboratory's designation is as follows:

CAB Name: Siemic, Inc.
Physical Location: 2206 Ringwood Avenue, San Jose, CA 95131
Identification No.: US0160
Recognized Scope: EMC: AS/NZS 4251.1 (until 5/31/2009), AS/NZS 4251.2 (until 5/31/2009), AS/NZS CISPR 11, AS/NZS CISPR 14.1, AS/NZS CISPR 22, AS/NZS 61000.6.3, AS/NZS 61000.6.4
Radiocommunications: AS/NZS 4281, AS/NZS 4268, AS/NZS 4280.1, AS/NZS 4280.2, AS/NZS 4295, AS/NZS 4582, AS/NZS 4583, AS/NZS 4769.1, AS/NZS 4769.2, AS/NZS 4770, AS/NZS 4771
Telecommunications: AS/ACIF S002:05, AS/ACIF S003:06, AS/ACIF S004:06, AS/ACIF S006:01, AS/ACIF S016:01, AS/ACIF S031:01, AS/ACIF S038:01, AS/ACIF S040:01, AS/ACIF S041:05, AS/ACIF S043.2:06, AS/NZS 60950.1

You may submit test data to ACMA to verify that the equipment to be imported into Australia satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements. Recognized CABs are listed on the NIST website at <http://ts.nist.gov/mra>. Please contact Ms. Ramona Saar, at (301) 975-5521 or ramona.saar@nist.gov if you have questions.

Sincerely,

David F. Alderman
Group Leader, Standards Coordination and Conformity Group
Standards Services Division

Enclosure

cc: Snell Leong, Siemic, Inc.; Ramona Saar, NIST



Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 62 of 66
www.siemic.com.cn

SIEMIC ACCREDITATION DETAILS: Australia NATA Recognition



Leslie Bai
SIEMIC, Inc.
2206 Ringwood Avenue
San Jose, CA 95131

November 4, 2008

Under Australian government legislation, the Australian Communications and Media Authority (ACMA) has determined the National Association of Testing Authorities, Australia (NATA) as an accreditation body as per Section 409(1) of the Telecommunications Act 1997 (Cth). Pursuant to Section 409(2) of the Telecommunications Act 1997 (Cth), I am pleased to advise that your laboratory has been determined as a Recognised Testing Authority (RTA).

This determination has been made on the basis of your accreditation by A2LA accreditation no. 2742.01 and the Mutual Recognition Agreement between NATA and A2LA. It is effective from 11 July 2008. RTA status applies only to the following standards and is contingent upon their continued inclusion in your laboratory's scope of accreditation.

**AS/ACIF S002, AS/ACIF S003, AS/ACIF S004,
AS/ACIF S006, AS/ACIF S016, AS/ACIF S031,
AS/ACIF S038, AS/ACIF S041 and
AS/ACIF S043.2**

As an RTA, your laboratory has the following obligations:

1. the laboratory shall continue to meet all of the accreditation criteria of A2LA;
2. the authorised representative of the laboratory shall notify NATA of changes to the staff or operations of the laboratory which would affect the performance of the tests for which the laboratory has been determined;
3. compliance of equipment shall be reported on test reports bearing the A2LA logo/endorsement.

Current information on the Australian Communications and Media Authority and regulatory requirements for telecommunications products within Australia can be obtained from the ACMA's web-site at "<http://www.acma.gov.au>". Further information about NATA may be gained by visiting "<http://www.nata.asn.au>".

Please note that AS/ACIF S040 and New Zealand standards do not form part of the RTA scheme.

Your RTA listing will appear on the NATA website shortly.

Kind Regards

Chris Norton,
Senior Scientific Officer
Measurement Science and Technology
National Association of Testing Authorities (NATA)
71-73 Flemington Road
North Melbourne Vic 3051
Australia
Ph: +61 3 9329 1633 Fx: +61 3 9326 5148
E-Mail: Christopher.Norton@nata.asn.au
Internet: www.nata.asn.au



Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 63 of 66
www.siemic.com.cn

SIEMIC ACREDITATION DETAILS: VCCI Radiated Test Site Registration No. R-3083



CERTIFICATE

Company: SIEMIC Inc.

<Member No. 3081 >

Facility: SIEMIC Inc.

(Radiation 3 meter site)

Location of Facility:

2206 Ringwood Avenue, San Jose, CA 95131 USA

*This is to certify that the following measuring facility
has been registered in accordance with the Rules
for Voluntary Control Measures*

Registration No.: R-3083

Date of Registration: June 12, 2009

This Certificate is valid until September 30, 2010

VCCI Council





Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 64 of 66
www.siemic.com.cn

SIEMIC ACREDITATION DETAILS: VCCI Conducted (Main Port) Test Site Registration No. C-3421



VCCI Council

CERTIFICATE

Company: SIEMIC Inc.

<Member No. 3081 >

Facility: SIEMIC Inc.

(Main Ports Conducted Interference Measurement)

Location of Facility:

2206 Ringwood Avenue, San Jose, CA 95131 USA

*This is to certify that the following measuring facility
has been registered in accordance with the Rules
for Voluntary Control Measures*

Registration No.: C-3421

Date of Registration: June 12, 2009

This Certificate is valid until September 30, 2010

VCCI Council





Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 65 of 66
www.siemic.com.cn

SIEMIC ACREDITATION DETAILS: VCCI Conducted (Telecom Port) Test Site Registration No. T-1597



CERTIFICATE

Company: SIEMIC Inc.

<Member No. 3081 >

Facility: SIEMIC Inc.

(Telecominication Ports Conducted Interference Measurement)

Location of Facility:

2206 Ringwood Avenue, San Jose, CA 95131 USA

*This is to certify that the following measuring facility
has been registered in accordance with the Rules
for Voluntary Control Measures*

Registration No.: T-1597

Date of Registration: June 12, 2009

This Certificate is valid until September 30, 2010

VCCI Council





SIEMIC, INC.

Accessing global markets

Title: RF Test Report for Ray Stone Palm
Model: ZZB-2
To: FCC 15.247:2009

Serial#: 1003026
Issue Date: November 18, 2010
Page 66 of 66
www.siemic.com.cn