

**RF Exposure Evaluation****Limit**

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1310 & 2.1091

Table 1-Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300	61.4	0.163	1.0	6
300–1500	-	-	f/300	6
1500–100,000	-	-	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300	27.5	0.073	0.2	30
300–1500	-	-	f/1500	30
1500–100,000	-	-	1.0	30

Note: f = frequency in MHz

**Evaluation Method**

$$\text{Transmission formula: } P_d = (\text{Pout} * G) / (4 * \pi * R^2)$$

Where

Pd = power density in mW/cm<sup>2</sup>, Pout = output power to antenna in mW, G = gain of antenna in linear scale;  $\pi = 3.1416$ , R = distance between observation point and center of the radiator in cm

**Conducted Power Results & Manufacturing tolerance**

Specification	Operating Mode	Conducted Peak Output Power (dBm)	Target (dBm)	Tolerance $\pm$ (dB)
2.4GWIFI	802.11b	14.22	14	1
	802.11g	14.66	14	1
	802.11n(HT20)	15.87	15	1
	802.11n(HT40)	12.54	12	1

**Evaluation Results**

Spec.	Operating Mode	Antenna Distance (cm)	Conducted Output Power		Gain of antenna in linear scale	Power Density (mW /cm <sup>2</sup> )	Limit (mW /cm <sup>2</sup> )	Result
			dBm	mW				
2.4GWIFI	802.11b	20	15	31.62	1.58	0.010	1	PASS
	802.11g	20	15	31.62	1.58	0.010	1	PASS
	802.11n(HT20)	20	16	39.81	1.58	0.013	1	PASS
	802.11n(HT40)	20	13	19.95	1.58	0.006	1	PASS

*Remark:*

1. Output power including tune up tolerance;
2. The maximum 2.4G antenna gain is 2dBi
3. The exposure safety distance is 20cm.

**Simulation Transmission**

EUT can only work in 2.4GWIFI mode

The formula of calculated the Simulation Transmission MPE is:

CPD1/LPD1+CPD2/LPD2+.....etc.<1

CPD=Calculation Maximum Power Denisty

Mode	Calculate	Limit	Result
2.4GWIFI mode	0.013	1	Pass

**Conclusion**

The measurement results comply with the FCC Limit per 47 CFR 1.1310 & 2.1091 for the uncontrolled RF Exposure and MPE compliance per KDB 447498 v06.