



RF Exposure Evaluation

FOR

Phonetone Technology (Shenzhen) Co., Ltd.

Cell Phone Signal booster

Test Model: N70AN-US59

Prepared for : Phonetone Technology (Shenzhen) Co., Ltd.
Address : Room 404, Building 12, Qianlong Garden, Minzhi Street, Bao'an District, Shenzhen, China

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.
Address : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Shajing Street, Baoan District, Shenzhen, China
Tel : (+86)755-82591330
Fax : (+86)755-82591332
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : March 11, 2023
Number of tested samples : 2
Serial number : Prototype
Date of original test : March 11, 2023 ~ April 24, 2024
Date of difference test : February 24, 2025 ~ February 26, 2025
Date of Report : February 26, 2025



**RF Exposure Evaluation****Report Reference No. : LCSA02245060EB**

Date of Issue..... : February 26, 2025

Testing Laboratory Name..... : Shenzhen LCS Compliance Testing Laboratory Ltd.Address..... : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Shajing Street,
Baoan District, Shenzhen, ChinaTesting Location/ Procedure..... : Full application of Harmonised standards ■
Partial application of Harmonised standards □
Other standard testing method □**Applicant's Name..... : Phonetone Technology (Shenzhen) Co., Ltd.**Address..... : Room 404, Building 12, Qianlong Garden, Minzhi Street, Bao'an
District, Shenzhen, China**Test Specification**Standard..... : **CFR 47 § 1.1310**
CFR 47 § 2.1091
KDB447498 D01 General RF Exposure Guidance v06

Test Report Form No..... : LCSEMC-1.0

TRF Originator..... : Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF..... : Dated 2011-03

Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test Item Description..... : Cell Phone Signal boosterTrade Mark..... : INVCALL, **INVCALL**, ANNTLENT, **ANNTLENT**,
PHONETONE, **PHONETONE**, CELSGN, **CELSGN**

Test Model..... : N70AN-US59

For AC Adapter(model: SK02T-0500200U):

Ratings..... : Input: 100-240V~50/60Hz 0.35A Max

Output: 5V---2A

Result : Positive**Compiled by:**

Kevin Huang/ Administrator

Supervised by:

Cary Luo/ Technique principal

Approved by:

Gavin Liang / Manager



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen,
518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity

**TEST REPORT**

Test Report No. :	LCSA02245060EB	<u>February 26, 2025</u> Date of issue
--------------------------	-----------------------	---

Test Model.....	: N70AN-US59
EUT.....	: Cell Phone Signal booster
Applicant.....	: Phonetone Technology (Shenzhen) Co., Ltd.
Address.....	: Room 404, Building 12, Qianlong Garden, Minzhi Street, Bao'an District, Shenzhen, China
Telephone.....	: /
Fax.....	: /
Manufacturer.....	: Phonetone Technology (Shenzhen) Co., Ltd.
Address.....	: Room 404, Building 12, Qianlong Garden, Minzhi Street, Bao'an District, Shenzhen, China
Telephone.....	: /
Fax.....	: /
Factory.....	: Phonetone Technology (Shenzhen) Co., Ltd.
Address.....	: Room 404, Building 12, Qianlong Garden, Minzhi Street, Bao'an District, Shenzhen, China
Telephone.....	: /
Fax.....	: /

Test Result	Positive
--------------------	-----------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.



Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity



Revision History

Revision	Issue Date	Revisions	Revised By
000	February 26, 2025	Initial Issue	---





TABLE OF CONTENTS

Description	Page
1. PRODUCT INFORMATION	6
2. DESCRIPTION OF TEST FACILITY	6
3. EVALUATION METHOD	7
4. LIMIT	7
5. MPE CALCULATION METHOD	8
6. ANTENNA INFORMATION	8
7. CONDUCTED POWER	9
8. MANUFACTURING TOLERANCE	10
9. MEASUREMENT RESULTS	11
10. CONCLUSION	11





1. Product Information

EUT	: Cell Phone Signal booster
Equipment Type	: Fixed Wideband Consumer Zone Enhancers
Test Model	: N70AN-US59
Power Supply	For AC Adapter(model: SK02T-0500200U): : Input: 100-240V~50/60Hz 0.35A Max Output: 5V---2A
Hardware Version	: N70AN-CA60 V1.0
Software Version	: N70AN-CA60 V1.0 Lower 700MHz Band (B12) Uplink: 698~716MHz, Downlink: 728~746MHz Upper 700MHz Band (B13) Uplink: 777~787MHz, Downlink: 747~757MHz
Frequency Range	: Cellular Band (B5) Uplink: 824~849MHz, Downlink: 869~894MHz PCS Band (B2, B25) Uplink: 1850~1915MHz, Downlink: 1930~1995MHz AWS Band(B4, B66) Uplink: 1710~1780MHz, Downlink: 2110~2200MHz
Max Gain	: Uplink: ≤67dB Downlink: ≤64dB
Mobile Antenna Gain	: 8dBi
Max Antenna Port Output Power	: Uplink: ≤20dBm Downlink: ≤7dBm
Emission Designator	: F9W, G7D, G7W, GXW, W7D
FCC Classification	: B2W/Wideband Consumer Booster(CMRS)
Operating Temperature	: -20°C~+65°C

2. Description of Test Facility

FCC Registration Number is 254912.
NVLAP Accreditation Code is 600167-0.
FCC Designation Number is CN5024.
CAB identifier is CN0071.
CNAS Registration Number is L4595.
Industry Canada Registration Number is 9642A.





3. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

4. Limit

4. 1 Refer Evaluation Method

[ANSI C95.1-2019](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices.



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



4.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Uncontrolled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

5. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

6. Antenna Information

EUT can only use antennas certificated as follows provided by manufacturer;

Mode	Frequency (MHz)	Outdoor Antenna Gain (dBi) (Log Periodic Antenna, Model: AN201)	Cable loss (dB)
Uplink	698-716	6	1.80
	777-787	6	1.80
	824-849	6	2.00
	1850-1915	8	2.95
	1710-1780	8	2.70
Mode	Frequency (MHz)	Indoor Antenna Gain (dBi) (Indoor Panel Antenna, Model: AN101)	Cable loss (dB)
Downlink	728-746	7	1.80
	747-757	7	1.80
	869-894	7	2.00
	1930-1995	7	2.95
	2110-2200	7	3.20



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



7. Conducted Power

Operation Band		Frequency (MHz)	Max Output Power (dBm)	Antenna Gain (dBi)	Cable Loss	EIRP Power (dBm)
Uplink	Lower 700 Band (698-716)	707	17.75	6	1.80	21.95
	Upper 700 Band (777-787)	782	17.85	6	1.80	22.05
	Cellular Band (824-849)	836.5	17.66	6	2.00	21.66
	PCS Band (1850-1915)	1882.5	17.59	8	2.95	22.64
	AWS Band (1710-1780)	1732.5	17.82	8	2.70	23.12
Downlink	Lower 700 Band (728-746)	737	6.17	7	1.80	11.37
	Upper 700 Band (747-757)	752	6.88	7	1.80	12.08
	Cellular Band (869-894)	881.5	6.69	7	2.00	11.69
	PCS Band (1930-1995)	1962.5	5.97	7	2.95	10.02
	AWS Band (2110-2200)	2132.5	5.80	7	3.20	9.60





8. Manufacturing Tolerance

Operation Band		Frequency (MHz)	Max Output Power (dBm)	Target (dBm)	Tolerance $\pm$ (dB)
Uplink	Lower 700 Band (698-716)	707	17.75	17.5	1.0
	Upper 700 Band (777-787)	782	17.85	17.5	1.0
	Cellular Band (824-849)	836.5	17.66	17.5	1.0
	PCS Band (1850-1915)	1882.5	17.59	17.5	1.0
	AWS Band (1710-1780)	1732.5	17.82	17.5	1.0
Downlink	Lower 700 Band (728-746)	737	6.17	6.5	1.0
	Upper 700 Band (747-757)	752	6.88	6.5	1.0
	Cellular Band (869-894)	881.5	6.69	6.5	1.0
	PCS Band (1930-1995)	1962.5	5.97	6	1.0
	AWS Band (2110-2200)	2132.5	5.80	6	1.0





9. Measurement Results

9.1 Standalone MPE Evaluation

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r = 20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

Operation Band		Frequency (MHz)	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
			dBm	mW				
Uplink	Lower 700 Band (698-716)	707	18.5	70.7946	6	3.9811	0.0561	1.0000
	BRS Band (2500-2570)	2535	18.5	70.7946	6	3.9811	0.0561	1.0000
	Cellular Band (824-849)	836.5	18.5	70.7946	6	3.9811	0.0561	1.0000
	PCS Band (1850-1915)	1882.5	18.5	70.7946	8	6.3096	0.0889	1.0000
	AWS Band (1710-1780)	1732.5	18.5	70.7946	8	6.3096	0.0889	1.0000
Downlink	Lower 700 Band (728-746)	737	7.5	5.6234	7	5.0119	0.0056	1.0000
	BRS Band (2620-2690)	2655	7.5	5.6234	7	5.0119	0.0056	1.0000
	Cellular Band (869-894)	881.5	7.5	5.6234	7	5.0119	0.0056	1.0000
	PCS Band (1930-1995)	1962.5	7	5.0119	7	5.0119	0.0050	1.0000
	AWS Band (2110-2200)	2132.5	7	5.0119	7	5.0119	0.0050	1.0000

9.2 Simultaneous Transmission MPE Evaluation

Not need consider simultaneous transmission

10. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----THE END OF REPORT-----

