

Wizard Control Systems, Inc. dba American Digital Technologies

WTX 915

Report No. AMDI0007

Report Prepared By



www.nwemc.com
1-888-EMI-CERT

© 2010 Northwest EMC, Inc

EMC Test Report

Certificate of Test

Last Date of Test: November 11, 2010
Wizard Control Systems, Inc. dba American Digital Technologies
Model: WTX 915

Emissions			
Test Description	Specification	Test Method	Pass/Fail
Carrier Frequency Separation	FCC 15.247:2010	ANSI C63.10:2009	Pass
Dwell Time	FCC 15.247:2010	ANSI C63.10:2009	Pass
Number of Hopping Frequencies	FCC 15.247:2010	ANSI C63.10:2009	Pass
Occupied Bandwidth	FCC 15.247:2010	ANSI C63.10:2009	Pass
Output Power	FCC 15.247:2010	ANSI C63.10:2009	Pass
Band Edge Compliance	FCC 15.247:2010	ANSI C63.10:2009	Pass
Spurious Conducted Emissions	FCC 15.247:2010	ANSI C63.10:2009	Pass
Duty Cycle Correction	FCC 15.247:2010	ANSI C63.10:2009	Pass
Spurious Radiated Emissions	FCC 15.247:2010	ANSI C63.10:2009	Pass

Modifications made to the product

See the Modifications section of this report

Test Facility

The measurement facility used to collect the data is located at:

Northwest EMC, Inc.
22975 NW Evergreen Parkway, Suite 400
Hillsboro, OR 97124

Phone: (503) 844-4066 Fax: 844-3826

This site has been fully described in a report filed with and accepted by the FCC (Federal Communications Commission) and Industry Canada (Site filing #2834D-2).

Approved By:



Don Factice, IS Manager



NVLAP Lab Code: 200630-0

This report must not be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government of the United States of America.

Product compliance is the responsibility of the client, therefore the tests and equipment modes of operation represented in this report were agreed upon by the client, prior to testing. This Report may only be duplicated in its entirety. The results of this test pertain only to the sample(s) tested. The specific description is noted in each of the individual sections of the test report supporting this certificate of test.

Revision Number	Description	Date	Page Number
00	None		

Barometric Pressure

The recorded barometric pressure has been normalized to sea level.



Accreditations and Authorizations

FCC

Accredited by NVLAP for performance of FCC radio, digital, and ISM device testing. Our Open Area Test Sites, certification chambers, and conducted measurement facilities have been fully described in reports filed with the FCC and accepted by the FCC in letters maintained in our files. Northwest EMC has been accredited by ANSI to ISO / IEC Guide 65 as a product certifier. We have been designated by the FCC as a Telecommunications Certification Body (TCB). This allows Northwest EMC to certify transmitters to FCC specifications in accordance with 47 CFR 2.960 and 2.962.



NVLAP

Northwest EMC, Inc. is accredited under the National Voluntary Laboratory Accreditation Program (NVLAP) for satisfactory compliance with the requirements of ISO/IEC 17025 for Testing Laboratories. NVLAP is administered by the National Institute of Standards and Technology (NIST), an agency of the U.S. Commerce Department. The NVLAP accreditation encompasses Electromagnetic Compatibility Testing in accordance with the European Union EMC Directive 2004/108/EC, and ANSI C63.4. Additionally, Northwest EMC is accredited by NVLAP to perform radio testing in accordance with the European Union R&TTE Directive 1999/5/EEC, the requirements of FCC, and the RSS radio standards for Industry Canada.



NVLAP LAB CODE 200629-0
NVLAP LAB CODE 200630-0
NVLAP LAB CODE 200676-0
NVLAP LAB CODE 200761-0
NVLAP LAB CODE 200881-0

Industry Canada

Accredited by NVLAP for performance of Industry Canada RSS and ICES testing. Our Open Area Test Sites and certification chambers comply with RSS-Gen, Issue 2 and have been filed with Industry Canada and accepted. Northwest EMC has been accredited by ANSI to ISO / IEC Guide 65 as a product certifier. We have been designated by NIST and recognized by Industry Canada as a Certification Body (CB) per the APEC Mutual Recognition Arrangement (MRA). This allows Northwest EMC to certify transmitters to Industry Canada technical requirements. (Site Filing Numbers - Hillsboro: 2834D-1, 2834D-2, Sultan: 2834C-1, Irvine: 2834B-1, 2834B-2, Brooklyn Park: 2834E-1)



CAB

Designated by NIST and validated by the European Commission as a Conformity Assessment Body (CAB) to conduct tests and approve products to the EMC directive and transmitters to the R&TTE directive, as described in the U.S. - EU Mutual Recognition Agreement.



NEMKO

Assessed and accredited by NEMKO (Norwegian testing and certification body) for European emissions and immunity testing. As a result of NEMKO's laboratory assessment, they will accept test results from Northwest EMC, Inc. for product certification (Authorization No. ELA 119).





Accreditations and Authorizations

Australia/New Zealand

The National Association of Testing Authorities (NATA), Australia has been appointed by the ACA as an accreditation body to accredit test laboratories and competent bodies for EMC standards. Accredited test reports or assessments by competent bodies must carry the NATA logo. Test reports made by an overseas laboratory that has been accredited for the relevant standards by an overseas accreditation body that has a Mutual Recognition Agreement (MRA) with NATA are also accepted as technical grounds for product conformity. The report should be endorsed with the respective logo of the accreditation body (NVLAP).



VCCI

Accepted as an Associate Member to the VCCI, Acceptance No. 564. Conducted and radiated measurement facilities have been registered in accordance with Regulations for Voluntary Control Measures, Article 8. (Registration Numbers. - Hillsboro: C-1071, R-1025, G-84, C-2687, T-1658, and R-2318, Irvine: R-1943, G-85, C-2766, and T-1659, Sultan: R-871, G-83, C-1784, and T-1511, Brooklyn Park: R-3125, G-86, G-141, C-3464, and T-1634).



BSMI

Northwest EMC has been designated by NIST and validated by C-Taipei (BSMI) as a CAB to conduct tests as described in the APEC Mutual Recognition Agreement (US0017). License No. SL2-IN-E-1017.



GOST

Northwest EMC, Inc. has been assessed and accredited by the Russian Certification bodies Certinform VNIIINMASH, CERTINFO, SAMTES, and Federal CHEC, to perform EMC and Hygienic testing for Information Technology Products. As a result of their laboratory assessment, they will accept test results from Northwest EMC, Inc. for product certification



KCC

Northwest EMC, Inc is a CAB designated by MRA partners and recognized by Korea. (Assigned Lab Numbers: Hillsboro: US0017, Irvine: US0158, Sultan: US0157)



VIETNAM

Vietnam MIC has approved Northwest EMC as an accredited test lab. Per Decision No. 194/QD-QLCL (dated December 15, 2009), Northwest EMC test reports can be used for Vietnam approval submissions.



SCOPE

For details on the Scopes of our Accreditations, please visit:

<http://www.nwemc.com/accreditations/>



Northwest EMC Locations





Oregon
Labs EV01-EV12
22975 NW Evergreen Pkwy
Suite 400
Hillsboro, OR 97124
(503) 844-4066

California
Labs OC01-OC13
41 Tesla
Irvine, CA 92618
(949) 861-8918

Minnesota
Labs MN01-MN08
9349 W Broadway Ave.
Brooklyn Park,
MN 55445
(763) 425-2281

Washington
Labs SU01-SU07
14128 339th Ave. SE
Sultan, WA 98294
(360) 793-8675

New York
Labs WA01-WA04
4939 Jordan Rd.
Elbridge, NY 13060
(315) 685-0796



Party Requesting the Test

Company Name:	Wizard Control Systems, Inc. dba American Digital Technologies
Address:	PO Box 5245 4582 Salem-Dallas Hwy
City, State, Zip:	Salem, OR 97304
Test Requested By:	Aaron Montesano
Model:	WTX 915
First Date of Test:	November 10, 2010
Last Date of Test:	November 11, 2010
Receipt Date of Samples:	November 10, 2010
Equipment Design Stage:	Preproduction
Equipment Condition:	No Damage

Information Provided by the Party Requesting the Test**Functional Description of the EUT (Equipment Under Test):**

902-928 MHz radio. +20 dBm expected output power.

Testing Objective:

To demonstrate compliance to FCC 15.247 specifications.

CONFIGURATION 1 AMDI0007

EUT			
Description	Manufacturer	Model/Part Number	Serial Number
EUT - Radiated	Wizard Control Systems, Inc. dba American Digital Technologies	WTX 915	None

CONFIGURATION 2 AMDI0007

EUT			
Description	Manufacturer	Model/Part Number	Serial Number
EUT – Direct Connection	Wizard Control Systems, Inc. dba American Digital Technologies	WTX 915	None

Equipment modifications					
Item	Date	Test	Modification	Note	Disposition of EUT
1	11/10/2010	Number of Hopping Frequencies	Tested as delivered to Test Station.	No EMI suppression devices were added or modified during this test.	EUT remained at Northwest EMC following the test.
2	11/10/2010	Occupied Bandwidth	Tested as delivered to Test Station.	No EMI suppression devices were added or modified during this test.	EUT remained at Northwest EMC following the test.
3	11/10/2010	Output Power	Tested as delivered to Test Station.	No EMI suppression devices were added or modified during this test.	EUT remained at Northwest EMC following the test.
4	11/10/2010	Band Edge Compliance	Tested as delivered to Test Station.	No EMI suppression devices were added or modified during this test.	EUT remained at Northwest EMC following the test.
5	11/10/2010	Spurious Conducted Emissions	Tested as delivered to Test Station.	No EMI suppression devices were added or modified during this test.	EUT remained at Northwest EMC following the test.
6	11/10/2010	Carrier Frequency Separation	Tested as delivered to Test Station.	No EMI suppression devices were added or modified during this test.	EUT remained at Northwest EMC following the test.
7	11/10/2010	Spurious Radiated Emissions	Tested as delivered to Test Station.	No EMI suppression devices were added or modified during this test.	EUT remained at Northwest EMC following the test.
8	11/11/2010	Dwell Time	Tested as delivered to Test Station.	No EMI suppression devices were added or modified during this test.	EUT remained at Northwest EMC following the test.
9	11/11/2010	Duty Cycle Correction	Tested as delivered to Test Station.	No EMI suppression devices were added or modified during this test.	Scheduled testing was completed.

Testing was performed using the mode(s) of operation and configuration(s) noted within the report. The individuals and/or the organization requesting the test provided the modes, configurations and settings used to complete the evaluation. The actual test parameters are specified in the test data, this includes items such as investigated frequency range (scanned) and test levels. The testing methods and performance specifications, as well as the test site used for the evaluation are indicated in the test data.

TEST EQUIPMENT

Description	Manufacturer	Model	ID	Last Cal.	Interval
Spectrum Analyzer	Agilent	E4440A	AFD	6/1/2009	24
40GHz DC Block	Miteq	DCB4000	AMD	8/5/2010	13
Attenuator, 6 dB, 'SMA'	N/A	93459 3330A-6	AUF	4/1/2010	13
EV06 Direct Connect Cable	ESM Cable Corp.	TT	ECA	NCR	0

MEASUREMENT UNCERTAINTY

A measurement uncertainty estimation has been performed for each test per our internal quality document WP 342. The estimation is used to compare the measured result with its "true" or theoretically correct value. The expanded measurement uncertainty for radiated emissions measurements is less than +/- 4 dB, and for conducted emissions measurements is less than +/- 2.7 dB. Our measurement data meets or exceeds the measurement uncertainty requirements of CISPR 16-4; therefore, the test data can be compared directly to the specification limit to determine compliance. The calculations for measurement uncertainty are available upon request.

TEST DESCRIPTION

The carrier frequency separation was measured between each of 5 hopping channels in the middle of the authorized band. The measurements were made using a direct connection between the RF output of the EUT and the spectrum analyzer. The hopping function of the EUT was enabled.

The frequency hopping system must have a channel separation of at least 25 kHz or the 20 dB occupied bandwidth of the channels. This system uses an occupied bandwidth of 367 kHz, requiring a channel separation greater than that.


CARRIER FREQUENCY SEPARATION

EUT: WTX 915	Work Order: AMDI0007		
Serial Number: none	Date: 11/10/10		
Customer: Wizard Control Systems, Inc. dba American Digital Technologies	Temperature: 22°C		
Attendees: Aaron Montesano, Aaron Yarnell	Humidity: 45%		
Project: None	Barometric Pres.: 29.65		
Tested by: Rod Peloquin	Job Site: EV06		
TEST SPECIFICATIONS			
FCC 15.247:2010			
ANSI C63.10:2009			
Test Method			
COMMENTS			
Frequency hopping mode			
DEVIATIONS FROM TEST STANDARD			
Configuration #	2		
 Signature			
CHANNEL SEPARATION	Value	Limit	Results
	477 kHz	≥ 367 kHz	Pass

CHANNEL SEPARATION

Result: Pass

Value: 477 kHz

Limit: ≥ 367 kHz

Testing was performed using the mode(s) of operation and configuration(s) noted within the report. The individuals and/or the organization requesting the test provided the modes, configurations and settings used to complete the evaluation. The actual test parameters are specified in the test data, this includes items such as investigated frequency range (scanned) and test levels. The testing methods and performance specifications, as well as the test site used for the evaluation are indicated in the test data.

TEST EQUIPMENT						
Description	Manufacturer	Model	ID	Last Cal.	Interval	
Spectrum Analyzer	Agilent	E4440A	AFD	6/1/2009	24	
40GHz DC Block	Miteq	DCB4000	AMD	8/5/2010	13	
Attenuator 20 dB, SMA M/F 26GHz	S.M. Electronics	SA26B-20	AUY	8/6/2010	13	
EV06 Direct Connect Cable	ESM Cable Corp.	TT	ECA	NCR	0	

MEASUREMENT UNCERTAINTY

A measurement uncertainty estimation has been performed for each test per our internal quality document WP 342. The estimation is used to compare the measured result with its "true" or theoretically correct value. The expanded measurement uncertainty for radiated emissions measurements is less than +/- 4 dB, and for conducted emissions measurements is less than +/- 2.7 dB. Our measurement data meets or exceeds the measurement uncertainty requirements of CISPR 16-4; therefore, the test data can be compared directly to the specification limit to determine compliance. The calculations for measurement uncertainty are available upon request.

TEST DESCRIPTION

The Dwell time was calculated by using a direct connection between the EUT and the spectrum analyzer. The EUT was operated in a frequency hopping mode. The measurement was made in a zero span while centered on the middle channel.

The requirement to be met is a dwell time of no greater than .4 seconds in a 10 second period. The radio operates on 50 channels with an occupied bandwidth of 437 kHz. The requirement for the 10 second period is met as the occupied bandwidth is greater than 250 kHz and less than 500 kHz

EMC

DWELL TIME

EUT: WTX 915

Work Order: AMDI0007

Serial Number: none

Date: 11/11/10

Customer: Wizard Control Systems, Inc. dba American Digital Technologies

Temperature: 22°C

Attendees: Aaron Montesano, Aaron Yarnell

Humidity: 45%

Project: None

Barometric Pres.: 29.65

Tested by: Rod Peloquin

Power: 3 VDC

Job Site: EV06

TEST SPECIFICATIONS

Test Method

FCC 15.247:2010

ANSI C63.10:2009

COMMENTS

Frequency Hopping Mode

DEVIATIONS FROM TEST STANDARD

No Deviations

Configuration #

2

Signature



Pulse Width

Value

Limit

Results

Period

15.95 ms

.4 s in 10 s

.207 ms

10 Second Sweep

809 ms

.4 s in 10 s

.207 ms

13 Pulses

.4 s in 10 s

.207 ms


Dwell time = 13 transmissions x 15.95 ms = .207 s in 10 second period

Pulse Width

Result: .207 ms

Value: 15.95 ms

Limit: .4 s in 10 s




Period

Result: .207 ms

Value: 809 ms

Limit: .4 s in 10 s




10 Second Sweep

Result: .207 ms

Value: 13 Pulses

Limit: .4 s in 10 s



Testing was performed using the mode(s) of operation and configuration(s) noted within the report. The individuals and/or the organization requesting the test provided the modes, configurations and settings used to complete the evaluation. The actual test parameters are specified in the test data, this includes items such as investigated frequency range (scanned) and test levels. The testing methods and performance specifications, as well as the test site used for the evaluation are indicated in the test data.

TEST EQUIPMENT

Description	Manufacturer	Model	ID	Last Cal.	Interval
Spectrum Analyzer	Agilent	E4440A	AFD	6/1/2009	24
40GHz DC Block	Miteq	DCB4000	AMD	8/5/2010	13
Attenuator 20 dB, SMA M/F 26GHz	S.M. Electronics	SA26B-20	AUY	8/6/2010	13
EV06 Direct Connect Cable	ESM Cable Corp.	TT	ECA	NCR	0

MEASUREMENT UNCERTAINTY

A measurement uncertainty estimation has been performed for each test per our internal quality document WP 342. The estimation is used to compare the measured result with its "true" or theoretically correct value. The expanded measurement uncertainty for radiated emissions measurements is less than +/- 4 dB, and for conducted emissions measurements is less than +/- 2.7 dB. Our measurement data meets or exceeds the measurement uncertainty requirements of CISPR 16-4; therefore, the test data can be compared directly to the specification limit to determine compliance. The calculations for measurement uncertainty are available upon request.

TEST DESCRIPTION

The number of hopping frequencies was measured across the authorized band. The measurements were made using a direct connection between the RF output of the EUT and the spectrum analyzer. The hopping function of the EUT was enabled.

The system has a 20 dB occupied bandwidth greater than 250 kHz as noted elsewhere in the report. The system must therefore have at least 25 hopping channels

NUMBER OF HOPPING FREQUENCIES

EUT: WTX 915

Work Order: AMDI0007

Serial Number: none

Date: 11/10/10

Customer: Wizard Control Systems, Inc. dba American Digital Technologies

Temperature: 22°C

Attendees: Aaron Montesano, Aaron Yarnell

Humidity: 45%

Project: None

Barometric Pres.: 29.65

Tested by: Rod Peloquin

Power: 3 VDC

Job Site: EV06

TEST SPECIFICATIONS

Test Method

FCC 15.247:2010

ANSI C63.10:2009

COMMENTS

None

DEVIATIONS FROM TEST STANDARD

Configuration #

2



Signature

NUMBER OF HOPPING FREQUENCIES

Value

Limit


Results

50

≥ 25

Pass

NUMBER OF HOPPING FREQUENCIES		
Result: Pass	Value: 50	Limit: ≥ 25



OCCUPIED BANDWIDTH

Testing was performed using the mode(s) of operation and configuration(s) noted within the report. The individuals and/or the organization requesting the test provided the modes, configurations and settings used to complete the evaluation. The actual test parameters are specified in the test data, this includes items such as investigated frequency range (scanned) and test levels. The testing methods and performance specifications, as well as the test site used for the evaluation are indicated in the test data.

TEST EQUIPMENT

Description	Manufacturer	Model	ID	Last Cal.	Interval
Spectrum Analyzer	Agilent	E4440A	AFD	6/1/2009	24
40GHz DC Block	Miteq	DCB4000	AMD	8/5/2010	13
EV06 Direct Connect Cable	ESM Cable Corp.	TT	ECA	NCR	0
Attenuator 20 dB, SMA M/F 26GHz	S.M. Electronics	SA26B-20	AUY	8/6/2010	13

MEASUREMENT UNCERTAINTY

A measurement uncertainty estimation has been performed for each test per our internal quality document WP 342. The estimation is used to compare the measured result with its "true" or theoretically correct value. The expanded measurement uncertainty for radiated emissions measurements is less than +/- 4 dB, and for conducted emissions measurements is less than +/- 2.7 dB. Our measurement data meets or exceeds the measurement uncertainty requirements of CISPR 16-4; therefore, the test data can be compared directly to the specification limit to determine compliance. The calculations for measurement uncertainty are available upon request.

TEST DESCRIPTION


The occupied bandwidth was measured at the low, medium, and high transmit frequencies. The measurement was made using a direct connection between the RF output of the EUT and the spectrum analyzer. The EUT was transmitting at its maximum data rate in the normal hopping mode.

To support the Dwell Time requirement in a 10 second period, the occupied bandwidth of the channel must be greater than 250 kHz. A frequency hopping system in this rule part must always have an occupied bandwidth less than 500 kHz.


OCCUPIED BANDWIDTH

EUT: WTX 915	Work Order: AMDI0007	
Serial Number: none	Date: 11/10/10	
Customer: Wizard Control Systems, Inc. dba American Digital Technologies	Temperature: 22°C	
Attendees: Aaron Montesano, Aaron Yarnell	Humidity: 45%	
Project: None	Barometric Pres.: 29.65	
Tested by: Rod Peloquin	Job Site: EV06	
TEST SPECIFICATIONS		
FCC 15.247:2010		
ANSI C63.10:2009		
COMMENTS		
Hopping mode		
DEVIATIONS FROM TEST STANDARD		
No Deviations		
Configuration #	2	
Signature		
<i>Rod Peloquin</i>		
Value	Limit	Results
380 kHz	≥ 250 kHz, ≤ 500 kHz	Pass
367 kHz	≥ 250 kHz, ≤ 500 kHz	Pass
336 kHz	≥ 250 kHz, ≤ 500 kHz	Pass


Low Channel		
Result: Pass	Value: 380 kHz	Limit: ≥ 250 kHz, ≤ 500 kHz



Mid Channel		
Result: Pass	Value: 367 kHz	Limit: ≥ 250 kHz, ≤ 500 kHz



High Channel		
Result: Pass	Value: 336 kHz	Limit: ≥ 250 kHz, ≤ 500 kHz



OUTPUT POWER

Testing was performed using the mode(s) of operation and configuration(s) noted within the report. The individuals and/or the organization requesting the test provided the modes, configurations and settings used to complete the evaluation. The actual test parameters are specified in the test data, this includes items such as investigated frequency range (scanned) and test levels. The testing methods and performance specifications, as well as the test site used for the evaluation are indicated in the test data.

TEST EQUIPMENT						
Description	Manufacturer	Model	ID	Last Cal.	Interval	
Spectrum Analyzer	Agilent	E4440A	AFD	6/1/2009	24	
EV06 Direct Connect Cable	ESM Cable Corp.	TT	ECA	NCR	0	
40GHz DC Block	Miteq	DCB4000	AMD	8/5/2010	13	
Attenuator 20 dB, SMA M/F 26GHz	S.M. Electronics	SA26B-20	AUY	8/6/2010	13	
Power Meter	Gigatronics	8651A	SPM	1/7/2010	13	
Power Sensor	Gigatronics	80701A	SPL	1/7/2010	13	
Attenuator, 6 dB, 'SMA'	N/A	93459 3330A-6	AUF	4/1/2010	13	
Signal Generator	Agilent	E8257D	TGX	12/10/2008	24	

MEASUREMENT UNCERTAINTY

A measurement uncertainty estimation has been performed for each test per our internal quality document WP 342. The estimation is used to compare the measured result with its "true" or theoretically correct value. The expanded measurement uncertainty for radiated emissions measurements is less than +/- 4 dB, and for conducted emissions measurements is less than +/- 2.7 dB. Our measurement data meets or exceeds the measurement uncertainty requirements of CISPR 16-4; therefore, the test data can be compared directly to the specification limit to determine compliance. The calculations for measurement uncertainty are available upon request.

TEST DESCRIPTION

The peak output power was measured with the EUT set to low, medium, and high transmit frequencies. The measurement was made using a direct connection between the RF output of the EUT and a spectrum analyzer. The EUT was transmitting at its maximum data rate in a no hop mode.

De Facto EIRP Limit: Per 47 CFR 15.247 (b)(1-3), the EUT meets the de facto EIRP limit of +36dBm.

OUTPUT POWER

EUT: WTX 915	Work Order: AMDI0007
Serial Number: none	Date: 11/10/10
Customer: Wizard Control Systems, Inc. dba American Digital Technologies	Temperature: 22°C
Attendees: Aaron Montesano, Aaron Yarnell	Humidity: 45%
Project: None	Barometric Pres.: 29.65
Tested by: Rod Peloquin	Job Site: EV06

TEST SPECIFICATIONS

FCC 15.247:2010	Test Method
	ANSI C63.10:2009

COMMENTS

None


DEVIATIONS FROM TEST STANDARD

No Deviations


Configuration #	2	 Signature
-----------------	---	--

	Value	Limit	Results
Low Channel	53.4 mW	1 W	Pass
Mid Channel	58.6 mW	1 W	Pass
High Channel	63.1 mW	1 W	Pass


Low Channel		
Result: Pass	Value: 53.4 mW	Limit: 1 W



Mid Channel		
Result: Pass	Value: 58.6 mW	Limit: 1 W



High Channel		
Result: Pass	Value: 63.1 mW	Limit: 1 W



BAND EDGE COMPLIANCE

Testing was performed using the mode(s) of operation and configuration(s) noted within the report. The individuals and/or the organization requesting the test provided the modes, configurations and settings used to complete the evaluation. The actual test parameters are specified in the test data, this includes items such as investigated frequency range (scanned) and test levels. The testing methods and performance specifications, as well as the test site used for the evaluation are indicated in the test data.

TEST EQUIPMENT

Description	Manufacturer	Model	ID	Last Cal.	Interval
Spectrum Analyzer	Agilent	E4440A	AFD	6/1/2009	24
40GHz DC Block	Miteq	DCB4000	AMD	8/5/2010	13
Attenuator 20 dB, SMA M/F 26GHz	S.M. Electronics	SA26B-20	AUY	8/6/2010	13
EV06 Direct Connect Cable	ESM Cable Corp.	TT	ECA	NCR	0

MEASUREMENT UNCERTAINTY

A measurement uncertainty estimation has been performed for each test per our internal quality document WP 342. The estimation is used to compare the measured result with its "true" or theoretically correct value. The expanded measurement uncertainty for radiated emissions measurements is less than +/- 4 dB, and for conducted emissions measurements is less than +/- 2.7 dB. Our measurement data meets or exceeds the measurement uncertainty requirements of CISPR 16-4; therefore, the test data can be compared directly to the specification limit to determine compliance. The calculations for measurement uncertainty are available upon request.


TEST DESCRIPTION

The spurious RF conducted emissions at the edges of the authorized band were measured with the EUT set to low and high transmit frequencies. The measurement was made using a direct connection between the RF output of the EUT and the spectrum analyzer. The EUT was transmitting at its maximum data rate in a no hop mode. The channels closest to the band edges were selected. The spectrum was scanned across each band edge from 5 MHz below the band edge to 5 MHz above the band edge.


BAND EDGE COMPLIANCE

EUT: WTX 915	Work Order: AMDI0007		
Serial Number: none	Date: 11/10/10		
Customer: Wizard Control Systems, Inc. dba American Digital Technologies	Temperature: 22°C		
Attendees: Aaron Montesano, Aaron Yarnell	Humidity: 45%		
Project: None	Barometric Pres.: 29.65		
Tested by: Rod Peloquin	Job Site: EV06		
TEST SPECIFICATIONS			
FCC 15.247:2010			
ANSI C63.10:2009			
Test Method			
COMMENTS			
None			
DEVIATIONS FROM TEST STANDARD			
No Deviations			
Configuration #	2		
Signature 			
	Value	Limit	Results
Low Channel	-57.2 dBc	≤ -20 dBc	Pass
High Channel	-53.5 dBc	≤ -20 dBc	Pass

Low Channel		
Result: Pass	Value: -57.2 dBc	Limit: ≤ -20 dBc



High Channel		
Result: Pass	Value: -53.5 dBc	Limit: ≤ -20 dBc



Testing was performed using the mode(s) of operation and configuration(s) noted within the report. The individuals and/or the organization requesting the test provided the modes, configurations and settings used to complete the evaluation. The actual test parameters are specified in the test data, this includes items such as investigated frequency range (scanned) and test levels. The testing methods and performance specifications, as well as the test site used for the evaluation are indicated in the test data.

TEST EQUIPMENT

Description	Manufacturer	Model	ID	Last Cal.	Interval
Spectrum Analyzer	Agilent	E4440A	AFD	6/1/2009	24
40GHz DC Block	Miteq	DCB4000	AMD	8/5/2010	13
Attenuator 20 dB, SMA M/F 26GHz	S.M. Electronics	SA26B-20	AUY	8/6/2010	13
EV06 Direct Connect Cable	ESM Cable Corp.	TT	ECA	NCR	0

MEASUREMENT UNCERTAINTY

A measurement uncertainty estimation has been performed for each test per our internal quality document WP 342. The estimation is used to compare the measured result with its "true" or theoretically correct value. The expanded measurement uncertainty for radiated emissions measurements is less than +/- 4 dB, and for conducted emissions measurements is less than +/- 2.7 dB. Our measurement data meets or exceeds the measurement uncertainty requirements of CISPR 16-4; therefore, the test data can be compared directly to the specification limit to determine compliance. The calculations for measurement uncertainty are available upon request.


TEST DESCRIPTION

The spurious RF conducted emissions were measured with the EUT set to low, medium, and high transmit frequencies. The measurements were made using a direct connection between the RF output of the EUT and the spectrum analyzer. The EUT was transmitting at its maximum data rate in a no hop mode. For each transmit frequency, the spectrum was scanned throughout the specified frequency.


SPURIOUS CONDUCTED EMISSIONS

EUT: WTX 915	Work Order: AMDI0007			
Serial Number: none	Date: 11/10/10			
Customer: Wizard Control Systems, Inc. dba American Digital Technologies	Temperature: 22°C			
Attendees: Aaron Montesano, Aaron Yarnell	Humidity: 45%			
Project: None	Barometric Pres.: 29.65			
Tested by: Rod Peloquin	Job Site: EV06			
TEST SPECIFICATIONS				
FCC 15.247:2010				
ANSI C63.10:2009				
COMMENTS				
None				
DEVIATIONS FROM TEST STANDARD				
No Deviations				
Configuration #	2			
Signature				
		Value	Limit	Results
Low Channel				
0 - 3 GHz		-61.3 dBc	≤ -20 dBc	Pass
2.99 GHz - 10 GHz		< -65 dBc	≤ -20 dBc	Pass
Mid Channel				
0 - 3 GHz		-61.5 dBc	≤ -20 dBc	Pass
2.99 GHz - 10 GHz		< -65 dBc	≤ -20 dBc	Pass
High Channel				
0 - 3 GHz		-62.6 dBc	≤ -20 dBc	Pass
2.99 GHz - 10 GHz		< -65 dBc	≤ -20 dBc	Pass


Low Channel, 0 - 3 GHz		
Result: Pass	Value: -61.3 dBc	Limit: ≤ -20 dBc




Low Channel, 2.99 GHz - 10 GHz		
Result: Pass	Value: < -65 dBc	Limit: ≤ -20 dBc




Mid Channel, 0 - 3 GHz		
Result: Pass	Value: -61.5 dBc	Limit: ≤ -20 dBc




Mid Channel, 2.99 GHz - 10 GHz		
Result: Pass	Value: < -65 dBc	Limit: ≤ -20 dBc



High Channel, 0 - 3 GHz		
Result: Pass	Value: -62.6 dBc	Limit: ≤ -20 dBc



High Channel, 2.99 GHz - 10 GHz		
Result: Pass	Value: < -65 dBc	Limit: ≤ -20 dBc



Testing was performed using the mode(s) of operation and configuration(s) noted within the report. The individuals and/or the organization requesting the test provided the modes, configurations and settings used to complete the evaluation. The actual test parameters are specified in the test data, this includes items such as investigated frequency range (scanned) and test levels. The testing methods and performance specifications, as well as the test site used for the evaluation are indicated in the test data.

TEST EQUIPMENT					
Description	Manufacturer	Model	ID	Last Cal.	Interval
Spectrum Analyzer	Agilent	E4440A	AFD	6/1/2009	24
40GHz DC Block	Miteq	DCB4000	AMD	8/5/2010	13
Attenuator 20 dB, SMA M/F 26GHz	S.M. Electronics	SA26B-20	AUY	8/6/2010	13
EV06 Direct Connect Cable	ESM Cable Corp.	TT	ECA	NCR	0

MEASUREMENT UNCERTAINTY

A measurement uncertainty estimation has been performed for each test per our internal quality document WP 342. The estimation is used to compare the measured result with its "true" or theoretically correct value. The expanded measurement uncertainty for radiated emissions measurements is less than +/- 4 dB, and for conducted emissions measurements is less than +/- 2.7 dB. Our measurement data meets or exceeds the measurement uncertainty requirements of CISPR 16-4; therefore, the test data can be compared directly to the specification limit to determine compliance. The calculations for measurement uncertainty are available upon request.

TEST DESCRIPTION

To derive average emission measurements, a duty cycle correction factor per 15.35(c) was utilized:

Duty Cycle = On time/100 milliseconds (or the period, whichever is less)

Where "On time" = $N1L1 + N2L2 + \dots$

Where $N1$ is the number of type 1 pulses, $L1$ is length of type 1 pulses, $N2$ is the number of type 2 pulses, $L2$ is the length of type 2 pulses, etc.

Therefore, Duty Cycle = $(N1L1 + N2L2 + \dots)/100\text{mS}$ or T , whichever is less, where T is the period of the pulse train.

The measured values for the EUT's pulse train are as follows:

Period = 100 mSec

Pulsewidth of Pulse= 15.95 mSec

Number of Pulses = 1


Duty Cycle = $20 \log [(15.95)/100] = -15.9 \text{ dB}$

DUTY CYCLE CORRECTION


EUT: WTX 915	Work Order: AMDI0007		
Serial Number: none	Date: 11/11/10		
Customer: Wizard Control Systems, Inc. dba American Digital Technologies	Temperature: 22°C		
Attendees: Aaron Montesano, Aaron Yarnell	Humidity: 45%		
Project: None	Barometric Pres.: 29.65		
Tested by: Rod Peloquin	Job Site: EV06		
TEST SPECIFICATIONS			
FCC 15.247:2010			
ANSI C63.10:2009			
COMMENTS			
Frequency Hopping mode			
DEVIATIONS FROM TEST STANDARD			
No Deviations			
Configuration #	2		
<i>Rod Peloquin</i> Signature			
	Value	Limit	Results
Pulse Width	15.95	N/A	0.1595
100ms Period	100	N/A	0.1595

$$20 * \log (15.95/100) = -15.9 \text{ dB}$$

Pulse Width		
Result: 0.160	Value: 15.95 ms	Limit: N/A



100ms Period		
Result: 0.160	Value: 100 ms	Limit: N/A



Spurious Radiated Emissions

Testing was performed using the mode(s) of operation and configuration(s) noted within the report. The individuals and/or the organization requesting the test provided the modes, configurations and settings used to complete the evaluation. The actual test parameters are specified in the test data, this includes items such as investigated frequency range (scanned) and test levels. The testing methods and performance specifications, as well as the test site used for the evaluation are indicated in the test data.

MODES OF OPERATION

Transmitting Low channel.

Transmitting Mid channel.

Transmitting High channel.

POWER SETTINGS INVESTIGATED

3 VDC

FREQUENCY RANGE INVESTIGATED

Start Frequency	30 MHz	Stop Frequency	12500 MHz
-----------------	--------	----------------	-----------

SAMPLE CALCULATIONS

Radiated Emissions: Field Strength = Measured Level + Antenna Factor + Cable Factor - Amplifier Gain + Distance Adjustment Factor + External Attenuation

TEST EQUIPMENT

Description	Manufacturer	Model	ID	Last Cal.	Interval
High Pass Filter	Micro-Tronics	50108	HGF	1/18/2010	13
Attenuator	Pasternack	PE7005-20	AUN	7/14/2010	13
.5-1 GHz Notch Filter	K&L Microwave	3TNF-500/1000-N/N	HFT	1/8/2010	13
Antenna, Horn	ETS	3160.07	AHZ	9/8/2010	24
Antenna, Horn	ETS	3115	AIB	9/8/2010	24
Antenna, Biconilog	EMCO	3141	AXG	2/15/2010	13
EV12 Cables	N/A	Standard Gain Horn Cables	EVU	7/14/2010	13
EV12 Cables	N/A	Double Ridge Horn Cables	EVT	10/23/2009	13
EV12 Cables	N/A	Bilog Cables	EVS	7/14/2010	13
Pre-Amplifier	Miteq	AMF-6F-08001200-30-10P	AVH	7/14/2010	13
Pre-Amplifier	Miteq	AMF-3D00100800-32-13P	AVF	7/14/2010	13
Pre-Amplifier	Miteq	AM-1616-1000	AVM	7/14/2010	13
Spectrum Analyzer	Agilent	E4440A	AAX	5/14/2010	12

MEASUREMENT BANDWIDTHS

	Frequency Range	Peak Data	Quasi-Peak Data	Average Data
	(MHz)	(kHz)	(kHz)	(kHz)
0.01 - 0.15	1.0	0.2	0.2	0.2
0.15 - 30.0	10.0	9.0	9.0	9.0
30.0 - 1000	100.0	120.0	120.0	120.0
Above 1000	1000.0	N/A	N/A	1000.0

Measurements were made using the bandwidths and detectors specified. No video filter was used.

MEASUREMENT UNCERTAINTY

A measurement uncertainty estimation has been performed for each test per our internal quality document WP 342. The estimation is used to compare the measured result with its "true" or theoretically correct value. Our measurement data meets or exceeds the measurement uncertainty requirements of CISPR 16-4. The measurement uncertainty estimation is available upon request.

TEST DESCRIPTION

The highest gain of each type of antenna to be used with the EUT was tested. The EUT was configured for low, mid, and high band transmit frequencies. For each configuration, the spectrum was scanned throughout the specified range. In addition, measurements were made in the restricted bands to verify compliance. While scanning, emissions from the EUT were maximized by rotating the EUT on a turntable, adjusting the position of the EUT and the EUT antenna in three orthogonal axis, and adjusting measurement antenna height and polarization, and manipulating the EUT antenna in 3 orthogonal planes (per ANSI C63.10:2009). A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.

Spurious Radiated Emissions

EUT: WTX 915	Work Order: AMDI0007
Serial Number: none	Date: 11/10/10
Customer: Wizard Control Systems, Inc. dba American Digital Technologies	Temperature: 22°C
Attendee: Aaron Montesano	Humidity: 45%
Project: None	Barometric Pres.: 29.65

Tested by: Ethan Schoonover Power: 3 VDC Job Site: EV12

TEST SPECIFICATIONS

Test Method

FCC 15.247:2010 ANSI C63.10:2009

TEST PARAMETERS

Antenna Height(s) (m) 1 - 4 Test Distance (m) 3

COMMENTS

None



EUT OPERATING MODES

Transmitting,

DEVIATIONS FROM TEST STANDARD

No deviations.

Run #	1
Configuration #	1
Results	Pass

Signature 

Freq (MHz)	Amplitude (dBuV)	Factor (dB)	Azimuth (degrees)	Height (meters)	Duty Cycle Correction Factor	External Attenuation (dB)	Polarity	Detector	Distance Adjustment (dB)	Adjusted dBuV/m	Spec. Limit dBuV/m	Compared to Spec. (dB)	Comments
2744.767	67.5	1.1	237.0	1.0	15.9	0.0	H-Horn	AV	0.0	52.7	54.0	-1.3	EUT Flat
2744.833	66.7	1.1	47.0	1.0	15.9	0.0	H-Horn	AV	0.0	51.9	54.0	-2.1	EUT Vert
2744.833	65.0	1.1	306.0	1.1	15.9	0.0	V-Horn	AV	0.0	50.2	54.0	-3.8	EUT Flat
2744.627	68.7	1.1	237.0	1.0	0.0	0.0	H-Horn	PK	0.0	69.8	74.0	-4.2	EUT Flat
2744.847	64.4	1.1	294.0	1.5	15.9	0.0	V-Horn	AV	0.0	49.6	54.0	-4.4	EUT Horz
2744.640	67.7	1.1	47.0	1.0	0.0	0.0	H-Horn	PK	0.0	68.8	74.0	-5.2	EUT Vert
2744.747	62.6	1.1	205.0	1.6	15.9	0.0	V-Horn	AV	0.0	47.8	54.0	-6.2	EUT Vert
2744.720	62.5	1.1	128.0	1.0	15.9	0.0	H-Horn	AV	0.0	47.7	54.0	-6.3	EUT Horz
2744.807	66.0	1.1	306.0	1.1	0.0	0.0	V-Horn	PK	0.0	67.1	74.0	-6.9	EUT Flat
2744.673	65.6	1.1	294.0	1.5	0.0	0.0	V-Horn	PK	0.0	66.7	74.0	-7.3	EUT Horz
2744.660	63.7	1.1	128.0	1.0	0.0	0.0	H-Horn	PK	0.0	64.8	74.0	-9.2	EUT Horz
2744.820	63.4	1.1	205.0	1.6	0.0	0.0	V-Horn	PK	0.0	64.5	74.0	-9.5	EUT Vert

Spurious Radiated Emissions												PSA 2008.07.21	EMI 2008.1.9
EMC							TEST SPECIFICATIONS						
EUT: WTX 915 Serial Number: none Customer: Wizard Control Systems, Inc. dba American Digital Technologies Attendees: Aaron Montesano Project: None Tested by: Ethan Schoonover							Work Order: AMDI0007 Date: 11/10/10 Temperature: 22°C Humidity: 45% Barometric Pres.: 29.65 Job Site: EV12						
TEST PARAMETERS							Test Method						
FCC 15.247:2010							ANSI C63.10:2009						
TEST PARAMETERS													
Antenna Height(s) (m)		1 - 4		Test Distance (m)		3		Comments		None			
EUT OPERATING MODES													
Transmitting													
DEVIATIONS FROM TEST STANDARD													
No deviations.													
Run #	2		Signature										
Configuration #	1												
Results	Pass												
<p>The scatter plot shows dBuV/m on the y-axis (0.0 to 80.0) versus MHz on the x-axis (1000.000 to 7000.000). A horizontal blue line at 74.0 dBuV/m represents the specification limit. Green diamond markers represent the EUT data points, which are clustered between 40.0 and 70.0 dBuV/m across the frequency range.</p>													
Freq (MHz)	Amplitude (dBuV)	Factor (dB)	Azimuth (degrees)	Height (meters)	Duty Cycle Correction Factor	External Attenuation (dB)	Polarity	Detector	Distance Adjustment (dB)	Adjusted dBuV/m	Spec. Limit dBuV/m	Compared to Spec. (dB)	Comments
2710.300	67.9	0.9	229.0	1.0	15.9	0.0	H-Horn	AV	0.0	52.9	54.0	-1.1	EUT flat on table.
2780.853	67.0	1.3	229.0	1.0	15.9	0.0	H-Horn	AV	0.0	52.4	54.0	-1.6	EUT flat on table.
5420.480	55.7	11.6	304.0	1.0	15.9	0.0	H-Horn	AV	0.0	51.4	54.0	-2.6	EUT Vert.
2710.113	68.8	0.9	229.0	1.0	0.0	0.0	H-Horn	PK	0.0	69.7	74.0	-4.3	EUT flat on table.
5420.320	57.9	11.6	304.0	1.0	0.0	0.0	H-Horn	PK	0.0	69.5	74.0	-4.5	EUT Vert.
2780.880	68.1	1.3	229.0	1.0	0.0	0.0	H-Horn	PK	0.0	69.4	74.0	-4.6	EUT flat on table.
2710.293	64.2	0.9	276.0	1.0	15.9	0.0	V-Horn	AV	0.0	49.2	54.0	-4.8	EUT flat on table.
5420.473	52.3	11.6	163.0	1.0	15.9	0.0	H-Horn	AV	0.0	48.0	54.0	-6.0	EUT flat on table.
3659.727	57.7	5.7	325.0	1.0	15.9	0.0	H-Horn	AV	0.0	47.5	54.0	-6.5	EUT Vert.
2780.847	61.9	1.3	314.0	1.0	15.9	0.0	V-Horn	AV	0.0	47.3	54.0	-6.7	EUT flat on table.
2780.840	61.8	1.3	145.0	1.0	15.9	0.0	H-Horn	AV	0.0	47.2	54.0	-6.8	EUT Vert.
3707.673	56.5	5.9	0.0	1.5	15.9	0.0	H-Horn	AV	0.0	46.5	54.0	-7.5	EUT Vert.
3613.593	56.8	5.5	324.0	1.0	15.9	0.0	H-Horn	AV	0.0	46.4	54.0	-7.6	EUT Vert.
2710.407	65.3	0.9	276.0	1.0	0.0	0.0	V-Horn	PK	0.0	66.2	74.0	-7.8	EUT flat on table.
5420.667	54.4	11.6	163.0	1.0	0.0	0.0	H-Horn	PK	0.0	66.0	74.0	-8.0	EUT flat on table.
3707.633	55.2	5.9	327.0	1.0	15.9	0.0	V-Horn	AV	0.0	45.2	54.0	-8.8	EUT Vert.
3659.840	59.1	5.7	325.0	1.0	0.0	0.0	H-Horn	PK	0.0	64.8	74.0	-9.2	EUT Vert.
5420.473	48.8	11.6	236.0	1.3	15.9	0.0	V-Horn	AV	0.0	44.5	54.0	-9.5	EUT Vert.
2780.800	63.0	1.3	314.0	1.0	0.0	0.0	V-Horn	PK	0.0	64.3	74.0	-9.7	EUT flat on table.
2780.933	63.0	1.3	145.0	1.0	0.0	0.0	H-Horn	PK	0.0	64.3	74.0	-9.7	EUT Vert.