

## TEST REPORT For FCC

Test Report No. : TK-FR10020

Date of Issue : 12/09/2010

FCC ID : YZEI-SCOPETX

Description of Product : Wireless Transmitter

Model No. : i-scope TX

Applicant : DONGJIN MEDICAL Co., Ltd.  
1654-1 Donghwa-ri Munmak-eup Wonju-si,  
Gangwon-do, Korea

Manufacturer : DONGJIN MEDICAL Co., Ltd.  
1654-1 Donghwa-ri Munmak-eup Wonju-si,  
Gangwon-do, Korea


Standards : FCC Part 15.247

Test Date : 11/29/2010 – 12/09/2010

Test Results :  PASS  FAIL


The test results relate only to the items tested.

Tested by:



Kyu-Chul Shin  
Test Engineer  
Date: 12/09/2010

Reviewed by:



KT Kang  
Technical Manager  
Date: 12/09/2010

## THRU-KES CO.,LTD.

477-6, Hager-Ri, Yaju-Up, Yaju-Gun Kyunggi-Do, 469-803, Korea  
Tel: +82-31-425-6200 / Fax: +82-31-424-0450

## TABLE OF CONTENTS

1.0	General Product Description .....	3
1.1	Tested Frequency .....	3
1.2	Tested Mode .....	3
1.3	Model Differences .....	4
1.4	Device Modifications .....	4
1.5	Peripheral Devices .....	4
1.6	Calibration Details of Equipment Used for Measurement .....	5
1.7	Test Facility.....	5
1.8	Laboratory Accreditations and Listings .....	5
2.0	Summary of tests .....	6
2.1	Technical Characteristic Test.....	7
2.1.1	Carrier Frequency Separation .....	7
2.1.2	Number of Hopping Frequencies .....	9
2.1.3	20 dB bandwidth .....	11
2.1.4	Time of Occupancy (Dwell Time) .....	13
2.1.5	Maximum peak Conducted Output Power.....	15
2.1.6	Band-edge.....	18
2.1.7	Field Strength of Emissions .....	23
2.1.8	AC Conducted Emissions.....	28
	APPENDIX A – Test Equipment Used For Tests .....	31

## 1.0 General Product Description

Equipment model name	:	i-scope TX
Serial number	:	Prototype
EUT condition	:	Pre-production, not damaged
Antenna type	:	chip antenna      Gain 2dBi
Frequency Range	:	2402 ~ 2480 MHz
RF output power	:	6.12 dBm Peak Conducted
Number of channels	:	38
Type of Modulation(Data Rate)	:	GFSK
Power Source	:	DC 3.7V

### 1.1 Tested Frequency

	LOW	MID	HIGH
Frequency (MHz)	2404	2444	2479

### 1.2 Tested Mode

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Tested Ch	Modulation Technology	Modulation Type
Low, Mid, High	FHSS	GFSK

### 1.3 Model Differences

Not applicable

### 1.4 Device Modifications

The following modifications were necessary for compliance:  
Not applicable

### 1.5 Peripheral Devices

Device	Manufacturer	Model No.	Serial No.	FCC ID or DoC
EUT	DONGJIN MEDICAL Co., Ltd.	i-scope TX	-	-
Notebook	F U J I T S U L T D	LIFEBOOK S-5582	434230343466	DoC

## 1.6 Calibration Details of Equipment Used for Measurement

Test equipment and test accessories are calibrated on regular basis. The maximum time between calibrations is one year or what is recommended by the manufacturer, whichever is less. All test equipment calibrations are traceable to the Korea Research Institute of Standards and Science (KRISS), therefore, all test data recorded in this report is traceable to KRISS.

## 1.7 Test Facility

The measurement facility is located at 477-6, Hager-Ri, Yaju-Up, Yaju-Gun Kyunggi-Do, 469-803, Korea. Tel: +82-31-883-5092/Fax: +82-31-883-5169. The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

## 1.8 Laboratory Accreditations and Listings

Country	Agency	Scope of Accreditation	Logo
USA	FCC	3 & 10 meter Open Area Test Sites and one conducted site to perform FCC Part 15/18 measurements.	 343818
KOREA	KCC	EMI (10 meter Open Area Test Site and two conducted sites) Radio(3 & 10 meter Open Area Test Sites and one conducted site)	 KR100
Canada	IC	3 & 10 meter Open Area Test Sites and one conducted site	 4769B-1

## 2.0 Summary of tests

FCC Part Section(s)	Parameter	Limit	Test Condition	Status (note 1)
15.247(a)	Carrier Frequency Separation	> 25 kHz	Conducted	C
15.247(a)	Number of Hopping Frequencies	> 15 hops		C
15.247(a)	20 dB Bandwidth	-		C
15.247	Dwell Time	< 0.4 seconds		C
15.247(b)	Transmitter Output Power	< 1W		C
15.247(d)	Conducted Spurious emission	> 20 dBc		C
15.247(d)	Band Edge	> 20 dBc		C
15.209	Field Strength of Harmonics	< 54 dBuV (at 3m)	Radiated	C
15.207	AC Conducted Emissions	EN 55022	Line Conducted	C

Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable

Note 2: The data in this test report are traceable to the national or international standards.

The sample was tested according to the following specification:

- FCC Part 15.247, ANSI C63.4-2003

## 2.1 Technical Characteristic Test

### 2.1.1 Carrier Frequency Separation

#### Test Location

RF Test Room

#### Test Procedures

The carrier frequency separation was measured with a spectrum analyzer connected to the antenna terminal, while EUT has its hopping function enabled.

After the trace being stable, the reading value between the peaks of the adjacent channels using the marker-delta function was recorded as the measurement results.

The spectrum analyzer is set to:

Span = 3 MHz (wide enough to capture the peaks of two adjacent channels)

RBW = 30 kHz ( $\geq$  1% of the span) Sweep = auto

VBW = 30 kHz ( $\geq$  RBW) Detector function = peak

Trace = max hold




Figure 1 : Measurement setup for the carrier frequency separation


#### Limit

The EUT shall have hopping channel carrier frequencies separated minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

#### Test Results

Frequency (MHz)	Adjacent Hopping Channel Separation (MHz)	Minimum Bandwidth (kHz)	Result
2444	2.00	25	Complies

See next pages for actual measured spectrum plots.

**Carrier Frequency Separation**

## 2.1.2 Number of Hopping Frequencies

### Test Location

RF Test Room

### Test Procedures

The number of hopping frequencies was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

The spectrum analyzer is set to:

Frequency range      1: Start = 2389.5 MHz, Stop = 2439.5 MHz  
                          2: Start = 2439.5 MHz, Stop = 2489.5 MHz

Span = 50 MHz


RBW = 300 kHz ( $\geq$  1% of the span)

VBW = 300 kHz ( $\geq$  RBW)

Trace = max hold

Sweep = auto

Detector function = peak



### Limit



The EUT in the 2400-2483.5 MHz band shall use at least 15 channels.

### Test Results

Total number of Hopping Channels	Result
38	Complies

See next pages for actual measured spectrum plots.

## Number of Hopping Frequencies



### 2.1.3 20 dB bandwidth

#### Test Location

RF Test Room

#### Test Procedures

The bandwidth at 20 dB below the highest inband spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels.

After the trace being stable, Use the marker-to peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

Span = 2 MHz (approximately 2 or 3 times of the 20 dB bandwidth)


RBW = 30 kHz ( $\geq$  1% of the span)

Sweep = auto

VBW = 30 kHz ( $\geq$  RBW)

Detector function = peak

Trace = max hold




#### Test Results

##### Data Rate : GFSK

Frequency (MHz)	Measured Bandwidth (MHz)	Result
2444	1.245	Complies

See next pages for actual measured spectrum plots.(worst case)

**20 dB Bandwidth****Data Rate : GPSK**

Date: 9.DEC.2010 15:00:17

## 2.1.4 Time of Occupancy (Dwell Time)

### Test Location

RF Test Room

### Test Procedures

The dwell time was measured with a spectrum analyzer connected to the antenna terminal, while EUT has its hopping function enabled.

The spectrum analyzer is set to:

Center frequency = the highest, middle, and the lowest channels

Span = zero


RBW = 1 MHz

Trace = max hold

VBW = 1 MHz ( $\geq$  RBW)

Detector function = peak

Sweep = as necessary to capture the entire dwell time per hopping channel




### Limit

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

### Test Results

Channel Frequency (MHz)	Test Results	
	Dwell Time (ms)	Result
2444	242.00	Complies

See next pages for actual measured spectrum plots. (Worst case)

**Time of Occupancy for PACKET Type DH 1(GFSK)**

Date: 9.DEC.2010 15:02:47

## 2.1.5 Maximum peak Conducted Output Power

### Test Location

RF Test Room

### Test Procedures

The maximum peak conducted output power was measured with a spectrum analyzer connected to the antenna terminal, while EUT has its hopping function disabled at the highest, middle and the lowest available channels.

The spectrum analyzer is set to:


Center frequency = the highest, middle, and the lowest channels

Span = 5 MHz (approximately 5 times of the 20 dB bandwidth)

RBW = 1 MHz (greater than the 20 dB bandwidth of the emission being measured)

VBW = 1 MHz ( $\geq$  RBW)      Detector function = peak

Trace = max hold      Sweep = auto



### Limit

< 1 W



### Test Results


Data Rate : GPSK

Frequency (MHz)	Peak output power(dBm)	Peak output power(mW)	Result
2404	4.23	2.648	Complies
2444	5.89	3.881	Complies
2479	6.12	4.092	Complies

See next pages for actual measured spectrum plots.

## Maximum peak Conducted Output Power - GFSK





## 2.1.6 Band-edge

### Test Location

RF Test Room

### Test Procedures

The bandwidth at 20 dB down from the highest inband spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT has its hopping function disabled at the highest, middle and the lowest available channels.

#### The spectrum analyzer is set to:

Center frequency = the highest, middle, and the lowest channels

RBW = 100 kHz


VBW = 100 kHz ( $\geq$  RBW)

Span = 100 MHz

Trace = max hold

Detector function = peak

Sweep = auto



### Limit

> 20 dBc



### Test Results


All conducted emission in any 100 kHz bandwidth outside of the spectrum band was at least 20 dB lower than the highest inband spectral density.

Therefore the applying equipment meets the requirement.


See next pages for actual measured spectrum plots.

## Band – edge - GFSK




**Band – edge (at 20 dB blow) – Low channel  
Frequency Range = 30 MHz ~ 10<sup>th</sup> harmonic**

**Band – edge (at 20 dB blow) – Mid channel**  
**Frequency Range = 30 MHz ~ 10<sup>th</sup> harmonic**



**Band – edge (at 20 dB blow) – High channel  
Frequency Range = 30 MHz ~ 10<sup>th</sup> harmonic**



## 2.1.7 Field Strength of Emissions

### Test Location

Testing was performed at a test distance of 3 meter Open Area Test Site

### Test Procedures

The height of the measuring antenna was varied between 1 to 4 m and the table was rotated a full revolution in order to obtain maximum values of the electric field intensity. The measurement was made in both the vertical and horizontal polarization, and the maximum value is presented in the report.

The spectrum analyzer is set to:


Center frequency = the worst channel

Frequency Range = 30 MHz ~ 10<sup>th</sup> harmonic

RBW = 120 kHz (30 MHz ~ 1 GHz)      VBW  $\geq$  RBW  
= 1 MHz (1 GHz ~ 10<sup>th</sup> harmonic)

Span = 100 MHz      Detector function = Quasi-peak

Trace = max hold



### Limit

#### - 15.209(a)

Frequency(MHz)	Field Strength uV/m@3m	Field Strength dBuV/m@3m
30-88	100**	40
88-216	150**	43.5
216-960	200**	46
Above 960	500	54

\*\* Except as provided in 15.209(g). fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72MHz, 76-88MHz, 174-216MHz, 470-806MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

**Test Results**

EUT	Wireless Transmitter	Measurement Detail	
Model	i-scope TX	Frequency Range	Below 1000MHz
Channel	Normal linking	Detector function	Quasi-Peak

The requirements are:

Complies

Frequency (MHz)	Measured Data (dBuV/m)	Margin (dB)	Remark
39.10	34.20	5.80	Quasi-Peak

**Test Data**

No	Emission Frequency (MHz)	Meter Reading dBuV/m	Ant. Polarity	Correction Factor dB	Cable Loss dB	Field Strength (dBuV/m)	Margin (dBuV)	Limit (dBuV/m)
1	39.10	21.4	V	10.45	2.35	34.20	5.80	40
2	214.60	18.9	V	15.91	2.69	37.53	5.97	43.5
3	258.10	19.0	V	16.51	2.93	38.48	7.52	46
4	472.90	18.3	V	17.10	4.16	39.54	6.46	46
5	711.50	13.5	H	20.86	5.43	39.79	6.21	46

## Test Results

EUT	Wireless Transmitter	Measurement Detail	
Model	i-scope TX	Frequency Range	1-25GHz
Frequency	2404MHz	Detector function	Average/Peak

The requirements are:

Complies

Frequency (MHz)	Measured Data (dBuV/m)	Margin (dB)	Remark
4808.084	43.41/47.66	10.59/26.34	Average/Peak

## Test Data

Frequency	Reading A/P	Pol.	Height	Correction			Limits/ Detector A/P	Result A/P	Margin A/P
				Factor					
[MHz]	[dBuV/m]	[m]	Antenna	Amp.Gain	Cable	[dBuV/m]	[dBuV/m]	[dB]	
4808.084	34.79/39.04	H	1	33.90	31.60	6.32	54/74	43.41/47.66	10.59/26.34

### Remark :

1. We have tested three mode (X, Y, Z).
2. Test mode is GFSK

## Restricted band edge test data

Measured frequency range : 2310-2390 MHz, 2483.5-2500 MHz

Frequency	Reading Peak	Pol.	Height	Correction			Limits/ Detector Peak	Result Peak
				Factor				
[MHz]	[dBuV/m]	[m]	Antenna	Cable	[dBuV/m]	[dBuV/m]		
2389.91	19.02	H	3.5	27.42	4.62	74	51.06	
2484.84	14.27	H	3.5	27.42	4.84	74	46.53	

## Test Results

EUT	Wireless Transmitter	Measurement Detail	
Model	i-scope TX	Frequency Range	1-25GHz
Frequency	2444MHz	Detector function	Average/Peak

The requirements are:

Complies

Frequency (MHz)	Measured Data (dBuV/m)	Margin (dB)	Remark
4887.95	41.50/46.27	12.50/27.73	Average/Peak

## Test Data

Frequency [MHz]	Reading A/P	Pol.	Height [m]	Correction			Limits/ Detector A/P	Result A/P	Margin A/P			
				Factor								
				Antenna	Amp.Gain	Cable						
4887.95	32.82/37.59	V	1.0	33.90	31.60	6.38	54/74	41.50/46.27	12.50/27.73			

### Remark :

1. We have tested three mode (X, Y, Z).
2. Test mode is GFSK

## Restricted band edge test data

Measured frequency range : 2310-2390 MHz, 2483.5-2500 MHz

Frequency [MHz]	Reading Peak	Pol.	Height [m]	Correction			Limits/ Detector Peak	Result Peak		
				Factor						
				Antenna	Cable					
2389.5	14.57	V	1.0	28.5	4.62		74	47.69		
2483.8	14.82	V	1.0	28.5	4.84		74	48.16		

## Test Results

EUT	Wireless Transmitter	Measurement Detail	
Model	i-scope TX	Frequency Range	1-25GHz
Frequency	2479MHz	Detector function	Average/Peak

The requirements are:

Complies

Frequency (MHz)	Measured Data (dBuV/m)	Margin (dB)	Remark
4957.97	38.26/40.35	7.01/24.92	Average/Peak

## Test Data

Frequency [MHz]	Reading A/P	Pol.	Height [m]	Correction			Limits/ Detector A/P	Result A/P	Margin A/P			
				Factor								
				Antenna	Amp.Gain	Cable						
4958.00	32.51/36.78	V	1	33.90	31.60	6.43	54/74	41.24/45.51	12.76/28.49			

\* No emissions were detected at a level greater than 20dB below limit

### Remark :

1. We have tested three mode (X, Y, Z).
2. Test mode is GFSK

## Restricted band edge test data

Measured frequency range : 2310-2390 MHz, 2483.5-2500 MHz

Frequency [MHz]	Reading Peak	Pol.	Height [m]	Correction			Limits/ Detector Peak	Result Peak		
				Factor						
				Antenna	Cable					
2375.34	13.62	V	1.0	28.5	4.62		74	46.74		
2483.61	16.29	V	1.0	28.5	4.84		74	49.63		

## 2.1.8 AC Conducted Emissions

### Test Location

Shielded Room

### Frequency Range of Measurement

150 kHz to 30 MHz

### Instrument Settings

IF Band Width: 9 kHz

### Test Procedures

The EUT was placed on a non-metallic table 0.8m above the metallic, grounded floor and 0.4m from the reference ground plane wall. The distance to other metallic surfaces was at least 0.8m.

Amplitude measurements were performed with a quasi-peak detector and an average detector.

### Limit

#### - 15.207(a)

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56*	56 to 46*
0.5 ~ 5	56	46
5 ~ 30	60	50

\* Decreases with the logarithm of the frequency.

### Test Results


Complies

Frequency (MHz)	Measured Data (dBuV/m)	Margin (dB)	Remark
0.195	50.993	12.828	Quasi-peak


**Test Data**

frequency	Correction		Phase Hot/ Neutral	Quasi peak			Average		
	[MHz]	LISN		Limit	Measure	Result	Limit	Measure	Result
0.198	0.051	0.100	H	63.7	49.900	50.051	53.7	38.170	38.321
0.264	0.056	0.100	H	61.3	44.040	44.196	51.3	35.390	35.546
0.396	0.050	0.100	H	57.9	41.840	41.990	47.9	38.210	38.360
2.439	0.069	0.134	H	56.0	39.470	39.673	46.0	38.000	38.203
2.769	0.075	0.112	H	56.0	39.610	39.798	46.0	38.170	38.358
3.099	0.081	0.100	H	56.0	39.300	39.481	46.0	37.880	38.061
5.403	0.126	0.137	H	60.0	40.810	41.073	50.0	38.050	38.313
5.601	0.134	0.123	H	60.0	42.200	42.457	50.0	40.040	40.297
5.799	0.142	0.111	H	60.0	42.570	42.823	50.0	40.150	40.403
0.195	0.093	0.100	N	63.8	50.800	50.993	53.8	40.470	40.663
0.393	0.061	0.100	N	58.0	38.810	38.971	48.0	35.160	35.321
0.459	0.054	0.100	N	56.7	37.850	38.004	46.7	34.730	34.884
0.525	0.050	0.100	N	56.0	39.820	39.970	46.0	38.050	38.200
2.232	0.072	0.152	N	56.0	37.780	38.004	46.0	36.530	36.754
2.691	0.077	0.117	N	56.0	37.910	38.104	46.0	36.600	36.794
5.448	0.138	0.133	N	60.0	39.570	39.841	50.0	36.560	36.831
5.646	0.146	0.120	N	60.0	38.490	38.755	50.0	36.860	37.125
5.844	0.154	0.108	N	60.0	39.010	39.272	50.0	36.150	36.412

**[HOT]**



**[NEUTRAL]**



## APPENDIX A – Test Equipment Used For Tests

No	Description	Manufacturer	Model No.	Serial No.	Due Cal.
1	Test Transmitter	Rohde & Schwarz	ESHS 10	862970/018	2011.05.06
2	Test Transmitter	Rohde & Schwarz	ESVS 10	826008/014	2011.05.06
3	Spectrum Analyzer	Hewlett Packard	8566B	2311A02394	2011.05.06
4	Spectrum Analyzer	Rohde & Schwarz	FSV30	100736	2011.12.01
5	Modulation Analyzer	Hewlett Packard	8901B	3438A05094	2011.05.06
6	Audio analyzer	Hewlett Packard	8903B	3011A12915	2011.05.06
7	Preamplifier	Hewlett Packard	8447F	2805A02570	2011.05.06
8	Preamplifier	A.H. Systems	PAM-0118	164	2011.05.06
9	Signal Generator	Hewlett Packard	8673D	2708A00448	2011.05.06
10	Power Meter	Hewlett Packard	437B	312U24787	2011.05.06
11	Power Sensor	Hewlett Packard	8482B	3318A06943	2011.05.06
12	Loop Antenna	Rohde & Schwarz	HFH2-Z2.335.4711.52	826532/006	2011.02.06
13	Dipole Antenna	Rohde & Schwarz	VHAP	574	2011.07.07
14	Dipole Antenna	Rohde & Schwarz	VHAP	575	2011.07.17
15	Dipole Antenna	Rohde & Schwarz	UHAP	545	2011.07.17
16	Dipole Antenna	Rohde & Schwarz	UHAP	546	2011.07.07
17	Biconical Antenna	Eaton Corp.	94455-1	0977	2011.07.03
18	Biconical Antenna	EMCO	3104C	9111-2468	2011.07.03
19	Log Periodic Antenna	EMCO	3146	2051	2011.06.05
20	Log Periodic Antenna	EMCO	3146	8901-2320	2011.07.03
21	Horn Antenna	A.H. Systems	SAS-571	414	2011.03.16
22	Waveform Generator	Hewlett Packard	33120A	US34001190	2011.05.06
23	Digital Oscilloscope	Tektronix	TDS 340A	B012287	2011.05.06
24	Dummy Load	Bird Electronics	8251	11511	2011.05.06

## Test Setup Photos and Configuration

### Conducted Voltage Emissions



## Radiated Electric Field Emissions

