

# Test Report # 317294 A

---

**Equipment Under Test:** JCT BT 01

---

**Test Date(s):** 8/28/17 – 10/4/17

---

**Prepared for:**  
Raffel Systems  
Attn: Edward Nowak  
N112 W14600 Mequon Rd.  
Germantown, WI 53022

---

---

**Report Issued by:** Shane Dock, EMC Engineer

Signature:



Date: 4/5/2018

---

**Report Reviewed by:** Adam Alger, Quality Systems Engineer

Signature:



Date: 11/03/2017

---

**Report Constructed by:** Shane Dock EMC Engineer

Signature:



Date: 3/13/2018

---

*This test report may not be reproduced, except in full, without written approval of Laird Technologies, Inc.*

Company: Raffel Systems	Page 1 of 28	Name: JCT BT 01
Report: 317294 A		Model: JCTBT-01
Job:C-2794		Serial: Engineering Sample

## CONTENTS

Contents.....	2
Laird Technologies Test Services in Review .....	3
1    Test Report Summary .....	4
2    Client Information.....	5
2.1    Equipment Under Test (EUT) Information .....	5
2.2    Product Description .....	5
2.3    Modifications Incorporated for Compliance.....	5
2.4    Deviations and Exclusions from Test Specifications .....	5
2.5    Additional Information.....	5
2.6    Channel Plan .....	6
3    References .....	6
4    Uncertainty Summary .....	7
5    Test Data .....	8
5.1    Antenna Port Conducted Emissions.....	8
5.2    Radiated Emissions .....	20
5.3    AC Mains Conducted Emissions .....	25
6    Revision History .....	28

Company: Raffel Systems	Page 2 of 28	Name: JCT BT 01
Report: 317294 A		Model: JCTBT-01
Job:C-2794		Serial: Engineering Sample

## Laird Technologies Test Services in Review

The Laird Technologies, Inc. laboratory located at W66 N220 Commerce Court Cedarburg, Wisconsin, 53012 USA is recognized through the following organizations:



### A2LA – American Association for Laboratory Accreditation

*Accreditation based on ISO/IEC 17025: 2005 with Electrical (EMC) Scope*

*A2LA Certificate Number: 1255.01*

*Scope of accreditation includes all test methods listed herein, unless otherwise noted.*



### Federal Communications Commission (FCC) – USA

*Accredited recognition of two 3 meter Semi-Anechoic Chambers*

*Accredited Test Firm Registration Number: 953492*



Government  
of Canada

### Innovation, Science and Economic Development Canada

*ISED Site listing of two 3 meter Semi-Anechoic Chambers based on RSS-GEN – Issue 4*

*File Number: IC 3088A-2*

*File Number: IC 3088A-3*

Company: Raffel Systems	Page 3 of 28	Name: JCT BT 01
Report: 317294 A		Model: JCTBT-01
Job:C-2794		Serial: Engineering Sample

## 1 TEST REPORT SUMMARY

During **8/28/17 – 10/4/17** the Equipment Under Test (EUT), **JCT BT 01**, as provided by **Raffel Systems** was tested to the following requirements:

Requirement	Description	Specification	Method	Result
FCC: 15.247 (a)(2) IC: RSS-247 5.2 (1)	Digital Modulation System 6 dB bandwidth	500 kHz	FCC KDB 558074	Pass
FCC: 2.1049 IC: RSS-GEN 6.6	Occupied Bandwidth	Reported	ANSI C63.10	Pass
FCC: 15.247 (b)(3) IC: RSS-247 5.4 (4)	Maximum Conducted Output Power	30 dBm	FCC KDB 558074	Pass
FCC: 15.247 (e) IC: RSS-247 5.2 (2)	Digital Modulation System Power Spectral Density	8 dBm / 3 kHz	FCC KDB 558074	Pass
FCC: 15.247 (d) IC: RSS-247 5.5	RF Spurious Emissions at the Transmitter Antenna Terminal	20 dBc	FCC KDB 558074	Pass
FCC: 15.247 (d) IC: RSS-GEN 8.10	Spurious Radiated Emissions in Restricted Bands	FCC 15.209 RSS-GEN 8.9	ANSI C63.10	Pass
FCC: 2.1055 (d) IC: RSS-GEN 6.11	Frequency Stability	Reported	ANSI C63.10	Pass
FCC: 15.207 IC: RSS-GEN 8.8	AC Power Line Conducted Emissions	0.150-30 MHz	ANSI C63.10	Pass

### Notice:

The results relate only to the item tested and described in this report. Any modifications made to the equipment under test after the specified test date(s) may invalidate the data herein.

If the resulting measurement margin is seen to be within the uncertainty value, as listed in this report, the possibility exists that this unit may not meet the required limit specification if subsequently tested.

Company: Raffel Systems	Page 4 of 28	Name: JCT BT 01
Report: 317294 A		Model: JCTBT-01
Job:C-2794		Serial: Engineering Sample

## 2 CLIENT INFORMATION

Company Name	Raffel Systems
Contact Person	Edward Nowak
Address	N112 W14600 Mequon Rd. Germantown, WI 53022

### 2.1 Equipment Under Test (EUT) Information

*The following information has been supplied by the client*

Product Name	JCT BT 01
Model Number	JCTBT-01
Serial Number	Engineering Sample
FCC/IC ID	FCC ID: YZHJCTBT01 IC: 9314A-JCTBT01

### 2.2 Product Description

System is used to communicate with integrated cup holders in furniture with multiple power motion actuators. This module interfaces with a custom App giving the end user capability to control furniture functionality either via the cupholder interface or the App. The App may also provide additional functionality not present on the cup controls (for instance home position, memory functionality, massage, etc).

### 2.3 Modifications Incorporated for Compliance

None noted at time of test

### 2.4 Deviations and Exclusions from Test Specifications

None noted at time of test

### 2.5 Additional Information

EUT emissions peaked out in all orientations. Unit tested with USB port Occupied and with an output power of -18 as the set. Unit programmed via buttons on cupholder. Unit connected to sample motor.

Company: Raffel Systems	Page 5 of 28	Name: JCT BT 01
Report: 317294 A		Model: JCTBT-01
Job:C-2794		Serial: Engineering Sample

## 2.6 Channel Plan

EUT emissions tested for Low Mid and High Channel.

Low – 2402 MHz

Mid – 2440 MHz

High – 2480 MHz

## 3 REFERENCES

Publication	Edition	Date
CFR 47 Part 15	-	2017
ANSI C63.10	-	2013
KDB 558074	V4	2017
RSS-247	2	2017
RSS GEN	4	2014

Company: Raffel Systems	Page 6 of 28	Name: JCT BT 01
Report: 317294 A		Model: JCTBT-01
Job:C-2794		Serial: Engineering Sample

## 4 UNCERTAINTY SUMMARY

Using the guidance of the following publications the calculated measurement uncertainty represents an expanded uncertainty expressed at approximately the 95 % confidence level, using a coverage factor of  $k = 2$ .

References	Version / Date
CISPR 16-4-1	Ed. 2 (2009-02)
CISPR 16-4-2	Ed. 2 (2011-06)
CISPR 32	Ed. 1 (2012-01)
ANSI C63.23	2012
A2LA P103	February 4, 2016
A2LA P103c	August 10, 2015
ETSI TR 100-028	V1.3.1 (2001-03)

Measurement Type	Configuration	Uncertainty $\pm$
Radiated Emissions	Biconical Antenna	5.0 dB
Radiated Emissions	Log Periodic Antenna	5.3 dB
Radiated Emissions	Horn Antenna	4.7 dB
AC Line Conducted Emissions	Artificial Mains Network	3.4 dB
Telecom Conducted Emissions	Asymmetric Artificial Network	4.9 dB
Disturbance Power Emissions	Absorbing Clamp	4.1 dB
Radiated Immunity	3 Volts/meter	2.2 dB
Conducted Immunity	CDN/EM/BCI	2.4/3.5/3.4 dB
EFT Burst/Surge	Peak pulse voltage	164 volts
ESD Immunity	15 kV level	1377 Volts

Parameter	ETSI U.C. $\pm$	U.C. $\pm$
Radio Frequency, from F0	$1 \times 10^{-7}$	$0.55 \times 10^{-7}$
Occupied Channel Bandwidth	5 %	2 %
RF conducted Power (Power Meter)	1.5 dB	1.2 dB
RF conducted emissions (Spectrum Analyzer)	3.0 dB	1.7 dB
All emissions, radiated	6.0 dB	5.3 dB
Temperature	1 °C	0.65 °C
Humidity	5 %	2.9 %
Supply voltages	3 %	1 %


Company: Raffel Systems	Page 7 of 28	Name: JCT BT 01
Report: 317294 A		Model: JCTBT-01
Job:C-2794		Serial: Engineering Sample

## 5 TEST DATA

### 5.1 Antenna Port Conducted Emissions

<b>Description of Measurement</b>	<p>The direct measurement of emissions at the antenna port of the EUT is achieved by use of a RF connection to a spectrum analyzer or power meter.</p> <p>The cable and attenuator factors are loaded into the analyzer or power meter allowing for direct measurement readings without the need for further corrections.</p>
<b>Example Calculations</b>	<p>Measurement (dBm) + Cable factor (dB) + External Attenuator (dB) = Corrected Reading (dBm)</p> <p>Margin (dB) = Limit (dBm) – Corrected Reading (dBm)</p>

#### Block Diagram



Company: Raffel Systems		Name: JCT BT 01
Report: 317294 A	Page 8 of 28	Model: JCTBT-01
Job:C-2794		Serial: Engineering Sample

### 5.1.1 Antenna Port Conducted Emissions – Bandwidth

<b>Operator</b>	Shane Dock
<b>Test Date</b>	9/20/17
<b>Location</b>	Conducted RF Measurement Area
<b>Temp. / R.H.</b>	70 degrees Fahrenheit / 53% RH
<b>Requirement</b>	OBW: FCC: 2.1049 IC: RSS-GEN 6.6 DTS BW: FCC: 15.247 (a)(2) IC: RSS-247 5.2 (1)
<b>Method</b>	ANSI C63.10 Section 6.9.2 FCC KDB 558074 D01 DTS Meas Guidance V04, Section 8

#### Limits:

**6 dB BW (MHz)**

> 500

#### Test Parameters

<b>Frequency</b>	2402, 2440, 2480 MHz
------------------	----------------------

#### Tables

Channel	Low	Mid	High
6dB BW (kHz)	708.6	714.9	704.8
99% BW (kHz)	1060.7	1060.7	1059.8

#### Instrumentation



Smart Technology. Delivered.


Date : 29-Aug-2017 Test : Conducted RF Testing Job : C-2794

PE : Shane Dock Customer : Raffel Systems Quote : 317294


No.	Asset	Description	Manufacturer	Model	Serial	Cal Date	Cal Due Date	Equipment Status
1	EE 960087	44GHz EXA Spectrum Analyzer	Agilent	N9010A	MY53400296	12/22/2016	12/22/2017	Active Calibration
2	AA 960143	Phaseflex	Gore	EKD01D01048.0	5546519	6/26/2015	6/25/2017	Active Calibration

Company: Raffel Systems	Page 9 of 28	Name: JCT BT 01
Report: 317294 A		Model: JCTBT-01
Job:C-2794		Serial: Engineering Sample


## Plots



99% BW Low



99% BW Mid



99% BW High

### 5.1.2 Antenna Port Conducted Emissions – Maximum Conducted Output Power

<b>Operator</b>	Shane Dock
<b>Test Date</b>	9/20/17
<b>Location</b>	Conducted RF Measurement Area
<b>Temp. / R.H.</b>	70 degrees Fahrenheit / 53% RH
<b>Requirement</b>	15.247 (b) (3)
<b>Method</b>	FCC KDB 558074 D01 DTS Meas Guidance V04, section 9.1.1

#### Limits:

Maximum Conducted Output Power (watts)	Maximum Conducted Output Power (dBm)
1	30

#### Test Parameters

<b>Frequency</b>	2402, 2440, 2480 MHz
<b>RBW</b>	3 MHz



#### Table

Channel	Low	Mid	High
Pout Conducted (dBm)	-19.725	-19.771	-19.898


**Worst Case Margin = 30.000 dBm – (-19.725 dBm) = 49.725 dB**

Company: Raffel Systems	Page 11 of 28	Name: JCT BT 01
Report: 317294 A		Model: JCTBT-01
Job:C-2794		Serial: Engineering Sample

## Plots



Low Channel Pout



High Channel Pout

Mid Channel Pout

Company: Raffel Systems	
Report: 317294 A	
Job:C-2794	

Name: JCT BT 01
Model: JCTBT-01
Serial: Engineering Sample

### 5.1.3 Antenna Port Conducted Emissions – RF Spurious Emissions

<b>Operator</b>	Shane Dock
<b>Test Date</b>	9/20/17
<b>Location</b>	Conducted RF Measurement Area
<b>Temp. / R.H.</b>	70 degrees Fahrenheit / 53% RH
<b>Requirement</b>	15.247 ( d )
<b>Method</b>	FCC KDB 558074 D01 DTS Meas Guidance V04, section 11

#### Limits:

##### RF Spurious Limit

20 dBc


#### Test Parameters

<b>Frequency</b>	30-25000 MHz
<b>Settings</b>	2402, 2440, 2480 MHz Channels
<b>RBW</b>	100k
<b>VBW</b>	300k
<b>Trace</b>	Max Hold
<b>Detector</b>	Peak
<b>Note</b>	All emissions are >10 dB below the limit.

Company: Raffel Systems	Page 13 of 28	Name: JCT BT 01
Report: 317294 A		Model: JCTBT-01
Job:C-2794		Serial: Engineering Sample


## Plots

### Reference Levels (Worst-Case Shown)




Low Channel

Mid Channel




High Channels


Company: Raffel Systems	Page 14 of 28	Name: JCT BT 01
Report: 317294 A		Model: JCTBT-01
Job:C-2794		Serial: Engineering Sample




30-1000 MHz (Low)




1000-10000 MHz (Low)




30-1000 MHz (Mid)



1000-10000 MHz (Mid)




30-1000 MHz (High)




1000-10000 MHz (High)

Company: Raffel Systems	
Report: 317294 A	
Job:C-2794	

Name: JCT BT 01
Model: JCTBT-01
Serial: Engineering Sample



10000-25000 MHz (Low)



10000-25000 MHz (Mid)

Lower Band Edge



10000-25000 MHz (High)

Upper Band Edge

Company: Raffel Systems	Page 16 of 28	Name: JCT BT 01
Report: 317294 A		Model: JCTBT-01
Job:C-2794		Serial: Engineering Sample

### 5.1.4 Antenna Port Conducted Emissions – Power Spectral Density

<b>Operator</b>	Shane Dock
<b>Test Date</b>	9/20/17
<b>Location</b>	Conducted RF Measurement Area
<b>Temp. / R.H.</b>	70 degrees Fahrenheit / 53% RH
<b>Requirement</b>	15.247 ( e )
<b>Method</b>	FCC KDB 558074 D01 DTS Meas Guidance V04, Section 10.2

#### Limits:

##### PSD (dBm/3 kHz)

< 8

#### Test Parameters

<b>Frequency</b>	2402, 2440, 2480 MHz
<b>RBW</b>	100kHz
<b>VBW</b>	300kHz
<b>Trace</b>	Max Hold
<b>Detector</b>	Peak

#### Table

Channel	Low	Mid	High
PSD (dBm)	-20.385	-20.515	-20.627

Worst Case Margin = 8.000 dBm – (-20.385 dBm) = 28.385 dB

Company: Raffel Systems	Page 17 of 28	Name: JCT BT 01
Report: 317294 A		Model: JCTBT-01
Job:C-2794		Serial: Engineering Sample

## Plots



Company: Raffel Systems	Page 18 of 28	Name: JCT BT 01
Report: 317294 A		Model: JCTBT-01
Job:C-2794		Serial: Engineering Sample

### 5.1.5 Antenna Port Conducted Emissions – Frequency Stability

<b>Operator</b>	Shane Dock
<b>Test Date</b>	10/4/17
<b>Location</b>	Conducted measurement area
<b>Temp. / R.H.</b>	71 degrees Fahrenheit / 56% RH
<b>Requirement</b>	FCC: 2.1055 (d) IC: RSS-GEN 6.11
<b>Method</b>	ANSI C63.10 Section 6.8

#### Test Parameters

<b>Frequency</b>	2402, 2440, 2480 MHz
<b>Channels</b>	Low, Mid, High
<b>Frequencies (Nominal)</b>	2402, 2440, 2480 Mhz
<b>Voltages</b>	102, 120, and 138 VAC (60 Hz)

**Table (Values below listed in Hz at the given voltages)**


Channel	102 VAC	120 VAC	138 VAC	Deviation (Hz)
Low	2402070400	2402070400	2402070400	0
Mid	2440071100	2440071200	2440071200	100
High	2480072500	2480072500	2480072500	0

Company: Raffel Systems	Page 19 of 28	Name: JCT BT 01
Report: 317294 A		Model: JCTBT-01
Job:C-2794		Serial: Engineering Sample

## 5.2 Radiated Emissions

<b>Description of Measurement</b>	<p>The frequency spectrum is investigated for intentional and / or unintentional signals emanating from the EUT by use of a standardized test site and measurement antenna.</p> <p>The antenna, cable, pre-amp, and other necessary measurement system correction factors are loaded onto the EMI receiver / spectrum analyzer when the measurements are performed allowing the data to be gathered and reported as corrected values.</p> <p>The maximum emissions from the EUT are determined by turn-table azimuth rotation (360°) and scanning of the measurement antenna. Maximized levels are noted at degree values of azimuth, measurement antenna height, and measurement antenna polarity.</p>
<b>Example Calculations</b>	<p>Measurement (dB<math>\mu</math>V) + Cable factor (dB) + Other (dB) + Antenna Factor (dB/m) = Corrected Reading (dB<math>\mu</math>V/m)</p> <p>Margin (dB) = Limit (dB<math>\mu</math>V/m) - Corrected Reading (dB<math>\mu</math>V/m)</p> <p>Example at 4000 MHz:</p> <p>Reading = 40 dB<math>\mu</math>V + 3.4 dB + 0.9 dB + 6.5 dB/m = 50.8 dB<math>\mu</math>V/m</p> <p>Average Limit = <math>20 \log (500) = 54</math> dB<math>\mu</math>V/m</p> <p>Margin = 54 dB<math>\mu</math>V/m - 50.8 dB<math>\mu</math>V/m = 3.2 dB</p>

### Block Diagram



Company: Raffel Systems		Name: JCT BT 01
Report: 317294 A	Page 20 of 28	Model: JCTBT-01
Job:C-2794		Serial: Engineering Sample

### 5.2.1 Radiated Emissions

<b>Operator</b>	Shane Dock
<b>Test Date</b>	8/28/17 – 9/14/17
<b>Location</b>	Chamber 5, Chamber 3
<b>Temp. / R.H.</b>	69 degrees Fahrenheit / 55% RH
<b>Requirement</b>	FCC: 15.247 (d) IC: RSS-GEN 8.10
<b>Method</b>	ANSI C63.10 Sections 6.5 and 6.6

#### Limits:

	30-88 MHz	88-216 MHz	216 – 960 MHz	960+ MHz
Field Strength (μV/m)	100	150	200	500
Field Strength (dBμV/m)	40.0	43.5	46.0	54.0

#### Test Parameters

<b>Frequency</b>	30-25000
<b>Distance</b>	3M
<b>Settings</b>	Unit tested at Low, Mid, High Channels
<b>Settings</b>	RBW = 120kHz, VBW 1.2 MHz (<1 GHz) RBW = 1 MHz, VBW = 3 MHZ (>1 GHz)
<b>Notes</b>	Measurements taken in restricted bands. For measurements above 1 GHz, antenna used with a tilt gear to keep EUT within the cone of radiation. Absorbers were also added to the floor of the chamber while measuring emissions above 1 GHz. Emissions under 1 GHz are not a function of Tx Mode.  Unit tested with customer-provided ferrite.
<b>Example Calculation</b>	Limit (dBμV) = $20 * \log[\text{Limit } (\mu\text{V})]$ 40 = $20 * \log (100)$ Raw Data + Antenna Factor + Cable Factor = Reported Data 19.77 dBμV + 12.50 dB/m + 0.93 dB = 38.80 dBμV/m

Company: Raffel Systems	Page 21 of 28	Name: JCT BT 01
Report: 317294 A		Model: JCTBT-01
Job:C-2794		Serial: Engineering Sample

## Instrumentation



Date : 29-Aug-2017 Test : Spurious Emissions Job : C-2794  
 PE: Shane Dock Customer : Raffel Systems Quote : 317294

No.	Asset	Description	Manufacturer	Model	Serial	Cal Date	Cal Due Date	Equipment Status
1	AA 960158	Double Ridge Horn Antenna	ETS Lindgren	3117	109300	4/12/2017	4/12/2018	Active Calibration
2	EE 960159	Low Noise Amplifier	Mini-Circuits	ZVA-213X-S+	462101702	4/12/2017	4/12/2018	Active Calibration
3	AA 960171	Cable - low loss 6m	A.H. Systems, Inc	SAC-26G-6	386	3/31/2016	11/21/2017	Active Verification
4	EE 960085	EMI Receiver	Agilent	N9038A	MY51210148	5/12/2017	5/12/2018	Active Calibration
5	AA 960174	Small Horn Antenna	ETS Lindgren	3116C-PA	00206880	5/1/2017	5/1/2018	Active Calibration
6	AA 960128	Biconical Antenna	ETS Lindgren	3110B	00062899	4/13/2017	4/13/2018	Active Calibration
7	AA 960078	Log Periodic Antenna	EMCO	93146	9701-4855	4/17/2017	4/17/2018	Active Calibration
8	AA 960153	High Pass Filter 2.4 GHz	KWM	HPF-L-14186	7272-04	5/2/2017	5/2/2018	Active Calibration

**Table**

Frequency (MHz)	Channel	EUT orientation	Antenna Polarity	Height (cm)	Azimuth (degree)	Peak Reading (dB $\mu$ V/m)	Peak Limit (dB $\mu$ V/m)	Peak Margin (dB)	Avg Reading (dB $\mu$ V/m)	Avg Limit (dB $\mu$ V/m)	Avg Margin (dB)
4960.00	High	Flat	Horiz	181.42	188.00	52.3	74.0	21.7	47.7	54.0	6.3
4880.00	Mid	Flat	Horiz	184.85	186.75	50.8	74.0	23.2	46.4	54.0	7.6
4804.00	Low	Flat	Horiz	174.61	149.75	50.5	74.0	23.5	45.6	54.0	8.4

Frequency (MHz)	Channel	EUT orientation	Antenna Polarity	Height (cm)	Azimuth (degree)	Peak Reading (dB $\mu$ V/m)	Peak Limit (dB $\mu$ V/m)	Peak Margin (dB)
2385.09	Low	Horiz	Vert	203.00	96.50	47.4	74.0	26.6
2483.61	High	Horiz	Vert	203.00	96.50	48.9	74.0	25.1

Frequency (MHz)	Channel	EUT orientation	Antenna Polarity	Height (cm)	Azimuth (degree)	Avg Reading (dB $\mu$ V/m)	Avg Limit (dB $\mu$ V/m)	Avg Margin (dB)
2376.77	Low	Horiz	Vert	203.00	96.50	34.9	54.0	19.1
2485.52	High	Horiz	Vert	203.00	96.50	35.0	54.0	19.0

Company: Raffel Systems	Page 22 of 28	Name: JCT BT 01
Report: 317294 A		Model: JCTBT-01
Job:C-2794		Serial: Engineering Sample


## Plots (Worst-Case Shown)




30 – 200 MHz




200 – 1000 MHz




1 – 2.31 GHz



Lower Band Edge (Average)




Lower Band Edge (Peak)




Upper Band Edge (Average)

Company: Raffel Systems	
Report: 317294 A	
Job:C-2794	


Name: JCT BT 01
Model: JCTBT-01
Serial: Engineering Sample




Upper Band Edge (Peak)



2.5 – 4 GHz



4 – 18 GHz



18 – 25 GHz

### 5.3 AC Mains Conducted Emissions

A line impedance stabilization network (LISN) or artificial mains network (AMN) allows the emissions of the power supply conductors to be measured while isolating the EUT from the supply mains.

#### Description of Measurement

The AMN, cable, and other necessary measurement system correction factors are loaded onto the EMI receiver when the measurements are performed. The data is gathered and reported as the corrected values.


Maximum emissions are determined with a peak max hold trace then measurements at a selection of the highest points are made with quasi-peak and average detectors. Results are recorded and compared to limit for each line. (e.g. line and neutral)

#### Example Calculations

Measurement (dB $\mu$ V) + Cable factor (dB) + Other (dB) = Corrected Reading (dB $\mu$ V)

Margin (dB) = Limit (dB $\mu$ V) - Corrected Reading (dB $\mu$ V)

#### Block Diagram



Company: Raffel Systems	Page 25 of 28	Name: JCT BT 01
Report: 317294 A		Model: JCTBT-01
Job:C-2794		Serial: Engineering Sample

### 5.3.1 AC Mains Conducted Emissions

<b>Operator</b>	Jon Dilley
<b>QA</b>	Adam Alger
<b>Test Date</b>	9/15/17
<b>Location</b>	EMC Lab
<b>Temp. / R.H.</b>	70 degrees F / 60% RH
<b>Requirement</b>	FCC: 15.207 IC: RSS-GEN 8.8
<b>Method</b>	ANSI C63.10 Section 6.2

#### Limits:

Frequency of Emission (MHz)	Quasi-Peak Limit (dBuV)	Average Limit (dBuV)
0.15 - 0.50	66 to 56	56 to 46
0.5 - 5	56	46
5-30	60	50

#### Test Parameters

<b>Frequency</b>	0.15 – 30 MHz
<b>Settings</b>	RBW 9 kHz
<b>Settings</b>	VBW 90 kHz
<b>EUT Power</b>	120V 60 Hz

#### Instrumentation



Smart Technology. Delivered.

Date : 29-Aug-2017	Test : Conducted Emissions	Job : C-2794						
PE: Shane Dock	Customer: Raffel Systems	Quote : 317294						
No.	Asset	Description	Manufacturer	Model	Serial	Cal Date	Cal Due Date	Equipment Status
1	EE 960088	EMI Receiver	Agilent	N9038A	MY51210138	3/2/2017	3/2/2018	Active Calibration
2	EE 960162	LISN	COM-POWER	LI-215A	191969	8/28/2017	8/28/2018	Active Calibration

Tested By: 

Quality Assurance: 

Company: Raffel Systems	Page 26 of 28	Name: JCT BT 01
Report: 317294 A		Model: JCTBT-01
Job: C-2794		Serial: Engineering Sample

**Table**

Mode	Line	Frequency (MHz)	Q-Peak Reading (dB $\mu$ V)	Q-Peak Limit (dB $\mu$ V)	Quasi-Peak Margin (dB)	Average Reading (dB $\mu$ V)	Average Limit (dB $\mu$ V)	Average Margin (dB)
Tx	L1	0.438	41.8	57.1	15.3	24.3	47.1	22.8
Tx	L1	0.726	41.7	56.0	14.3	24.4	46.0	21.6
Tx	L1	29.955	41.8	60.0	18.2	24.3	50.0	25.7
Tx	L2	0.429	42.4	57.3	14.8	24.7	47.3	22.6
Tx	L2	0.739	42.4	56.0	13.6	24.7	46.0	21.3
Tx	L2	29.618	42.4	60.0	17.6	24.7	50.0	25.3

**Plots**


## 6 REVISION HISTORY

Version	Date	Notes	Person
V0	10/16/17	First Draft	Shane Dock
V1	10/26/17	Updated Draft	Shane Dock
V2	3/13/18	Final Draft	Shane Dock
V3	3/28/18	Updated Draft	Shane Dock
V4	4/5/18	Instrumentation Correction	Shane Dock

**END OF REPORT**

Company: Raffel Systems	Page 28 of 28	Name: JCT BT 01
Report: 317294 A		Model: JCTBT-01
Job:C-2794		Serial: Engineering Sample