

ELECTROMAGNETIC EMISSION COMPLIANCE REPORT FOR LOW-POWER, NON-LICENSED TRANSMITTER

Test Report No. : OT-18N-RWD-041
AGR No. : A188A-213
Applicant : LG Innotek Co., Ltd.
Address : 26, Hanamsandan 5beon-ro Gwangsan-gu, 506-731, Gwangju, South Korea
Manufacturer : LG Innotek Co., Ltd.
Address : 26, Hanamsandan 5beon-ro Gwangsan-gu, 506-731, Gwangju, South Korea
Type of Equipment : Electronic Shelf Label
FCC ID. : YZP-REBETZ37E
Model Name : REBE-TZ37E
Multiple Model Name : REBE-TZ37F
Serial number : N/A
Total page of Report : 7 pages (including this page)
Date of Incoming : November 20, 2018
Date of issue : November 27, 2018


SUMMARY

The equipment complies with the regulation; **FCC PART 15 SUBPART C Section 15.247**

This test report only contains the result of a single test of the sample supplied for the examination.

It is not a generally valid assessment of the features of the respective products of the mass-production.

Reviewed by:

Ki-Hong, Nam / Chief Engineer
ONETECH Corp.

Approved by:


Keun-Young, Choi / Vice President
ONETECH Corp.

CONTENTS

	PAGE
1. VERIFICATION OF COMPLIANCE	4
2. GENERAL INFORMATION	5
2.1 PRODUCT DESCRIPTION.....	5
2.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT.....	5
3. EUT MODIFICATIONS.....	5
4. MAXIMUM PERMISSIBLE EXPOSURE.....	6
4.1 RF EXPOSURE CALCULATION	6
4.2 EUT DESCRIPTION.....	6
4.3 CALCULATED MPE SAFE DISTANCE.....	7

Revision History

Rev. No.	Issue Report No.	Issued Date	Revisions	Section Affected
0	OT-18N-RWD-041	2018.11.27	Initial Release	All

1. VERIFICATION OF COMPLIANCE

Applicant : LG Innotek Co., Ltd.
Address : 26, Hanamsandan 5beon-ro Gwangsan-gu, 506-731, Gwangju, South Korea
Contact Person : Jeong, Inchang / Director
Telephone No. : +86-62-950-0332
FCC ID : YZP-REBETZ37E
Model Name : REBE-TZ37E
Serial Number : N/A
Date : November 27, 2018

EQUIPMENT CLASS	DTS – DIGITAL TRANSMISSION SYSTEM
E.U.T. DESCRIPTION	Electronic Shelf Label
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.10: 2013
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT	Certification
AUTHORIZATION REQUESTED	
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 SUBPART C Section 15.247
Modifications on the Equipment to Achieve Compliance	None
Final Test was Conducted On	3 m, Semi Anechoic Chamber

- The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

2. GENERAL INFORMATION

2.1 Product Description

The LG Innotek Co., Ltd., Model REBE-TZ37E (referred to as the EUT in this report) is a Electronic Shelf Label. The product specification described herein was obtained from product data sheet or user's manual.

Device Type	Electronic Shelf Label
Temperature Range	+10 °C ~ +30 °C
Operating Frequency	2 405 MHz ~ 2 480 MHz
RF Output Power	7.53 dBm
Number of Channel	16 Channel
Modulation Type	O-QPSK
Antenna Type	PCB Antenna
Antenna Gain	Antenna 0: 0.79 dBi
	Antenna 1: -0.54 dBi
List of each Osc. or crystal Freq.(Freq. >= 1 MHz)	32 MHz, 32.768 kHz
RATED SUPPLY VOLTAGE	DC 3.0 V

2.2 Alternative type(s)/model(s); also covered by this test report.

- The following lists consist of the added model and their differences.

Model Name	Differences	Tested
REBE-TZ37E	Basic Model.	<input checked="" type="checkbox"/>
REBE-TZ37F	These models are identical to basic model except for the Back cover hook.	<input type="checkbox"/>

Note: 1. Applicant consigns only basic model to test. Therefore this test report just guarantees the units, which have been tested.

2. The Applicant/manufacturer is responsible for the compliance of all variants.

3. EUT MODIFICATIONS

- None

4. MAXIMUM PERMISSIBLE EXPOSURE

4.1 RF Exposure Calculation

According to the FCC rule 1.1310 table 1B, the limit for the maximum permissible RF exposure for an uncontrolled environment are $f/1500$ mW/cm 2 for the frequency range between 300 MHz and 1 500 MHz and 1.0 mW/cm 2 for the frequency range between 1 500 MHz and 100 000 MHz.

The electric field generated for a 1 mW/cm 2 exposure is calculated as follows:

$$E = \sqrt{(30 * P * G) / d}, \text{ and } S = E^2 / Z = E^2 / 377, \text{ because } 1 \text{ mW/cm}^2 = 10 \text{ W/m}^2$$

Where

S = Power density in mW/cm 2 , Z = Impedance of free space, 377 Ω

E = Electric field strength in V/m, G = Numeric antenna gain, and d = distance in meter

Combining equations and rearranging the terms to express the distance as a function of the remaining variable

$$d = \sqrt{(30 * P * G) / (377 * 10 S)}$$

Changing to units of mW and cm, using P (mW) = P (W) / 1 000, d (cm) = 0.01 * d (m)

$$d = 0.282 * \sqrt{(P * G) / S}$$

Where

d = distance in cm, P = Power in mW, G = Numeric antenna gain, and S = Power density in mW/cm 2

4.2 EUT Description

Kind of EUT	Electronic Shelf Label
Operating Frequency Band	<input type="checkbox"/> Wireless Microphone: 494.000 MHz ~ 501.000 MHz <input type="checkbox"/> and 498.200 MHz ~ 505.200 MHz <input type="checkbox"/> WLAN: 2 412 MHz ~ 2 462 MHz <input type="checkbox"/> WLAN: 5 180 MHz ~ 5 320 MHz / 5 500 MHz ~ 5 700 MHz <input type="checkbox"/> WLAN: 5 745 MHz ~ 5 825 MHz <input type="checkbox"/> Bluetooth: 2 402 MHz ~ 2 480 MHz <input checked="" type="checkbox"/> Zigbee: 2 405 MHz ~ 2 480 MHz
Device Category	<input type="checkbox"/> Portable (< 20 cm separation) <input type="checkbox"/> Mobile (> 20 cm separation) <input checked="" type="checkbox"/> Others
Max. Output Power	7.53 dBm
Used Antenna	PCB Antenna
Used Antenna Gain	Antenna 0: 0.79 dBi
	Antenna 1: -0.54 dBi
Exposure Evaluation Applied	<input checked="" type="checkbox"/> MPE <input type="checkbox"/> SAR <input type="checkbox"/> N/A

4.3 Calculated MPE Safe Distance

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance	Max tune up power		Antenna Gain		Safe Distance (cm)	Power Density (mW/cm²) @ 20 cm Separation	Limit (mW/cm²)
			(dBm)	(dBm)	(mW)	Log			
2 405 ~ 2 480	Zigbee	7.50 ± 0.5	8.00	6.31	0.79	1.20	0.78	0.001 5	1.00

According to above table, for 2 405 MHz ~ 2 480 MHz Band, safe distance,

$$D = 0.282 * \sqrt{(6.31 * 1.20) / 1.00} = 0.78 \text{ cm}$$

For getting power density at 20 cm separation in above table, following formula was used.

$$S = P * G / (4\pi * R^2) = 6.31 * 0.79 / (4 * 3.14 * 20^2) = 0.001 5$$

Where:

S = Power Density,

P = Power input to the external antenna (Output power from the EUT antenna port (dBm) – cable loss (dB)),

G = Gain of Transmit Antenna (linear gain), R = Distance from Transmitting Antenna



Tested by: Hyung-Kwon, Oh / Assistant Manager