

TEST REPORT

of

FCC CFR 47 part 1, 1.1307(b), 1.1310

FCC ID: YZP-RNTDST01A

Equipment Under Test : IP Camera
Model Name : RNTD-ST01A
Applicant : LG INNOTEK CO., LTD.
Manufacturer : LG INNOTEK CO., LTD.
Date of Test(s) : 2016.03.18 ~ 2016.04.29
Date of Issue : 2016.05.12

In the configuration tested, the EUT complied with the standards specified above.

Tested By:

Date:

2016.05.12



Youngmin Park

Approved By:

Date:

2016.05.12



Hyunchae You

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

INDEX

<u>Table of Contents</u>	Page
1. General Information -----	3
2. RF Exposure Evaluation -----	4

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

1. General Information

1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

-Wireless Div. 2FL, 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 435-837

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx>.

Telephone : + 82 31 688 0901

FAX : + 82 31 688 0921

1.2. Details of applicant

Applicant : LG INNOTEK CO., LTD.

Address : 26, Hanamsandan 5beon-ro, Gwangsan-gu, Gwangju, 62229, Korea

Contact Person : Jeong, In-Chang

Phone No. : +82 10 2326 9972

1.3. Description of EUT

Kind of Product		IP Camera
Model Name		RNTD-ST01A
Power Supply		DC 5 V
Frequency Range		2 412 MHz ~ 2 462 MHz (11b/g/n_HT20)
Modulation Technique		DSSS, OFDM
Number of Channels		11 channels (11b/g/n_HT20)
Antenna Type		PCB Antenna (MIMO)
Antenna Gain	Port#1	1.81 dB i
	Port#2	1.76 dB i

1.4. Declaration by the manufacturer

- The device supports 11b mode with single transmission at only Antenna 1 port and 11g,11n_HT20 mode with multi transmission at the same time.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

1.5. Test report revision

Revision	Report number	Date of Issue	Description
0	F690501/RF-RTL009779	2016.05.02	Initial
1	F690501/RF-RTL009779-1	2016.05.12	Added correlated gain for calculation

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

2. RF Exposure Evaluation

2.1. Environmental evaluation and exposure limit according to FCC CFR 47 part 1, 1.1307(b), 1.1310

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength(V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time
(A) Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	*100	6
3.0 – 30	1842/f	4.89/f	*900/f ²	6
30 - 300	61.4	0.163	1.0	6
300 – 1 500	-	-	f/300	6
1 500 – 100 000	-	-	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3 – 1.34	614	1.63	*100	30
1.34 – 30	824/f	2.19/f	*180/f ²	30
30 - 300	27.5	0.073	0.2	30
300 – 1 500	-	-	f/1500	30
<u>1 500 – 100 000</u>	-	-	<u>1.0</u>	<u>30</u>

2.1.1. Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where P_d = power density in mW/cm^2

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

$\pi = 3.1416$

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, 1 mW/cm^2 . If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

2.1.2. Test Result of RF Exposure Evaluation

Test Item : RF Exposure Evaluation Data

2.1.3. Output Power into Antenna & RF Exposure Evaluation Distance

WLAN (2.4G)

- Maximum tune up tolerance

Channel	Channel Frequency (MHz)	Output Average Power to Antenna (dB m)	Antenna Gain (dB i)	Duty Cycle (%)	Power Density at 20 cm (mW/cm ²)	Limits (mW/cm ²)
1	2 412	18.5	4.80	100	0.042 533	1

Note :

1. The power density Pd (5th column) at a distance of 20 cm calculated from the friis transmission formula is far below the limit of 1 mW/cm².
2. The worst case was only reported in each operating mode.
3. Unequal antenna gains, with equal transmit powers. For antenna gains given by G₁, G₂, ..., G_N dB i
(i) If transmit signals are correlated, then
Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/N_{ANT}]$ dB i [Note the "20"s in the denominator of each exponent and the square of the sum of terms; the object is to combine the signal levels coherently.]

Directional Gain = 4.80 dB i

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.