



FCC PART 22H, PART 24E TEST REPORT

For

Enet Times Technology Co., Ltd.

Unit24F, Block C, World Trade Plaza, Fuhong Road, Shenzhen, Guangdong, China

FCC ID: YZQDG600

Report Type:
Original Report

Test Engineer:

Report Number:

Report Date:

Reviewed By:

Test Laboratory:

Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP*, or any agency of the Federal Government.

* This report contains data that are not covered by the NVLAP accreditation and are marked with an asterisk "*\pm" (Rev.2)

Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	
Objective	
RELATED SUBMITTAL(S)/GRANT(S)	
TEST METHODOLOGY TEST FACILITY	
SYSTEM TEST CONFIGURATION	
DESCRIPTION OF TEST CONFIGURATION	
EQUIPMENT MODIFICATIONS	
CONFIGURATION OF TEST SETUPBLOCK DIAGRAM OF TEST SETUP	
SUMMARY OF TEST RESULTS	
FCC §1.1307 & §2.1093 - RF EXPOSURE	
APPLICABLE STANDARD	
TEST RESULT	
FCC §2.1047 - MODULATION CHARACTERISTIC	9
FCC §2.1046, §22.913 (A) & §24.232 (C) - RF OUTPUT POWER	10
APPLICABLE STANDARD	
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS	
Test Data	
FCC §2.1049, §22.917, §22.905 & §24.238 - OCCUPIED BANDWIDTH	13
APPLICABLE STANDARD	13
Test Procedure	13
TEST EQUIPMENT LIST AND DETAILS.	
TEST DATA	13
FCC §2.1051, §22.917(A) & §24.238(A) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS	17
APPLICABLE STANDARD	17
Test Procedure	
TEST EQUIPMENT LIST AND DETAILS	
TEST DATA	
FCC §2.1053, §22.917 & §24.238 - SPURIOUS RADIATED EMISSIONS	21
APPLICABLE STANDARD	21
TEST PROCEDURE	21
TEST EQUIPMENT LIST AND DETAILS	
TEST DATA	
FCC §22.917(A) & §24.238(A) - BAND EDGES	23
APPLICABLE STANDARD	
TEST PROCEDURE	
TEST DATA	
Test Data	
FCC §2.1055, §22.355 & §24.235 - FREQUENCY STABILITY	27

Pov	Aron	Compliance	Laborator	ioc Corn	(Chanzhan)
Dav	Area	Combinance	Laborator	ies Cord.	(Shellzhen)

ANNEX A - PRODUCT SIMILARTITY DECLARATION LETTER	30
TEST DATA	28
TEST EQUIPMENT LIST AND DETAILS.	
Test Procedure	27
APPLICABLE STANDARD	27

Report No.: RSZ111104003-00a

FCC Part 22H/24E Page 3 of 30

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Enet Times Technology Co., Ltd.*'s product, model number: *DG600 (FCC ID: YZQDG600)* or the "EUT" in this report was a *GSM Dual Sim Dual Standby Mobile Phone*, which was measured approximately: 11.2 cm (L) x 5.8 cm (W) x 1.1 cm (H), rated input voltage: DC 3.7 V battery.

Report No.: RSZ111104003-00a

Frequency Range:

Cellular Band: 824-849 MHz (Tx), 869-894 MHz (Rx) PCS Band: 1850-1910 MHz (Tx), 1930-1990 MHz (Rx)

Bluetooth: 2400-2483.5 MHz (Tx/Rx)

Modulation Mode: GMSK

Transmitter Output Power:

Cellular Band: 33 dBm, PCS Band: 30 dBm

Note: The series product, model DG600 and ALVO SLIM, we select DG600 to perform full test items. The difference between them is the model number, which was explained in the attached declaration letter.

* All measurement and test data in this report was gathered from production sample serial number: 1111005 (Assigned by BACL, Shenzhen). The EUT was received on 2011-11-04.

Objective

This type approval report is prepared on behalf of *Enet Times Technology Co., Ltd.* in accordance with Part 2, Subpart J, Part 22 Subpart H, and Part 24 Subpart E of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC rules for output power, modulation characteristic, occupied bandwidth, and spurious emission at antenna terminal, spurious radiated emission, frequency stability, band edge and radiated margin.

Related Submittal(s)/Grant(s)

Part 15B JBP and Part 15.247 DSS submission with FCC ID: YZQDG600

Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2, Sub-part J as well as the following parts:

Part 22 Subpart H - Public Mobile Services

Part 24 Subpart E - Personal Communication Services

Applicable Standards: TIA/EIA 603-C, ANSI C63.4-2009.

All radiated and conducted emissions measurements were performed at Bay Area Compliance Laboratories Corp. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

FCC Part 22H/24E Page 4 of 30

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp.(Shenzhen) to collect test data is located on the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Report No.: RSZ111104003-00a

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is an ISO/IEC 17025 accredited laboratory, and is accredited by National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



The current scope of accreditations can be found at http://ts.nist.gov/Standards/scopes/2007070.htm

FCC Part 22H/24E Page 5 of 30

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The EUT was configured for testing according to TIA/EIA-603-C.


The GSM/PCS item test was performed with the EUT operating at normal mode.

The GPRS item test was performed with the EUT operating at testing mode.


Equipment Modifications

No modifications were made to the EUT.

Configuration of Test Setup



Block Diagram of Test Setup



FCC Part 22H/24E Page 6 of 30

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result	
§1.1307, §2.1093	RF Exposure (SAR)	Compliance*	
\$2.1046; \$22.913 (a); \$24.232 (c)	RF Output Power	Compliance	
§2.1047	Modulation Characteristics	N/A	
§2.1049; §22.905 §22.917; §24.238	99% & 26 dB Occupied Bandwidth	Compliance	
§2.1051, §22.917 (a); §24.238 (a)	Spurious Emissions at Antenna Terminal	Compliance	
\$2.1053 \$22.917 (a); \$24.238 (a)	Field Strength of Spurious Radiation	Compliance	
§22.917 (a); §24.238 (a)	Out of band emission, Band Edge	Compliance	
\$2.1055 \$22.355; \$24.235	Frequency stability vs. temperature Frequency stability vs. voltage	Compliance	

Report No.: RSZ111104003-00a

Note: * Please refer to SAR report released by BACL, report number: RSZ111104003-20

FCC Part 22H/24E Page 7 of 30

FCC §1.1307 & §2.1093 - RF EXPOSURE

Report No.: RSZ111104003-00a

Applicable Standard

FCC §1.1307 and §2.1093.

Test Result

Compliance, please refer to the SAR report: RSZ111104003-20

FCC Part 22H/24E Page 8 of 30

FCC §2.1047 - MODULATION CHARACTERISTIC

According to FCC $\S 2.1047(d)$, Part 22H & 24E there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

Report No.: RSZ111104003-00a

FCC Part 22H/24E Page 9 of 30

FCC §2.1046, §22.913 (a) & §24.232 (c) - RF OUTPUT POWER

Applicable Standard

According to FCC §2.1046 and §22.913 (a), the ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 watts.


Report No.: RSZ111104003-00a

According to FCC §2.1046 and §24.232 (c), mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications..

Test Procedure

Conducted method:

The RF output of the transmitter was connected to the wireless test set and the spectrum analyzer through sufficient attenuation.



Radiated method:

TIA 603-C section 2.2.17

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Horn Antenna	DRH-118	A052604	2011-05-05	2012-05-04
Rohde & Schwarz	Signal Analyzer	FSIQ 26	609358	2011-07-08	2012-07-07
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2011-07-05	2012-07-04
НР	Signal Generator	HP8657A	2849U00982	2011-10-28	2012-10-27
НР	Synthesized Sweeper	8341B	2624A00116	2011-11-07	2012-11-06
COM POWER	Dipole Antenna	AD-100	041000	2011-09-25	2012-09-25
A.H. System	Horn Antenna	SAS-200/571	135	2011-05-17	2012-05-17
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	109038	2011-10-28	2012-10-27

^{*} **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

FCC Part 22H/24E Page 10 of 30

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa

The testing was performed by Tiger Ye on 2011-11-10.

Conducted Power:

Cellular Band (Part 22H)

Report No.: RSZ111104003-00a

Mode	Channel Frequency (MHz)		Output Power (dBm)	Limit (dBm)
	128	824.2	31.95	38.45
GSM	190	836.6	32.02	38.45
	251	848.8	32.01	38.45

Mode	Channel	Frequency		Output Po	wer (dBm)	
Mode	Channel	(MHz)	1 slot	2 slots	3 slots	4 slots
	128	824.2	32.64	31.74	No St	ıpport
GPRS	190	836.6	32.71	31.68	No St	ipport
	251	848.8	32.75	31.61	No St	ipport

PCS Band (Part 24E)

Mode	Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)
	512	1850.2	29.05	33
GSM	661	1880.0	28.97	33
	810	1909.8	29.00	33

Mode	Channel	Frequency		Output Po	wer (dBm)	
Wiode	Channel	(MHz)	1 slot	2 slots	3 slots	4 slots
	512	1850.2	29.44	29.11	No Su	ipport
GPRS	661	1880.0	29.38	29.12	No Su	ipport
	810	1909.8	29.42	29.12	No Su	ipport

FCC Part 22H/24E Page 11 of 30

ERP & EIRP:

ERP for Cellular Band (Part 22H)

Report No.: RSZ111104003-00a

	Indic	ated	Table	Test A	ntenna	Su	ıbstituted		Antenna	Cable	Absolute	Part 22H
F	Frequency (MHz)	S.A. Reading (dBµV)	Angle Degree	Height (m)	Polar (H/V)	Frequency (MHz)	S.G. Level (dBm)	Ant. Polar (H/V)	Gain Correction (dBd)	Loss (dB)	Level (dBm)	Limit (dBm)
						Low C	hannel					
	824.4	98.35	240	1.9	Н	824.4	26.5	Н	0	0.67	25.83	38.45
	824.4	102.80	180	1.2	V	824.4	29.7	V	0	0.67	29.03	38.45

EIRP for PCS Band (Part 24E)

	Indic	ated	Table	Test A	ntenna	Su	ıbstituted		Antenna	Cable	Absolute	Part 24E
	Frequency (MHz)	S.A. Reading (dBµV)	Angle Degree	Height (m)	Polar (H/V)	Frequency (MHz)	S.G. Level (dBm)	Ant. Polar (H/V)	Gain Correction (dBi)	Loss (dB)	Level (dBm)	Limit (dBm)
						Middle (Channel					
I	1909.8	88.36	330	1.9	Н	1909.8	16.8	Н	6.2	1.04	15.96	33
	1909.8	94.05	180	1.2	V	1909.8	24.6	V	6.2	1.04	29.76	33

FCC Part 22H/24E Page 12 of 30

FCC §2.1049, §22.917, §22.905 & §24.238 - OCCUPIED BANDWIDTH

Report No.: RSZ111104003-00a


Applicable Standard

FCC §2.1049, §22.917, §22.905 and §24.238.

Test Procedure

The RF output of the transmitter was connected to the simulator and the spectrum analyzer through sufficient attenuation.

The resolution bandwidth of the spectrum analyzer was set at 3 kHz (Cellular /PCS) and the 26 dB & 99% bandwidth was recorded.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Spectrum Analyzer	ESCI	849720/019	2011-07-08	2012-07-07
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	109038	2011-10-28	2012-10-27

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56%
ATM Pressure:	100.0kPa

The testing was performed by Tiger Ye on 2011-11-08 and 2011-11-15

FCC Part 22H/24E Page 13 of 30

GMSK Modulation:

Cellular Band (Part 22H)

Report No.: RSZ111104003-00a

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Occupied Bandwidth (kHz)
190	836.6	244	312

PCS Band (Part 24E)


Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Occupied Bandwidth (kHz)
661	1880.0	240	316

Please refer to the following plots.


FCC Part 22H/24E Page 14 of 30

Cellular Band (Part 22H)

99% Occupied Bandwidth




26 dB Occupied Bandwidth




FCC Part 22H/24E Page 15 of 30

PCS Band (Part 24E)

99% Occupied Bandwidth



26 dB Occupied Bandwidth



FCC Part 22H/24E Page 16 of 30

FCC §2.1051, §22.917(a) & §24.238(a) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS

Report No.: RSZ111104003-00a


Applicable Standard

FCC §2.1051, §22.917(a) and §24.238(a).

The spectrum was to be investigated to the tenth harmonics of the highest fundamental frequency as specified in § 2.1051.

Test Procedure

The RF output of the transceiver was connected to a spectrum analyzer and simulator through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 100 kHz. Sufficient scans were taken to show any out of band emissions up to 10^{th} harmonic.



Test Equipment List and Details

Manufacturer	Description Model		Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	109038	2011-10-28	2012-10-27
Wainwright Germany	Band Reject Filter	WRCG1850/1910- 1835/1925-40/8SS	22	2011-02-28	2012-02-28
Wainwright Germany	Band Reject Filter	WRCG823/850- 813/860-40/8SS	7	2011-02-28	2012-02-28
Rohde & Schwarz	Spectrum Analyzer	FSIQ26	849720/019	2011-07-08	2012-07-07

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions


Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa

The testing was performed by Tiger Ye on 2011-11-08 and 2011-0-11-15.


FCC Part 22H/24E Page 17 of 30

Cellular Band (Part 22H)

30 - 1000 MHz - Middle Channel




1 – 10 GHz - Middle Channel




FCC Part 22H/24E Page 18 of 30

PCS Band (Part 24E)

30 - 1000 MHz - Middle Channel




1 - 3 GHz - Middle Channel



FCC Part 22H/24E Page 19 of 30

3 - 20 GHz - Middle Channel



FCC Part 22H/24E Page 20 of 30

FCC §2.1053, §22.917 & §24.238 - SPURIOUS RADIATED EMISSIONS

Report No.: RSZ111104003-00a

Applicable Standard

FCC §2.1053, §22.917 and §24.238.

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the receiving antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in $dB = 10 \lg (TXpwr in Watts/0.001) - the absolute level$

Spurious attenuation limit in $dB = 43 + 10 \text{ Log}_{10}$ (power out in Watts)

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Horn Antenna	DRH-118	A052604	2011-05-05	2012-05-04
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2011-07-05	2012-07-04
Rohde & Schwarz	Signal Analyzer	FSIQ 26	609358	2011-07-08	2012-07-07
Mini-Circuits	Amplifier	ZVA-213+	T-E27H	2011-03-08	2012-03-07
НР	Signal Generator	HP8657A	2849U00982	2011-10-28	2012-10-27
НР	Amplifier	HP8447D	2944A09795	2011-08-02	2012-08-02
НР	Synthesized Sweeper	8341B	2624A00116	2011-11-07	2012-11-06
COM POWER	Dipole Antenna	AD-100	041000	2011-09-25	2012-09-25
A.H. System	Horn Antenna	SAS-200/571	135	2011-05-17	2012-05-17
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	109038	2011-10-28	2012-10-27

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

FCC Part 22H/24E Page 21 of 30

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa

The testing was performed by Tiger Ye on 2011-11-12.

Test mode: Transmitting

Below 1 GHz:

Note: the data which below 20 dB to the limit was not recorded.

Above 1 GHz:

Cellular Band (Part 22H)

Report No.: RSZ111104003-00a

Indica	ted	Table	Test A	ntenna		Substitu	ted		Absolute		
Frequency (MHz)	S.A. Reading (dBµV)	Angle Degree	Height (m)	Polar (H/V)	Frequency (MHz)	Level (dBm)	Ant. Gain (dBi)	Cable Loss (dB)	Level (dBm)	Limit (dBm)	Margin (dB)
	Middle Channel										
2510.1	67.23	170	2.1	V	2510.1	-31.27	7.3	1.73	-25.7	-13	12.70
2510.1	67.16	320	1.8	Н	2510.1	-31.34	7.3	1.73	-25.77	-13	12.77
1673.1	61.58	190	1.7	V	1673.1	-39.92	6.2	1.19	-34.91	-13	21.91
4182.9	55.31	160	1.6	Н	4182.9	-40.79	7.6	3.18	-36.37	-13	23.37
1673.1	59.47	250	1.1	Н	1673.1	-42.03	6.2	1.19	-37.02	-13	24.02
5019.6	51.67	140	2.1	Н	5019.6	-42.83	7.9	3.21	-38.14	-13	25.14
4182.9	52.69	340	1.2	V	4182.9	-43.41	7.6	3.18	-38.99	-13	25.99
5019.6	47.36	250	1.6	V	5019.6	-47.14	7.9	3.21	-42.45	-13	29.45

PCS Band (Part 24E)

Indica	ted	Table	Test A	ntenna		Substitu	ted		Absolute		
Frequency (MHz)	S.A. Reading (dBµV)	Angle	Height (m)	Polar (H/V)	Frequency (MHz)	Level (dBm)	Ant. Gain (dBi)	Cable Loss (dB)	Level (dBm)	Limit (dBm)	Margin (dB)
Middle Channel											
9549.1	46.52	140	2.1	Н	9549.1	-40.68	7.4	3.34	-36.62	-13	23.62
9549.1	45.3	250	1.6	V	9549.1	-41.9	7.4	3.34	-37.84	-13	24.84
5602.3	38.62	160	1.6	Н	5602.3	-53.88	8.3	2.18	-47.76	-13	34.76
3739.1	41.53	155	2.3	Н	3739.1	-53.67	7.4	2.11	-48.38	-13	35.38
3739.1	40.95	189	1.1	V	3739.1	-54.25	7.4	2.11	-48.96	-13	35.96
5602.3	36.49	340	1.2	V	5602.3	-56.01	8.3	2.18	-49.89	-13	36.89

FCC Part 22H/24E Page 22 of 30

FCC §22.917(a) & §24.238(a) - BAND EDGES

Applicable Standard

According to FCC 22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.


Report No.: RSZ111104003-00a

According to FCC 24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P) dB$.

Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

The center of the spectrum analyzer was set to block edge frequency, RBW set to 10 kHz.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Spectrum Analyzer	ESCI	849720/019	2011-07-08	2012-07-07
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	109038	2011-10-28	2012-10-27

^{*} **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa

The testing was performed by Tiger Ye on 2011-11-09.

FCC Part 22H/24E Page 23 of 30

Please refer to the following tables and plots.

Cellular Band (Part 22H)


Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.997	-14.84	-13
849.022	-17.42	-13

PCS Band (Part 24E)


Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.998	-21.75	-13
1910.006	-20.04	-13

FCC Part 22H/24E Page 24 of 30

Cellular Band, Left Band Edge




Cellular Band, Right Band Edge




FCC Part 22H/24E Page 25 of 30

PCS Band, Left Band Edge



PCS Band, Right Band Edge



FCC Part 22H/24E Page 26 of 30

FCC §2.1055, §22.355 & §24.235 - FREQUENCY STABILITY

Applicable Standard

FCC §2.1055 (a), § 2.1055 (d), §22.355, §24.235

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency Tolerance for Tr	ransmitters in	n the Public	Mobile Services
----------------------------	----------------	--------------	------------------------

Report No.: RSZ111104003-00a

Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤3 watts (ppm)	Mobile ≤ 3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929.	5.0	N/A	N/A
929 to 960.	1.5	N/A	N/A
2110 to 2220	10.0	N/A	N/A


According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stays within the authorized frequency block.

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to communication test set via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the communication test set.

Frequency Stability vs. Voltage: An external variable DC power supply was connected to the battery terminals of the equipment under test. The voltage was set to 115% of the nominal value and was then decreased until the transmitter light no longer illuminated; i.e., the battery end point. The output frequency was recorded for each battery voltage.



FCC Part 22H/24E Page 27 of 30

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
WUHUAN	Temperature & Humidity Chamber	HTP205	20021115	2011-06-04	2012-06-03
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	109038	2011-10-28	2012-10-27
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2011-11-11	2012-11-10

^{*} **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions

Temperature:	25 °C	
Relative Humidity:	56 %	
ATM Pressure:	100.0kPa	

The testing was performed by Tiger Ye on 2011-11-15.

Cellular Band (Part 22H)

Middle Channel, f ₀ =836.6 MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30		28	0.0334688	2.5
-20		23	0.0274922	2.5
-10		25	0.0298829	2.5
0		23	0.0274922	2.5
10	3.7	26	0.0310782	2.5
20		24	0.0286875	2.5
30		28	0.0334688	2.5
40		29	0.0346641	2.5
50		27	0.0322735	2.5
25	V min.= 3.5	28	0.0334688	2.5

FCC Part 22H/24E Page 28 of 30

PCS Band (Part 24E)

Middle Channel, f _o =1880.0 MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30		27	0.0143617	Pass
-20		24	0.012766	Pass
-10		24	0.012766	Pass
0	3.7	23	0.012234	Pass
10		27	0.0143617	Pass
20		25	0.0132979	Pass
30		26	0.0138298	Pass
40		24	0.012766	Pass
50		25	0.0132979	Pass
25	V min.= 3.5	28	0.0148936	Pass

FCC Part 22H/24E Page 29 of 30

ANNEX A - PRODUCT SIMILARTITY DECLARATION LETTER

Report No.: RSZ111104003-00a



Enet Times Technology Co., LTD Unit24F, BlockC,World Trade Plaza,Fuhong Road, Shenzhen, China

Tel: 0755-25327168 Fax: 0755-25327000 Date: 2011-11-18

Declaration of Similarity

To:

Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of Wan Li Industrial Bldg., Shihua Rd., FuTian Free Trade Zone, Shenzhen, China Phone: +86 755 33320018, Fax: +86 755 33320008 http://www.baclcorp.com.cn

We, Enet Times Technology Co., LTD. hereby declare that our product: GSM Dual Sim Dual Standby Mobile Phone, Model: DG600 and ALVO SLIM. These two models are electrically and mechanically identical, share the same PCB Layout and components. And the differences between them are the model number. Model DG600 was tested by BACL.

Sincerely,

Will 7hu

General Manager

***** END OF REPORT *****

FCC Part 22H/24E Page 30 of 30