FCC Radio Test Report

FCC ID: YZTDONARBT1280

This report concerns (check one): Original Grant Class II Change

Project No.: 1011C125
Equipment: MINI Keyboard

Model Name : BT1280

Applicant : Donar Electronics Technology CO.,LTD

Address: D Building, No.2, Zhentou Road, Huangbu Industrial Zone, Shajing, Bao'an District,

Shenzhen, China

Manufacturer Donar Electronics Technology CO.,LTD
Address D Building, No. 2, Zhentou Road, Huangbi

D Building, No.2, Zhentou Road, Huangbu Industrial Zone, Shajing, Bao'an District,

Shenzhen, China

Tested by:

Neutron Engineering Inc. EMC Laboratory

Date of Receipt: Nov. 11, 2010

Date of Test:

Nov. 11, 2010 ~ Nov. 29, 2010

Testing Engineer : Yuan

(Ivan Cao)

Technical Manager :

(Leo Hung)

Authorized Signatory : Steven L

Neutron Engineering Inc.

No.3, Jinshagang 1st Road, ShiXia, Dalang Town, Dong Guan, China.

TEL: (0769) 8318-3000 FAX: (0769) 8319-6000



Declaration

Neutron represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with the standards traceable to National Measuremen Laboratory (**NML**) of **R.O.C.**, or National Institute of Standards and Technology (**NIST**) of **U.S.A.**

Neutron's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identica electrical and mechanical components. **Neutron** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **Neutron** issued reports.

Neutron's reports must not be used by the client to claim product endorsement by the authorities or any agency of the Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public anc **Neutron-self**, extracts from the test report shall not be reproduced except in full with **Neutron**'s authorized written approval.

Neutron's laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Report No.: NEI-FCCP-1-1011C125 Page 2 of 65

	Table of Contents	Page
1. CERTIFIC	CATION	6
2.SUMMAR	RY OF TEST RESULTS	7
2.1 TEST		8
	UREMENT UNCERTAINTY	8
	···-··-	
	L INFORMATION	9
	RAL DESCRIPTION OF EUT	9
	RIPTION OF TEST MODES	11
	OF PARAMETERS OF TEXT SOFTWARE SETTING	11
	K DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTE	D 12
3.5 DESCI	RIPTION OF SUPPORT UNITS(CONDUCTED MODE)	13
4. EMC EMI	SSION TEST	14
	UCTED EMISSION MEASUREMENT	14
	OWER LINE CONDUCTED EMISSION LIMITS	14
	IEASUREMENT INSTRUMENTS LIST AND SETTING EST PROCEDURE	14 15
	EVIATION FROM TEST STANDARD	15
	EST SETUP	15
	UT OPERATING CONDITIONS	16
	EST RESULTS	17
	TED EMISSION MEASUREMENT	18
	ADIATED EMISSION LIMITS IEASUREMENT INSTRUMENTS LIST ANS SETTING	18 19
	EST PROCEDURE	20
4.2.4 D	EVIATION FROM TEST STANDARD	20
	EST SETUP	21
	UT OPERATING CONDITIONS EST RESULTS (BETWEEN30 – 1000 MHZ)	21 22
	EST RESULTS (BETWEEN30 - 1000 MHZ)	22 24
	OF HOPPING CHANNEL	36
5.1 APPLI	ED PROCEDURES / LIMIT	36
5.1.1 M	EASUREMENT INSTRUMENTS LIST AND SETTING	36
_	EST PROCEDURE	36
	EVIATION FROM STANDARD	36 36
	EST SETUP UT OPERATION CONDITIONS	36 36
	EST RESULTS	37

Report No.: NEI-FCCP-1-1011C125 Page 3 of 65

Table of Contents	Page
6 . AVERAGE TIME OF OCCUPANCY	38
6.1 APPLIED PROCEDURES / LIMIT	38
6.1.1 MEASUREMENT INSTRUMENTS LIST	38
6.1.2 TEST PROCEDURE	38
6.1.3 DEVIATION FROM STANDARD	38
6.1.4 TEST SETUP	39
6.1.5 EUT OPERATION CONDITIONS	39
6.1.6 TEST RESULTS	40
7. HOPPING CHANNEL SEPARATION MEASUREMENT	46
7.1 APPLIED PROCEDURES / LIMIT	46
7.1.1 MEASUREMENT INSTRUMENTS LIST AND SETTING	46
7.1.2 TEST PROCEDURE	46
7.1.3 DEVIATION FROM STANDARD 7.1.4 TEST SETUP	46
7.1.4 TEST SETUP 7.1.5 EUT OPERATION CONDITIONS	46 46
7.1.6 TEST RESULTS	47
8 . BANDWIDTH TEST	49
8.1 APPLIED PROCEDURES / LIMIT	49
8.1.1 MEASUREMENT INSTRUMENTS LIST AND SETTING	49
8.1.2 TEST PROCEDURE	49
8.1.3 DEVIATION FROM STANDARD	49
8.1.4 TEST SETUP	49
8.1.5 EUT OPERATION CONDITIONS	49
8.1.6 TEST RESULTS	50
9 . PEAK OUTPUT POWER TEST	52
9.1 APPLIED PROCEDURES / LIMIT	52
9.1.1 MEASUREMENT INSTRUMENTS LIST AND SETTING	52
9.1.2 TEST PROCEDURE	52
9.1.3 DEVIATION FROM STANDARD	52 53
9.1.4 TEST SETUP 9.1.5 EUT OPERATION CONDITIONS	52 52
9.1.6 TEST RESULTS	52 53
10 . ANTENNA CONDUCTED SPURIOUS EMISSION	55
10.1 APPLIED PROCEDURES / LIMIT	55
10.1.1 MEASUREMENT INSTRUMENTS LIST AND SETTING	55
10.1.2 TEST PROCEDURE	55
10.1.3 DEVIATION FROM STANDARD	55
10.1.4 TEST SETUP	55
10.1.5 EUT OPERATION CONDITIONS	55

Report No.: NEI-FCCP-1-1011C125 Page 4 of 65



Table of Contents	Page
10.1.6 TEST RESULTS	56
11 . RF EXPOSURE TEST	62
11.1 APPLIED PROCEDURES / LIMIT	62
11.1.1 MEASUREMENT INSTRUMENTS LIST	62
11.1.2 MPE CALCULATION METHOD	63
11.1.3 DEVIATION FROM STANDARD	63
11.1.4 TEST SETUP	63
11.1.5 EUT OPERATION CONDITIONS	63
11.1.6 TEST RESULTS	64
12 . EUT TEST PHOTO	65

Report No.: NEI-FCCP-1-1011C125 Page 5 of 65

1. CERTIFICATION

Equipment: MINI Keyboard

Brand Name: N/A Model Name: BT1280

Applicant: Donar Electronics Technology CO.,LTD

Date of Test: Nov. 11, 2010 ~ Nov. 29, 2010 Test Item: ENGINEERING SAMPLE

Standards: FCC Part15, Subpart C(15.247) / ANSI C63.4: 2003

The above equipment has been tested and found compliance with the requirement of the relative standards by Neutron Engineering Inc. EMC Laboratory.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. NEI-FCCP-1-1011C125) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of NVLAP and TAF according to the ISO-17025 quality assessment standard and technical standard(s).

Report No.: NEI-FCCP-1-1011C125 Page 6 of 65

2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C				
Standard Section	Test Item	Judgment	Remark	
15.207	Conducted Emission	N/A	Note(1)/(2)	
15.247(d)	Antenna conducted Spurious Emission	PASS		
15.247 (a)(1)	Hopping Channel Separation	PASS		
15.247 (b)(1)	Peak Output Power	PASS		
15.247(d)/15.209	Radiated Spurious Emission	PASS		
15.247 (a)(1)(iii)	Number of Hopping Frequency	PASS		
15.247 (a)(1)(iii)	Dwell Time	PASS		
15.205	Restricted Bands	PASS		
15.203	Antenna Requirement	PASS		
1.1307 1.1310 2.1091 2.1093	RF Exposure Compliance	PASS		

NOTE:

- (1)" N/A" denotes test is not applicable in this Test Report
- (2) The EUT used new battery.

Report No.: NEI-FCCP-1-1011C125 Page 7 of 65

2.1 TEST FACILITY

The test facilities used to collect the test data in this report is **DG-C02/DG-CB03** at the location of No.3, Jinshagang 1st Road, ShiXia, Dalang Town, Dong Guan, China.523792 Neutron's test firm number is 319330

2.2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

The reported uncertainty of measurement $\mathbf{y} \pm \mathbf{U}$, where expended uncertainty \mathbf{U} is based on a standard uncertainty multiplied by a coverage factor of $\mathbf{k=2}$, providing a level of confidence of approximately $\mathbf{95}$ % $^{\circ}$

A. Conducted Measurement:

Test Site	Method	Measurement Frequency Range	U , (dB)	NOTE
DG-C02	CISPR	150 KHz ~ 30MHz	1.94	

B. Radiated Measurement:

Test Site	Method	Measurement Frequency Range	Ant. H / V	U , (dB)	NOTE
	DG-CB03 CISPR	30MHz ~ 200MHz	V	3.82	
DG-CB03		30MHz ~ 200MHz	Н	3.60	
		200MHz ~ 1,000MHz	V	3.86	
		200MHz ~ 1,000MHz	Н	3.94	

Report No.: NEI-FCCP-1-1011C125 Page 8 of 65



3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Equipment	MINI Keyboard		
Brand Name	N/A		
Model Name	BT1280		
OEM Brand/Model Name	N/A		
Model Difference	same model name is BT differ in appearance colo		
	The EUT is a MINI Keyb		
	Operation Frequency:	2402~2480 MHz	
	Modulation Type: Bit Rate of Transmitter	-GFSK(1Mbps)	
	Number of Channel	79 CH	
	Antenna Designation:	Please see Note 3.	
Product Description	Antenna Gain(Peak)	Please see Note 3.	
	Output Power:	-6.43 dBm	
	exhibited in User's Manu	n, features, or specification ual, the EUT is considered as an More details of EUT technical er to the User's Manual.	
Channel List	Please refer to the Note	2.	
Power Source	DC Voltage supplied from battery		
Power Rating	DC 3.0V		
Connecting I/O Port(s)	Please refer to the User's Manual		
Products Covered	N/A		
EUT Modification(s)	N/A		

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

Report No.: NEI-FCCP-1-1011C125 Page 9 of 65



2.

	Channel List				
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

Table for Filed Antenna

Ant	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	YoFree	YFBT01	РСВ	N/A	2.78	BT Antenna

Report No.: NEI-FCCP-1-1011C125 Page 10 of 65

3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	CH00 (1Mbps) EUT only
Mode 2	CH39 (1Mbps) EUT only
Mode 3	CH78 (1Mbps) EUT only

The EUT system operated these modes were found to be the worst case during the pre-scanning test as Following:

For Conducted Emission			
Final Test Mode Description			
-	"N/A" denotes test is not applicable in this Test Report		

For Radiated Emission			
Final Test Mode	Description		
Mode 1	CH00 (1Mbps) EUT only		
Mode 2	CH39 (1Mbps) EUT only		
Mode 3	CH78 (1Mbps) EUT only		

Note:


- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The EUT used new battery.

3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS

Test software Version	Test program: Bluetool				
Frequency	2402 MHz 2402 MHz 2402 MHz				
Parameters-1Mbps	-4 -4 -4				

Report No.: NEI-FCCP-1-1011C125 Page 11 of 65



Report No.: NEI-FCCP-1-1011C125 Page 12 of 65



3.1 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.	Note
E-1	MINI Keyboard	N/A	BT1280	YZTDONARBT1280	N/A	EUT

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in <code>[Length]</code> column.

Report No.: NEI-FCCP-1-1011C125 Page 13 of 65

4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
FREQUENCT (IVII12)	Quasi-peak	Average	Quasi-peak	Average	Stariuaru
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR

0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

4.1.2 MEASUREMENT INSTRUMENTS LIST AND SETTING

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	LISN	EMCO	3816/2	00052765	May.26.2011
2	LISN	Rolf Heine	NNB-2-16Z	99044	May.26.2011
3	50Ω Terminator	SHX	TF2-3G-A	08122901	May.26.2011
4	Transient Limiter	Agilent	11947A	3107A03668	May.26.2011
5	Test Cable	N/A	C-06_C03	N/A	Nov.15.2011
6	EMI TEST RECEIVER	R&S	ESCS30	8333641017	May.26.2011

Remark: "N/A" denotes No Model No., Serial No. or No Calibration specified.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

Report No.: NEI-FCCP-1-1011C125 Page 14 of 65


4.1.3 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item -EUT Test Photos.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

Report No.: NEI-FCCP-1-1011C125 Page 15 of 65



4.1.6 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

The EUT was programmed to be in continuously transmitting / Hopping on mode.

Report No.: NEI-FCCP-1-1011C125 Page 16 of 65

4.1.7 TEST RESULTS

EUT:	MINI Keyboard	Model Name :	BT1280	
Temperature:		Relative Humidity:		
Pressure :		Test Voltage :		
Test Mode:	"N/A" denotes test is not applicable in this Test Report			

Remark

- (1) All readings are QP Mode value unless otherwise stated AVG in column of Note I the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform In this case, a " * " marked in AVG Mode column of Interference Voltage Measured In the Note of Interference Voltage Measured Interference Interference Voltage Measured Int
- (2) Measuring frequency range from 150KHz to 30MHz •
- (3) "N/A" denotes test is not applicable in this Test Report

Report No.: NEI-FCCP-1-1011C125 Page 17 of 65

4.2 RADIATED EMISSION MEASUREMENT

4.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies	Field Strength	Measurement Distance
(MHz)	(micorvolts/meter)	(meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	(dBuV/m) (at 3M)		
FREQUENCY (IVIDZ)	PEAK	AVERAGE	
Above 1000	74	54	

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower

Report No.: NEI-FCCP-1-1011C125 Page 18 of 65

4.2.2 MEASUREMENT INSTRUMENTS LIST ANS SETTING

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Triple Loop Antenna	R&S	HFH2-Z2	830749/020	May.27.2011
2	Bi-log Antenna	Schwarbeck	VULB9160	9160-3232	May.26.2011
3	Horn Antenna	ETS	3115	00075789	May.12.2011
4	Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170340	Dec.16.2010
5	Amplifier	HP	8447D	2944A09673	May.26.2011
6	Amplifier	Agilent	8449B	3008A02274	May.26.2011
7	Amplifier	EMC	EMC2654045	980039	Aug.12.2011
8	Test Receiver	R&S	ESCI	100895	May.26.2011
9	Spectrum Analyzer	R&S	FSP 40	100185	Nov.26.2011
10	Test Cable	N/A	C-01_CB03	N/A	Jul.05.2011
11	Test Cable	HUBER+SUHNER	SUCOFLEX_8 m	313794/4	Apr.12.2011
12	Controller	СТ	SC100	N/A	N/A

Remark: "N/A" denotes No Model Name / Serial No. and No Calibration specified.

Spectrum Parameter	Setting		
Attenuation	Auto		
Start Frequency	1000 MHz		
Stop Frequency	10th carrier harmonic		
RB / VB (emission in restricted	4 Mile /4 Mile for Dook 4 Mile /401 le for Avorono		
band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average		

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

Report No.: NEI-FCCP-1-1011C125 Page 19 of 65



4.2.3 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.2.4 D	DEVIATION	FROM TEST	STANDARD
---------	-----------	-----------	----------


No deviation

Report No.: NEI-FCCP-1-1011C125 Page 20 of 65




4.2.5 TEST SETUP

(A) Radiated Emission Test Set-Up Frequency Below 1 GHz



(B) Radiated Emission Test Set-Up Frequency Above 1 GHz



4.2.6 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.

Report No.: NEI-FCCP-1-1011C125 Page 21 of 65


4.2.7 TEST RESULTS (BETWEEN30 - 1000 MHZ)

EUT:	MINI Keyboard	Model Name :	BT1280
Temperature:	23 ℃	Relative Humidity:	51 %
Pressure:	1010 hPa	Test Voltage :	DC 3.0V
Test Mode :	TX 2402MHz -CH00-1Mbps		

Freq.	Ant.	Reading(RA)	Corr.Factor(CF)	Measured(FS)	Limits(QP)	Margin	Note
(MHz)	H/V	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	11010
89.67	V	47.15	-19.07	28.08	43.50	- 15.42	
165.80	V	47.83	-17.45	30.38	43.50	- 13.12	
245.60	V	50.67	-14.83	35.84	46.00	- 10.16	
336.81	V	46.87	-11.16	35.71	46.00	- 10.29	
399.60	V	37.99	-9.03	28.96	46.00	- 17.04	
496.87	V	39.83	-7.41	32.42	46.00	- 13.58	

Remark:

- (1) Reading in which marked as QP or Peak means measurements by using are Quasi-Peak Mode or Peak Mode with Detector BW=120KHz ; SPA setting in RBW=120KHz, VBW =120KHz, Swp. Time = 0.3 sec./MHz $^{\circ}$
- (2) All readings are Peak unless otherwise stated QP in column of ${}^{\mathbb{F}}$ Note $_{\mathbb{J}}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform $_{\circ}$
- (3) Measuring frequency range from 30MHz to 1000MHz $^{\circ}$
- (4) If the peak scan value lower limit more than 20dB, then this signal data does not show in table $^{\circ}$




Report No.: NEI-FCCP-1-1011C125 Page 22 of 65

EUT:	MINI Keyboard	Model Name :	BT1280
Temperature:	23 ℃	Relative Humidity:	51 %
Pressure:	1010 hPa	Test Voltage :	DC 3.0V
Test Mode :	TX 2402MHz –CH00-1Mbps		

Freq. (MHz)	Ant. H/V	Reading(RA) (dBuV)	Corr.Factor(CF) (dB)	Measured(FS) (dBuV/m)	Limits(QP) (dBuV/m)	Margin (dB)	Note
101.83	Н	46.73	-18.40	28.33	43.50	- 15.17	
133.45	Н	51.13	-17.99	33.14	43.50	- 10.36	
223.69	Н	51.75	-15.77	35.98	46.00	- 10.02	
330.87	Ι	41.12	-11.31	29.81	46.00	- 16.19	
401.86	Н	34.11	-8.98	25.13	46.00	- 20.87	·
499.35	Н	37.57	-7.37	30.20	46.00	- 15.80	

Remark:

- (1) Reading in which marked as QP or Peak means measurements by using are Quasi-Peak Mode or Peak Mode with Detector BW=120KHz ; SPA setting in RBW=120KHz, VBW =120KHz, Swp. Time = 0.3 sec./MHz $^{\circ}$
- (2) All readings are Peak unless otherwise stated QP in column of ${}^{\mathbb{F}}$ Note $_{\mathbb{J}}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform $_{\circ}$
- (3) Measuring frequency range from 30MHz to 1000MHz \circ
- (4) If the peak scan value lower limit more than 20dB, then this signal data does not show in table ${}^{\circ}$



Report No.: NEI-FCCP-1-1011C125 Page 23 of 65

4.2.8 TEST RESULTS (ABOVE 1000 MHZ)

EUT:	MINI Keyboard	Model Name :	BT1280
Temperature:	25 ℃	Relative Humidity:	51 %
Pressure:	1010 hPa	Test Voltage :	DC 3.0V
Test Mode :	TX 2402MHz – CH 00-1Mbps		


Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Limit		
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2390.00	V	21.15	10.36	31.61	52.76	41.97	74.00	54.00	X/E
2401.85	V	60.99	60.36	31.60	92.59	91.96			X/F
4804.02	V	42.82	31.08	5.17	47.99	36.25	74.00	54.00	X/H


Remark:

- (1) All readings are Peak unless otherwise stated QP in column of ${}^{\mathbb{F}}$ Note ${}_{\mathbb{J}}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform ${}_{\circ}$
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission •
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna

Report No.: NEI-FCCP-1-1011C125 Page 24 of 65

Neutron Engineering Inc.=





Report No.: NEI-FCCP-1-1011C125 Page 25 of 65

EUT: MINI Keyboard		Model Name :	BT1280
Temperature:	25 ℃	Relative Humidity:	51 %
Pressure:	1010hPa	Test Voltage :	DC 3.0V
Test Mode :	TX 2402MHz – CH 00-1Mbps		


Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Limit		
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2390.00	Н	21.33	10.31	31.61	52.94	41.92	74.00	54.00	X/E
2402.20	Н	59.09	58.43	31.60	90.69	90.03			X/F
4804.02	Н	40.36	30.02	5.17	45.53	35.19	74.00	54.00	X/H

Remark:

- (1) All readings are Peak unless otherwise stated QP in column of ${}^{\mathbb{F}}$ Note ${}_{\mathbb{J}}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform ${}_{\circ}$
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency. "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission •
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna

Report No.: NEI-FCCP-1-1011C125 Page 26 of 65

Neutron Engineering Inc.=



EUT:	MINI Keyboard	Model Name :	BT1280
Temperature:	25 ℃	Relative Humidity:	51 %
Pressure:	1010 hPa	Test Voltage :	DC 3.0V
Test Mode :	TX 2441MHz –CH39-1Mbps		


Freq.	Ant.Pol.	Read	ling	Ant./CF	A	ct.	Liı	mit	
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2441.05	V	61.88	61.26	31.55	93.43	92.81			X/F
4881.98	V	41.69	31.31	5.56	47.25	36.87	74.00	54.00	X/H


Remark:

- (1) All readings are Peak unless otherwise stated QP in column of $^{\mathbb{F}}$ Note $_{\mathbb{J}}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform $_{\circ}$
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency. "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna

Report No.: NEI-FCCP-1-1011C125 Page 28 of 65

Neutron Engineering Inc.=





Report No.: NEI-FCCP-1-1011C125 Page 29 of 65

EUT:	MINI Keyboard	Model Name :	BT1280
Temperature:	25 ℃	Relative Humidity:	51 %
Pressure:	1010 hPa	Test Voltage :	DC 3.0V
Test Mode :	TX 2441MHz –CH39-1Mbps		


Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Limit		
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2441.15	Н	58.74	58.09	31.55	90.29	89.64			X/F
4881.98	Н	40.57	29.46	5.56	46.13	35.02	74.00	54.00	X/H

Remark:

- (1) All readings are Peak unless otherwise stated QP in column of ${}^{\mathbb{F}}$ Note ${}_{\mathbb{J}}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform ${}_{\circ}$
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency. "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna

Report No.: NEI-FCCP-1-1011C125 Page 30 of 65

Neutron Engineering Inc.=



EUT:	MINI Keyboard	Model Name :	BT1280
Temperature:	25 ℃	Relative Humidity:	51 %
Pressure:	1010hPa	Test Voltage :	DC 3.0V
Test Mode :	TX 2480MHz –CH78-1Mbps		


Freq.	Ant.Pol.	Rea	ding	Ant./CF	A	ct.	Lir	mit	
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2480.05	V	63.52	62.75	31.50	95.02	94.25			X/F
2483.50	V	25.39	22.32	31.50	56.89	53.82	74.00	54.00	X/E
4960.26	V	42.40	31.98	5.94	48.34	37.92	74.00	54.00	X/H

Remark:

- (1) All readings are Peak unless otherwise stated QP in column of ${}^{\mathbb{F}}$ Note $_{\mathbb{J}}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform $_{\circ}$
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency. "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission •
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna

Report No.: NEI-FCCP-1-1011C125 Page 32 of 65

Neutron Engineering Inc.=



EUT:	MINI Keyboard	Model Name :	BT1280
Temperature:	25 ℃	Relative Humidity:	51 %
Pressure :	1010 hPa	Test Voltage :	DC 3.0V
Test Mode :	TX 2480MHz –CH78-1Mbps		


Freq.	Ant.Pol.	Rea	ding	Ant./CF	A	ct.	Liı	mit	
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2480.00	Н	59.72	59.02	31.50	91.22	90.52			X/F
2483.50	Н	22.23	18.71	31.50	53.73	50.21	74.00	54.00	X/E
4960.26	Н	40.21	29.34	5.94	46.15	35.28	74.00	54.00	X/H

Remark:

- (1) All readings are Peak unless otherwise stated QP in column of ${}^{\mathbb{F}}$ Note ${}_{\mathbb{J}}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform ${}_{\circ}$
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency. "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission •
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna

Report No.: NEI-FCCP-1-1011C125 Page 34 of 65

Neutron Engineering Inc.=



5. NUMBER OF HOPPING CHANNEL

5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C						
Section	Test Item	Frequency Range (MHz)	Result			
15.247 (a)(1)(iii)	Number of Hopping Channel	2400-2483.5	PASS			

5.1.1 MEASUREMENT INSTRUMENTS LIST AND SETTING

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov.26.2011

Remark: "N/A" denotes No Model Name, Serial No. or No Calibration specified.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> Operating Frequency Range
RB	100 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

5.1.2 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 100KHz, VBW=100KHz, Sweep time = Auto.

5.1.3 DEVIATION FROM STANDARD

No deviation.

5.1.4 TEST SETUP

EUT	SPECTRUM
	ANALYZER


5.1.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.

Report No.: NEI-FCCP-1-1011C125 Page 36 of 65

EUT:	MINI Keyboard	Model Name :	BT1280
Temperature:	25 ℃	Relative Humidity:	51 %
Pressure: 1015 hPa		Test Voltage :	DC 3.0V
Test Mode :	Hopping Mode -1Mbps		

Number of Hopping Channel	79
---------------------------	----



Report No.: NEI-FCCP-1-1011C125 Page 37 of 65

6. AVERAGE TIME OF OCCUPANCY

6.1 APPLIED PROCEDURES / LIMIT

	FCC Part15 (15.247), Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result	
15.247 (a)(1)(iii)	Average Time of Occupancy	0.4sec	2400-2483.5	PASS	

6.1.1 MEASUREMENT INSTRUMENTS LIST

I	ltem	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
	1	Spectrum Analyzer	R&S	FSP 40	100185	Nov.26.2011

Remark: "N/A" denotes No Model Name, Serial No. or No Calibration specified.


6.1.2 TEST PROCEDURE

- a. The transmitter output (antenna port) was connected to the spectrum analyzer
- b. Set RBW of spectrum analyzer to 1MHz and VBW to 1MHz.
- c. Use a video trigger with the trigger level set to enable triggering only on full pulses.
- d. Sweep Time is more than once pulse time.
- e. Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- f. Measure the maximum time duration of one single pulse.
- a. Set the EUT for DH5, DH3 and DH1 packet transmitting.
- h. Measure the maximum time duration of one single pulse.
- i. DH5 Packet permit maximum 1600/79/6 = 3.37 hops per second in each channel (5 time slots RX, 1 time slot TX). So, the dwell time is the time duration of the pulse times $3.37 \times 31.6 = 106.6$ within 31.6 seconds.
- j. DH3 Packet permit maximum 1600 / 79 / 4 = 5.06 hops per second in each channel (3 time slots RX, 1 time slot TX). So, the dwell time is the time duration of the pulse times $5.06 \times 31.6 = 160$ within 31.6 seconds.
- k. DH1 Packet permit maximum 1600 / 79 / 2 = 10.12 hops per second in each channel (1 time slot RX, 1 time slot TX). So, the dwell time is the time duration of the pulse times $10.12 \times 31.6 = 320$ within 31.6 seconds.

6.1.3 DEVIATION FROM STANDARD

No deviation.

Report No.: NEI-FCCP-1-1011C125 Page 38 of 65



ANALYZER


6.1.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.


Report No.: NEI-FCCP-1-1011C125 Page 39 of 65

EUT:	MINI Keyboard	Model Name :	BT1280
Temperature:	25 ℃	Relative Humidity:	51 %
Pressure:	1012 hPa	Test Voltage :	DC 3.0V
Test Mode :	CH00-DH1/DH3/DH5 -1Mbps		

Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limits (s)
DH5	2402 MHz	2.9850	0.3184	0.4000
DH3	2402 MHz	1.7250	0.2760	0.4000
DH1	2402 MHz	0.2900	0.0928	0.4000




Report No.: NEI-FCCP-1-1011C125 Page 40 of 65




EUT:	MINI Keyboard	Model Name :	BT1280
Temperature:	20 ℃	Relative Humidity:	60 %
Pressure :	1012 hPa	Test Voltage :	DC 3.0V
Test Mode :	CH39 -DH1/DH3/DH5-1Mbps		

Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limits (s)
DH5	2441 MHz	2.9650	0.3163	0.4000
DH3	2441 MHz	1.7250	0.2760	0.4000
DH1	2441 MHz	0.4300	0.1376	0.4000




Report No.: NEI-FCCP-1-1011C125 Page 42 of 65




EUT:	MINI Keyboard	Model Name :	BT1280
Temperature:	20 ℃	Relative Humidity:	60 %
Pressure :	1012 hPa	Test Voltage :	DC 3.0V
Test Mode :	CH78 -DH1/DH3/DH5-1Mbps		

Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limits (s)
DH5	2480 MHz	2.9650	0.3163	0.4000
DH3	2480 MHz	1.7050	0.2728	0.4000
DH1	2480 MHz	0.4250	0.1360	0.4000



Report No.: NEI-FCCP-1-1011C125 Page 44 of 65



7. HOPPING CHANNEL SEPARATION MEASUREMENT

7.1 APPLIED PROCEDURES / LIMIT

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

7.1.1 MEASUREMENT INSTRUMENTS LIST AND SETTING

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov.26.2011

Remark: "N/A" denotes No Model Name, Serial No. or No Calibration specified.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	10 kHz (20dB Bandwidth) / 30 kHz (Channel Separation)
VB	100 kHz (20dB Bandwidth) / 100 kHz (Channel Separation)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


7.1.2 TEST PROCEDURE

- a. The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
- b. The resolution bandwidth of 10 kHz and the video bandwidth of 100 kHz were utilised for 20 dB bandwidth measurement.
- c. The resolution bandwidth of 30 kHz and the video bandwidth of 100 kHz were utilised for channel separation measurement.

7.1.3 DEVIATION FROM STANDARD

No deviation.

7.1.4 TEST SETUP



7.1.5 EUT OPERATION CONDITIONS


The EUT was programmed to be in Hopping on mode.

Report No.: NEI-FCCP-1-1011C125 Page 46 of 65

EUT:	MINI Keyboard	Model Name :	BT1280
Temperature:	25 ℃	Relative Humidity:	51 %
Pressure :	1012 hPa	Test Voltage :	DC 3.0V
Test Mode : Hopping on -CH00 / CH39 /CH78-1Mbps			

Frequency	Ch. Separation (MHz)	20dB Bandwidth (kHz)	Result
2402 MHz	1	976.00	Complies
2441 MHz	1	992.00	Complies
2480 MHz	1	996.00	Complies

Ch. Separation Limits: >20dB bandwidth or >2/3 of 20dB bandwidth



Report No.: NEI-FCCP-1-1011C125 Page 47 of 65

Neutron Engineering Inc. CH39 -1Mbps *RBW 30 kHz * VBW 100 kHz 1.002000000 MHz Ref 0 dBm *Att 10 dB SWT 5 ms Center 2.4415 GHz 300 kHz/ Span 3 MHz Date: 24.NOV.2010 20:57:12 CH78 -1Mbps *RBW 30 kHz Delta 1 [T1] * VBW 100 kHz Ref 0 dBm *Att 10 dB 1.002000000 MHz 1 PK MAXH

Date: 24.NOV.2010 20:57:53

Center 2.4795 GHz

Span 3 MHz

8. BANDWIDTH TEST

8.1 APPLIED PROCEDURES / LIMIT

	FCC Part15 (15.247) , Subpart C					
Section Test Item Limit Frequency Range (MHz) Result				Result		
15.247 (a)(2)	Bandwidth	<= 1 MHz (20dB bandwidth)	2400-2483.5	PASS		

8.1.1 MEASUREMENT INSTRUMENTS LIST AND SETTING

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov.26.2011

Remark: "N/A" denotes No Model Name, Serial No. or No Calibration specified.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	10 kHz (20dB Bandwidth) / 30 kHz (Channel Separation)
VB	100 kHz (20dB Bandwidth) / 100 kHz (Channel Separation)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

8.1.2 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 10KHz, VBW=100KHz, Sweep time = Auto.

8.1.3 DEVIATION FROM STANDARD

No deviation.

8.1.4 TEST SETUP




8.1.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.

Report No.: NEI-FCCP-1-1011C125 Page 49 of 65

EUT:	MINI Keyboard	Model Name :	BT1280
Temperature:	25 ℃	Relative Humidity:	51 %
Pressure :	1012 hPa	Test Voltage :	DC 3.0V
Test Mode :	CH00 / CH39 /CH78-1Mbps		

Frequency	20dB Bandwidth (KHz)	Channel Separation (MHz)	Result
2402 MHz	976.00	<= 1MHz	PASS
2441 MHz	992.00	<= 1MHz	PASS
2480 MHz	996.00	<= 1MHz	PASS



Report No.: NEI-FCCP-1-1011C125 Page 50 of 65

Neutron Engineering Inc. CH39 -1Mbps *RBW 10 kHz Delta 1 [T1] * VBW 100 kHz Ref 0 dBm *Att 10 dB SWT 10 ms 992.000000000 kHz OBW970.000000000 kHz Marker 1 [T1 -30 46 dBm .440450000 GHz Temp 1 [T1 OBW] 440510000 GHz Temp 2 [T1 OBW] -27.33 2.441480000 GHz Center 2.441 GHz 500 kHz/ Span 5 MHz Date: 24.NOV.2010 20:33:05 CH78 -1Mbps *RBW 10 kHz Delta 1 [T1] * VBW 100 kHz Ref 0 dBm *Att 10 dB SWT 10 ms 996.000000000 kHz .0000000000 MHz Marker 1 [T1 .479440000 GHz Temp 1 [T1 OBW] .479490000 GHz [T1 OBW] .480490000 GHz

Report No.: NEI-FCCP-1-1011C125 Page 51 of 65

Span 5 MHz

Center 2.48 GHz

Date: 24.NOV.2010 20:43:34

9. PEAK OUTPUT POWER TEST

9.1 APPLIED PROCEDURES / LIMIT

71. 71. 1 = 1. 1							
	FCC Part15 (15.247) , Subpart C						
Section	Test Item	Limit	Frequency Range (MHz)	Result			
15.247 (b)(1)	Peak Output Power	1watt or 30dBm	2400-2483.5	PASS			

9.1.1 MEASUREMENT INSTRUMENTS LIST AND SETTING

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov.26.2011

Remark: "N/A" denotes No Model Name, Serial No. or No Calibration specified.

9.1.2 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 1MHz, VBW= 1MHz, Sweep time = Auto.

9.1.3 DEVIATION FROM STANDARD

No deviation.

9.1.4 TEST SETUP

EUT	SPECTRUM
	ANALYZER

9.1.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.


Report No.: NEI-FCCP-1-1011C125 Page 52 of 65

EUT:	MINI Keyboard	Model Name :	BT1280
Temperature:	25 ℃	Relative Humidity:	51 %
Pressure:	1012 hPa	Test Voltage :	DC 3.0V
Test Mode :	CH00/ CH39 /CH78 -1Mbps		

Test Channel	Frequency (MHz)	Peak Output Power (dBm)	LIMIT (dBm)	LIMIT (W)
CH00	2402	-6.43	30	1
CH39	2441	-7.73	30	1
CH78	2480	-7.61	30	1



Report No.: NEI-FCCP-1-1011C125 Page 53 of 65



10. ANTENNA CONDUCTED SPURIOUS EMISSION

10.1 APPLIED PROCEDURES / LIMIT

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

10.1.1 MEASUREMENT INSTRUMENTS LIST AND SETTING

ltem	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov.26.2011

Remark: "N/A" denotes No Model Name, Serial No. or No Calibration specified.


10.1.2 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 100KHz, VBW=100KHz, Sweep time = Auto.

10.1.3 DEVIATION FROM STANDARD

No deviation.

10.1.4 TEST SETUP



10.1.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.


Report No.: NEI-FCCP-1-1011C125 Page 55 of 65


EUT:	MINI Keyboard	Model Name :	BT1280
Temperature:	25 ℃	Relative Humidity:	51 %
Pressure: 1012 hPa Test \		Test Voltage :	DC 3.0V
Test Mode :	CH00 / CH39 / CH78-1Mbps & Hopping on mode		


The max. radio frequency power in any 100kHz bandwidth outside the frequency band		The max. radio frequency power in any 100 kHz bandwidth within the frequency band.		
FREQUENCY(MHz)	POWER(dBm)	FREQUENCY(MHz)	POWER(dBm)	
2383.60	-68.06	2492.00	-68.89	
Result				


In any 100kHz bandwidth outside the frequency band, the radio frequency power is at least 20dB below that in the 100kHz bandwidth within the band that contains the highest lever of the desired power.


Report No.: NEI-FCCP-1-1011C125 Page 56 of 65























11. RF EXPOSURE TEST

11.1 APPLIED PROCEDURES / LIMIT

These devices are not exempted from compliance does not exceed the Commission's RF exposure guidelines. Unless a device operates at substantially low power levels, with a low gain antenna(s), supporting information is generally needed to establish the various potential operating configurations and exposure conditions of a transmitter and its antenna(s) in order to determine compliance with the RF exposure guidelines.

In order to demonstrate compliance with MPE requirement(see Section 2.1091),the following information is typically needed:

Calculation that estimates the minimum separation distance (20 cm or more) between an antenna and persons required to satisfy power density limits defined for free space.

Antenna installation and device operating instructions for installers(professional/unskilled users), and the parties responsible for ensuring compliance with the RF exposure requirement Any caution statements and/or warming labels that are necessary in order to comply with the exposure limits Any other RF exposure related issues that may affect MPE compliance.

FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency(RF) radiation as specified in 1.1307(b).

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz; *Plane-wave equivalent power density

11.1.1 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov.26.2011

Remark: "N/A" denotes No Model Name, Serial No. or No Calibration specified.

Report No.: NEI-FCCP-1-1011C125 Page 62 of 65

11.1.2 MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

P :power input to the antenna in Mw

EIRP : Equivalent(effective) isotropic radiated power.

S :power density mW/cm²

G ;numeric gain of antenna relative to isotropic radiator

R :distance to centre of radiation in cm

FCC radio frequency exposure limits may be exceeded at distances closer than r cm from the antenna of this device

$$r = \sqrt{\frac{PG}{4\pi S}} = \sqrt{\frac{EIRP}{4\pi S}}$$

11.1.3 DEVIATION FROM STANDARD

No deviation.

11.1.4 TEST SETUP

EUT SPECTRUM ANALYZER

11.1.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.

Report No.: NEI-FCCP-1-1011C125 Page 63 of 65

EUT:	MINI Keyboard	Model Name :	BT1280
Temperature:	25 ℃	Relative Humidity:	51 %
Pressure:	1012 hPa	Test Voltage :	DC 3.0V
Test Mode :	CH00 (2402 MHz), CH39(2441	MHz), CH78 (2480	MHz) -1Mbps

Frequency (MHz)	Antenna Gain (dBi)	Peak Output Power (dBm)	Calculated EIRP (mW)	FCC Threshold (mW)	Test Result
2402	2.78	-6.43	0.4315	24.98	Complies
2441	2.78	-7.73	0.3199	24.58	Complies
2480	2.78	-7.61	0.3289	24.19	Complies


Note: Shown calculated EIRP is "worst case" scenario (peak power value) showing definite compliance with the threshold level.

Report No.: NEI-FCCP-1-1011C125 Page 64 of 65



12. EUT TEST PHOTO

Radiated Measurement Photos





Report No.: NEI-FCCP-1-1011C125 Page 65 of 65