Electronic Warfare Associates, Inc.

TEST REPORT FOR

Access Point Model: SKEY-KC

Tested To The Following Standards:

FCC Part 15 Subpart C Sections 15.207, 15.249 and RSS 210 Issue 8

Report No.: 94579-11

Date of issue: August 19, 2013



This test report bears the accreditation symbol indicating that the testing performed herein meets the test and reporting requirements of ISO/IEC 17025 under the applicable scope of EMC testing for CKC Laboratories, Inc.

We strive to create long-term, trust based relationships by providing sound, adaptive, customer first testing services. We embrace each of our customers' unique EMC challenges, not as an interruption to set processes, but rather as the reason we are in business.



TABLE OF CONTENTS

| Administrative Information | 3 |
|--|----|
| Test Report Information | 3 |
| Report Authorization | 3 |
| Test Facility Information | 4 |
| Software Versions | 4 |
| Site Registration & Accreditation Information | 4 |
| Summary of Results | 5 |
| Conditions During Testing | 5 |
| Equipment Under Test | 6 |
| Peripheral Devices | 6 |
| FCC Part 15 Subpart C | 7 |
| 15.31(e) Voltage Variations | 7 |
| 15.207 AC Conducted Emissions | 9 |
| 15.249(a)(b) RF Power Output | 18 |
| -20dBc Occupied Bandwidth | 22 |
| 15.249(a)(d) Field Strength of Harmonics and Spurious Emissions / Bandedge | 25 |
| RSS-210 | 40 |
| 99 % Bandwidth | 40 |
| Supplemental Information | 43 |
| Measurement Uncertainty | 43 |
| Emissions Test Details | 43 |



ADMINISTRATIVE INFORMATION

Test Report Information

REPORT PREPARED FOR: REPORT PREPARED BY:

Electronic Warfare Associates, Inc.

13873 Park Center Rd.

Herndon, VA 20171

Dianne Dudley

CKC Laboratories, Inc.

5046 Sierra Pines Drive

Mariposa, CA 95338

Representative: Jason Pizzillo Project Number: 94579

Customer Reference Number: P210000039

DATE OF EQUIPMENT RECEIPT: July 22, 2013

DATE(S) OF TESTING: July 22 - August 9, 2013

Report Authorization

The test data contained in this report documents the observed testing parameters pertaining to and are relevant for only the sample equipment tested in the agreed upon operational mode(s) and configuration(s) as identified herein. Compliance assessment remains the client's responsibility. This report may not be used to claim product endorsement by A2LA or any government agencies. This test report has been authorized for release under quality control from CKC Laboratories, Inc.

Steve Behm

Director of Quality Assurance & Engineering Services CKC Laboratories, Inc.

Steve 2 Be

Page 3 of 44 Report No.: 94579-11



Test Facility Information



Our laboratories are configured to effectively test a wide variety of product types. CKC utilizes first class test equipment, anechoic chambers, data acquisition and information services to create accurate, repeatable and affordable test results.

TEST LOCATION(S): CKC Laboratories, Inc. 1120 Fulton Place Fremont, CA 94539

Software Versions

| CKC Laboratories Proprietary Software | Version |
|---------------------------------------|---------|
| EMITest Emissions | 5.00.14 |
| Immunity | 5.00.07 |

Site Registration & Accreditation Information

| Location | CB # | TAIWAN | CANADA | FCC | JAPAN | |
|----------|--------|----------------|---------|--------|--------|--|
| Fremont | US0082 | SL2-IN-E-1148R | 3082B-1 | 958979 | A-0149 | |

Page 4 of 44 Report No.: 94579-11



SUMMARY OF RESULTS

Standard / Specification: FCC Part 15 Subpart C 15.207, 15.249 and RSS 210 Issue 8

| Description | Test Procedure/Method | Results |
|--|--|---------|
| | | |
| Voltage Variation | FCC Part 15 Subpart C Section 15.31(e) / ANSI C63.4 (2003) | Pass |
| | | |
| Conducted Emissions | FCC Part 15 Subpart C Section 15.207 / ANSI C63.4 (2003) | Pass |
| | | |
| RF Power Output | FCC Part 15 Subpart C Section 15.249(a)(b) / ANSI C63.4 (2003) | Pass |
| | | |
| -20dBc Occupied Bandwidth | FCC Part 15 Subpart C Section 15.249/ 2.1049 / ANSI C63.4 (2003) | Pass |
| | | |
| Field Strength of Harmonics and Spurious Emissions / Bandedge | FCC Part 15 Subpart C Section 15.249(a)(d) / ANSI C63.4 (2003) | Pass |
| | | |
| 99 % Bandwidth | RSS 210 Issue 8 | Pass |
| | | |

Conditions During Testing

This list is a summary of the conditions noted for or modifications made to the equipment during testing.

Summary of Conditions

The customer changed the routing of the differential traces in the Ethernet section of the EUT during spurious emissions testing.

Page 5 of 44 Report No.: 94579-11



EQUIPMENT UNDER TEST (EUT)

EQUIPMENT UNDER TEST

Access Point AC/DC Power Adapter

Manuf: Electronic Warfare Associates, Inc. Manuf: TRIAD

Model: SKEY-KC Model: WSU075-1000 Serial: ENG1 / ENG2 Serial: E345519

PERIPHERAL DEVICES

The EUT was not tested with peripheral devices.

Page 6 of 44 Report No.: 94579-11



FCC PART 15 SUBPART C

This report contains EMC emissions test results under United States Federal Communications Commission (FCC) 47 CFR 15C requirements for Unlicensed Radio Frequency Devices, Subpart C - Intentional Radiators.

15.31(e) Voltage Variations

Test Conditions / Setup

Test Location: CKC Laboratories, Inc. • 1120 Fulton Place • Fremont, CA 94539 • (510) 249-1170

Customer: Electronic Warfare Associates, Inc.

Specification: 15.31e

Work Order #: 94579 Date: 7/27/2013
Test Type: Radiated Scan Time: 10:16:39
Equipment: Access Point Sequence#: 11

Manufacturer: Electronic Warfare Associates, Inc. Tested By: Hieu Song Nguyenpham

Model: SKEY-KC S/N: ENG1

Test Equipment:

| | r | | | | |
|----|----------|-------------------|-----------|------------------|--------------|
| ID | Asset # | Description | Model | Calibration Date | Cal Due Date |
| T1 | AN00852 | Biconilog Antenna | CBL 6111C | 11/28/2012 | 11/28/2014 |
| T2 | ANP00880 | Cable | RG214U | 7/30/2012 | 7/30/2014 |
| Т3 | ANP05300 | Cable | RG214/U | 3/25/2013 | 3/25/2015 |
| | AN02668 | Spectrum Analyzer | E4446A | 2/22/2013 | 2/22/2015 |

Equipment Under Test (* = EUT):

| ` | | | | |
|---------------------|--------------------|-------------|---------|--|
| Function | Manufacturer | Model # | S/N | |
| Access Point* | Electronic Warfare | SKEY-KC | ENG1 | |
| | Associates, Inc. | | | |
| AC/DC Power Adapter | TRIAD | WSU075-1000 | E345519 | |

Support Devices:

| Function | Manufacturer | Model # | S/N | |
|----------|--------------|---------|-----|--|
|----------|--------------|---------|-----|--|

Page 7 of 44 Report No.: 94579-11



Test Conditions / Notes:

Software Used: C and is permanently burned into memory as binary machine language (two different processors, PIC and CC1110)

Temperature: 23.3°C Humidity: 39 %

Atmospheric Pressure: 101.1 kPa

High Clock: 26MHz

transmit operating frequency= 923MHz

RF Output= 0dBm

Gain of the antenna= +1 dBi

The EUT is a fixed device. It is placed on the 80cm Styrofoam table. The EUT is set in continue transmit. RJ 45 cable is looped back to active RJ 45 port.

15.31e: Adjust the power voltage +/- 15% (102V and 138V), the RF output power is not changing.

Page 8 of 44 Report No.: 94579-11



15.207 AC Conducted Emissions

Test Data Sheets

Test Location: CKC Laboratories, Inc. • 1120 Fulton Place • Fremont, CA 94539 • (510) 249-1170

Customer: **Electronic Warfare Associates, Inc.**

Specification: 15.207 AC Mains - Average

Work Order #: 94579 Date: 7/25/2013
Test Type: Conducted Emissions Time: 16:50:47
Equipment: Access Point Sequence#: 7

Manufacturer: Electronic Warfare Associates, Inc. Tested By: Hieu Song Nguyenpham

Model: SKEY-KC 120V 60Hz

S/N: ENG1

Test Equipment:

| ID | Asset # | Description | Model | Calibration Date | Cal Due Date |
|----|----------|-------------------|--------------|------------------|--------------|
| T1 | ANP01211 | Attenuator | PE7002-10 | 4/2/2013 | 4/2/2015 |
| T2 | ANP00880 | Cable | RG214U | 7/30/2012 | 7/30/2014 |
| Т3 | ANP05300 | Cable | RG214/U | 3/25/2013 | 3/25/2015 |
| | AN02668 | Spectrum Analyzer | E4446A | 2/22/2013 | 2/22/2015 |
| T4 | ANP05258 | High Pass Filter | HE9615-150K- | 12/6/2012 | 12/6/2014 |
| | | | 50-720B | | |
| T5 | AN00493 | 50uH LISN-L1 (L) | 3816/NM | 3/4/2013 | 3/4/2015 |
| | | Loss W/O European | | | |
| | | Adapter | | | |
| | AN00493 | 50uH LISN-L(2) N | 3816/NM | 3/4/2013 | 3/4/2015 |
| | | Loss W/O European | | | |
| | | Adapter | | | |

Equipment Under Test (* = EUT):

| Equipment Chaci Test (| – EUI). | | | |
|------------------------|-------------------------------------|-------------|---------|--|
| Function | Manufacturer | Model # | S/N | |
| Access Point* | Electronic Warfare Associates, Inc. | SKEY-KC | ENG1 | |
| AC/DC Power Adapter | TRIAD | WSU075-1000 | E345519 | |

Support Devices:

Page 9 of 44 Report No.: 94579-11



Test Conditions / Notes:

Conducted Emission

Frequency Range: 150kHz to 30MHz

Software Used: C and is permanently burned into memory as binary machine language (two different processors,

PIC and CC1110)

Temperature: 23.3°C Humidity: 39 %

Atmospheric Pressure: 101.1 kPa

High Clock: 26MHz

Transmitting operating frequency= 923MHz

RF Output= 0dBm

Gain of the antenna= +1 dBi

The EUT is a fixed device. It is placed on the 80cm Styrofoam table and set continuously transmitting. The EUT is set in continue transmit. RJ 45 cable is looped back to active RJ 45 port.

Ext Attn: 0 dB

| Measurement Data: Reading listed by margin. | | | | | rain | Test Lead: Black | | | | | |
|---|----------|------|--------------|------|------|------------------|-------|------|------|--------|-------|
| # | | | T1 | T2 | T3 | T4 | Dist | | | Morain | Polar |
| # | Freq | Rdng | T5 | | | | | Corr | Spec | Margin | Polaf |
| | MHz | dΒμV | dB | dB | dB | dB | Table | dΒμV | dΒμV | dB | Ant |
| 1 | 473.607k | 34.6 | +9.6 +0.1 | +0.1 | +0.0 | +0.1 | +0.0 | 44.5 | 46.5 | -2.0 | Black |
| 2 | 711.403k | 30.5 | +9.6 +0.1 | +0.1 | +0.0 | +0.1 | +0.0 | 40.4 | 46.0 | -5.6 | Black |
| 3 | 706.313k | 30.5 | +9.6 +0.1 | +0.1 | +0.0 | +0.1 | +0.0 | 40.4 | 46.0 | -5.6 | Black |
| 4 | 708.494k | 30.2 | +9.6 +0.1 | +0.1 | +0.0 | +0.1 | +0.0 | 40.1 | 46.0 | -5.9 | Black |
| 5 | 1.894M | 30.1 | +9.6 +0.1 | +0.1 | +0.0 | +0.1 | +0.0 | 40.0 | 46.0 | -6.0 | Black |
| 6 | 403.795k | 31.9 | +9.6 +0.1 | +0.1 | +0.0 | +0.0 | +0.0 | 41.7 | 47.8 | -6.1 | Black |
| 7 | 2.702M | 29.8 | +9.6 +0.1 | +0.1 | +0.0 | +0.1 | +0.0 | 39.7 | 46.0 | -6.3 | Black |
| 8 | 1.260M | 29.5 | +9.6 +0.1 | +0.1 | +0.0 | +0.1 | +0.0 | 39.4 | 46.0 | -6.6 | Black |
| 9 | 741.946k | 29.5 | +9.5 +0.1 | +0.1 | +0.0 | +0.1 | +0.0 | 39.3 | 46.0 | -6.7 | Black |
| 10 | 754.308k | 29.2 | +9.6 +0.1 | +0.1 | +0.0 | +0.2 | +0.0 | 39.2 | 46.0 | -6.8 | Black |
| 11 | 1.354M | 29.2 | +9.6 +0.1 | +0.1 | +0.0 | +0.1 | +0.0 | 39.1 | 46.0 | -6.9 | Black |
| 12 | 874.297k | 29.1 | +9.6 +0.1 | +0.1 | +0.0 | +0.2 | +0.0 | 39.1 | 46.0 | -6.9 | Black |
| 13 | 1.200M | 29.2 | +9.6 +0.1 | +0.1 | +0.0 | +0.1 | +0.0 | 39.1 | 46.0 | -6.9 | Black |
| 14 | 631.410k | 29.0 | +9.7 +0.1 | +0.1 | +0.0 | +0.1 | +0.0 | 39.0 | 46.0 | -7.0 | Black |


Page 10 of 44 Report No.: 94579-11



| 15 1.27 | 73M 29.1 | +9.6 | +0.1 | +0.0 | +0.1 | +0.0 | 39.0 | 46.0 | -7.0 | Black |
|----------|-----------|------|------|------|------|------|------|------|-------|-------|
| | | +0.1 | | | | | | | | |
| 16 810.3 | 303k 28.9 | +9.6 | +0.1 | +0.0 | +0.2 | +0.0 | 38.9 | 46.0 | -7.1 | Black |
| | | +0.1 | | | | | | | | |
| 17 468.3 | 305k 31.8 | +9.6 | +0.1 | +0.0 | +0.1 | +0.0 | 41.7 | 56.5 | -14.8 | Black |
| QP | | +0.1 | | | | | | | | |
| 18 351.1 | .89k 33.5 | +9.6 | +0.1 | +0.0 | +0.1 | +0.0 | 43.4 | 58.9 | -15.5 | Black |
| QP | | +0.1 | | | | | | | | |
| 19 269.3 | 350k 35.0 | +9.6 | +0.1 | +0.0 | +0.2 | +0.0 | 45.0 | 61.1 | -16.1 | Black |
| QP | | +0.1 | | | | | | | | |
| 20 201.0 | 000k 37.4 | +9.6 | +0.1 | +0.0 | +0.2 | +0.0 | 47.4 | 63.6 | -16.2 | Black |
| QP | | +0.1 | | | | | | | | |
| 21 351.1 | 89k 19.0 | +9.6 | +0.1 | +0.0 | +0.1 | +0.0 | 28.9 | 48.9 | -20.0 | Black |
| Ave | | +0.1 | | | | | | | | |
| ^ 351.1 | 89k 37.7 | +9.6 | +0.1 | +0.0 | +0.1 | +0.0 | 47.6 | 48.9 | -1.3 | Black |
| | | +0.1 | | | | | | | | |
| ^ 351.1 | 89k 36.4 | +9.6 | +0.1 | +0.0 | +0.1 | +0.0 | 46.3 | 48.9 | -2.6 | Black |
| | | +0.1 | | | | | | | | |
| 24 468.3 | 305k 14.4 | +9.6 | +0.1 | +0.0 | +0.1 | +0.0 | 24.3 | 46.5 | -22.2 | Black |
| Ave | | +0.1 | | | | | | | | |
| ^ 468.3 | 35.2 35.2 | +9.6 | +0.1 | +0.0 | +0.1 | +0.0 | 45.1 | 46.5 | -1.4 | Black |
| | | +0.1 | | | | | | | | |
| 26 269.3 | 350k 18.3 | +9.6 | +0.1 | +0.0 | +0.2 | +0.0 | 28.3 | 51.1 | -22.8 | Black |
| Ave | | +0.1 | | | | | | | | |
| ^ 269.3 | 350k 40.1 | +9.6 | +0.1 | +0.0 | +0.2 | +0.0 | 50.1 | 51.1 | -1.0 | Black |
| | | +0.1 | | | | | | | | |
| ^ 269.3 | 350k 37.6 | +9.6 | +0.1 | +0.0 | +0.2 | +0.0 | 47.6 | 51.1 | -3.5 | Black |
| | | +0.1 | | | | | | | | |
| 29 201.0 | 000k 19.6 | +9.6 | +0.1 | +0.0 | +0.2 | +0.0 | 29.6 | 53.6 | -24.0 | Black |
| Ave | | +0.1 | | | | | | | | |
| ^ 201.0 | 000k 43.0 | +9.6 | +0.1 | +0.0 | +0.2 | +0.0 | 53.0 | 53.6 | -0.6 | Black |
| | | +0.1 | | | | | | | | |
| ^ 201.0 | 000k 40.2 | +9.6 | +0.1 | +0.0 | +0.2 | +0.0 | 50.2 | 53.6 | -3.4 | Black |
| | | +0.1 | | | | | | | | |
| | | | | | | | | | | |



CKC Laboratories, Inc. Date: 7/25/2013 Time: 16:50:47 Electronic Warfare Associates, Inc WO#: 94579 Test Lead: Black 120V 60Hz Sequence#: 7





Test Location: CKC Laboratories, Inc. • 1120 Fulton Place • Fremont, CA 94539 • (510) 249-1170

Customer: **Electronic Warfare Associates, Inc.**

Specification: 15.207 AC Mains - Average

Work Order #: 94579 Date: 7/25/2013
Test Type: Conducted Emissions Time: 4:52:21 PM

Equipment: Access Point Sequence#: 8

Manufacturer: Electronic Warfare Associates, Inc. Tested By: Hieu Song Nguyenpham

SKEY-KC 120V 60Hz

S/N: ENG1

Test Equipment:

Model:

| _ | | | | | |
|----|----------|-------------------|--------------|------------------|--------------|
| ID | Asset # | Description | Model | Calibration Date | Cal Due Date |
| T1 | ANP01211 | Attenuator | PE7002-10 | 4/2/2013 | 4/2/2015 |
| T2 | ANP00880 | Cable | RG214U | 7/30/2012 | 7/30/2014 |
| T3 | ANP05300 | Cable | RG214/U | 3/25/2013 | 3/25/2015 |
| | AN02668 | Spectrum Analyzer | E4446A | 2/22/2013 | 2/22/2015 |
| T4 | ANP05258 | High Pass Filter | HE9615-150K- | 12/6/2012 | 12/6/2014 |
| | | | 50-720B | | |
| | AN00493 | 50uH LISN-L1 (L) | 3816/NM | 3/4/2013 | 3/4/2015 |
| | | Loss W/O European | | | |
| | | Adapter | | | |
| T5 | AN00493 | 50uH LISN-L(2) N | 3816/NM | 3/4/2013 | 3/4/2015 |
| | | Loss W/O European | | | |
| | | Adapter | | | |

Equipment Under Test (* = EUT):

| Function | Manufacturer | Model # | S/N | |
|---------------------|--------------------|-------------|---------|--|
| Access Point* | Electronic Warfare | SKEY-KC | ENG1 | |
| | Associates, Inc. | | | |
| AC/DC Power Adapter | TRIAD | WSU075-1000 | E345519 | |

Support Devices:

| Function | Manufacturer | Model # | C/NI |
|----------|--------------|----------|--------------|
| runcuon | Manufacturer | MIOUCI # | 3/1 N |

Test Conditions / Notes:

Conducted Emission

Frequency Range: 150kHz to 30MHz

Software Used: C and is permanently burned into memory as binary machine language (two different processors, PIC and CC1110)

Temperature: 23.3°C Humidity: 39 %

Atmospheric Pressure: 101.1 kPa

High Clock: 26MHz

Transmitting operating frequency= 923MHz

RF Output= 0dBm

Gain of the antenna= +1 dBi

The EUT is a fixed device. It is placed on the 80cm Styrofoam table and set continuously transmitting. The EUT is set in continue transmit. RJ 45 cable is looped back to active RJ 45 port.

Page 13 of 44 Report No.: 94579-11



Ext Attn: 0 dB

| Measur | rement Data: | Re | eading lis | ted by ma | argin. | | | Test Lea | d: White | | |
|--------|--------------|-----------|--------------|-----------|--------|------|-------|-----------|----------|--------|-------|
| # | Freq | Rdng | T1 T5 | T2 | T3 | T4 | Dist | Corr | Spec | Margin | Polar |
| | MHz | $dB\mu V$ | dB | dB | dB | dB | Table | $dB\mu V$ | dΒμV | dB | Ant |
| 1 | 469.970k | 32.2 | +9.6 +0.6 | +0.1 | +0.0 | +0.1 | +0.0 | 42.6 | 46.5 | -3.9 | White |
| 2 | 205.267k | 38.5 | +9.6 +0.6 | +0.1 | +0.0 | +0.2 | +0.0 | 49.0 | 53.4 | -4.4 | White |
| 3 | 207.448k | 38.4 | +9.6 +0.6 | +0.1 | +0.0 | +0.2 | +0.0 | 48.9 | 53.3 | -4.4 | White |
| 4 | 472.878k | 31.7 | +9.6 +0.6 | +0.1 | +0.0 | +0.1 | +0.0 | 42.1 | 46.5 | -4.4 | White |
| 5 | 209.630k | 38.2 | +9.6 +0.6 | +0.1 | +0.0 | +0.2 | +0.0 | 48.7 | 53.2 | -4.5 | White |
| 6 | 467.788k | 31.7 | +9.6 +0.6 | +0.1 | +0.0 | +0.1 | +0.0 | 42.1 | 46.6 | -4.5 | White |
| 7 | 216.902k | 37.7 | +9.6 +0.6 | +0.1 | +0.0 | +0.2 | +0.0 | 48.2 | 52.9 | -4.7 | White |
| 8 | 475.787k | 31.3 | +9.6 +0.6 | +0.1 | +0.0 | +0.1 | +0.0 | 41.7 | 46.4 | -4.7 | White |
| 9 | 275.806k | 35.5 | +9.6 +0.6 | +0.1 | +0.0 | +0.2 | +0.0 | 46.0 | 50.9 | -4.9 | White |
| 10 | 348.526k | 33.6 | +9.6 +0.6 | +0.1 | +0.0 | +0.1 | +0.0 | 44.0 | 49.0 | -5.0 | White |
| 11 | 345.617k | 33.7 | +9.6 +0.6 | +0.1 | +0.0 | +0.1 | +0.0 | 44.1 | 49.1 | -5.0 | White |
| 12 | 425.610k | 32.0 | +9.6 +0.6 | +0.1 | +0.0 | +0.0 | +0.0 | 42.3 | 47.3 | -5.0 | White |
| 13 | 352.162k | 33.5 | +9.6 +0.6 | +0.1 | +0.0 | +0.1 | +0.0 | 43.9 | 48.9 | -5.0 | White |
| 14 | 350.708k | 33.4 | +9.6 +0.6 | +0.1 | +0.0 | +0.1 | +0.0 | 43.8 | 48.9 | -5.1 | White |
| 15 | 284.532k | 35.0 | +9.6 +0.6 | +0.1 | +0.0 | +0.2 | +0.0 | 45.5 | 50.7 | -5.2 | White |
| 16 | 341.254k | 33.5 | +9.6 +0.6 | +0.1 | +0.0 | +0.1 | +0.0 | 43.9 | 49.2 | -5.3 | White |
| 17 | 281.623k | 35.0 | +9.6 +0.6 | +0.1 | +0.0 | +0.2 | +0.0 | 45.5 | 50.8 | -5.3 | White |
| 18 | 272.897k | 35.2 | +9.6 +0.6 | +0.1 | +0.0 | +0.2 | +0.0 | 45.7 | 51.0 | -5.3 | White |
| 19 | 355.798k | 33.1 | +9.6 +0.6 | +0.1 | +0.0 | +0.1 | +0.0 | 43.5 | 48.8 | -5.3 | White |
| 20 | 347.072k | 33.3 | +9.6 +0.6 | +0.1 | +0.0 | +0.1 | +0.0 | 43.7 | 49.0 | -5.3 | White |
| 21 | 343.436k | 33.4 | +9.6 +0.6 | +0.1 | +0.0 | +0.1 | +0.0 | 43.8 | 49.1 | -5.3 | White |




| 22 | 270.715k | 35.2 | +9.6 +0.6 | +0.1 | +0.0 | +0.2 | +0.0 | 45.7 | 51.1 | -5.4 | White |
|----|----------|------|--------------|------|------|------|------|------|------|------|-------|
| 23 | 219.084k | 36.9 | +9.6 +0.6 | +0.1 | +0.0 | +0.2 | +0.0 | 47.4 | 52.9 | -5.5 | White |
| 24 | 279.442k | 34.8 | +9.6 +0.6 | +0.1 | +0.0 | +0.2 | +0.0 | 45.3 | 50.8 | -5.5 | White |
| 25 | 339.073k | 33.3 | +9.6 +0.6 | +0.1 | +0.0 | +0.1 | +0.0 | 43.7 | 49.2 | -5.5 | White |
| 26 | 485.968k | 30.2 | +9.6 +0.6 | +0.1 | +0.0 | +0.1 | +0.0 | 40.6 | 46.2 | -5.6 | White |
| 27 | 483.787k | 30.3 | +9.6 +0.6 | +0.1 | +0.0 | +0.1 | +0.0 | 40.7 | 46.3 | -5.6 | White |
| 28 | 1.196M | 30.0 | +9.6 +0.6 | +0.1 | +0.0 | +0.1 | +0.0 | 40.4 | 46.0 | -5.6 | White |
| 29 | 491.786k | 30.1 | +9.6 +0.6 | +0.1 | +0.0 | +0.1 | +0.0 | 40.5 | 46.1 | -5.6 | White |
| 30 | 286.714k | 34.4 | +9.6 +0.6 | +0.1 | +0.0 | +0.2 | +0.0 | 44.9 | 50.6 | -5.7 | White |
| 31 | 1.256M | 29.8 | +9.6 +0.6 | +0.1 | +0.0 | +0.1 | +0.0 | 40.2 | 46.0 | -5.8 | White |
| 32 | 357.980k | 32.5 | +9.6 +0.6 | +0.1 | +0.0 | +0.1 | +0.0 | 42.9 | 48.8 | -5.9 | White |
| 33 | 1.758M | 29.7 | +9.6 +0.6 | +0.1 | +0.0 | +0.1 | +0.0 | 40.1 | 46.0 | -5.9 | White |
| 34 | 1.881M | 29.7 | +9.6 +0.6 | +0.1 | +0.0 | +0.1 | +0.0 | 40.1 | 46.0 | -5.9 | White |
| 35 | 706.312k | 29.6 | +9.6 +0.6 | +0.1 | +0.0 | +0.1 | +0.0 | 40.0 | 46.0 | -6.0 | White |
| 36 | 1.826M | 29.6 | +9.6 +0.6 | +0.1 | +0.0 | +0.1 | +0.0 | 40.0 | 46.0 | -6.0 | White |
| 37 | 423.428k | 31.0 | +9.6 +0.6 | +0.1 | +0.0 | +0.0 | +0.0 | 41.3 | 47.4 | -6.1 | White |
| 38 | 703.403k | 29.4 | +9.6 +0.6 | +0.1 | +0.0 | +0.1 | +0.0 | 39.8 | 46.0 | -6.2 | White |
| 39 | 699.040k | 29.3 | +9.6 +0.6 | +0.1 | +0.0 | +0.1 | +0.0 | 39.7 | 46.0 | -6.3 | White |
| 40 | 696.131k | 29.3 | +9.6 +0.6 | +0.1 | +0.0 | +0.1 | +0.0 | 39.7 | 46.0 | -6.3 | White |
| 41 | 488.877k | 29.5 | +9.6 +0.6 | +0.1 | +0.0 | +0.1 | +0.0 | 39.9 | 46.2 | -6.3 | White |
| 42 | 1.183M | 29.3 | +9.6 +0.6 | +0.1 | +0.0 | +0.1 | +0.0 | 39.7 | 46.0 | -6.3 | White |
| 43 | 1.855M | 29.3 | +9.6 +0.6 | +0.1 | +0.0 | +0.1 | +0.0 | 39.7 | 46.0 | -6.3 | White |
| 44 | 1.804M | 29.3 | +9.6 +0.6 | +0.1 | +0.0 | +0.1 | +0.0 | 39.7 | 46.0 | -6.3 | White |
| 45 | 1.277M | 29.3 | +9.6 +0.6 | +0.1 | +0.0 | +0.1 | +0.0 | 39.7 | 46.0 | -6.3 | White |
| 46 | 693.949k | 29.2 | +9.6 +0.6 | +0.1 | +0.0 | +0.1 | +0.0 | 39.6 | 46.0 | -6.4 | White |
| 47 | 1.243M | 29.2 | +9.6 +0.6 | +0.1 | +0.0 | +0.1 | +0.0 | 39.6 | 46.0 | -6.4 | White |
| I | | | | | | | | | | | |

Page 15 of 44 Report No.: 94579-11




| 48 | 493.967k | 29.2 | +9.6 | +0.1 | +0.0 | +0.1 | +0.0 | 39.6 | 46.1 | -6.5 | White |
|----|----------|------|------|------|------|------|------|------|------|------|-------|
| | | | +0.6 | | | | | | | | |
| 49 | 557.962k | 29.1 | +9.6 | +0.1 | +0.0 | +0.1 | +0.0 | 39.5 | 46.0 | -6.5 | White |
| | | | +0.6 | | | | | | | | |
| 50 | 708.493k | 29.1 | +9.6 | +0.1 | +0.0 | +0.1 | +0.0 | 39.5 | 46.0 | -6.5 | White |
| | | | +0.6 | | | | | | | | |


CKC Laboratories, Inc. Date: 7/25/2013 Time: 4:52:21 PM. Electronic Warfare Associates, Inc WO#: 94579 Test Lead: White 120V 60Hz Sequence#: 8





Test Setup Photos







15.249(a)(b) RF Power Output

Test Conditions / Setup

Test Location: CKC Laboratories, Inc. • 1120 Fulton Place • Fremont, CA 94539 • (510) 249-1170

Customer: Electronic Warfare Associates, Inc.

Specification: 15.249 Carrier and Spurious Emissions (902-928 MHz Transmitter)
Work Order #: 94579 Date: 7/27/2013
Test Type: Radiated Scan Time: 10:16:39
Equipment: Access Point Sequence#: 11

Manufacturer: Electronic Warfare Associates, Inc. Tested By: Hieu Song Nguyenpham

Model: SKEY-KC S/N: ENG1

Test Equipment:

| ID | Asset # | Description | Model | Calibration Date | Cal Due Date |
|----|----------|-------------------|-----------|------------------|--------------|
| T1 | AN00852 | Biconilog Antenna | CBL 6111C | 11/28/2012 | 11/28/2014 |
| T2 | ANP00880 | Cable | RG214U | 7/30/2012 | 7/30/2014 |
| Т3 | ANP05300 | Cable | RG214/U | 3/25/2013 | 3/25/2015 |
| | AN02668 | Spectrum Analyzer | E4446A | 2/22/2013 | 2/22/2015 |

Equipment Under Test (* = EUT):

| Function | Manufacturer | Model # | S/N | |
|---------------------|--------------------|-------------|---------|--|
| Access Point* | Electronic Warfare | SKEY-KC | ENG1 | |
| | Associates, Inc. | | | |
| AC/DC Power Adapter | TRIAD | WSU075-1000 | E345519 | |

Support Devices:

| r | MC | N/ 1.1.1/ | CAI |
|----------|--------------|-----------|-----|
| Function | Manufacturer | Model # | S/N |

Test Conditions / Notes:

Fundamental of the EUT

Software Used: C and is permanently burned into memory as binary machine language (two different processors, PIC and CC1110)

Temperature: 23.3°C Humidity: 39 %

Atmospheric Pressure: 101.1 kPa

High Clock: 26MHz

transmit operating frequency= 923MHz

RF Output= 0dBm

Gain of the antenna= +1 dBi

The EUT is a fixed device. It is placed on the 80cm Styrofoam table and set continuously transmitting. A RJ 45 cable is looped back to active RJ 45 port.


Page 18 of 44 Report No.: 94579-11



Test Data


Ext Attn: 0 dB

| Measu | Measurement Data: | | Reading listed by margin. | | | Test Distance: 3 Meters | | | | | |
|-------|-------------------|-----------|---------------------------|------|------|-------------------------|-------|----------------|----------------|--------|-------|
| # | Freq | Rdng | T1 | T2 | T3 | | Dist | Corr | Spec | Margin | Polar |
| | MHz | $dB\mu V$ | dB | dB | dB | dB | Table | $dB\mu V/m \\$ | $dB\mu V/m \\$ | dB | Ant |
| 1 | 923.000M | 61.5 | +22.7 | +3.5 | +0.9 | | +0.0 | 88.6 | 94.0 | -5.4 | Horiz |
| 2 | 923.000M | 55.4 | +22.7 | +3.5 | +0.9 | | +0.0 | 82.5 | 94.0 | -11.5 | Vert |



Horizontal







Vertical



Test Setup Photos







-20dBc Occupied Bandwidth

Test Conditions / Setup

Test Location: CKC Laboratories, Inc. • 1120 Fulton Place • Fremont, CA 94539 • (510) 249-1170

Customer: Electronic Warfare Associates, Inc.

Specification: **OBW**

Work Order #: 94579 Date: 7/27/2013
Test Type: Radiated Scan Time: 10:16:39
Equipment: Access Point Sequence#: 11

Manufacturer: Electronic Warfare Associates, Inc. Tested By: Hieu Song Nguyenpham

Model: SKEY-KC S/N: ENG1

Test Equipment:

| ID | Asset # | Description | Model | Calibration Date | Cal Due Date |
|----|----------|-------------------|-----------|------------------|--------------|
| T1 | AN00852 | Biconilog Antenna | CBL 6111C | 11/28/2012 | 11/28/2014 |
| T2 | ANP00880 | Cable | RG214U | 7/30/2012 | 7/30/2014 |
| Т3 | ANP05300 | Cable | RG214/U | 3/25/2013 | 3/25/2015 |
| | AN02668 | Spectrum Analyzer | E4446A | 2/22/2013 | 2/22/2015 |

Equipment Under Test (* = EUT):

| -1F | — /- | | | |
|---------------------|--------------------|-------------|---------|--|
| Function | Manufacturer | Model # | S/N | |
| Access Point* | Electronic Warfare | SKEY-KC | ENG1 | |
| | Associates, Inc. | | | |
| AC/DC Power Adapter | TRIAD | WSU075-1000 | E345519 | |

Support Devices:

| Function | Manufacturer | Model # | S/N |
|----------|--------------|---------|-----|
| | | | 121 |

Test Conditions / Notes:

Software Used: C and is permanently burned into memory as binary machine language (two different processors, PIC and CC1110)

Temperature: 23.3°C Humidity: 39 %

Atmospheric Pressure: 101.1 kPa

High Clock: 26MHz

transmit operating frequency= 923MHz

RF Output= 0dBm


Gain of the antenna= +1 dBi

The EUT is a fixed device. It is placed on the 80cm Styrofoam table. The EUT is set in continue transmit. RJ 45 cable is looped back to active RJ 45 port.

Page 22 of 44 Report No.: 94579-11



Test Data




Page 23 of 44 Report No.: 94579-11



Test Setup Photos







15.249(a)(d) Field Strength of Harmonics and Spurious Emissions / Bandedge

Test Data Sheets

Test Location: CKC Laboratories, Inc. • 1120 Fulton Place • Fremont, CA 94539 • (510) 249-1170

Customer: Electronic Warfare Associates, Inc.

Specification: Under #: 15.249 Carrier and Spurious Emissions (902-928 MHz Transmitter)

Work Order #: Date: 8/9/2013

Test Type: Radiated Scan Time: 14:23:06

Equipment: Access Point Sequence#: 28

Manufacturer: Electronic Warfare Associates, Inc. Tested By: Hieu Song Nguyenpham

Model: SKEY-KC S/N: ENG2

Test Equipment:

| ID | Asset # | Description | Model | Calibration Date | Cal Due Date |
|----|----------|-------------------|---------|------------------|--------------|
| T1 | AN00432 | Loop Antenna | 6502 | 4/2/2013 | 4/2/2015 |
| T2 | ANP00880 | Cable | RG214U | 7/30/2012 | 7/30/2014 |
| Т3 | ANP05300 | Cable | RG214/U | 3/25/2013 | 3/25/2015 |
| | AN02870 | Spectrum Analyzer | E4440A | 12/21/2011 | 12/21/2013 |

Equipment Under Test (* = EUT):

| 1 1 | - /: | | | |
|---------------------|--------------------|-------------|---------|---|
| Function | Manufacturer | Model # | S/N | |
| AC/DC Power Adapter | TRIAD | WSU075-1000 | E345519 | |
| Access Point* | Electronic Warfare | SKEY-KC | ENG2 | · |
| | Associates, Inc. | | | |

Support Devices:

| Function Manufacturer | Model # | S/N | |
|-----------------------|---------|-----|--|
|-----------------------|---------|-----|--|

Page 25 of 44 Report No.: 94579-11



Test Conditions / Notes:

Radiated Spurious Emission

Frequency Range: 9kHz to 30MHz

Software Used: C and is permanently burned into memory as binary machine language (two different processors,

PIC and CC1110)

Temperature: 21.1°C Humidity: 42 %

Atmospheric Pressure: 101.0 kPa

High Clock: 26MHz

transmit operating frequency= 923MHz

RF Output= 0dBm

Gain of the antenna= +1 dBi

9kHz -150 kHz; RBW=200 Hz, VBW=200 Hz; 150 kHz-30 MHz; RBW=9 kHz, VBW=9 kHz; 30 MHz-1000 MHz; RBW=120 kHz, VBW=120 kHz, 1000 MHz-10000MHz, RBW=1 MHz, VBW=1 MHz.

The EUT is a fixed device. It is placed on the 80cm Styrofoam table and at the center of a turning table. The EUT is set continuously transmit. A RJ 45 Cable is looped back to active RJ 45 port

Note: The customer changed the routing of the differential traces in the Ethernet section of the EUT.


Ext Attn: 0 dB

| Measur | ement Data: | Re | ading list | ted by ma | argin. | | Τe | est Distance | e: 3 Meters | | |
|--------|-------------|------|------------|-----------|--------|----|-------|--------------|----------------|--------|-------|
| # | Freq | Rdng | T1 | T2 | T3 | | Dist | Corr | Spec | Margin | Polar |
| | MHz | dΒμV | dB | dB | dB | dB | Table | $dB\mu V/m$ | $dB\mu V/m \\$ | dB | Ant |
| 1 | 754.213k | 37.3 | +9.6 | +0.1 | +0.0 | | -40.0 | 7.0 | 30.0 | -23.0 | Perpe |
| 2 | 490.784k | 39.0 | +9.8 | +0.1 | +0.0 | | -40.0 | 8.9 | 33.8 | -24.9 | Paral |
| 3 | 915.197k | 32.8 | +9.5 | +0.1 | +0.0 | | -40.0 | 2.4 | 28.3 | -25.9 | Perpe |
| 4 | 1.064M | 31.2 | +9.7 | +0.1 | +0.0 | | -40.0 | 1.0 | 27.0 | -26.0 | Paral |
| 5 | 1.509M | 27.0 | +9.8 | +0.1 | +0.0 | | -40.0 | -3.1 | 24.0 | -27.1 | Perpe |
| 6 | 1.246M | 28.0 | +9.8 | +0.1 | +0.0 | | -40.0 | -2.1 | 25.6 | -27.7 | Paral |

Page 26 of 44 Report No.: 94579-11



CKC Laboratories, Inc Date: 8/9/2013 Time: 14:23:06 Electronic Warfare Associates, Inc WO#: 94579 Test Distance: 3 Meters Sequence#: 28



Readings
 X QP Readings
 ▼ Ambient

O Peak Readings

Average Readings

1 - 15.249 Carrier and Spurious Emissions (902-928 MHz Transmitter)



Test Location: CKC Laboratories, Inc. • 1120 Fulton Place • Fremont, CA 94539 • (510) 249-1170

Customer: Electronic Warfare Associates, Inc.

Specification: 15.249 Carrier and Spurious Emissions (902-928 MHz Transmitter)
Work Order #: 94579 Date: 8/9/2013
Test Type: Radiated Scan Time: 09:43:44
Equipment: Access Point Sequence#: 16

Manufacturer: Electronic Warfare Associates, Inc. Tested By: Hieu Song Nguyenpham

Model: SKEY-KC S/N: ENG2

Test Equipment:

| I csi Liqu | tpintent. | | | | |
|------------|-----------|-------------------|-----------|------------------|--------------|
| ID | Asset # | Description | Model | Calibration Date | Cal Due Date |
| T1 | AN00852 | Biconilog Antenna | CBL 6111C | 11/28/2012 | 11/28/2014 |
| T2 | ANP00880 | Cable | RG214U | 7/30/2012 | 7/30/2014 |
| Т3 | ANP05300 | Cable | RG214/U | 3/25/2013 | 3/25/2015 |
| T4 | AN00730 | Preamp | 8447D | 1/17/2013 | 1/17/2015 |
| T5 | ANP01183 | Cable | CNT-195 | 10/24/2011 | 10/24/2013 |
| | AN02870 | Spectrum Analyzer | E4440A | 12/21/2011 | 12/21/2013 |

Equipment Under Test (* = EUT):

| Function | Manufacturer | Model # | S/N | |
|---------------------|--------------------|-------------|---------|--|
| AC/DC Power Adapter | TRIAD | WSU075-1000 | E345519 | |
| Access Point* | Electronic Warfare | SKEY-KC | ENG2 | |
| | Associates, Inc. | | | |

Support Devices:

| TI | | | | |
|----------|--------------|---------|-----|--|
| Function | Manufacturer | Model # | S/N | |

Test Conditions / Notes:

Radiated Spurious Emission

Frequency Range: 30MHz to 1000MHz

Software Used: C and is permanently burned into memory as binary machine language (two different processors,

PIC and CC1110)

Temperature: 21.1°C Humidity: 42 %

Atmospheric Pressure: 101.0 kPa

High Clock: 26MHz

transmit operating frequency= 923MHz

RF Output= 0dBm

Gain of the antenna= +1 dBi

9 kHz -150 kHz; RBW=200 Hz, VBW=200 Hz; 150 kHz-30 MHz; RBW=9 kHz, VBW=9 kHz; 30 MHz-1000 MHz; RBW=120 kHz, VBW=120 kHz, 1000 MHz-10000MHz, RBW=1 MHz, VBW=1 MHz.

The EUT is a fixed device. It is placed on the 80cm Styrofoam table and at the center of a turning table. The EUT is set continuously transmit. A RJ 45 Cable is looped back to active RJ 45 port.

Note: The customer changed the routing of the differential traces in the Ethernet section of the EUT.

Page 28 of 44 Report No.: 94579-11




Ext Attn: 0 dB

| Measu | rement Data: | Re | eading lis | ted by ma | ırgin. | | Т | est Distance | e: 3 Meters | | |
|-------|---------------|--------------|--------------|-----------|--------|----------|--------|--------------|-------------|--------|-------|
| # | Freq | Rdng | T1 T5 | T2 | Т3 | T4 | Dist | Corr | Spec | Margin | Polar |
| | MHz | dΒμV | dB | dB | dB | dB | Table | $dB\mu V/m$ | $dB\mu V/m$ | dB | Ant |
| 1 | 874.940M | 43.0 | +22.9 | +3.4 | +0.9 | -27.0 | +0.0 | 44.1 | 46.0 | -1.9 | Horiz |
| | QP | | +0.9 | | | | | | | | |
| ^ | 874.940M | 43.8 | +22.9 | +3.4 | +0.9 | -27.0 | +0.0 | 44.9 | 46.0 | -1.1 | Horiz |
| | | | +0.9 | | | | | | | | |
| ^ | 874.940M | 42.1 | +22.9 | +3.4 | +0.9 | -27.0 | +0.0 | 43.2 | 46.0 | -2.8 | Horiz |
| | | | +0.9 | | | | | | | | |
| 4 | 77.192M | 55.1 | +7.3 | +0.8 | +0.2 | -27.1 | +0.0 | 36.5 | 40.0 | -3.5 | Vert |
| | QP | | +0.2 | | | | | | | | |
| ^ | 77.192M | 56.9 | +7.3 | +0.8 | +0.2 | -27.1 | +0.0 | 38.3 | 40.0 | -1.7 | Vert |
| ^ | 77 100) (| 7.6.0 | +0.2 | 0.0 | 0.2 | 27.1 | 0.0 | 27.7 | 40.0 | 2.2 | ** |
| | 77.192M | 56.3 | +7.3 | +0.8 | +0.2 | -27.1 | +0.0 | 37.7 | 40.0 | -2.3 | Vert |
| 7 | 81.197M | 540 | +0.2 | .0.0 | .0.2 | -27.0 | . 0. 0 | 36.2 | 40.0 | 2.0 | XIt |
| - | 81.19/M QP | 54.2 | +7.8 +0.1 | +0.8 | +0.3 | -27.0 | +0.0 | 30.2 | 40.0 | -3.8 | Vert |
| ٨ | 81.197M | 55.5 | +7.8 | +0.8 | +0.3 | -27.0 | +0.0 | 37.5 | 40.0 | -2.5 | Vert |
| | 01.19/WI | 33.3 | +0.1 | +0.6 | +0.5 | -27.0 | +0.0 | 31.3 | 40.0 | -2.3 | VEIL |
| ٨ | 81.197M | 55.2 | +7.8 | +0.8 | +0.3 | -27.0 | +0.0 | 37.2 | 40.0 | -2.8 | Vert |
| | 01.17/14 | 33.2 | +0.1 | 10.0 | 10.3 | 27.0 | 10.0 | 37.2 | 10.0 | 2.0 | VOIC |
| 10 | 624.957M | 41.8 | +20.0 | +2.7 | +0.7 | -26.8 | +0.0 | 39.1 | 46.0 | -6.9 | Horiz |
| | QP | | +0.7 | | | | | | | | |
| ٨ | 624.957M | 42.8 | +20.0 | +2.7 | +0.7 | -26.8 | +0.0 | 40.1 | 46.0 | -5.9 | Horiz |
| | | | +0.7 | | | | | | | | |
| ^ | 624.957M | 42.4 | +20.0 | +2.7 | +0.7 | -26.8 | +0.0 | 39.7 | 46.0 | -6.3 | Horiz |
| | | | +0.7 | | | | | | | | |
| 13 | 750.002M | 39.1 | +22.1 | +3.0 | +0.8 | -26.9 | +0.0 | 39.0 | 46.0 | -7.0 | Horiz |
| | | | +0.9 | | | | | | | | |
| 14 | | 51.5 | +9.4 | +0.9 | +0.3 | -27.1 | +0.0 | 35.2 | 43.5 | -8.3 | Vert |
| | QP | # • • | +0.2 | | | <u> </u> | | | 10.7 | | ** |
| ٨ | 94.380M | 52.9 | +9.4 | +0.9 | +0.3 | -27.1 | +0.0 | 36.6 | 43.5 | -6.9 | Vert |
| | 04.2003.5 | 50.5 | +0.2 | .0.0 | .0.2 | 27.1 | .0.0 | 26.4 | 12.5 | 7.1 | 3.7 |
| ^ | 94.380M | 52.7 | +9.4 | +0.9 | +0.3 | -27.1 | +0.0 | 36.4 | 43.5 | -7.1 | Vert |
| | | | +0.2 | | | | | | | | |



CKC Laboratories, Inc Date: 8/9/2013 Time: 09:43:44 Electronic Warfare Associates, Inc WO#: 94579 Test Distance: 3 Meters Sequence#: 16



Readings

× QP Readings

▼ Ambient

Peak Readings
 Average Readings
 1 - 15.249 Carrier and Spurious Emissions (902-928 MHz Transmitter)



Test Location: CKC Laboratories, Inc. • 1120 Fulton Place • Fremont, CA 94539 • (510) 249-1170

Customer: Electronic Warfare Associates, Inc.

Specification: 15.249 Carrier and Spurious Emissions (902-928 MHz Transmitter)
Work Order #: 94579 Date: 8/9/2013
Test Type: Radiated Scan Time: 13:45:53
Equipment: Access Point Sequence#: 25

Manufacturer: Electronic Warfare Associates, Inc. Tested By: Hieu Song Nguyenpham

Model: SKEY-KC S/N: ENG2

Test Equipment:

| 1 cst Equi | P | | | | |
|------------|----------|-------------------|-----------------|------------------|--------------|
| ID | Asset # | Description | Model | Calibration Date | Cal Due Date |
| T1 | AN03114 | Preamp | AMF-7D- | 4/11/2013 | 4/11/2015 |
| | | | 00101800-30-10P | | |
| T2 | AN02157 | Horn Antenna-ANSI | 3115 | 1/23/2013 | 1/23/2015 |
| | | C63.5 | | | |
| Т3 | AN03015 | Cable | 32022-2-29094K- | 5/6/2013 | 5/6/2015 |
| | | | 24TC | | |
| T4 | AN03302 | Cable | 32026-29094K- | 3/21/2012 | 3/21/2014 |
| | | | 29094K-72TC | | |
| T5 | ANP01210 | Cable | FSJ1P-50A-4A | 2/19/2013 | 2/19/2015 |
| | AN02870 | Spectrum Analyzer | E4440A | 12/21/2011 | 12/21/2013 |
| T6 | AN03172 | High Pass Filter | HM1155-11SS | 2/9/2012 | 2/9/2014 |

Equipment Under Test (* = EUT):

| Function | Manufacturer | Model # | S/N | |
|---------------------|--------------------|-------------|---------|--|
| AC/DC Power Adapter | TRIAD | WSU075-1000 | E345519 | |
| Access Point* | Electronic Warfare | SKEY-KC | ENG2 | |
| | Associates, Inc. | | | |

Support Devices:

| Function | Manufacturer | Model # | S/N | |
|----------|--------------|---------|-----|--|

Test Conditions / Notes:

Radiated Spurious Emission

Frequency Range: 1000MHz to 10000MHz

Software Used: C and is permanently burned into memory as binary machine language (two different processors,

PIC and CC1110)

Temperature: 21.1°C Humidity: 42 %

Atmospheric Pressure: 101.0 kPa

High Clock: 26MHz

transmit operating frequency= 923MHz

RF Output= 0dBm

Gain of the antenna= +1 dBi

9 kHz-150 kHz; RBW=200 Hz, VBW=200 Hz; 150 kHz-30 MHz; RBW=9 kHz, VBW=9 kHz;

30 MHz-1000 MHz; RBW=120 kHz, VBW=120 kHz, 1000 MHz-10000MHz; RBW=1 MHz, VBW=1 MHz.

The EUT is a fixed device. It is placed on the 80cm Styrofoam table and at the center of a turning table. The EUT is set continuously transmit. A RJ 45 Cable is looped back to active RJ 45 port.

Note: The customer changed the routing of the differential traces in the Ethernet section of the EUT.

Page 31 of 44 Report No.: 94579-11




Ext Attn: 0 dB

| Measi | urement Data: | Re | eading lis | ted by ma | argin. | | Т | est Distance | e: 3 Meters | 1 | |
|-------|---------------|------|------------|-----------|--------|------|-------|--------------|-------------|--------|-------|
| # | Freq | Rdng | T1 | T2 | Т3 | T4 | Dist | Corr | Spec | Margin | Polar |
| | | | T5 | T6 | | | | | | | |
| | MHz | dΒμV | dB | dB | dB | dB | Table | $dB\mu V/m$ | $dB\mu V/m$ | dB | Ant |
| 1 | 7383.943M | 63.7 | -59.4 | +36.8 | +1.0 | +1.9 | +0.0 | 49.5 | 54.0 | -4.5 | Vert |
| | Ave | | +5.4 | +0.1 | | | | | | | |
| ^ | 7383.943M | 67.2 | -59.4 | +36.8 | +1.0 | +1.9 | +0.0 | 53.0 | 54.0 | -1.0 | Vert |
| | | | +5.4 | +0.1 | | | | | | | |
| ^ | 7383.943M | 66.3 | -59.4 | +36.8 | +1.0 | +1.9 | +0.0 | 52.1 | 54.0 | -1.9 | Vert |
| | | | +5.4 | +0.1 | | | | | | | |
| 4 | 1002.002M | 59.3 | -59.1 | +23.9 | +0.1 | +0.7 | +0.0 | 46.8 | 54.0 | -7.2 | Vert |
| | | | +1.4 | +20.5 | | | | | | | |
| 5 | 5537.533M | 61.4 | -56.8 | +34.7 | +0.6 | +1.6 | +0.0 | 45.6 | 54.0 | -8.4 | Vert |
| | | | +4.0 | +0.1 | | | | | | | |
| 6 | 1125.125M | 68.3 | -59.2 | +24.8 | +0.1 | +0.7 | +0.0 | 43.9 | 54.0 | -10.1 | Horiz |
| | | | +1.4 | +7.8 | | | | | | | |
| 7 | 3691.689M | 65.7 | -59.3 | +31.9 | +0.5 | +1.3 | +0.0 | 43.5 | 54.0 | -10.5 | Horiz |
| | | | +3.2 | +0.2 | | | | | | | |
| 8 | 1250.250M | 73.6 | -59.3 | +25.3 | +0.1 | +0.8 | +0.0 | 43.3 | 54.0 | -10.7 | Horiz |
| | | | +1.6 | +1.2 | | | | | | | |

Page 32 of 44 Report No.: 94579-11



CKC Laboratories, Inc Date: 8/9/2013 Time: 13:45:53 Electronic Warfare Associates, Inc WO#: 94579 Test Distance: 3 Meters Sequence#: 25






Test Setup Photos



9kHz to 30MHz




9kHz to 30MHz






30MHz to 1GHz




30MHz to 1GHz





1GHz to 10GHz



1GHz to 10GHz



Bandedge

Test Conditions / Setup

Test Location: CKC Laboratories, Inc. • 1120 Fulton Place • Fremont, CA 94539 • (510) 249-1170

Customer: Electronic Warfare Associates, Inc.

Specification: Band edge

Work Order #: 94579 Date: 7/27/2013
Test Type: Radiated Scan Time: 10:16:39
Equipment: Access Point Sequence#: 11

Manufacturer: Electronic Warfare Associates, Inc. Tested By: Hieu Song Nguyenpham

Model: SKEY-KC S/N: ENG1

Test Equipment:

| ID | Asset # | Description | Model | Calibration Date | Cal Due Date |
|----|----------|-------------------|-----------|------------------|--------------|
| T1 | AN00852 | Biconilog Antenna | CBL 6111C | 11/28/2012 | 11/28/2014 |
| T2 | ANP00880 | Cable | RG214U | 7/30/2012 | 7/30/2014 |
| Т3 | ANP05300 | Cable | RG214/U | 3/25/2013 | 3/25/2015 |
| | AN02668 | Spectrum Analyzer | E4446A | 2/22/2013 | 2/22/2015 |

Equipment Under Test (* = EUT):

| Function | Manufacturer | Model # | S/N |
|---------------------|--------------------|-------------|---------|
| Access Point* | Electronic Warfare | SKEY-KC | ENG1 |
| | Associates, Inc. | | |
| AC/DC Power Adapter | TRIAD | WSU075-1000 | E345519 |

Support Devices:

| | Function | Manufacturer | Model # | S/N |
|--|----------|--------------|---------|-----|
|--|----------|--------------|---------|-----|

Test Conditions / Notes:

Software Used: C and is permanently burned into memory as binary machine language (two different processors, PIC and CC1110)

Temperature: 23.3°C Humidity: 39 %

Atmospheric Pressure: 101.1 kPa

High Clock: 26MHz

transmit operating frequency= 923MHz

RF Output= 0dBm


Gain of the antenna= +1 dBi

The EUT is a fixed device. It is placed on the 80cm Styrofoam table. The EUT is set in continue transmit. RJ 45 cable is looped back to active RJ 45 port.

Page 37 of 44 Report No.: 94579-11



Test Data




Page 38 of 44 Report No.: 94579-11



Test Setup Photos







RSS-210

99 % Bandwidth

Test Conditions / Setup

Test Location: CKC Laboratories, Inc. • 1120 Fulton Place • Fremont, CA 94539 • (510) 249-1170

Customer: Electronic Warfare Associates, Inc.

Specification:OBWWork Order #:94579Date: 7/27/2013Test Type:Radiated ScanTime: 10:16:39Equipment:Access PointSequence#: 11

Manufacturer: Electronic Warfare Associates, Inc. Tested By: Hieu Song Nguyenpham

Model: SKEY-KC S/N: ENG1

Test Equipment:

| | 1 | | | | |
|----|----------|-------------------|-----------|------------------|--------------|
| ID | Asset # | Description | Model | Calibration Date | Cal Due Date |
| T1 | AN00852 | Biconilog Antenna | CBL 6111C | 11/28/2012 | 11/28/2014 |
| T2 | ANP00880 | Cable | RG214U | 7/30/2012 | 7/30/2014 |
| Т3 | ANP05300 | Cable | RG214/U | 3/25/2013 | 3/25/2015 |
| | AN02668 | Spectrum Analyzer | E4446A | 2/22/2013 | 2/22/2015 |

Equipment Under Test (* = EUT):

| Function | Manufacturer | Model # | S/N |
|---------------------|--------------------|-------------|---------|
| Access Point* | Electronic Warfare | SKEY-KC | ENG1 |
| | Associates, Inc. | | |
| AC/DC Power Adapter | TRIAD | WSU075-1000 | E345519 |

Support Devices:

| Function | Manufacturer | Model # | S/N | |
|----------|--------------|---------|-----|--|

Page 40 of 44 Report No.: 94579-11



Test Conditions / Notes:

Software Used: C and is permanently burned into memory as binary machine language (two different processors, PIC and CC1110)

Temperature: 23.3°C Humidity: 39 %

Atmospheric Pressure: 101.1 kPa

High Clock: 26MHz


transmit operating frequency= 923MHz

RF Output= 0dBm

Gain of the antenna= +1 dBi

The EUT is a fixed device. It is placed on the 80cm Styrofoam table. The EUT is set in continue transmit. RJ 45 cable is looped back to active RJ 45 port.

Test Data




Page 41 of 44 Report No.: 94579-11



Test Setup Photos







SUPPLEMENTAL INFORMATION

Measurement Uncertainty

| Uncertainty Value | Parameter |
|-------------------|---------------------------|
| 4.73 dB | Radiated Emissions |
| 3.34 dB | Mains Conducted Emissions |
| 3.30 dB | Disturbance Power |

The reported measurement uncertainties are calculated based on the worst case of all laboratory environments from CKC Laboratories, Inc. test sites. Only those parameters which require estimation of measurement uncertainty are reported. The reported worst case measurement uncertainty is less than the maximum values derived in CISPR 16-4-2. Reported uncertainties represent expanded uncertainties expressed at approximately the 95% confidence level using a coverage factor of k=2. Compliance is deemed to occur provided measurements are below the specified limits.

Emissions Test Details

TESTING PARAMETERS

Unless otherwise indicated, the following configuration parameters are used for equipment setup: The cables were routed consistent with the typical application by varying the configuration of the test sample. Interface cables were connected to the available ports of the test unit. The effect of varying the position of the cables was investigated to find the configuration that produced maximum emissions. Cables were of the type and length specified in the individual requirements. The length of cable that produced maximum emissions was selected.

The equipment under test (EUT) was set up in a manner that represented its normal use, as shown in the setup photographs. Any special conditions required for the EUT to operate normally are identified in the comments that accompany the emissions tables.

The emissions data was taken with a spectrum analyzer or receiver. Incorporating the applicable correction factors for distance, antenna, cable loss and amplifier gain, the data was reduced as shown in the table below. The corrected data was then compared to the applicable emission limits. Preliminary and final measurements were taken in order to ensure that all emissions from the EUT were found and maximized.

CORRECTION FACTORS

The basic spectrum analyzer reading was converted using correction factors as shown in the highest emissions readings in the tables. For radiated emissions in $dB\mu V/m$, the spectrum analyzer reading in $dB\mu V$ was corrected by using the following formula. This reading was then compared to the applicable specification limit.

Page 43 of 44 Report No.: 94579-11



| SAMPLE CALCULATIONS | | | | | | |
|---------------------|----------------------|----------|--|--|--|--|
| | Meter reading (dBμV) | | | | | |
| + | Antenna Factor | (dB) | | | | |
| + | Cable Loss | (dB) | | | | |
| - | Distance Correction | (dB) | | | | |
| - | Preamplifier Gain | (dB) | | | | |
| = | Corrected Reading | (dBμV/m) | | | | |

TEST INSTRUMENTATION AND ANALYZER SETTINGS

The test instrumentation and equipment listed were used to collect the emissions data. A spectrum analyzer or receiver was used for all measurements. Unless otherwise specified, the following table shows the measuring equipment bandwidth settings that were used in designated frequency bands. For testing emissions, an appropriate reference level and a vertical scale size of 10 dB per division were used.

| MEASURING EQUIPMENT BANDWIDTH SETTINGS PER FREQUENCY RANGE | | | | | | |
|--|---------------------|------------------|-------------------|--|--|--|
| TEST | BEGINNING FREQUENCY | ENDING FREQUENCY | BANDWIDTH SETTING | | | |
| CONDUCTED EMISSIONS | 150 kHz | 30 MHz | 9 kHz | | | |
| RADIATED EMISSIONS | 9 kHz | 150 kHz | 200 Hz | | | |
| RADIATED EMISSIONS | 150 kHz | 30 MHz | 9 kHz | | | |
| RADIATED EMISSIONS | 30 MHz | 1000 MHz | 120 kHz | | | |
| RADIATED EMISSIONS | 1000 MHz | >1 GHz | 1 MHz | | | |

SPECTRUM ANALYZER/RECEIVER DETECTOR FUNCTIONS

The notes that accompany the measurements contained in the emissions tables indicate the type of detector function used to obtain the given readings. Unless otherwise noted, all readings were made in the "positive peak" detector mode. Whenever a "quasi-peak" or "average" reading was recorded, the measurement was annotated with a "QP" or an "Ave" on the appropriate rows of the data sheets. In cases where quasi-peak or average limits were employed and data exists for multiple measurement types for the same frequency then the peak measurement was retained in the report for reference, however the numbering for the affected row was removed and an arrow or carrot ("A") was placed in the far left-hand column indicating that the row above takes precedence for comparison to the limit. The following paragraphs describe in more detail the detector functions and when they were used to obtain the emissions data.

Peak

In this mode, the spectrum analyzer or receiver recorded all emissions at their peak value as the frequency band selected was scanned. By combining this function with another feature called "peak hold," the measurement device had the ability to measure intermittent or low duty cycle transient emission peak levels. In this mode the measuring device made a slow scan across the frequency band selected and measured the peak emission value found at each frequency across the band.

Quasi-Peak

Quasi-peak measurements were taken using the quasi-peak detector when the true peak values exceeded or were within 2 dB of a quasi-peak specification limit. Additional QP measurements may have been taken at the discretion of the operator.

Average

Average measurements were taken using the average detector when the true peak values exceeded or were within 2 dB of an average specification limit. Additional average measurements may have been taken at the discretion of the operator. If the specification or test procedure requires trace averaging, then the averaging was performed using 100 samples or as required by the specification. All other average measurements are performed using video bandwidth averaging. To make these measurements, the test engineer reduces the video bandwidth on the measuring device until the modulation of the signal is filtered out. At this point the measuring device is set into the linear mode and the scan time is reduced.

Page 44 of 44 Report No.: 94579-11