

RF EXPOSURE EVALUATION REPORT

Product Name: Smart Door Station
Trade Mark: GRANDSTREAM
Model No.: GDS3727
Report Number: 25040917185RFC-5
Test Standards: FCC 47 CFR Part 1 Subpart I
FCC ID: YZZGDS3727
Test Result: PASS
Date of Issue: July 23, 2025

Prepared for:

Grandstream Networks, Inc.
126 Brookline Ave., 3rd Floor Boston, MA 02215, USA

Prepared by:

Shenzhen UnionTrust Quality and Technology Co., Ltd.
16/F, Block A, Building 6th, Baoneng Science and Technology Park,
Longhua Street, Longhua District, Shenzhen, China
TEL: +86-755-2823 0888
FAX: +86-755-2823 0886

Prepared by:



David Chen
Senior Project Engineer

Reviewed by:



Kevin Liang
Assistant Manager

Approved by:



Billy Li
Technical Director

Date:

July 23, 2025

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS102-V1.1

Version

Version No.	Date	Description
V1.0	July 23, 2025	Original



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS102-V1.1

CONTENTS

1. GENERAL INFORMATION	4
1.1 CLIENT INFORMATION	4
1.2 EUT INFORMATION	4
1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	4
1.4 OTHER INFORMATION	7
1.5 GENERAL DESCRIPTION OF APPLIED STANDARDS	8
1.6 DEVIATION FROM STANDARDS	8
1.7 ABNORMALITIES FROM STANDARD CONDITIONS	8
1.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER	8
2. EQUIPMENT LIST	8
3. MPE EVALUATION	9
3.1 REFERENCE DOCUMENTS FOR EVALUATION	9
3.2 MPE COMPLIANCE REQUIREMENT	9
3.2.1 LIMITS	9
3.2.2 TEST PROCEDURE	9
3.3 MPE CALCULATION METHOD	9
3.4 MPE CALCULATION RESULTS	10
3.4.1 FOR WLAN	10
3.4.2 FOR BT	12
3.4.3 FOR RFID/NFC	12
3.4.1 SIMULTANEOUS MULTI-BAND TRANSMISSION MPE ANALYSIS	13
APPENDIX 1 PHOTOS OF TEST SETUP	14
APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS	14

1. GENERAL INFORMATION

1.1 CLIENT INFORMATION

Applicant:	Grandstream Networks, Inc.
Address of Applicant:	126 Brookline Ave., 3rd Floor Boston, MA 02215, USA
Manufacturer:	Grandstream Networks, Inc.
Address of Manufacturer:	126 Brookline Ave., 3rd Floor Boston, MA 02215, USA

1.2 EUT INFORMATION

Product Name:	Smart Door Station		
Model No.:	GDS3727		
Trade Mark:	GRANDSTREAM		
DUT Stage:	Identical Prototype		
EUT Supports Function: (Provided by the customer)	2.4 GHz ISM Band:	IEEE 802.11b/g/n/ax	
		Bluetooth V5.0	
	5 GHz U-NII Bands:	5 150 MHz to 5 250 MHz	IEEE 802.11a/n/ac/ax
		5 250 MHz to 5 350 MHz	IEEE 802.11a/n/ac/ax
		5 470 MHz to 5 725 MHz	IEEE 802.11a/n/ac/ax
		5 725 MHz to 5 850 MHz	IEEE 802.11a/n/ac/ax
	NFC:	13.553 MHz to 13.567 MHz	
	RF ID:	13.553 MHz to 13.567 MHz	
		125 kHz	
Sample Received Date:	April 9, 2025		

Remark: The above EUT's information was provided by customer. Please refer to the specifications or user's manual for more detailed description.

1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD

For BT_LE	
Frequency Band:	2400 MHz to 2483.5 MHz
Frequency Range:	2402 MHz to 2480 MHz
Bluetooth Version:	Bluetooth LE/2LE/LE Code
Type of Modulation:	GFSK
Number of Channels:	40
Channel Separation:	2 MHz
Antenna Type:	PIFA Antenna
Antenna Gain: (Provided by the customer)	1.17 dBi
Maximum Peak Power:	8.82 dBm

For 2.4 GHz ISM Band of Wi-Fi	
Frequency Band:	2400 MHz to 2483.5 MHz
Frequency Range:	2412 MHz to 2462 MHz
Support Standards:	IEEE 802.11b/g/n-HT20/n-HT40/ax-HE20/ax-HE40
Type of Modulation:	IEEE 802.11b: DSSS(CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM(64-QAM, 16-QAM, QPSK, BPSK) IEEE 802.11n-HT20: OFDM(64-QAM, 16-QAM, QPSK, BPSK) IEEE 802.11n-HT40: OFDM(64-QAM, 16-QAM, QPSK, BPSK) IEEE 802.11ax: OFDM/OFDMA ^{Note} (1024QAM, 256QAM, 64QAM, 16QAM,

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS102-V1.1

	QPSK, BPSK)
Data Rate:	IEEE 802.11b: Up to 11 Mbps IEEE 802.11g: Up to 54 Mbps IEEE 802.11n-HT20: Up to MCS7 IEEE 802.11n-HT40: Up to MCS7 IEEE 802.11ax-HE20/ HE40: Up to MCS11
Number of Channels:	IEEE 802.11b: 11 IEEE 802.11g: 11 IEEE 802.11n-HT20/ax-HE20: 11 IEEE 802.11n-HT40/ax-HE40: 7
Channel Separation:	5 MHz
Antenna Type:	PIFA Antenna
Antenna Gain: (Provided by the customer)	1.17 dBi
Maximum Peak Power:	IEEE 802.11b: 21.06 dBm IEEE 802.11g: 21.08 dBm IEEE 802.11n-HT20: 18.99 dBm IEEE 802.11n-HT40: 18.94 dBm IEEE 802.11ax-HE20: 19.00 dBm IEEE 802.11ax-HE40: 18.87 dBm
Maximum e.i.r.p	IEEE 802.11b: 22.23 dBm IEEE 802.11g: 22.25 dBm IEEE 802.11n-HT20: 20.16 dBm IEEE 802.11n-HT40: 20.11 dBm IEEE 802.11ax-HE20: 20.17 dBm IEEE 802.11ax-HE40: 20.04 dBm
Note: For 802.11ax modes, the device not support partial RU mode	

For 5 GHz U-NII Bands of Wi-Fi	
Frequency Bands:	5150 MHz to 5250 MHz (U-NII-1)
	5250 MHz to 5350 MHz (U-NII-2A)
	5470 MHz to 5725 MHz (U-NII-2C) ^{Note1}
	5725 MHz to 5850 MHz (U-NII-3)
Frequency Ranges:	5180 MHz to 5240 MHz
	5260 MHz to 5320 MHz
	5500 MHz to 5720 MHz
	5745 MHz to 5825 MHz
Support Standards:	IEEE 802.11a/n/ac/ax
TPC Function:	Not Support
DFS Operational mode:	Slave without radar Interference detection function
Type of Modulation:	IEEE 802.11a: OFDM(64QAM, 16QAM, QPSK, BPSK)
	IEEE 802.11n: OFDM(64QAM, 16QAM, QPSK, BPSK)
	IEEE 802.11ac: OFDM(256QAM, 64QAM, 16QAM, QPSK, BPSK)
	IEEE 802.11ax: OFDM /OFDMA ^{Note2} (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)
Channel Spacing:	IEEE 802.11a/n-HT20/ac-VHT20/ax-HE20: 20 MHz
	IEEE 802.11n-HT40/ac-VHT40/ax-HE40: 40 MHz
Data Rate:	IEEE 802.11a: Up to 54 Mbps
	IEEE 802.11n-HT20: Up to MCS7
	IEEE 802.11n-HT40: Up to MCS7
	IEEE 802.11ac-VHT20: Up to MCS8

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS102-V1.1

Number of Channels:	IEEE 802.11ac-VHT40: Up to MCS9				
	IEEE 802.11ax-HE20/HE40: Up to MCS11				
	5150 MHz to 5250 MHz: 4 for IEEE 802.11a/n-HT20/ac-VHT20/ax-HE20 2 for IEEE 802.11n-HT40)/ac-VHT40/ax-HE40				
	5250 MHz to 5350 MHz: 4 for IEEE 802.11a/n-HT20/ac-VHT20/ax-HE20 2 for IEEE 802.11n-HT40)/ac-VHT40/ax-HE40				
Antenna Type:	Dipole Antenna				
	5150 MHz to 5250 MHz: 4.55 dBi				
	5250 MHz to 5350 MHz: 4.55 dBi				
	5470 MHz to 5725 MHz: 4.55 dBi				
Antenna Gain: (Provided by the customer)	5725 MHz to 5850 MHz: 4.55 dBi				
Maximum conducted output power (dBm):		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
	IEEE 802.11a:	19.03	19.08	16.35	17.93
	IEEE 802.11n-HT20:	18.94	14.28	18.81	17.46
	IEEE 802.11n-HT40:	18.44	18.24	16.34	17.32
	IEEE 802.11ac-VHT20	18.31	14.76	19.35	17.69
	IEEE 802.11ac-VHT40	18.45	18.21	16.02	17.23
	IEEE 802.11ax-HE20	18.35	18.09	18.95	17.53
	IEEE 802.11ax-HE40	18.69	18.50	19.64	17.32
Note:					
1. For 802.11ax modes, the device not support partial RU mode					

1.4 OTHER INFORMATION

Test channels for BT_LE				
Type of Modulation	Tx/Rx Frequency	Test RF Channel Lists		
GFSK	2402 MHz to 2480 MHz	Lowest(L)	Middle(M)	Highest(H)
		Channel 0	Channel 19	Channel 39
		2402 MHz	2440 MHz	2480 MHz

Test channels for 2.4 GHz ISM Band of Wi-Fi				
Mode	Tx/Rx Frequency	Test RF Channel Lists		
		Lowest(L)	Middle(M)	Highest(H)
IEEE 802.11b	2412 MHz to 2462 MHz	Channel 1	Channel 6	Channel 11
		2412 MHz	2437 MHz	2462 MHz
IEEE 802.11g	2412 MHz to 2462 MHz	Channel 1	Channel 6	Channel 11
		2412 MHz	2437 MHz	2462 MHz
IEEE 802.11n-HT20 IEEE 802.11ax-HE20	2412 MHz to 2462 MHz	Channel 1	Channel 6	Channel 11
		2412 MHz	2437 MHz	2462 MHz
IEEE 802.11n-HT40 IEEE 802.11ax-HE40	2422 MHz to 2452 MHz	Channel 3	Channel 7	Channel 9
		2422 MHz	2437 MHz	2452 MHz

Test channels for 5 GHz U-NII Bands of Wi-Fi					
Mode	Tx/Rx Frequency	Test RF Channel Lists			
		Lowest(L)	Middle(M)	Highest(H)	Straddle band
IEEE 802.11a IEEE 802.11n-HT20 IEEE 802.11ac-VHT20 IEEE 802.11ax-HE20	5150 MHz to 5250 MHz	Channel 36	Channel 44	Channel 48	--
		5180 MHz	5220 MHz	5240 MHz	--
	5250 MHz to 5350 MHz	Channel 52	Channel 60	Channel 64	--
		5260 MHz	5300 MHz	5320 MHz	--
	5470 MHz to 5725 MHz	Channel 100	Channel 116	Channel 140	Channel 144
		5500 MHz	5580 MHz	5700 MHz	5720 MHz
	5725 MHz to 5850 MHz	Channel 149	Channel 157	Channel 165	--
		5745 MHz	5785 MHz	5825 MHz	--
IEEE 802.11n-HT40 IEEE 802.11ac-VHT40 IEEE 802.11ax-HE40	5150 MHz to 5250 MHz	Channel 38	--	Channel 46	--
		5190 MHz	--	5230 MHz	--
	5250 MHz to 5350 MHz	Channel 54	--	Channel 62	--
		5270 MHz	--	5310 MHz	--
	5470 MHz to 5725 MHz	Channel 102	Channel 110	Channel 134	Channel 142
		5510 MHz	5550 MHz	5670 MHz	5710 MHz
	5725 MHz to 5850 MHz	Channel 151	--	Channel 159	--
		5755 MHz	--	5795 MHz	--
		--	5775 MHz	--	--

1.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product, according to the specifications of the manufacturers. It must comply with the requirements of the following standards:

FCC 47 CFR Part 1 Subpart I

All test items have been performed and recorded as per the above standards

1.6 DEVIATION FROM STANDARDS

None.

1.7 ABNORMALITIES FROM STANDARD CONDITIONS

None.

1.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

2. EQUIPMENT LIST

Please refer to the RF test report.

3. MPE EVALUATION

3.1 REFERENCE DOCUMENTS FOR EVALUATION

No.	Identity	Document Title
1	FCC 47 CFR Part 1 Subpart I	PROCEDURES IMPLEMENTING THE NATIONAL ENVIRONMENTAL POLICY ACT OF 1969
2	KDB 447498 D01 General RF Exposure Guidance v06	RF EXPOSURE PROCEDURES AND EQUIPMENT AUTHORIZATION POLICIES FOR MOBILE AND PORTABLE DEVICES

3.2 MPE COMPLIANCE REQUIREMENT

3.2.1 Limits

3.2.1.1 FCC 47 CFR Part 1 Subpart I

According to §1.1307(b)(1), system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

Note: f = frequency in MHz: * = Plane-wave equivalents power density.

3.2.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

3.3 MPE CALCULATION METHOD

FCC 47 CFR Part 1 Subpart I

$$S = PG/4\pi R^2 = EIRP/4\pi R^2$$

S = power density (in appropriate units, e.g., mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor is normally numeric gain.

R = 20cm, distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

3.4 MPE CALCULATION RESULTS

Note: For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

3.4.1 For WLAN

For Wi-Fi function, operating at 2412MHz to 2462 MHz for IEEE802.11b/g/n/ax and operating at 5150 MHz to 5250 MHz for IEEE802.11a/n/ac/ax and operating at 5250 MHz to 5350 MHz for IEEE802.11a/n/ac/ax and operating at 5470 MHz to 5725 MHz for IEEE802.11a/n/ac/ax and operating at 5725 MHz to 5850 MHz for IEEE802.11a/n/ac/ax.

3.4.1.1 Antenna Type:

PIFA Antenna

3.4.1.2 Antenna Gain:

2412MHz to 2462 MHz: 1.17 dBi
5150 MHz to 5250 MHz: 4.55 dBi
5250 MHz to 5350 MHz: 4.55 dBi
5470 MHz to 5725 MHz: 4.55 dBi
5725 MHz to 5850 MHz: 4.55 dBi

3.4.1.3 Results for FCC 47 CFR Part 1 Subpart I

Operating Mode		Freq.	Declared maximum conducted output power	Max. positive tolerance according manufacturer	Antenna Gain	Calculated maximum EIRP	Declared maximum EIRP	MPE Limit	MPE Value
		(MHz)	(dBm)		(dBi)	(dBm)	(mW)	(mw/cm²)	
SISO	IEEE 802.11b	2412	21	1	1.17	23.17	207.4914	1	0.0413
		2437	21	1	1.17	23.17	207.4914	1	0.0413
		2462	21	1	1.17	23.17	207.4914	1	0.0413
	IEEE 802.11g	2412	21	1	1.17	23.17	207.4914	1	0.0413
		2437	21	1	1.17	23.17	207.4914	1	0.0413
		2462	21	1	1.17	23.17	207.4914	1	0.0413
	IEEE 802.11n-HT20 IEEE 802.11ax-HE20	2412	19	1	1.17	21.17	130.9182	1	0.0260
		2437	19	1	1.17	21.17	130.9182	1	0.0260
		2462	19	1	1.17	21.17	130.9182	1	0.0260
	IEEE 802.11n-HT40 IEEE 802.11ax-HE40	2422	18	1	1.17	20.17	103.9920	1	0.0207
		2437	18	1	1.17	20.17	103.9920	1	0.0207
		2452	18	1	1.17	20.17	103.9920	1	0.0207
	IEEE 802.11a	5180	19	1	4.55	24.55	285.1018	1	0.0567
		5220	19	1	4.55	24.55	285.1018	1	0.0567
		5240	19	1	4.55	24.55	285.1018	1	0.0567
		5260	19	1	4.55	24.55	285.1018	1	0.0567
		5300	19	1	4.55	24.55	285.1018	1	0.0567
		5320	19	1	4.55	24.55	285.1018	1	0.0567
		5500	16	1	4.55	21.55	142.8894	1	0.0284
		5580	14	1	4.55	19.55	90.1571	1	0.0179
		5700	14	1	4.55	19.55	90.1571	1	0.0179
		5720	14	1	4.55	19.55	90.1571	1	0.0179
		5745	17	1	4.55	22.55	179.8871	1	0.0358
		5785	17	1	4.55	22.55	179.8871	1	0.0358
		5825	17	1	4.55	22.55	179.8871	1	0.0358
	IEEE 802.11n-HT20 802.11ac-VHT20	5180	18	1	4.55	23.55	226.4644	1	0.0451
		5220	18	1	4.55	23.55	226.4644	1	0.0451
		5240	18	1	4.55	23.55	226.4644	1	0.0451

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS102-V1.1

Operating Mode	Freq.	Declared maximum conducted output power	Max. positive tolerance according manufacturer	Antenna Gain	Calculated maximum EIRP	Declared maximum EIRP	MPE Limit	MPE Value
	(MHz)	(dBm)		(dBi)	(dBm)	(mW)	(mw/cm ²)	
	5260	14	1	4.55	19.55	90.1571	1	0.0179
	5300	14	1	4.55	19.55	90.1571	1	0.0179
	5320	14	1	4.55	19.55	90.1571	1	0.0179
	5500	19	1	4.55	24.55	285.1018	1	0.0567
	5580	18	1	4.55	23.55	226.4644	1	0.0451
	5700	18	1	4.55	23.55	226.4644	1	0.0451
	5720	18	1	4.55	23.55	226.4644	1	0.0451
	5745	17	1	4.55	22.55	179.8871	1	0.0358
	5785	17	1	4.55	22.55	179.8871	1	0.0358
	5825	17	1	4.55	22.55	179.8871	1	0.0358
IEEE 802.11ax-HE20	5180	18	1	4.55	23.55	226.4644	1	0.0451
	5220	18	1	4.55	23.55	226.4644	1	0.0451
	5240	18	1	4.55	23.55	226.4644	1	0.0451
	5260	18	1	4.55	23.55	226.4644	1	0.0451
	5300	18	1	4.55	23.55	226.4644	1	0.0451
	5320	18	1	4.55	23.55	226.4644	1	0.0451
	5500	18	1	4.55	23.55	226.4644	1	0.0451
	5580	18	1	4.55	23.55	226.4644	1	0.0451
	5700	18	1	4.55	23.55	226.4644	1	0.0451
	5720	18	1	4.55	23.55	226.4644	1	0.0451
	5745	17	1	4.55	22.55	179.8871	1	0.0358
	5785	17	1	4.55	22.55	179.8871	1	0.0358
	5825	17	1	4.55	22.55	179.8871	1	0.0358
IEEE 802.11n-HT40 IEEE 802.11ac-VHT40	5190	18	1	4.55	23.55	226.4644	1	0.0451
	5230	18	1	4.55	23.55	226.4644	1	0.0451
	5270	18	1	4.55	23.55	226.4644	1	0.0451
	5310	18	1	4.55	23.55	226.4644	1	0.0451
	5510	16	1	4.55	21.55	142.8894	1	0.0284
	5550	16	1	4.55	21.55	142.8894	1	0.0284
	5670	14	1	4.55	19.55	90.1571	1	0.0179
	5710	14	1	4.55	19.55	90.1571	1	0.0179
	5755	17	1	4.55	22.55	179.8871	1	0.0358
	5795	17	1	4.55	22.55	179.8871	1	0.0358
	5190	18	1	4.55	23.55	226.4644	1	0.0451
	5230	18	1	4.55	23.55	226.4644	1	0.0451
	5270	18	1	4.55	23.55	226.4644	1	0.0451
	5310	18	1	4.55	23.55	226.4644	1	0.0451
	5510	19	1	4.55	24.55	285.1018	1	0.0567
	5550	19	1	4.55	24.55	285.1018	1	0.0567
	5670	17	1	4.55	22.55	179.8871	1	0.0358
	5710	17	1	4.55	22.55	179.8871	1	0.0358
	5755	17	1	4.55	22.55	179.8871	1	0.0358
	5795	17	1	4.55	22.55	179.8871	1	0.0358
IEEE 802.11ax-HE40	5190	18	1	4.55	23.55	226.4644	1	0.0451
	5230	18	1	4.55	23.55	226.4644	1	0.0451
	5270	18	1	4.55	23.55	226.4644	1	0.0451
	5310	18	1	4.55	23.55	226.4644	1	0.0451
	5510	19	1	4.55	24.55	285.1018	1	0.0567
	5550	19	1	4.55	24.55	285.1018	1	0.0567
	5670	17	1	4.55	22.55	179.8871	1	0.0358
	5710	17	1	4.55	22.55	179.8871	1	0.0358

3.4.2 For BT

For BT_LE/2LE/ LE Code function, operating at 2402MHz to 2480 MHz for GFSK and

3.4.2.1 Antenna Type:

PIFA Antenna

3.4.2.2 Antenna Gain:

2402MHz to 2480 MHz: 1.17 dBi

3.4.2.3 Results for FCC 47 CFR Part 1 Subpart I

Operating Mode	Freq.	Declared maximum conducted output power	Max. positive tolerance according manufacturer	Antenna Gain	Calculated maximum EIRP	Declared maximum EIRP	MPE Limit	MPE Value
	(MHz)	(dBm)	(dBm)	(dBi)	(dBm)	(mW)	(mW /cm ²)	
LE/2LE/ LE Code	2402-2480	8	1	1.17	10.17	10.3992	1	0.0021

3.4.3 For RFID/NFC

Operating Mode	Freq.	Maximum Field Strength:	Declared maximum EIRP	Declared maximum EIRP	Declared maximum EIRP	Limit	
	(MHz)	(dBμV/m at 3 meter)	(dBm)	V/m	A/m	V/m	A/m
RFID/NFC	13.56	54.23	-41.00	0.0005	0.0000014	60.77	0.162
RFID	0.125	49.57	-45.66	0.0003	0.0000008	614	1.63

3.4.1 Simultaneous Multi-band Transmission MPE Analysis

3.4.4.1 List of Mode for Simultaneous Multi-band Transmission

No.	Configurations	Support/Not Support
1	2.4G _WLAN + BT + RFID + NFC	Support
2	5G_WLAN + BT+ RFID + NFC	Support
3	2.4G _WLAN + 5G_WLAN	Not Support

3.4.4.1 Results for transmit simultaneously

FCC 47 CFR Part 1 Subpart I

No.	Configurations	Maximum MPE Value					Limits
		WLAN (mw/cm ²)	BT (mw/cm ²)	NFC (V/m)	RFID (V/m)	Transmit simultaneou sly	
1	2.4G _WLAN + BT+ RFID + NFC	0.0413	0.0021	0.0005	0.0003	0.0434	1
2	5G_WLAN + BT+ RFID + NFC	0.0567	0.0021	0.0005	0.0003	0.0588	1

Note:

According to KDB 447498 D01 General RF Exposure Guidance v06, At the transmit simultaneously calculation method is as follows:

$$\text{Transmit simultaneously MPE} = \Sigma \text{ of MPE ratios}$$

$$\text{MPE ratios} = \text{Field strengths or power density} / \text{MPE limit at the test frequency}$$

APPENDIX 1 PHOTOS OF TEST SETUP

N/A

APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS

Refer to Appendix 2 for EUT external and internal Photos.

*** End of Report ***

The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of UnionTrust, this report can't be reproduced except in full.
