

FCC §15.247 (i) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

| Limits for General Population/Uncontrolled Exposure | | | | |
|---|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| Frequency Range (MHz) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm ²) | Averaging Time (Minutes) |
| 0.3-1.34 | 614 | 1.63 | *(100) | 30 |
| 1.34-30 | 824/f | 2.19/f | *(180/f ²) | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | / | / | f/1500 | 30 |
| 1500-100,000 | / | / | 1.0 | 30 |

f = frequency in MHz

* = Plane-wave equivalent power density

a)

Result

Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

| Frequency (MHz) | Antenna Gain | | Tune up conducted power | | Evaluation Distance (cm) | Power Density (mW/cm ²) | MPE Limit (mW/cm ²) |
|-----------------|--------------|-----------|-------------------------|--------|--------------------------|-------------------------------------|---------------------------------|
| | (dBi) | (numeric) | (dBm) | (mW) | | | |
| 2412-2462 | 6.5 | 4.47 | 27.0 | 501.19 | 27 | 0.245 | 1 |
| 5150-5250 | 10.5 | 11.22 | 20.5 | 112.20 | 27 | 0.137 | 1 |
| 5250-5350 | 10.5 | 11.22 | 16.0 | 39.81 | 27 | 0.049 | 1 |
| 5470-5725 | 10.5 | 11.22 | 15.0 | 31.62 | 27 | 0.039 | 1 |
| 5725-5850 | 10.5 | 11.22 | 26.0 | 398.11 | 27 | 0.488 | 1 |

- Note: 1. The tune up conducted power was declared by the applicant.
 2. The 2.4G Wi-Fi can transmit at the same time with the 5G Wi-Fi.
 3. For the 2.4G Wi-Fi, as it can support the beam-forming function, so the directional antenna gain should add the $10\lg 2$, $3.5\text{dBi} + 10\lg 2 = 6.5\text{dBi}$.
 4. For the 5G Wi-Fi, as it can support the beam-forming function, so the directional antenna gain should add the $10\lg 4$, $4.5\text{dBi} + 10\lg 4 = 10.5\text{dBi}$.

Simultaneous transmitting consideration (worst case):

The ratio = $\text{MPE}_{2.4\text{G Wi-Fi}}/\text{limit} + \text{MPE}_{5\text{G Wi-Fi}}/\text{limit} = 0.245 + 0.488 = 0.733 < 1.0$, so simultaneous exposure is compliant.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 27cm from nearby persons.

Result: Compliant.