

FCC PART 15.231

TEST REPORT

For

Hangzhou Hamaton Tyre Valves Co.,Ltd.

12 East Zhenxing Road, Linping, Yuhang, Hangzhou, China

FCC ID: Z27HTS5A433

Report Type: CHPC		Product Type: TPMS Sensor
Test Engineer:	Matt Yao	New Ho. Yas
Report Number:	RKS160229001	- 00I
Report Date:	2016-03-14	
Reviewed By:	Jesse Huang EMC Manager	Jesse-Huanf
Prepared By:		6175000 88934268

Note: This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

TABLE OF CONTENTS

GENERAL INFORMATION	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	
Objective	
RELATED SUBMITTAL(S)/GRANT(S)	
TEST METHODOLOGY	
TEST FACILITY	
SYSTEM TEST CONFIGURATION	5
JUSTIFICATION	
EUT Exercise Software	
EQUIPMENT MODIFICATIONS	
BLOCK DIAGRAM OF TEST SETUP	5
SUMMARY OF TEST RESULTS	6
FCC§15.203 - ANTENNA REQUIREMENT	7
APPLICABLE STANDARD	
ANTENNA CONNECTED CONSTRUCTION	7
FCC §15.205, §15.209, §15.231 (E) - RADIATED EMISSIONS TEST	8
APPLICABLE STANDARD	
Measurement Uncertainty	
EUT SETUP	
EMI TEST RECEIVER SETUP.	
TEST EQUIPMENT LIST AND DETAILS	
TEST PROCEDURE	
APPLICABLE STANDARD	
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST RESULTS SUMMARY	
TEST DATA	
§15.231(C) - 20DB BANDWIDTH TESTING	
Requirement	
TEST EQUIPMENT LIST AND DETAILS.	14
TEST PROCEDURE	
TEST DATA	14
FCC §15.231(E) – TRANSMISSION AND SILENT PERIOD TESTING	
APPLICABLE STANDARD	
EUT Setup	
TEST EQUIPMENT LIST AND DETAILS	
TEST DATA	17
DECLADATION LETTED	10

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The Hangzhou Hamaton Tyre Valves Co., Ltd.'s product, model number: 97358 (FCC ID: Z27HTS5A433) the "EUT" is a TPMS Sensor, The EUT was measured approximately: 74 mm (L)* 49 mm (W)*24 mm (H). Rated input voltage: DC 3V from battery.

*The product's model: 97358, series model number: 97359. The differences between them are only the model number. No other changes are made to them. Model: 97358 was full tested.

Report No.: RKS160229001-00I

*All measurement and test data in this report was gathered from production sample serial number: 160224006 (Assigned by BACL Kunshan). The EUT supplied by the applicant was received on 2016-02-24

Objective

This document is a test report based on the Electromagnetic Interference (EMI) tests performed on the EUT. The EMI measurements were performed according to the measurement procedure described in ANSI C63.10 - 2013.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.209, 15.35(c) and 15.231 rules.

This is the CIIPC application of the device. The difference between the original device and the current one is as follows:

- 1. Add new models (Model: 97358, 97359).
- 2. The original inductance of sensor was produced by Premo Group and the model: SDTR1103. The new inductance of sensor was produced by TDK and the model: TPL802727-722H

For the changes made to the device, all the test items were performed.

Related Submittal(s)/Grant(s)

No Related Submittals.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10 - 2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Lab Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement uncertainty with radiated emission is 5.87 dB for 30MHz-1GHz, and 4.84 dB for above 1GHz, 1.85dB for conducted measurement.

FCC Part 15.231 Page 3 of 19

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the Chenghu Road, Kunshan Development Zone No.248, Kunshan, Jiangsu, China.

Report No.: RKS160229001-00I

Test site at Bay Area Compliance Laboratories Corp. (Kunshan) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2014. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.10 - 2013.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 815570. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

FCC Part 15.231 Page 4 of 19

SYSTEM TEST CONFIGURATION

Justification

The system was configured in testing mode which was provided by manufacturer.

Report No.: RKS160229001-00I

EUT Exercise Software


No exercise software.

Equipment Modifications

No modification on the EUT.

Block Diagram of Test Setup

Below 1GHz:



FCC Part 15.231 Page 5 of 19

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.207	AC Line Conducted Emission	Not applicable*
§ 15.205, §15.209, §15.231 (e)	Radiated Emission Test	Compliance
§ 15.231 (c)	20dB Bandwidth Testing	Compliance
§ 15.231 (e)	Transmission and silent period testing	Compliance

Report No.: RKS160229001-00I

Not applicable*: The EUT is powered by battery only.

FCC Part 15.231 Page 6 of 19

FCC§15.203 - ANTENNA REQUIREMENT

Applicable Standard

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

Report No.: RKS160229001-00I

Antenna Connected Construction

The EUT has an internal antenna welded on the PCB and the antenna gain is 2dBi, which complied with 15.203. Please refer to the EUT Internal photos.


FCC Part 15.231 Page 7 of 19

FCC §15.205, §15.209, §15.231 (e) - RADIATED EMISSIONS TEST

Report No.: RKS160229001-00I


Applicable Standard

FCC §15.205, §15.209, §15.231 (e)



FCC Part 15.231 Page 8 of 19

Above 1 GHz:



Report No.: RKS160229001-00I

The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10 - 2013. The specification used was the FCC 15 \S 15.209, 15.205 and 15.231.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 5 GHz.

During the radiated emission test, the EMI test Receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30MHz - 1000MHz	100 kHz	300 kHz	100kHz	QP
1000 MHz – 5000 MHz	1MHz	3MHz	/	PK

FCC Part 15.231 Page 9 of 19

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sonoma Instrunent	Amplifier	330	171377	2015-09-16	2016-09-16
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2015-11-12	2016-11-11
Sunol Sciences	Broadband Antenna	ЈВ3	A090314-1	2015-09-12	2016-09-12
ETS	Horn Antenna	3115	6229	2015-11-07	2016-11-06
Rohde & Schwarz	Signal Analyzer	FSIQ26	100048	2015-11-12	2016-11-11
Mini	Pre-amplifier	ZVA-183-S+	857001418	2015-09-16	2016-09-16
champrotek	Chamber	Chamber A	1#	2015-09-17	2016-09-17
R&S	Auto test Software	EMC32	V 09.10.0	-	-
BACL	RF cable	KS-LAB-A01	KS-LAB-A01	2015-06-16	2016-12-15
BACL	RF cable	KS-LAB-A02	KS-LAB-A02	2015-06-16	2016-12-15

Report No.: RKS160229001-00I

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

According to §15.231, Intentional radiators operating under the provisions of this Section shall demonstrate compliance with the limits on the field strength of emissions, based on the average value of the measured emissions. As an alternative, compliance with the limits in the above table may be based on the use of measurement instrumentation with a CISPR quasi-peak detector.

FCC Part 15.231 Page 10 of 19

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Applicable Standard

According to §15.231 (e), the field strength of emissions from intentional radiators operated under this section shall not exceed the following

Report No.: RKS160229001-00I

Fundamental frequency (MHz)	Field strength of fundamental (microvolts/meter)	Field strength of spurious emission (microvolts/meter)
40.66-40.70	1,000	100
70-130	500	50
130-174	500 to 1,500 *	50 to 150 *
174-260	1,500	150
260-470	1,500 to 5,000 *	150 to 500*
Above 470	5,000	500

^{*}Linear interpolations.

The above field strength limits are specified at a distance of 3-meters the tighter limits apply at the band edges.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Loss + Cable Loss - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

FCC Part 15.231 Page 11 of 19

Test Results Summary

According to the data in the following table, the EUT complied with the CFR47 §15.205, §15.209, § 15.231 (e), with the worst margin reading of:

12.73dB at 433.92 MHz in the Horizontal polarization

Report No.: RKS160229001-00I

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_{\rm m} + U_{(L{\rm m})} \leq L_{\rm lim} + U_{\rm cispr}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Matt Yao on 2016-03-11

Test mode: Transmitting

Field Strength (Peak)

Е	Maximum	RX A	ntenna	Cable	Amplifier	Corrected	15.231(e)	
Frequency (MHz)	Reading (dBuV)	Polar (H/V)	Factor (dB)	Loss (dB)	Gain (dB)	Amplitude (dBμV/m)	Limit (dBµV/m)	Margin (dB)
433.92	80.86	V	15.5	1.4	25.2	72.56	92.87	20.31
433.92	77.13	Н	15.5	1.4	25.2	68.83	92.87	24.04
867.84	35.82	Н	22.4	2.3	25.2	35.32	72.87	37.55
867.84	32.65	V	22.4	2.3	25.2	32.15	72.87	40.72
1301.76	39.56	Н	24.5	2.9	31.1	35.86	74.00	38.14
1301.76	40.72	V	24.5	2.9	31.1	37.02	74.00	36.98

FCC Part 15.231 Page 12 of 19

Field Strength (Average)

	Peak	Antenna	Duty Cycle	Average	15.231(e)	
Frequency (MHz)	Measurement @3m (dBμV/m)	Polarity (H/V)	Correction Factor (dB)	Amp. (dBμV/m)	Limit (dBµV/m)	Margin (dB)
433.92	72.56	Н	-12.42	60.14	72.87	12.73
433.92	68.83	V	-12.42	56.41	72.87	16.46
867.84	35.32	Н	-12.42	22.90	52.87	29.97
867.84	32.15	V	-12.42	19.73	52.87	33.14
1301.76	35.86	Н	-12.42	23.44	54.00	30.56
1301.76	37.02	V	-12.42	24.60	54.00	29.40

Report No.: RKS160229001-00I

Note: All other spurious emission is the floor noise.

Note:

Calculate Average value based on duty cycle correction factor:


$$T_p=66.0 \text{ms}, T_{on}=15.8 \text{ ms}$$

Duty cycle=
$$T_{on}/T_{P}$$

= 15.8/66.0
=0.2394

Duty cycle factor= 20*log (duty cycle) = -12.42dB

Average=Peak+ Duty cycle factor



Date: 11.MAR.2016 16:10:26

FCC Part 15.231 Page 13 of 19

^{*}Within measurement uncertainty!

§15.231(c) - 20dB BANDWIDTH TESTING

Requirement

Per 15.231(c), The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. Bandwidth is determined at the points 20 dB down from the modulated carrier.

Report No.: RKS160229001-00I

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2015-11-12	2016-11-11

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Procedure

With the EUT's antenna attached, the waveform was received by the test antenna which was connected to the spectrum analyzer, plot the 20 dB bandwidth.

Test Data

Environmental Conditions

Temperature:	26 ℃
Relative Humidity:	53 %
ATM Pressure:	101.0 kPa

The testing was performed by Matt Yao on 2016-03-11

Test Mode: Transmitting

Please refer to following table and plot.


Channel Frequency	20dB Bandwidth	Limit	Result
(MHz)	(kHz)	(kHz)	
433.92	171.0	1084.8	Pass

Note: Limit = 0.25% * Center Frequency = 0.25% * 433.92 MHz = 1084.8 kHz 20dB Bandwidth=171.0 kHz<1084.8 kHz

FCC Part 15.231 Page 14 of 19

20 dB Bandwidth

Report No.: RKS160229001-00I



Date: 11.MAR.2016 16:14:41

FCC Part 15.231 Page 15 of 19


FCC §15.231(e) – TRANSMISSION AND SILENT PERIOD TESTING

Applicable Standard

Per 15.231(e), devices operated under the provisions of this paragraph shall be provided with a means for automatically limiting operation so that the duration of each transmission shall not be greater than one second and the silent period between transmissions shall be at least 30 times the duration of the transmission but in no case less than 10 seconds.

Report No.: RKS160229001-00I

EUT Setup



The deactivation test was performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10- 2013. The specification used was the FCC 15.231(e) limits.

FCC Part 15.231 Page 16 of 19

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sonoma Instrunent	Amplifier	330	171377	2015-09-16	2016-09-16
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2015-11-12	2016-11-11
Sunol Sciences	Broadband Antenna	ЈВ3	A090314-1	2015-09-12	2016-09-12
champrotek	Chamber	Chamber A	1#	2015-09-17	2016-09-17
R&S	Auto test Software	EMC32	V 09.10.0	-	-
BACL	RF cable	KS-LAB-A01	KS-LAB-A01	2015-06-16	2016-12-15
BACL	RF cable	KS-LAB-A02	KS-LAB-A02	2015-06-16	2016-12-15

Report No.: RKS160229001-00I

Test Data

Environmental Conditions

Temperature:	26 ℃	
Relative Humidity:	53 %	
ATM Pressure:	101.0 kPa	

The testing was performed by Matt Yao on 2016-03-11

Test Mode: Transmitting

Please refer to following table and plot.

Deactivation

Transmission period (s)	Limit (s)	Result
0.1316	< 1	Pass

Silent period

Silent period (s)	Limit (s)	Result
52.6	> 10	Pass

Note: The silent period between transmissions shall be at least 30 times the duration of the transmission but in no case less than 10 seconds.


The duration time is 0.1316s, $0.1316 \times 30 = 3.948s$.

FCC Part 15.231 Page 17 of 19

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).


Silent period

Report No.: RKS160229001-00I



Date: 11.MAR.2016 16:41:30

Transmission period



Date: 11.MAR.2016 16:50:12

FCC Part 15.231 Page 18 of 19

DECLARATION LETTER



Hangzhou Hamaton Tyre Valves Co.,Ltd. Add: 12 East Zhenxing Road, Linping, Yuhang, Hangzhou, China

Tel: 86-571-86159905 Fax: 86-571-86159905

E-Mail: zhangwb0892@163.com

Product Similarity Declaration

Report No.: RKS160229001-00I

Date: 2016-04-12

To:FEDERAL COMMUNICATIONS COMMISSIONS

Authorization and Evaluation Division

7435 Oakland Mills Road

Columbia, MD 21046

We, Hangzhou Hamaton Tyre Valves Co.,Ltd. hereby declare that we have a product named as TPMS sensor (Model: 97358 FCC ID: Z27HTS5A433) was tested by BACL, meanwhile, for our marketing purpose, we would like to list a series models (Model: 97359) on reports and certificate. The differences between them are only the model number. No other changes are made to them.

We confirm that all information above is true, and we'll be responsible for all the consequences. Please contact me if you have any question.

Signature:

Print Name: weibo zhang

Title: Quality Supervisor

***** END OF REPORT *****

FCC Part 15.231 Page 19 of 19