

# **Electromagnetic Compatibility Test Report**

Test Report No: MBX 210813 Rev.3 Issued on: November 28, 2013

> **Product Name Mini Hub**

**Tested According to** FCC 47 CFR, Part 15 Subpart B &C

## **Tests Performed for** Mobix Wireless Solutions Ltd.

25 Bazel St. POB 3849 Petach-Tikva, 49510 Israel Tel: +972 (3) 9213484

## QualiTech EMC Laboratory

30 Hasivim Street, P.O.Box 7500 Petah-Tikva, 4951169, Israel

Tel: +972-3-926 8443 Fax: +972-3-928 7490











Date: 28.11.2013 Rev. 2

The information contained herein is the property of QualiTech, EMC Lab and is supplied without liability for errors or omissions.

The copyright for this document vests in QualiTech, EMC Lab. All rights reserved.

This Test Report may not be reproduced, by any method, without the written permission of the QualiTech, EMC Lab.

If and when such permission is granted, the report must be reproduced only in the full format.

#### **Test Personnel**

Tests Performed By: -----

**Michael Shtier** 



Report Reviewed By: --

Rami Nataf Compliance Engineer & Operation Manager QualiTech EMC Laboratory



Report Approved By: ------

Maurice Dadoun EMC Lab. Manager

**QualiTech EMC Laboratory** 



## **Test Report Details:**

Test commencement date: 17.03.2013 Test completion date: 13.05.2013

Customer's Representative: Ofir Appelbaum

Issued on: 28.11.2013

#### **Revision details:**

Version	Date	Details/Reasons
Rev. 1	21.08.2013	-
Rev. 2	28.11.2013	1.Test results table in clause 3.1:Radiated Emissions (on page 8) updated to meet the test standard requirements.      2.The field strength of fundamental measurement was retested and the duty cycle took into account.(on page 16)
Rev .3	11.02.2014	on sections 3.1 & 4.1 the measurements noise level was documented

#### **Assessment Information:**

This report contains an assessment of the EUT against Electromagnetic Compatibility based upon tests carried out on the samples submitted. The results contained in this report relate only to the items tested. Manufactured products will not necessarily give identical results due to production and measurement tolerances. QualiTech, EMC Lab does not assume responsibility for any conclusion and generalization drawn from the test results with regards to other specimens or samples of type of the equipment represented by test item.

The EUT was setup and exercised using the configuration, modes of operation and arrangements defined in this report only.

#### **Modifications:**

**Modifications made to the EUT** 

None

Modifications made to the Test Standard

None

Mobix Wireless Solutions Ltd. Page 3 of 22 Mini Hub



# **Summary of Compliance Status:**

# FCC Part 15, Subpart C Part 15.249 – Intentional Radiators

Test Spec. Clause	Test Case	Remarks
FCC Part 15, Subpart B – Unintentional Radiators		•
§15.107	Conducted Limits	Pass
§15.109	Radiated Emission Limits	Pass
FCC Part 15, Subpart C – Intentional Radiators		•
§15.203	Antenna Connector requirement	Pass
§15.205	Radiated Emissions, Restricted Bands	Pass
§15.207	Conducted Limits	Pass
815 200	Radiated Emission Limits, General	Pass
§15.209	Requirements Complies	
	Operation within the Bands 902-928MHz,	
§15.249	2400-2483.5MHz, 5725-5875MHz, and	Pass
	24.0-24.25GHz	



Page 4 of 22 Mobix Wireless Solutions Ltd. Mini Hub



# Table of Contents

1.	GENERAL DESCRIPTION	6
1.1.	Description of the EUT /test Item:	6
2.	METHOD OF MEASUREMENTS	7
2.1.	Radiated Emissions Measurements in the restricted bands:	7
2.2.	Radiated Field Strength Measurements:	7
2.3.	Conducted Measurement:	7
2.4.	Radiated Emission measurements:	7
3.	REPORT OF MEASUREMENTS AND EXAMINATIONS	8
3.1.	Radiated Emission	8
3.2.	Power Line Emissions measurements	12
3.3.	Antenna Connector Requirements	14
3.4.	Radiated Emissions, Restricted Bands	15
4.	REPORT OF MEASUREMENTS AND EXAMINATIONS	16
4.1.	Field Strength of Fundamental & Harmonics	16
4.2.	Emissions radiated outside the band	19
5	APPENDIX	20



Date: 28.11.2013 Rev. 2

#### 1. General Description

#### 1.1. Description of the EUT /test Item:

**Product name: Mini Hub** 

FCC ID: Z2K400

FRN: 0021159595

#### **EUT Description:**

The n-DNet Mini Hub H100/400 main functions is serving as an n-DNet node and an interface between a single meter (electricity, gas or water meter) and the n-DNet network. The Mini Hub connects to the meter either by serial interface or by pulse output, collects the data, and transmits it to the concentrator periodically.

The communication to the concentrator is done using Mobix n-DNet technology utilizing the advantages of simultaneous data transfer over both the power lines and the air. The transmission over power lines (PLC) complies fully with the CENELEC (European committee for electromechanically standardization) specifications for usage of unlicensed bands over public electricity grid, and with the FCC definitions for the US markets. The Mini Hub unit interfaces seamlessly with non n-DNet devices either PLC or RF based. In this way it can serve as an n-DNet backbone for such devices. A group of Mini Hubs forms a mesh network which is served by an n-DNet concentrator device. The concentrator is then connected to Mobix MDM using any TCP interface (LAN, GPRS etc).

The MiniHub monitoring the meters, and is being polled by a data concentrator several times per day, over RF and PLC modems. When it has data to send back, it will reply on these polls with the accumulated data it is collecting. It has an internal power supply, and two modems to support the communication.

Mobix Wireless Solutions Ltd. Page 6 of 22 Mini Hub



2. Method of Measurements

#### 2.1. Radiated Emissions Measurements in the restricted bands:

For radiated emissions, which fall in the restricted bands the spectrum from 30MHz to 12.7 GHz was investigated following the guidelines in ANSI C63.4-2003

Measurements were performed with peak detector and repeated averaged with VBW=10Hz for frequencies above 1GHz, and quasi-peak detector below 1GHz.

#### 2.2. Radiated Field Strength Measurements:

During the testing process, the EUT was controlled via dedicated software. The EUT was operated at maximum power, continuous transmission and FSK data modulation.

The EUT was placed in an anechoic chamber, on a non-metallic table/support, 0.8m above the turntable, at 3 meter from the receive antenna, and its position where the maximum antenna gain occurs was identified. The peak and average readings of emissions were measured and recorded.

#### 2.3. Conducted Measurement:

The transmitter output was connected to the Spectrum Analyzer via an RF attenuator, and peak output power was measured.

#### 2.4. Radiated Emission measurements:

During the testing process, the EUT was controlled via dedicated software. The EUT was operated at in receive mode.

Measurements were performed at a 3-meter measurement distance in the semi-anechoic chamber in order to evaluate the radiated electromagnetic interference characteristics of the EUT. The EUT was placed on a non-metallic table/support, 0.8m above the turntable, was configured, arranged and operated in a manner consistent with typical application and load conditions.

An appropriate antenna depending upon the frequency range, per ANSI C63.4-2003 clause 4.1.5 was used. While the turntable was being rotated, the height of the antenna was varied from 1 to 4m for the frequency range of 30 MHz to 12.7 GHz. The highest radiated emission was detected by manipulating the system cables to the worst-case position. This process was repeated for both antenna polarizations. The amplitudes of worst-case emission were measured with the detector modes and resolution bandwidths

over various frequency ranges according to the requirements of ANSI C63.4-2003 clause 4.2.

Mobix Wireless Solutions Ltd. Page 7 of 22 Mini Hub



#### **Report of Measurements and Examinations 3.**

#### 3.1. **Radiated Emission**

Reference document:	47 CFR §15.109/209			
Test Requirements:	Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in Sec.15.209. Emission Level shall not exceed the limits of §15.109.			
Test setup:	See sec 2.1			
Method of testing:	Radiated			
Operating conditions:	Under normal test conditions	Pass		
S.A. Settings:	f <1GHz: RBW: 120kHz,VBW: 300kHz f >1GHz: RBW: 1MHz, VBW: 3MHz			
Mode of operation:	worse case result of intentional & unintentional transmission (max hold trace)			
Environment conditions:	Ambient Temperature: 22°c	Relative Atmospheric Pressure: 1011.4 hPa		
Test Result:	See below	See Plot 3.1.1 – Plot 3.1.6		

#### Test results: worse case result of intentional & unintentional transmission

Frequency [MHz]	Ant. Type	Ant. Pol.	Ant. Pos. [cm]	Turn- table Azimuth [°]	*Radiated Emission dB(µV/m)	Class B Limit at 3m dB(µV/m)	Margin [dB]	Pass/ Fail	comment
30-1,000	Bilog	V&H	100-400	0-360	36.92	46.5	9.58	Pass	
1,000- 2,900	Horn	V&H	100-400	0-360	33.61	54	20.39	Pass	Noise Level
2,900- 18,000	Horn	V&H	100-400	0-360	18.25	54	35.75	Pass	Level

Note: Radiated Emission [ $dB\mu V/m$ ] = measured [ $dB\mu V$ ] + Correction-factor [dB(1/m)] Correction Factor = Antenna factor + Cable Loss

Page 8 of 22 **Mobix Wireless Solutions Ltd.** Mini Hub




Date: 28.11.2013 Rev. 2

#### **Horizontal Polarization** 30MHz-1GHz **Plot 3.1.1**

(D)

ACTV DET: PEAK MEAS DET: PEAK DP AVO MKR 912.8 MHz 36 92 d8µV/#




#### **Vertical Polarization** 30MHz-1GHz **Plot 3.1.2**

 $^{\circ}$ 

ACTV DET: PEAK MEAS DET: PEAK DP AVO

MKR 219.7 MHz 23 45 d8pV/m





Date: 28.11.2013 Rev. 2


#### Horizontal Polarization 1GHz-2.9GHz Plot 3.1.3

Þσ

ACTV DET: PEAK

MEAS DET: PEAK QP AVG

MKR 1.730 GHz 33.61 dB,V/m




#### Vertical Polarization 1GHz-2.9GHz Plot 3.1.4

Þσ

ACTV DET: PEAK

MEAS DET: PEAK QP AVG

MKR 2.739 GHz 36.31 dB,V/m






Date: 28.11.2013 Rev. 2

#### Horizontal Polarization 2.9GHz-18GHz Plot 3.1.5

ÞΦ


ACTV DET: PEAK
MEAS DET: PEAK QP AVG
MKR 17.69 GHz
48.24 dB,V/m



#### Vertical Polarization 2.9GHz-18GHz Plot 3.1.6

ÞΦ

ACTV DET: PEAK
MEAS DET: PEAK QP AVG
MKR 17.69 GHz
48.25 dB V/m





#### 3.2. Power Line Emissions measurements

	T			
Reference document:	47 CFR §15.107/207			
Test Requirements:	Anydevices using an AC power line are required to comply also with the conducted limits set forth in Sec.15.107/207			
Test setup:	See Sec. 2.2			
Operating conditions:	Under normal test conditions			
Method of testing:	Conducted Emissions	Pass		
S.A. Settings:	f <30MHz: RBW: 9kHz, VBW:30kHz			
Mode of operation:	worse case result of intentional & unintentional transmission (max hold trace)			
Environment conditions:	Ambient Temperature: 21°c	Relative Humidity: Atmospheric Pressure: 54% 1011.4 hPa		
Test Result:	See below	See Plot 3.2.1 - Plot 3.2.2		

Test Results: Test results: worse case result of intentional & unintentional transmission

## "Phase" Lead

Frequency	Measured Result [dBµV]		Limit [dBμV]		Margin [dB]		D/E-3
[MHz]	QP	AVR	QP	AVR	QP	AVR	Pass/Fail
0.332046	38.6	37.4	59.40	49.40	-20.80	-12.00	Pass
0.673063	28.4	26.6	56.00	46.00	-27.60	-19.40	Pass
1.245927	29	27	56.00	46.00	-27.00	-19.00	Pass
2.245903	27.9	25.2	56.00	46.00	-28.10	-20.80	Pass
5.627219	26.2	22.6	60.00	50.00	-33.80	-27.40	Pass
18.727554	25.4	21.6	60.00	50.00	-34.60	-28.40	Pass

#### "Neutral" Lead

Frequency	Measured Result [dBμV]		Limit [dBµV]		Margin [dB]		D/E-3
[MHz]	QP	AVR	QP	AVR	QP	AVR	Pass/Fail
0.332982	46	44.5	59.38	49.38	-13.38	-4.88	Pass
0.683398	35.8	33.8	56.00	46.00	-20.20	-12.20	Pass
1.237617	36.2	33.4	56.00	46.00	-19.80	-12.60	Pass
2.248838	35	32	56.00	46.00	-21.00	-14.00	Pass
3.938144	31.7	28.2	56.00	46.00	-24.30	-17.80	Pass
18.436531	34.5	28.8	60.00	50.00	-25.50	-21.20	Pass




Date: 28.11.2013 Rev. 2

#### Power Supply Ports 150kHz – 30MHz "Phase" Lead Plot 3.2.1

(%)


ACTV DET: PEAK MERS DET: PEAK OP AVG NKR 330 kHz 39.94 dBpV



Power Supply Ports 150kHz – 30MHz "Neutral" Lead Plot 3.2.2

(B)

ACTV DET: PEAK MERS DET: PEAK OP AVG NKR 340 kHz 45.06 dBpV





## **3.3.** Antenna Connector Requirements

Reference document:	47 CFR §15.203		
Test Requirements:	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with provisions of this section.		
Test Result:	The EUT had integral antenna. Pass		

Mobix Wireless Solutions Ltd. Page 14 of 22 Mini Hub



#### **3.4. Radiated Emissions, Restricted Bands**

Reference document:	47 CFR §15.205			
Test Requirements:	Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in section 15.209(a) (See section 15.205(c).			
Test setup:	See Sec. 2.1			
Operating conditions:	Under normal test conditions	Pass		
Method of testing:	Radiated			
S.A. Settings:	RBW: 1MHz, VBW: 3MHz, 10Hz			
Environment conditions:	Ambient Temperature: 22°c	Relative Humidity: Atmospheric Pressure: 48% 1011.4 hPa		
Test Result:	In restricted bands: no peaks found. See below	-		

#### **Test results:**

The EUT complies with the requirements of this Section since it does not operate close the Restricted Bands of Operation. The EUT operates at 915~MHz.

Page 15 of 22 Mini Hub



## 4. Report of Measurements and examinations

## 4.1. Field Strength of Fundamental & Harmonics

Reference document:	47 CFR §15.249 (a)	47 CFR §15.249 (a)				
	the field strength of emi	ssions from intention	al radiators operated w	vithin the	se frequency bands shall comply	
Test	Fundamental frequency	Field strength of fundamental (millivolts/meter)		Fi	ield strength of harmonics (microvolts/meter)	
Requirements:	902-928 MHz	2-928 MHz			500	
	2400-2483.5 MHz	4	50	500		
	5725-5875 MHz	4	50	500		
	24.0-24.25 GHz	2	250		2500	
Test setup:	See Sec. 2.2			•	<u> </u>	
Operating conditions:	Under normal test condi	itions				
Method of testing:	Radiated		Fail		Fail	
S.A. Settings:	RBW: 120kHz, VBW: 3	300kHz				
Environment conditions:	Ambient Temperature: 23°c		Relative Humidity	: 45%	Atmospheric Pressure: 1011.4 hPa	
Test Result:	See below		Plot 4	4.1.1 & 4.	1.2	

#### **Test Results:**

Frequency [MHz]	Measured field Strength, at 3m [dBµV/m] Peak Value	*Duty Cycle factor For AVG	Polarization	Calculated field Strength limit at 3m [dBµV/m]	Calculated field Strength limit at 3m [dBµV/m]	Margin [dB] Average	Margin [dB] Peak	Result	Comments
	,			Average	Peak				
915	101.1	-7.96	Vertical & Hormonal (worst case)	94	114	-0.86	-12.9	Pass	-
1,000- 10,000	46.17	-	Vertical & Hormonal (worst case)	54	74	-7.83	-27.83	Pass	Noise level

<sup>\*</sup>Duty Cycle factor = 20 log (40msec/100msec)=-7.95 db



Date: 28.11.2013 Rev. 2

#### RE Plot Plot 4.1.2

ACTV DET: PEAK

(H)

Signal Freq (MHz) PK Amp QP Amp AV Amp QP<sub>4</sub>L2 1 914.984873 101.1 100.8 100.9 53.8

MEAS DET: PEAK DP AVG
MKR 914.9849 MHz
101.15 dBµV/m

PREAMP ON

10

dB/
ATN

40 dB

MR WB
SC FC
ACORR

CENTER 914.9849 MHz

IF BW 120 kHz

AVO BW 300 kHz

SPAN 500.0 kHz


Duty Cycle factor = 20 log (40msec/100msec)=-7.95 db






Date: 28.11.2013 Rev. 2

#### RE Horizontal Polarization Plot 4.1.3



#### RE Vertical Polarization Plot 4.1.4





4.2. Emissions radiated outside the band

Reference document:	47 CFR §15.249 (d)				
Test Requirements:	Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in § 15.209, whichever is the lesser attenuation.				
Test setup:	See Sec. 2.2				
Operating conditions:	Under normal test conditions				
Method of testing:	Radiated	Pass			
S.A. Settings:	RBW: 120kHz, VBW: 300kHz RBW: 120kHz, VBW: 300kHz				
Environment conditions:	Ambient Temperature: 23°c	Relative Humidity: 45%	Atmospheric Pressure: 1011.4 hPa		
Test Result:	See below	-			

#### **Test results:**

Frequency [MHz]	Measured field Strength, Peak Value at 3m [dBμV/m]	Polarization	Calculated field Strength limit at 3m [dBµV/m]	Result
All	emission were below the limit (se	-50 dbc	Pass	



#### **5.** Appendix

## Appendix A: List of Measuring Equipment used:

Equipment	Manufacturer	Model No.	Serial No.	Calibration Due Date	
CISPR16 EMI Receiver	HP	8546A	3710A00392	14.09.2013	
EMC Analyzer	HP	8593EM	3536A00131	10.12.2013	
Billog Antenna	Teseq	CBL 6141B	34119	03.07.2015	
Double Ridge Guide Horn antenna	A.R.A	DRG-118/A 17188		22.01.2015	
LISN	Fischer	50/250-25-2	9705	26.10.2013	
V-LISN	Schwarzbeck	NNBL 8226-2	120	14.04.2014	
Transient Limiter	Agilent	11947A	3107A04121	14.04.2014	
Current Probe	Fischer	F35A	44	25.10.2013	
CDN	Fischer	T2	9953	31.01.2014	
CDN	Fischer	T4	9817	31.01.2014	
Universal Telecom	Fischer	ISN F-071115-1057-1	20616	31.01.2014	
Discharge Simulator	Noiseken	ESS-2000	8000c03235	10.10.2013	
RF Signal Generator	Marconi (IFR)	2025	202301/940	12.11.2013	
Power Meter	Boonton	4230	26203	04.12.2013	
Power Sensor	Boonton	51015	31821	04.12.2013	
EFT Generator	EMtest	EFT 500 N8	V114911192	27.10.2013	
Coupling/Decoupling network for burst and surge	EMTest	CNI 503 A18/ 32A	V0947105536	04.10.2013	
Surge Generator combination wave,	EMTest	VCS 500 N10	V0824103874	04.10.2013	
RF Signal Generator	Marconi	2024	1122681029	08.11.2013	
Power Meter	Boonton	4235	26203	10.12.2013	
Power Sensor	Boonton	51015	31821	10.12.2013	
EM Injection Clamp	Fischer	F2031	348	31.01.2014	
CDN	Fischer	C1	9815	31.01.2014	
CDN	Fischer	M2	9824	31.01.2014	
CDN	Fischer	M3	9840	31.01.2014	
CDN	Fischer	T4 9817		02.01.2014	
ESD Generator	Noiseken	ESS-2000	8000C03235	10.10.2013	
ELF Magnetic Field Meter,	Holaday	HI-3624A	24A 00034615 20.		
Power Source & Analyzer	Pacific Power	140TMX	0233	10.11.2013	
Harmonics & Flickers Analyzer,	EM Test	DPA 500	V0627101584	01.10.2013	



#### **Appendix B: Accreditation Certificate**



# Accredited Laboratory A2LA has accredited

# QUALITECH

Petach-Tikva, Israel for technical competence in the field of

#### **Electrical Testing**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated 8 January 2009).

Presented this  $7^{\text{th}}$  day of December 2012.

President & CEO For the Accreditation Council

Certificate Number 1633.01 Valid to September 30, 2014

For the tests or types of tests to which this accreditation applies, please refer to the laboratory's Electrical Scope of Accreditation.

Page 21 of 22 Mobix Wireless Solutions Ltd. Mini Hub



End of the Test Report