

Page

: 1 of 37

Issued date FCC ID : September 28, 2011 : Z3D00KXN024W001A

Revised date

: November 16, 2011

RADIO TEST REPORT

Test Report No.: 31KE0363-SH-01-A

Applicant

Kyushukyohan Co., Ltd.

Type of Equipment

RF-Module

Model No.

KXN-RF24-01

FCC ID

Z3D00KXN024W001A

Test regulation

FCC Part15 Subpart C: 2011

Test result

Complied

- 1. This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
- 2. The results in this report apply only to the sample tested.
- 3. This sample tested is in compliance with the limits of the above regulation.
- 4. The test results in this test report are traceable to the national or international standards.
- 5. This test report must not be used by the customer to claim product certification, approval, or endorsement by any agency of the Federal Government.
- 6. The opinions and the interpretations to the result of the description in this report are outside scopes where UL Japan has been accredited.

Date of test:

August 5 to 12, 2011

Representative test engineer:

Tatsuya Arai Engineer of WiSE Japan, UL Verification Service

Approved by:

Ichiro Isozaki // Leader of WiSE Japan, UL Verification Service

JAB
Testing
RTL02610

The testing in which "Non-accreditation" is displayed is outside the accreditation scopes in UL Japan.

There is no testing item of "Non-accreditation".

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone Facsimile +81 463 50 6400

+81 463 50 6401

13-EM-F0429

Page : 2 of 37

Issued date : September 28, 2011 FCC ID : Z3D00KXN024W001A

Contents

	Page
SECTION 1: Customer information	3
SECTION 2: Equipment under test (E.U.T.)	3
SECTION 3: Test specification, procedures & results	4
SECTION 4: Operation of E.U.T. during testing	7
SECTION 5: Conducted emission	8
SECTION 6: 6dB bandwidth & Occupied bandwidth (99%)	8
SECTION 7: Maximum peak output power	9
SECTION 8: Spurious emission (Antenna port conducted)	9
SECTION 9: Radiated emission	10
SECTION 10: Peak Power density	11
Contents of APPENDIXES	12
APPENDIX 1: Photographs of test setup	13
APPENDIX 2: Test data	17
ADDENDIY 3. Tost instruments	36

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Page : 3 of 37

Issued date : September 28, 2011 FCC ID : Z3D00KXN024W001A Revised date : November 16, 2011

SECTION 1: Customer information

Company Name : Kyushukyohan Co., Ltd.

Address : 2-6-3, Kogane, Kokurakitaku, Kitakyusyu-shi, Fukuoka-ken, 802-0071 Japan

Telephone Number : +81-93-952-0226 Facsimile Number : +81-93-952-0216 Contact Person : Kurato Fujibayashi

SECTION 2: Equipment under test (E.U.T.)

2.1 Identification of E.U.T.

Type of Equipment : RF-Module
Model Number : KXN-RF24-01
Serial Number : Refer to Section 4.2

Rating : DC2.8 - 3.6V (Typical DC 3.3V)

Country of Mass-production : Japan

Condition of EUT : Production prototype

(Not for Sale: This sample is equivalent to mass-produced items.)

Receipt Date of Sample : August 5, 2011

Modification of EUT : No modification by the test lab.

2.2 Product description

Model: KXN-RF24-01 (referred to as the EUT in this report) is a RF-Module.

General Specification

Clock frequency(ies) in EUT : 16MHz

<Radio part>

Equipment type : Transceiver
Frequency of operation : 2402-2482MHz
Number of channels : 80 channels
Type of modulation : GFSK

Antenna type : 1/2 Lambda whip antenna

Antenna connector type : U.FL
Antenna gain : 2.14dBi
ITU code : F1D

Operation temperature range : -10 to +80 deg.C.

FCC Part15.31 (e)

The RF Module has its own regulator.

The RF Module is constantly provided voltage (DC2.0V) through the regulator regardless of input voltage. Therefore, this EUT complies with the requirement of 15.31(e).

FCC Part15.203

The EUT has a unique coupling/antenna connector (U.FL). Therefore the equipment complies with the requirement of 15.203.

UL Japan, Inc. Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Page : 4 of 37

Issued date : September 28, 2011 FCC ID : Z3D00KXN024W001A

SECTION 3: Test specification, procedures & results

3.1 Test specification

Test specification : FCC Part 15 Subpart C: 2011, final revised on July 8, 2011

and effective August 8, 2011

Title : FCC 47CFR Part15 Radio Frequency Device Subpart C Intentional Radiators

Section 15.207 Conducted limits

Section 15.209 Radiated emission limits, general requirements

Section 15.247 Operation within the bands 902-928MHz, 2400-2483.5MHz,

and 5725-5850MHz

3.2 Procedures & Results

Item	Test Procedure	Specification	Remarks	Deviation	Worst Margin	Results
Conducted emission	ANSI C63.4:2003 7. AC powerline conducted emission measurements	FCC 15.207	-	N/A	20.7dB Freq.: 0.2380MHz Phase: N Detection: Quasi-Peak Mode: Tx 2442MHz	Complied
6dB bandwidth	"Guidance on Measurement for Digital Transmission Systems Section 15.247" & ANSI C63.4:2003 13. Measurement of intentional radiators	FCC 15.247 (a)(2) & 15.209	Conducted	N/A		Complied
Maximum peak output power	"Guidance on Measurement for Digital Transmission Systems Section 15.247" & ANSI C63.4:2003 13. Measurement of intentional radiators	FCC 15.247 (b)(3) & 15.209	Conducted	N/A	See data	Complied
Spurious emission & Restricted band edges	"Guidance on Measurement for Digital Transmission Systems Section 15.247" & ANSI C63.4:2003 13. Measurement of intentional radiators	FCC 15.109, 15.247 (d) & 15.209	Conducted / Radiated	N/A	0.7dB Freq.: 2483.63MHz Polarization: Vertical Detection: Average Mode: Tx 2482MHz	Complied
Power density	"Guidance on Measurement for Digital Transmission Systems Section 15.247" & ANSI C63.4:2003 13. Measurement of intentional radiators n's Work Procedures No	FCC 15.247 (e)	Conducted	N/A	See data	Complied

UL Japan, Inc. Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Page : 5 of 37

Issued date : September 28, 2011 FCC ID : Z3D00KXN024W001A

3.3 Addition to standard

Item	Test Procedure	Specification	Remarks	Worst Margin	Results
1(99%)	ANSI C63.4:2003 13. Measurement of intentional radiators, RSS-Gen 4.6.1	RSS-Gen 4.6.1	Conducted	-	-
Note: UL Japan's Work Procedures No.13-EM-W0420 and 13-EM-W0422					

^{*} Other than above, no addition, exclusion nor deviation has been made from the standard.

3.4 Uncertainty

The following uncertainties have been calculated to provide a confidence level of 95% using a coverage factor k=2.

Item	Frequency range	No.1 SAC*1/SR*2 (±)	No.2 SAC/SR (±)	No.3 SAC/SR (±)
Conducted emission (AC Mains) AMN/LISN	150kHz-30MHz	3.0 dB	2.7 dB	3.1 dB
Radiated emission	9kHz-30MHz	3.3 dB	2.7 dB	3.4 dB
(Measurement distance: 3m)	30MHz-300MHz	4.7 dB	4.5 dB	4.7 dB
	300MHz-1GHz	4.5 dB	4.6 dB	4.6 dB
	1GHz-13GHz	3.9 dB	3.9 dB	4.0 dB
Radiated emission	13GHz-18GHz	4.8 dB	4.8 dB	4.8 dB
(Measurement distance: 1m)	18GHz-40GHz	4.4 dB	4.2 dB	4.2 dB

^{*1:} SAC=Semi-Anechoic Chamber

Conducted emission test

The data listed in this test report has enough margin, more than site margin.

Radiated emission test

The data listed in this report meets the limits unless the uncertainty is taken into consideration.

Antenna port conducted test

Power Measurement uncertainty above 1GHz for this test was: (±) 1.3dB

Spurious emission (Conducted), Power density Measurement (below 1GHz) uncertainty for this test was: (\pm) 1.9dB Spurious emission (Conducted), Power density Measurement (1G-3GHz) uncertainty for this test was: (\pm) 2.5dB Spurious emission (Conducted), Power density Measurement (3G-18GHz) uncertainty for this test was: (\pm) 3.8dB Spurious emission (Conducted), Power density Measurement (18G-26.5GHz) uncertainty for this test was: (\pm) 4.1dB Bandwidth Measurement uncertainty for this test was: (\pm) 5.4%

UL Japan, Inc. Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

^{*2:} SR= Shielded Room is applied besides radiated emission

Page : 6 of 37

Issued date : September 28, 2011 FCC ID : Z3D00KXN024W001A

3.5 Test location

UL Japan, Inc. Shonan EMC Lab.

1-22-3, Megumigaoka, Hiratsuka-shi, Kanagawa-ken 259-1220 JAPAN

Telephone number : +81 463 50 6400
Facsimile number : +81 463 50 6401
JAB Accreditation No. : RTL02610

	FCC Registration No.	IC Registration No.	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Maximum measurement distance
☑ No.1 Semi-anechoic chamber	697847	2973D-1	20.6 x 11.3 x 7.65	20.6 x 11.3	10m
☐ No.2 Semi-anechoic chamber	697847	2973D-2	20.6 x 11.3 x 7.65	20.6 x 11.3	10m
☑ No.3 Semi-anechoic chamber	697847	2973D-3	12.7 x 7.7 x 5.35	12.7 x 7.7	5m
☐ No.4 Full-anechoic chamber	-	-	8.1 x 5.1 x 3.55	8.1 x 5.1	-
☑ No.1 shielded room	-	-	6.8 x 4.1 x 2.7	6.8 x 4.1	-
☐ No.2 shielded room	-	-	6.8 x 4.1 x 2.7	6.8 x 4.1	-
☐ No.3 shielded room	-	-	6.3 x 4.7 x 2.7	6.3 x 4.7	-
☐ No.4 shielded room	-	-	4.4 x 4.7 x 2.7	4.4 x 4.7	-
☑ No.5 shielded room	-	-	7.8 x 6.4 x 2.7	7.8 x 6.4	-
☐ No.6 shielded room	-	-	7.8 x 6.4 x 2.7	7.8 x 6.4	-

3.6 Test setup, Data of test & Test instruments

Refer to Appendix 1 to 3.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Page : 7 of 37

Issued date : September 28, 2011 FCC ID : Z3D00KXN024W001A

SECTION 4: Operation of E.U.T. during testing


4.1 Operating mode

The EUT exercise program used during testing was designed to exercise the various system components in a manner similar to typical use.

Test item	Mode	Tested frequency			
All items	Transmitting	2402MHz, 2442MHz, 2482MHz			
*1) Software: None (controlled by jig)					
*2) Power setting: Fixed (End users cannot change the settings of the output power of the product.)					

Justification: The system was configured in typical fashion (as customer would normally use it) for testing.

4.2 Configuration and peripherals



^{*} Test data was taken under worse case conditions.

Description of EUT and support equipment

No.	Item	Model number	Serial number	Manufacturer	Remarks		
A	RF-Module	KXN-RF24-01	1	Nomura Engineering Co.,Ltd.	EUT		
В	Antenna	H2401SB	1	Dai-Ichi Denpa Kougyo Co., Ltd.	EUT		
C	Jig	-	-	Nomura Engineering Co.,Ltd.	-		
D	AC adaptor	LTE05W-S1	092900664	LI TONE ELECTRONICS CO., LTD.	-		

List of cables used

ľ	No.	Cable name	Length (m)	Shield (Cable)	Shield (Connector)	Remarks
	1	Antenna	0.15	Shielded	Shielded	-
	2	Signal	0.1	Unshielded	Unshielded	-
	3	DC	1.8	Unshielded	Unshielded	=

UL Japan, Inc. Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

^{*} Cabling and setup were taken into consideration and test data was taken under worse case conditions.

Page : 8 of 37

Issued date : September 28, 2011 FCC ID : Z3D00KXN024W001A

Revised date : October 5, 2011

SECTION 5: Conducted emission

5.1 Operating environment

The test was carried out in No.1 shielded room.

Temperature: Refer to test data (APPENDIX 2) Humidity: Refer to test data (APPENDIX 2)

5.2 Test configuration

EUT was placed on a platform of nominal size, 1m by 1.5m, raised 80cm above the conducting ground plane.

The table is made of Styrofoam and covered with polyvinyl chloride. That has very low permittivity.

The rear of tabletop was located 40cm to the vertical conducting plane. The rear of EUT, including peripherals was aligned and was flushed with rear of tabletop. All other surfaces of tabletop were at least 80cm from any other grounded conducting surface. AC adaptor was located 80cm from LISN and excess AC cable was bundled in center. I/O cables that were connected to the peripherals were bundled in center. They were folded back and for the forming a bundle 30cm to 40cm long and were hanged at a 40cm height to the ground plane.

Photographs of the set up are shown in Appendix 1.

5.3 Test conditions

Frequency range : 0.15 - 30MHz EUT position : Table top

5.4 Test procedure

The AC Mains Terminal Continuous disturbance Voltage had been measured with the EUT via test jig device within a shielded room. The test jig device was connected to a Line Impedance Stabilization Network (LISN).

An overview sweep with peak detection has been performed.

The measurements had been performed with a quasi-peak detector and if required, an average detector.

The conducted emission measurements were made with the following detector of the test receiver.

Detector Type : Quasi-Peak/ Average

IF Bandwidth : 9kHz

5.5 Results

Summary of the test results: Pass

Refer to APPENDIX 2

SECTION 6: 6dB bandwidth & Occupied bandwidth (99%)

Test procedure

The bandwidth was measured with a spectrum analyzer connected to the antenna port.

Summary of the test results: Pass

Refer to APPENDIX 2

UL Japan, Inc. Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Page : 9 of 37

Issued date : September 28, 2011 FCC ID : Z3D00KXN024W001A

SECTION 7: Maximum peak output power

Test procedure

The Maximum Peak Output Power was measured with a power meter connected to the antenna port.

Summary of the test results: Pass

Refer to APPENDIX 2

SECTION 8: Spurious emission (Antenna port conducted)

Test procedure

The spurious emission was measured with a spectrum analyzer connected to the antenna port.

In any 100kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator confirmed 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on a radiated measurement. In the frequency range below 30MHz, RBW was narrowed to separate the noise contents.

Then, wide-band noise near the limit was checked separately, however the noise was not detected as shown in the chart. (9kHz-150kHz:RBW=200Hz, 150kHz-30MHz:RBW=10kHz)

Summary of the test results: Pass

Refer to APPENDIX 2

UL Japan, Inc. Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Page : 10 of 37

Issued date : September 28, 2011 FCC ID : Z3D00KXN024W001A

SECTION 9: Radiated emission

9.1 Operating environment

The test was carried out in No.1 and No.3 Semi-Anechoic Chamber.

Temperature: Refer to test data (APPENDIX 2) Humidity: Refer to test data (APPENDIX 2)

9.2 Test configuration

EUT was placed on a platform of nominal size, 1m by 1.5m, raised 80cm above the conducting ground plane.

The table is made of Styrofoam and covered with polyvinyl chloride. That has very low permittivity.

The rear of EUT, including its peripherals was aligned and flushed with rear of tabletop.

Test was made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna was varied in height above the conducting ground plane to obtain the maximum signal strength. Photographs of the set up are shown in Appendix 1.

9.3 Test conditions

Frequency range : 30MHz to 26.5GHz

EUT position : Table top

9.4 Test procedure

The Radiated Electric Field Strength intensity has been measured on a semi-anechoic chamber with a ground plane and at a distance of 3m (below 13GHz) / 1m (above 13GHz). Measurements were performed with quasi-peak, peak and average detector. The measuring antenna height was varied between 1 and 4m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity. The measurements were performed for both vertical and horizontal antenna polarization.

The radiated emission measurements were made with the following detection of the test receiver and Spectrum Analyzer.

Frequency : 30-1000MHz 1000-26500MHz

Detection Type : Quasi-Peak Peak * Average

IF Bandwidth : 120kHz RBW: 1MHz/VBW: 3MHz RBW: 1MHz/VBW: 10Hz or 2.2kHz

The carrier level and noise levels were confirmed at each position of X, Y and Z axes of EUT to see the position of maximum noise, and the test was made at the position that has the maximum noise.

Worst position:

		Carrier	Spur	rious
		(Band edge)	30M-1GHz	1-26.5GHz
Horizontal	Module	Y	X	X
поптенна	Antenna	X	X	X
Vantical	Module	Z	X	X
Vertical	Antenna	Y	X	X

UL Japan, Inc. Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN


^{*} When using Spectrum analyzer, the test was made with adjusting span to zero by using peak hold.

^{*} The VBW was based on the inverse of the duty cycle (Refer to Appendix 2).

Page : 11 of 37

Issued date : September 28, 2011 FCC ID : Z3D00KXN024W001A

Figure 1. Antenna angle



11.5 Band edge

Band edge level at 2400MHz is less than 20dB of peak point of the carrier. Band edge level at 2390MHz, 2483.5MHz and 2483.63MHz are below the limits of FCC 15.209. Refer to the data of Radiated emission.

11.6 Results

Summary of the test results: Pass *No noise was detected above the 5th order harmonics.

Refer to APPENDIX 2

SECTION 10: Peak Power density

Test procedure

The peak power density was measured with a spectrum analyzer connected to the antenna port.

Instrument used : Spectrum Analyzer *1)

RBW : 3kHz

*1) PSD Option 1 of " Measurement of Digital Transmission Systems Operating under Section 15.247".

Summary of the test results: Pass

Refer to APPENDIX 2

UL Japan, Inc. Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Page : 12 of 37

Issued date : September 28, 2011 FCC ID : Z3D00KXN024W001A

Contents of APPENDIXES

APPENDIX 1: Photographs of test setup

Conducted emission Radiated emission Pre-check of the worst position

APPENDIX 2: Test data

Conducted emission 6dB bandwidth Maximum peak output power Radiated emission Spurious emission (Antenna port conducted) Peak power density 99% Occupied bandwidth

APPENDIX 3: Test instruments

Test instruments

UL Japan, Inc. Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN