



Project No.: TM-2309000356P
Report No.: TMWK2309003423KS

FCC ID: Z3K-EVOLVESLS10

Page 1 / 15
Rev.: 00

RF Exposure Evaluation Report

FCC 47 CFR § 2.1091

for
Evolve SLS 10 Monitor

Model Name.: 620105

Prepared for:

JET OPTOELECTRONICS CO.,LTD.
7F-2, No. 300, Yangguang St., Neihu Dist., Taipei City 11491,Taiwan

Prepared by

Compliance Certification Services Inc.
Wugu Laboratory
No.11, Wugong 6th Rd., Wugu Dist.,
New Taipei City, Taiwan.
Issue Date: February 16, 2024

Note: This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, NIST or any government agencies. The test results in the report only apply to the tested sample.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Report No.: TMWK2309003423KS

Page 2 / 15
Rev.: 00

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	February 16, 2024	Initial Issue	ALL	Peggy Tsai



Report No.: TMWK2309003423KS

Page 3 / 15
Rev.: 00

Table of Contents

1	ATTESTATION OF TEST RESULTS	4
2	TEST SPECIFICATION, METHODS AND PROCEDURES	5
3	DEVICE UNDER TEST (DUT) INFORMATION.....	6
3.1	DUT DESCRIPTION	6
3.2	WIRELESS TECHNOLOGIES	7
4	MAXIMUM PERMISSIBLE EXPOSURE	9
4.1	LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)	9
4.2	MPE CALCULATION METHOD	10
4.3	MPE EXEMPTION	11
4.4	MULTIPLE RF SOURCES	12
5	MPE EXEMPTION OPTION B.....	13
6	SIMULTANEOUS TRANSMISSION EXEMPT	14
6.1	SUM OF THE WIFI 2.4GHZ & WIFI 5GHZ+ BLUETOOTH	14
7	FACILITIES	15



Report No.: TMWK2309003423KS

Page 4 / 15
Rev.: 00

1 Attestation of Test Results

Applicant Name	JET OPTOELECTRONICS CO.,LTD.
Model Name	Evolve SLS 10 Monitor
Applicable Standards	FCC 47 CFR § 2.1091 FCC 47 CFR § 1.1307 FCC 47 CFR § 1.1310 Published RF exposure KDB procedures
Receive EUT Date:	September 21, 2023
Compliance Certification Services Inc. , tested the above equipment in accordance with the requirements set forth in the above standards. Determination of compliance is based on the results of the compliance measurement,not taking into account measurement instrumentation uncertainty.All indications of Pass/Fail in this report are opinions expressed by Compliance Certification Services Inc, based on interpretations and/or observations of test results. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.	
Approved & Released By: 	
Sky Zhou Asst. Section Manager Compliance Certification Services Inc.	



Report No.: TMWK2309003423KS

Page 5 / 15

Rev.: 00

2 Test Specification, Methods and Procedures

The tests documented in this report were performed in accordance with FCC 47 CFR § 2.1091, the following FCC Published RF exposure [KDB](#) procedures:

- 447498 D04 Interim General RF Exposure Guidance v01
- 865664 D02 RF Exposure Reporting v01r02



Report No.: TMWK2309003423KS

Page 6 / 15
Rev.: 00

3 Device Under Test (DUT) Information

3.1 DUT Description

Product	Evolve SLS 10 Monitor
Trade Name	JET OPTOELECTRONICS CO., LTD.
Model No.	620105
Model Discrepancy	N/A
Hardware Version	20230607 D01
Software Version	MAINLINE-115 MCU version V1.2.16
Serial number	H230811M5000020
Sample Stage	Identical prototype

3.2 Wireless Technologies

Frequency bands	☒ Bluetooth: 2402MHz-2480MHz ☒ 802.11b/g/n HT20/: 2412MHz ~ 2462 MHz ☐ 802.11n HT40/: 2422MHz ~ 2452MHz ☒ 802.11a/n HT20: 5180MHz ~ 5240MHz / 5260MHz ~ 5320MHz / 5500MHz ~ 5700MHz / 5745MHz ~ 5825MHz ☒ 802.11ac VHT20: 5180MHz ~ 5240MHz / 5260MHz ~ 5320MHz / 5500MHz ~ 5700MHz / 5745MHz ~ 5825MHz ☒ 802.11n HT40: 5190MHz ~ 5230MHz / 5270MHz ~ 5310MHz / 5510MHz ~ 5670MHz / 5755MHz ~ 5795MHz ☒ 802.11ac VHT 40: 5190MHz ~ 5230MHz / 5270MHz ~ 5310MHz / 5510MHz ~ 5670MHz / 5755MHz ~ 5795MHz ☒ 802.11ac VHT80: 5210MHz / 5290MHz / 5530MHz ~ 5610MHz / 5775MHz ☐ Others																																		
Exposure classification	☐ Occupational/Controlled exposure ☒ General Population/Uncontrolled exposure																																		
Antenna Specification	BT: PIFA Antenna / Gain: 2.70 dBi WIFI 2.4GHz: PIFA Antenna / Gain: 2.70 dBi Power Directional Gain: 5.71 dBi WIFI 5GHz: 5150~5250 PIFA Antenna / Gain: 3.80 dBi Power Directional Gain: 6.81 dBi 5250~5350: PIFA Antenna / Gain: 3.80 dBi Power Directional Gain: 6.81 dBi 5470~5725: PIFA Antenna / Gain: 3.80 dBi Power Directional Gain: 6.81 dBi 5725~5850 PIFA Antenna / Gain: 3.80 dBi Power Directional Gain: 6.81 dBi <table><tr><td>BT:</td><td>Antenna Gain :</td><td>2.70 dBi</td><td>(Numeric gain: 1.86)</td><td>Worst</td></tr><tr><td>2.4GHz:</td><td>Antenna Gain:</td><td>5.71 dBi</td><td>(Numeric gain: 3.72)</td><td>Worst</td></tr><tr><td>5GHz(U-NII-1):</td><td>Antenna Gain:</td><td>6.81 dBi</td><td>(Numeric gain: 4.80)</td><td>Worst</td></tr><tr><td>5GHz(U-NII-2A)</td><td>Antenna Gain:</td><td>6.81 dBi</td><td>(Numeric gain: 4.80)</td><td>Worst</td></tr><tr><td>5GHz(U-NII-2C)</td><td>Antenna Gain:</td><td>6.81 dBi</td><td>(Numeric gain: 4.80)</td><td>Worst</td></tr><tr><td>5GHz(U-NII-3):</td><td>Antenna Gain:</td><td>6.81 dBi</td><td>(Numeric gain: 4.80)</td><td>Worst</td></tr></table>					BT:	Antenna Gain :	2.70 dBi	(Numeric gain: 1.86)	Worst	2.4GHz:	Antenna Gain:	5.71 dBi	(Numeric gain: 3.72)	Worst	5GHz(U-NII-1):	Antenna Gain:	6.81 dBi	(Numeric gain: 4.80)	Worst	5GHz(U-NII-2A)	Antenna Gain:	6.81 dBi	(Numeric gain: 4.80)	Worst	5GHz(U-NII-2C)	Antenna Gain:	6.81 dBi	(Numeric gain: 4.80)	Worst	5GHz(U-NII-3):	Antenna Gain:	6.81 dBi	(Numeric gain: 4.80)	Worst
BT:	Antenna Gain :	2.70 dBi	(Numeric gain: 1.86)	Worst																															
2.4GHz:	Antenna Gain:	5.71 dBi	(Numeric gain: 3.72)	Worst																															
5GHz(U-NII-1):	Antenna Gain:	6.81 dBi	(Numeric gain: 4.80)	Worst																															
5GHz(U-NII-2A)	Antenna Gain:	6.81 dBi	(Numeric gain: 4.80)	Worst																															
5GHz(U-NII-2C)	Antenna Gain:	6.81 dBi	(Numeric gain: 4.80)	Worst																															
5GHz(U-NII-3):	Antenna Gain:	6.81 dBi	(Numeric gain: 4.80)	Worst																															

Maximum
tune up
power

BT	8.00 dBm	(6.310 mW)
BLE	8.00 dBm	(6.310 mW)

2.4GHz

IEEE 802.11b (Multiple)	19.50 dBm	(89.125 mW)
IEEE 802.11g (Multiple)	20.00 dBm	(100.000 mW)
IEEE 802.11n HT 20 (MIMO)	20.00 dBm	(100.00 mW)

5GHz (U-NII-1)

IEEE 802.11a (Multiple)	15.50 dBm	(35.48 mW)
IEEE 802.11n HT 20 (MIMO)	15.50 dBm	(35.48 mW)
IEEE 802.11n HT 40 (MIMO)	15.00 dBm	(31.62 mW)
IEEE 802.11ac VHT 20 (MIMO)	15.50 dBm	(35.48 mW)
IEEE 802.11ac VHT 40 (MIMO)	15.00 dBm	(31.62 mW)
IEEE 802.11ac VHT 80 (MIMO)	8.00 dBm	(6.31 mW)

5GHz (U-NII-2A)

IEEE 802.11a (Multiple)	15.50 dBm	(35.48 mW)
IEEE 802.11n HT 20 (MIMO)	15.50 dBm	(35.48 mW)
IEEE 802.11n HT 40 (MIMO)	15.50 dBm	(35.48 mW)
IEEE 802.11ac VHT 20 (MIMO)	15.50 dBm	(35.48 mW)
IEEE 802.11ac VHT 40 (MIMO)	15.50 dBm	(35.48 mW)
IEEE 802.11ac VHT 80 (MIMO)	12.00 dBm	(15.85 mW)

5GHz (U-NII-2C)

IEEE 802.11a (Multiple)	17.50 dBm	(56.23 mW)
IEEE 802.11n HT 20 (MIMO)	17.00 dBm	(50.12 mW)
IEEE 802.11n HT 40 (MIMO)	16.00 dBm	(39.81 mW)
IEEE 802.11ac VHT 20 (MIMO)	17.00 dBm	(50.12 mW)
IEEE 802.11ac VHT 40 (MIMO)	16.00 dBm	(39.81 mW)
IEEE 802.11ac VHT 80 (MIMO)	15.50 dBm	(35.48 mW)

5GHz (U-NII-3)

IEEE 802.11a (Multiple)	17.50 dBm	(56.23 mW)
IEEE 802.11n HT 20 (MIMO)	17.50 dBm	(56.23 mW)
IEEE 802.11n HT 40 (MIMO)	17.00 dBm	(50.12 mW)
IEEE 802.11ac VHT 20 (MIMO)	17.50 dBm	(56.23 mW)
IEEE 802.11ac VHT 40 (MIMO)	17.00 dBm	(50.12 mW)
IEEE 802.11ac VHT 80 (MIMO)	17.50 dBm	(56.23 mW)

Notes:

- For more details, please refer to the User's manual of the EUT.
- Disclaimer: Antenna information is provided by the applicant, test results of this report are applicable to the sample EUT received.
- The tune up power referred the AVG power of the test report TMWK2309003418KR, TMWK2309003419KR, TMWK2309003420KR and TMWK2309003421KR for RF Exposure assessment purpose.

4 Maximum Permissible Exposure

4.1 Limits for Maximum Permissible Exposure (MPE)

Table 1 - Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	* 100	6
3.0-30	1842/f	4.89/f	* 900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	* 100	30
1.34-30	824/f	2.19/f	* 180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
<u>1,500-100,000</u>			1.0	30

4.2 MPE Calculation Method

Calculation

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{377}$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377 d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \text{ Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

If, Substituting the MPE safe distance using d = 20 cm into Equation 1:

$$S = 0.000199 \times P \times G$$

4.3 MPE EXEMPTION

- (A) The available maximum time-averaged power is no more than 1 mW
- (B) The available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

- (C) Using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

Single RF Sources Subject to Routine Environmental Evaluation	
RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2 f$.
1,500-100,000	$19.2 R^2$.
Note: R is in meters, f is in MHz.	

4.4 Multiple RF sources

In the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation),

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$



5 MPE Exemption Option B

Bluetooth

Mode	Frequency (MHz)	R(m)	Max Tune-up power (dBm)	G(dBi)	Max Tune-up EIRP (dBm)	Max Tune-up ERP (dBm)	Max Tune-up ERP (mW)	ERP Threshold (mW)	MPE Exemption
BT	2480.00	0.2	8.0	2.70	10.70	8.55	7.161	3060	Complies
BLE	2480.00	0.2	8.0	2.70	10.70	8.55	7.161	3060	Complies

WIFI 2.4GHz (DTS)

Mode	Frequency (MHz)	R(m)	Max Tune-up power (dBm)	G(dBi)	Max Tune-up EIRP (dBm)	Max Tune-up ERP (dBm)	Max Tune-up ERP (mW)	ERP Threshold (mW)	MPE Exemption
IEEE 802.11b (Multiple)	2462.00	0.2	19.5	5.71	25.21	23.06	202.302	3060	Complies
IEEE 802.11g (Multiple)	2437.00	0.2	20.0	5.71	25.71	23.56	226.986	3060	Complies
IEEE 802.11n HT 20 (MIMO)	2437.00	0.2	20.0	5.71	25.71	23.56	226.986	3060	Complies

WIFI 5.2GHz (U-NII-1)

Mode	Frequency (MHz)	R(m)	Max Tune-up power (dBm)	G(dBi)	Max Tune-up EIRP (dBm)	Max Tune-up ERP (dBm)	Max Tune-up ERP (mW)	ERP Threshold (mW)	MPE Exemption
IEEE 802.11a (Multiple)	5240.00	0.2	15.5	6.81	22.31	20.16	103.753	3060	Complies
IEEE 802.11n HT 20 (MIMO)	5240.00	0.2	15.5	6.81	22.31	20.16	103.753	3060	Complies
IEEE 802.11n HT 40 (MIMO)	5230.00	0.2	15.0	6.81	21.81	19.66	92.470	3060	Complies
IEEE 802.11ac VHT 20 (MIMO)	5240.00	0.2	15.5	6.81	22.31	20.16	103.753	3060	Complies
IEEE 802.11ac VHT 40 (MIMO)	5230.00	0.2	15.0	6.81	21.81	19.66	92.470	3060	Complies
IEEE 802.11ac VHT 80 (MIMO)	5210.00	0.2	8.0	6.81	14.81	12.66	18.450	3060	Complies

WIFI 5.3GHz (U-NII-2A)

Mode	Frequency (MHz)	R(m)	Max Tune-up power (dBm)	G(dBi)	Max Tune-up EIRP (dBm)	Max Tune-up ERP (dBm)	Max Tune-up ERP (mW)	ERP Threshold (mW)	MPE Exemption
IEEE 802.11a (Multiple)	5320.00	0.2	15.5	6.81	22.31	20.16	103.753	3060	Complies
IEEE 802.11n HT 20 (MIMO)	5320.00	0.2	15.5	6.81	22.31	20.16	103.753	3060	Complies
IEEE 802.11n HT 40 (MIMO)	5270.00	0.2	15.5	6.81	22.31	20.16	103.753	3060	Complies
IEEE 802.11ac VHT 20 (MIMO)	5320.00	0.2	15.5	6.81	22.31	20.16	103.753	3060	Complies
IEEE 802.11ac VHT 40 (MIMO)	5270.00	0.2	15.5	6.81	22.31	20.16	103.753	3060	Complies
IEEE 802.11ac VHT 80 (MIMO)	5290.00	0.2	12.0	6.81	18.81	16.66	46.345	3060	Complies

WIFI 5.5GHz (U-NII-2C)

Mode	Frequency (MHz)	R(m)	Max Tune-up power (dBm)	G(dBi)	Max Tune-up EIRP (dBm)	Max Tune-up ERP (dBm)	Max Tune-up ERP (mW)	ERP Threshold (mW)	MPE Exemption
IEEE 802.11a (Multiple)	5720.00	0.2	17.5	6.81	24.31	22.16	164.437	3060	Complies
IEEE 802.11n HT 20	5720.00	0.2	17.0	6.81	23.81	21.66	146.555	3060	Complies
IEEE 802.11n HT 40	5710.00	0.2	16.0	6.81	22.81	20.66	116.413	3060	Complies
IEEE 802.11ac VHT 20	5720.00	0.2	17.0	6.81	23.81	21.66	146.555	3060	Complies
IEEE 802.11ac VHT 40	5710.00	0.2	16.0	6.81	22.81	20.66	116.413	3060	Complies
IEEE 802.11ac VHT 80	5610.00	0.2	15.5	6.81	22.31	20.16	103.753	3060	Complies

WIFI 5.8GHz (U-NII-3)

Mode	Frequency (MHz)	R(m)	Max Tune-up power (dBm)	G(dBi)	Max Tune-up EIRP (dBm)	Max Tune-up ERP (dBm)	Max Tune-up ERP (mW)	ERP Threshold (mW)	MPE Exemption
IEEE 802.11a (Multiple)	5825.00	0.2	17.5	6.81	24.31	22.16	164.437	3060	Complies
IEEE 802.11n HT20 (MIMO)	5825.00	0.2	17.5	6.81	24.31	22.16	164.437	3060	Complies
IEEE 802.11n HT40 (MIMO)	5795.00	0.2	17.0	6.81	23.81	21.66	146.555	3060	Complies
IEEE 802.11ac VHT20 (MIMO)	5825.00	0.2	17.5	6.81	24.31	22.16	164.437	3060	Complies
IEEE 802.11ac VHT40 (MIMO)	5795.00	0.2	17.0	6.81	23.81	21.66	146.555	3060	Complies
IEEE 802.11ac VHT80 (MIMO)	5775.00	0.2	17.5	6.81	24.31	22.16	164.437	3060	Complies

6 Simultaneous Transmission Exempt

In the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation),

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

Simultaneous Transmission Condition

RF Exposure Condition	Item	Capable Transmit Configurations		
	1	DTS	+	BT
	2	U-NII	+	BT

6.1 Sum of the WIFI 2.4GHz & WIFI 5GHz+ Bluetooth

WiFi 2.4GHz + Bluetooth

Mode	Frequency (MHz)	Max Tune-up ERP(mW)	ERP Threshold(mW)	simultaneous Transmission	simultaneous Transmission Limit
WiFi 2.4GHz	2437.00	226.986	3060	0.077	≤1
Bluetooth	2480.00	7.161	3060		

WiFi 5GHz + Bluetooth

Mode	Frequency (MHz)	Max Tune-up ERP(mW)	ERP Threshold(mW)	simultaneous Transmission	simultaneous Transmission Limit
WiFi 5GHz	5825.00	164.437	3060	0.056	≤1
Bluetooth	2480.00	7.161	3060		



Report No.: TMWK2309003423KS

Page 15 / 15
Rev.: 00

7 Facilities

All measurement facilities used to collect the measurement data are located at

☒ No.11, Wugong 6th Rd., Wugu Dist., New Taipei City, Taiwan.

☐ No. 12, Ln. 116, Wugong 3rd Rd., Wugu Dist., New Taipei City, Taiwan.

--End of Test Report--