



RoHS  
Compliant

D0

Font: Arial  
Text Height: 1.6mm

Label Text:

### FCC, UL LABEL DIMPLEX

54-160609-D0

REV	ECO	DESCRIPTION	DATE	IN
A0		PRE-RELEASED	05/04/17	DM
B0	2908	LABEL INFORMATION UPDATED; PRODUCTION RELEASE	5/30/2017	DM
C0		LABEL INFORMATION UPDATED; WIDTH WAS 1.438; LENGTH WAS 3.375	6/30/2017	DM
D0		FRENCH TRANSLATION ADDED; Size was 3.425 X 1.525; TEXT NOTE ADDED	7/5/2017	DM

DIMPLEX NORTH AMERICA LTD.

Model/ Modèle: CST-240

240VAC, 4000W,~60 Hz

Non-inductive/ Non-inductif

Functional Temperatures/

Température fonctionnelle:

-20°C (-4°F) - 80°C (176°F)

Operating Temperatures/

Température opérationnelle:

5°C (41°F) - 30°C (86°F)

For supply connections, use 12 AWG or  
larger wires rated for at least 80°C (176°F)

Pour les connexions d'alimentation, utilisez  
le numéro 12 AWG ou des fils plus grands  
évalués pour au moins de 80°C (176°F)

FCC ID: Z49-00008 IC: 6592A-00008

## CAUTION

HIGH VOLTAGE- DISCONNECT  
POWER BEFORE SERVICING

Font: ARIAL  
Height: 3.2mm

## AVERTISSEMENT

HAUTE TENSION-DÉBRANCHER  
AVANT LA MAINTENANCE

SIZE: 1.438 $\pm$ 0.06 X 3.375 $\pm$ 0.06  
 LABELLING SYSTEM : PGDQ2/PGDQ8 or PGJI2/PGJI8  
 MATERIAL: PRESSURE SENSITIVE STANDARD LABEL STOCK.  
 PERMANENT ADHESIVE WITH SPLIT BACKING OR  
 ROLL FORM.  
 COLOUR: BLACK MARKINGS ON WHITE BACKGROUND.

### NOTES:

1. REVISIONS TO SPECIFICATIONS STATED HEREIN MUST BE APPROVED BY ETRATECH ENGINEERING.

PROPRIETARY RIGHTS ARE INCLUDED IN THE INFORMATION DISCLOSED HEREIN. THIS INFORMATION IS SUBMITTED IN CONFIDENCE AND NEITHER THIS DOCUMENT NOR THE INFORMATION DISCLOSED HEREIN SHALL BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR USED OR DISCLOSED TO OTHERS FOR MANUFACTURING OR OTHER PURPOSE EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY ETRATECH INC.

DIMENSIONS ARE  
IN INCHES



DO NOT SCALE PRINTS  
TOLERANCES:

3 PLACES =  $\pm$  0.005"  
2 PLACES =  $\pm$  0.010"  
ANGULAR =  $\pm$  1°



**ETRATECH**  
BETTER CLIENT RELATIONSHIPS BY DESIGN

DRAWN BY

DAREN MILES

DATE

05/04/17

SCALE

NTS

SHEET

1 OF 1

CHECKED

APPROVED

DESCRIPTION

FCC, UL LABEL DIMPLEX

A

54-160609-D0

Label location

