



TEST REPORT

Applicant Name : Seeed Technology Co., Ltd.
Address : 9F, G3 Building, TCL International E City, Zhongshanyuan Road,
Nanshan District, Shenzhen, Guangdong Province, P.R.C
Report Number : SZNS211008-51520E-00A
FCC ID: Z4T-ODYSSEY-A

Test Standard (s)

FCC PART 15.247

Sample Description

Product: ODYSSEY-X86i51135
Trademark: Seeed Studio
Tested Model: ODYSSEY-I51135(64G+512G/z)
Multiple Product and Model: ODYSSEY-X86i31115 ODYSSEY-I31115(xx+yy/z)
ODYSSEY-X86i31125 ODYSSEY-I31125(xx+yy/z)
ODYSSEY-X86i51135 ODYSSEY-I51135(xx+yy/z)
(Note: xx: DDR, 8G/16G/32G/64G; yy: SSD, 128G/256G/512G;
z: wifi module)
Date Received: 2021-10-08
Date of Test: 2021-10-14 to 2021-11-22
Report Date: 2021-11-24

Test Result:	Pass*
--------------	-------

* In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Black Ding

Black Ding
EMC Engineer

Approved By:

Candy Li

Candy Li
EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk "★". Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China
Tel: +86 755-26503290 Fax: +86 755-26503396 Web: www.atc-lab.com

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
SPECIAL ACCESSORIES.....	6
EQUIPMENT MODIFICATIONS	6
SUPPORT EQUIPMENT LIST AND DETAILS	7
EXTERNAL I/O CABLE.....	7
BLOCK DIAGRAM OF TEST SETUP	8
SUMMARY OF TEST RESULTS	10
TEST EQUIPMENT LIST	11
FCC §15.247 (i) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)	12
FCC §15.203 – ANTENNA REQUIREMENT	13
APPLICABLE STANDARD	13
ANTENNA CONNECTOR CONSTRUCTION	13
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	14
APPLICABLE STANDARD	14
EUT SETUP	14
EMI TEST RECEIVER SETUP.....	14
TEST PROCEDURE	14
TRANSD FACTOR & MARGIN CALCULATION.....	15
TEST DATA	15
FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS.....	20
APPLICABLE STANDARD	20
EUT SETUP	20
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	21
TEST PROCEDURE	21
FACTOR & MARGIN CALCULATION	21
TEST DATA	21
FCC §15.247(a) (1)-CHANNEL SEPARATION TEST	28
APPLICABLE STANDARD	28
TEST PROCEDURE	28
TEST DATA	28
FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH & 99% OCCUPIED BANDWIDTH.....	31
APPLICABLE STANDARD	31
TEST PROCEDURE	31
TEST DATA	32
FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST	43
APPLICABLE STANDARD	43

TEST PROCEDURE	43
TEST DATA	43
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME).....	46
APPLICABLE STANDARD	46
TEST PROCEDURE	46
TEST DATA	46
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT	56
APPLICABLE STANDARD	56
TEST PROCEDURE	56
TEST DATA	56
FCC §15.247(d) - BAND EDGES TESTING	62
APPLICABLE STANDARD	62
TEST PROCEDURE	62
TEST DATA	62

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	ODYSSEY-X86i51135	
Trademark	Seed Studio	
Tested Model	ODYSSEY-I51135(64G+512G/z)	
Multiple Product and Model	ODYSSEY-X86i31115	ODYSSEY-I31115(xx+yy/z)
	ODYSSEY-X86i31125	ODYSSEY-I31125(xx+yy/z)
	ODYSSEY-X86i51135	ODYSSEY-I51135(xx+yy/z)
	(Note: xx: DDR, 8G/16G/32G/64G; yy: SSD, 128G/256G/512G; z: wifi module)	
Model difference	Please refer to the DoS letter	
Frequency Range	Bluetooth: 2402~2480MHz	
Maximum conducted Peak output power	Bluetooth: 3.27dBm	
Modulation Technique	Bluetooth: GFSK, $\pi/4$ -DQPSK, 8DPSK	
Antenna Specification*	External Antenna: 2.13dBi (provided by the applicant)	
Voltage Range	DC 12V from adapter.	
Sample serial number	SZNS211008-51520E-RF-S1	
Sample/EUT Status	Good condition	
Adapter 1 information	Model: HA-1600-12 Input: 100-240V~1.7A 50/60Hz, Output: DC 12V, 5A, 60W	
Adapter 2 information	Model: PA-1061-81 Input: 100-240V~, 50/60Hz 1.6A Output: DC 12V, 5A, 60W	

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

For Radiated Emissions testing, please refer to DA 00-705 Released March 30, 2000, Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		5%
RF Frequency		0.082×10^{-7}
RF output power, conducted		0.73dB
Unwanted Emission, conducted		1.6dB
AC Power Lines Conducted Emissions		2.72dB
Emissions, Radiated	9kHz - 30MHz	2.66dB
	30MHz - 1GHz	4.28dB
	1GHz - 18GHz	4.98dB
	18GHz - 26.5GHz	5.06dB
	26.5GHz - 40GHz	4.72dB
Temperature		1°C
Humidity		6%
Supply voltages		0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189. Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 429 7.01.

Listed by Innovation, Science and Economic Development Canada (ISED), the Registration Number is 5077A.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode and support modes as below, which provided by manufacturer.

Modulation	Data Rate (Mbps)
GFSK	1
$\pi/4$ -DQPSK	2
8DPSK	3

EUT Exercise Software

No software was used to test, “app DRTU”* provided by manufacturer.

The device was tested with the Power level is 7*.

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
DELL	Keyboard	L100	CN0RH66658985C018C
DELL	Mouse	MOC5UG	Unknown
PHILIPS	DP Monitor	275M7C	Unknown
DELL	HDMI Monitor	ST2310f	Unknown
ZHIKE	Solid State Drive 1	U300	USA210510105
ZHIKE	Solid State Drive 2	U300	USA210510106
BORY	NVME PCIE SSD	Unknown	800295763
Kingston	Memory bank 1	9905700-E15.AO OG	Unknown
Kingston	Memory bank 2	99P5711-002.AO OG	Unknown
Unknown	M.2 PCI-E	YX-520	2106H520A 128GA 18829
SCI	Earphone	SCRC-130A	Unknown
Lenovo	Notebook	T430	Unknown

External I/O Cable

Cable Description	Length (m)	From Port	To
Unshielded Detachable DC output Cable	1.15	Adapter 1	EUT
Unshielded Detachable DC output Cable	1.0	Adapter2	EUT
Unshielded Detachable AC power Cable	1.0	EUT	Adapter 1
Unshielded Detachable AC power Cable	1.5	EUT	Adapter 2
Shielded Detachable HDMI Cable	1.75	EUT	HDMI Monitor
Shielded Detachable DP Cable	1.75	EUT	DP Monitor
Unshielded Detachable USB Cable	1.5	EUT	Mouse
Unshielded Detachable USB Cable	1.5	EUT	Keyboard
Unshielded Detachable RJ45 Cable 1	3	Internet	EUT
Unshielded Detachable RJ45 Cable 2	3	Notebook	EUT
Unshielded Detachable earphone Cable	0.75	EUT	Earphone


Block Diagram of Test Setup

For conducted emission:




For Radiated Emission:

Below 1GHz:



Above 1GHz:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i), §2.1091	Maximum Permissible Exposure(MPE)	Compliant
§15.203	Antenna Requirement	Compliant
§15.207(a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209 & §15.247(d)	Radiated Emissions	Compliant
§15.247(a)(1)	20 dB Emission Bandwidth & 99% Occupied Bandwidth	Compliant
§15.247(a)(1)	Channel Separation Test	Compliant
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliant
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliant
§15.247(b)(1)	Peak Output Power Measurement	Compliant
§15.247(d)	Band edges	Compliant

Note: Per FCC Part 15B, pre-test for all models with different CPU, and the worst case about maximum emission is model of ODYSSEY-I51135(64G+512G/z), which was recorded in this report.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde& Schwarz	EMI Test Receiver	ESCI	100784	2021/02/03	2022/02/02
R & S	L.I.S.N.	ENV216	101314	2020/12/25	2021/12/24
Anritsu Corp	50Ω Coaxial Switch	MP59B	6200506474	2020/12/25	2021/12/24
Unknown	RF Coaxial Cable	N-2m	No.2	2020/12/25	2021/12/24
Conducted Emission Test Software: e3 19821b (V9)					
Radiated Emissions Test					
Rohde& Schwarz	Test Receiver	ESR	102725	2020/12/25	2021/12/24
Rohde&Schwarz	Spectrum Analyzer	FSV40	101949	2021/5/18	2022/5/17
SONOMA INSTRUMENT	Amplifier	310 N	186131	2020/12/25	2021/12/24
A.H. Systems, inc.	Preamplifier	PAM-0118P	531	2021/07/08	2022/07/07
Quinstar	Amplifier	QLW-184055 36-J0	15964001002	2020/11/28	2021/11/27
Anritsu Corp	50 Coaxial Switch	MP59B	6100237248	2020/12/25	2021/12/24
Schwarzbeck	Bilog Antenna	VULB9163	9163-323	2020/01/05	2023/01/04
Schwarzbeck	Horn Antenna	BBHA9120D	9120D-1067	2020/01/05	2023/01/04
Schwarzbeck	HORN ANTENNA	BBHA9170	9170-359	2020/01/05	2023/01/04
Wainwright	High Pass Filter	WHKX3.6/18 G-10SS	5	2020/12/25	2021/12/24
Unknown	RF Coaxial Cable	N-5m	No.3	2020/12/25	2021/12/24
Unknown	RF Coaxial Cable	N-1m	No.5	2020/12/25	2021/12/24
Unknown	RF Coaxial Cable	N-10m	No.7	2020/11/09	2021/11/08
Unknown	RF Coaxial Cable	N-2m	No.8	2020/11/09	2021/11/08
Radiated Emission Test Software: EZ EMC V 1.1.4.2					
RF Conducted Test					
Rohde&Schwarz	Spectrum Analyzer	FSV40	101495	2020/12/24	2021/12/23
Rohde & Schwarz	Open Switch and Control Unit	OSP120 +OSP -B157	101244 + 100866	2020/12/24	2021/12/23

* **Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §15.247 (i) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)**Applicable Standard**

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (Minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

Result**Calculated Formulary:**

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Frequency (MHz)	Antenna Gain		Tune up conducted power		Evaluation Distance (cm)	Power Density (mW/cm²)	MPE Limit (mW/cm²)
	(dBi)	(numeric)	(dBm)	(mW)			
2402-2480	2.13	1.63	3.5	2.24	20	0.0007	1

Note: 1. The tune up conducted power was declared by the applicant.

2. The BT and Wi-Fi can not transmit at the same time.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant.

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has one external Antenna arrangement for Bluetooth, which was used a unique coupling and the antenna gain is 2.13dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliant.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Transd Factor & Margin Calculation

The Transd factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss. The basic equation is as follows:

$$\text{Transd Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over limit of -7 dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

$$\begin{aligned}\text{Over Limit} &= \text{Level} - \text{Limit} \\ \text{Level} &= \text{Read Level} + \text{Factor}\end{aligned}$$

Test Data


Environmental Conditions

Temperature:	23 °C
Relative Humidity:	49 %
ATM Pressure:	101.0 kPa

The testing was performed by Bin Duan on 2021-11-22.


EUT operation mode: BT transmitting

Adapter 1:
AC 120V/60 Hz, Line



Site : Shielding Room
 Condition: Line
 Mode : BT


	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.158	9.88	13.85	23.73	55.55	-31.82	Average
2	0.158	9.88	32.75	42.63	65.55	-22.92	QP
3	0.263	9.80	28.71	38.51	51.32	-12.81	Average
4	0.263	9.80	31.63	41.43	61.32	-19.89	QP
5	0.313	9.80	19.98	29.78	49.89	-20.11	Average
6	0.313	9.80	25.51	35.31	59.89	-24.58	QP
7	0.942	9.81	12.51	22.32	46.00	-23.68	Average
8	0.942	9.81	17.28	27.09	56.00	-28.91	QP
9	3.029	9.93	15.05	24.98	46.00	-21.02	Average
10	3.029	9.93	22.24	32.17	56.00	-23.83	QP
11	16.076	10.08	15.40	25.48	50.00	-24.52	Average
12	16.076	10.08	21.32	31.40	60.00	-28.60	QP

AC 120V/60 Hz, Neutral

Site : Shielding Room
Condition: Neutral
Mode : BT


	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.157	9.92	16.68	26.60	55.60	-29.00	Average
2	0.157	9.92	32.51	42.43	65.60	-23.17	QP
3	0.259	9.97	29.26	39.23	51.47	-12.24	Average
4	0.259	9.97	33.85	43.82	61.47	-17.65	QP
5	0.300	9.96	24.39	34.35	50.24	-15.89	Average
6	0.300	9.96	28.40	38.36	60.24	-21.88	QP
7	1.971	9.92	13.46	23.38	46.00	-22.62	Average
8	1.971	9.92	19.87	29.79	56.00	-26.21	QP
9	2.966	9.99	15.22	25.21	46.00	-20.79	Average
10	2.966	9.99	21.34	31.33	56.00	-24.67	QP
11	16.464	10.09	21.68	31.77	50.00	-18.23	Average
12	16.464	10.09	26.49	36.58	60.00	-23.42	QP

Adapter 2:
AC 120V/60 Hz, Line



Site : Shielding Room
Condition: Line
Mode : BT

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.178	9.84	32.48	42.32	54.58	-12.26	Average
2	0.178	9.84	40.77	50.61	64.58	-13.97	QP
3	0.206	9.80	27.84	37.64	53.38	-15.74	Average
4	0.206	9.80	38.73	48.53	63.38	-14.85	QP
5	0.331	9.80	16.30	26.10	49.43	-23.33	Average
6	0.331	9.80	23.73	33.53	59.43	-25.90	QP
7	0.508	9.80	12.78	22.58	46.00	-23.42	Average
8	0.508	9.80	15.55	25.35	56.00	-30.65	QP
9	4.693	9.98	8.96	18.94	46.00	-27.06	Average
10	4.693	9.98	18.15	28.13	56.00	-27.87	QP
11	5.028	9.99	9.95	19.94	50.00	-30.06	Average
12	5.028	9.99	18.94	28.93	60.00	-31.07	QP



AC 120V/60 Hz, Neutral

Site : Shielding Room
 Condition: Neutral
 Mode : BT

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.160	9.92	33.82	43.74	55.49	-11.75	Average
2	0.160	9.92	43.06	52.98	65.49	-12.51	QP
3	0.206	10.00	26.72	36.72	53.36	-16.64	Average
4	0.206	10.00	35.13	45.13	63.36	-18.23	QP
5	0.333	9.94	18.31	28.25	49.38	-21.13	Average
6	0.333	9.94	25.04	34.98	59.38	-24.40	QP
7	0.554	9.91	16.60	26.51	46.00	-19.49	Average
8	0.554	9.91	20.23	30.14	56.00	-25.86	QP
9	4.932	10.05	7.68	17.73	46.00	-28.27	Average
10	4.932	10.05	15.67	25.72	56.00	-30.28	QP
11	5.239	10.05	6.32	16.37	50.00	-33.63	Average
12	5.239	10.05	15.42	25.47	60.00	-34.53	QP

FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS**Applicable Standard**

FCC §15.205; §15.209; §15.247(d)

EUT Setup**Below 1 GHz:****Above 1GHz:**

The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

The EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1 MHz	3 MHz	/	PK
	1 MHz	10 Hz	/	Average

If the maximized peak measured value complies with the limit, then it is unnecessary to perform an QP/Average measurement

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

Factor & Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned} \text{Over Limit} &= \text{Result} / \text{Corrected Amplitude} - \text{Limit} \\ \text{Result} / \text{Corrected Amplitude} &= \text{Read Level} + \text{Factor} \end{aligned}$$

Test Data



Environmental Conditions

Temperature:	23~24 °C
Relative Humidity:	48~49%
ATM Pressure:	101.0 kPa

The testing was performed by Black Ding on 2021-10-21 for below 1GHz and 2021-10-22 for above 1GHz.


EUT operation mode: Transmitting

(Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK mode at X axis, Y axis, Z axis, the worst case is at Z axis)


30MHz-1GHz: (worst case GFSK Mode, Low channel)**Adapter 1:****Horizontal:****Vertical**

Adapter 2:

Horizontal:



Vertical



Above 1GHz:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)				
GFSK Low Channel									
2310.00	51.18	PK	253	1.80	H	-6.84	44.34	74.00	-29.66
2310.00	50.42	PK	171	1.90	V	-6.84	43.58	74.00	-30.42
2390.00	53.49	PK	155	1.50	H	-6.44	47.05	74.00	-26.95
2390.00	52.41	PK	212	1.70	V	-6.44	45.97	74.00	-28.03
4804.00	41.84	PK	336	1.70	H	2.81	44.65	74.00	-29.35
4804.00	41.41	PK	16	2.20	V	2.81	44.22	74.00	-29.78
GFSK Middle Channel									
4880.00	41.38	PK	100	2.10	H	3.04	44.42	74.00	-29.58
4880.00	40.82	PK	5	1.20	V	3.04	43.86	74.00	-30.14
GFSK High Channel									
2483.50	52.93	PK	163	1.20	H	-5.96	46.97	74.00	-27.03
2483.50	51.80	PK	192	1.20	V	-5.96	45.84	74.00	-28.16
2500.00	50.14	PK	138	1.70	H	-5.88	44.26	74.00	-29.74
2500.00	49.29	PK	7	2.20	V	-5.88	43.41	74.00	-30.59
4960.00	40.87	PK	27	2.20	H	3.29	44.16	74.00	-29.84
4960.00	40.26	PK	228	2.10	V	3.29	43.55	74.00	-30.45
π/4-DQPSK Low channel									
2310.00	51.27	PK	115	1.10	H	-6.84	44.43	74.00	-29.57
2310.00	50.53	PK	160	1.10	V	-6.84	43.69	74.00	-30.31
2390.00	53.71	PK	237	1.20	H	-6.44	47.27	74.00	-26.73
2390.00	52.52	PK	26	1.70	V	-6.44	46.08	74.00	-27.92
4804.00	41.71	PK	225	2.00	H	2.81	44.52	74.00	-29.48
4804.00	41.23	PK	180	2.10	V	2.81	44.04	74.00	-29.96
π/4-DQPSK Middle channel									
4880.00	41.33	PK	268	2.00	H	3.04	44.37	74.00	-29.63
4880.00	40.69	PK	101	1.10	V	3.04	43.73	74.00	-30.27
π/4-DQPSK High channel									
2483.50	53.02	PK	184	1.80	H	-5.96	47.06	74.00	-26.94
2483.50	51.91	PK	173	2.10	V	-5.96	45.95	74.00	-28.05
2500.00	50.07	PK	50	1.10	H	-5.88	44.19	74.00	-29.81
2500.00	49.26	PK	113	1.40	V	-5.88	43.38	74.00	-30.62
4960.00	40.83	PK	261	1.40	H	3.29	44.12	74.00	-29.88
4960.00	40.20	PK	38	1.50	V	3.29	43.49	74.00	-30.51

8DPSK Low channel									
2310.00	51.33	PK	122	2.00	H	-6.84	44.49	74.00	-29.51
2310.00	50.58	PK	212	1.90	V	-6.84	43.74	74.00	-30.26
2390.00	53.66	PK	253	1.40	H	-6.44	47.22	74.00	-26.78
2390.00	52.55	PK	212	1.90	V	-6.44	46.11	74.00	-27.89
4804.00	41.66	PK	126	1.40	H	2.81	44.47	74.00	-29.53
4804.00	41.05	PK	112	1.20	V	2.81	43.86	74.00	-30.14
8DPSK Middle channel									
4880.00	41.19	PK	243	2.10	H	3.04	44.23	74.00	-29.77
4880.00	40.38	PK	209	1.10	V	3.04	43.42	74.00	-30.58
8DPSK High channel									
2483.50	52.93	PK	341	1.60	H	-5.96	46.97	74.00	-27.03
2483.50	51.67	PK	154	1.30	V	-5.96	45.71	74.00	-28.29
2500.00	50.21	PK	190	1.40	H	-5.88	44.33	74.00	-29.67
2500.00	49.30	PK	228	1.40	V	-5.88	43.42	74.00	-30.58
4960.00	40.89	PK	228	1.40	H	3.29	44.18	74.00	-29.82
4960.00	39.98	PK	189	1.00	V	3.29	43.27	74.00	-30.73

Note:

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Corrected Factor + Reading

Margin = Corrected. Amplitude – Limit

The other spurious emission which is in the noise floor level was not recorded.


The test result of peak was less than the limit of average, so just peak value were recorded.

1-18GHz


Pre-scan for GFSK mode

Low Channel

Horizontal:



Vertical:




18-25GHz


Pre-scan for GFSK mode:

Low Channel

Horizontal:



Vertical:



FCC §15.247(a) (1)-CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Test Procedure

1. Set the EUT in transmitting mode, maxhold the channel.
2. Set the adjacent channel of the EUT and maxhold another trace.
3. Measure the channel separation.

Test Data

Environmental Conditions

Temperature:	23 °C
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa

The testing was performed by Black Ding on 2021-10-14.


EUT operation mode: Transmitting

Test Result: Compliant.

Test Mode	Channel	Result[MHz]	Limit[MHz]	Verdict
DH1	Hop	1.009	≥ 0.622	PASS
2DH1	Hop	1.006	≥ 0.964	PASS
3DH1	Hop	1	≥ 0.962	PASS


Please refer to the below plots:

DH1_Ant1_Hop




Date: 14.OCT.2021 10:28:04

2DH1_Ant1_Hop



Date: 14.OCT.2021 09:56:17

3DH1_Ant1_Hop



Date: 14.OCT.2021 10:10:05

FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH & 99% OCCUPIED BANDWIDTH

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.


Test Procedure

The following conditions shall be observed for measuring the occupied bandwidth and 20 dB bandwidth:

- The transmitter shall be operated at its maximum carrier power measured under normal test conditions.
- The span of the spectrum analyzer shall be set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.
- The detector of the spectrum analyzer shall be set to “Sample”. However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or “Max Hold”) may be necessary to determine the occupied / 20 dB bandwidth if the device is not transmitting continuously.
- The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the actual occupied / 20 dB bandwidth and the video bandwidth (VBW) shall not be smaller than three times the RBW value. Video averaging is not permitted.

Note: It may be necessary to repeat the measurement a few times until the RBW and VBW are in compliance with the above requirement.

For the 99% emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99% emission bandwidth).



Test Data**Environmental Conditions**

Temperature:	23 °C
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa

The testing was performed by Black Ding on 2021-10-14.

EUT operation mode: Transmitting

Test Result: Compliant.


Test Mode	Channel[MHz]	20db EBW[MHz]	Limit[MHz]	Verdict
DH1	2402	0.927	---	PASS
	2441	0.933	---	PASS
	2480	0.933	---	PASS
2DH1	2402	1.443	---	PASS
	2441	1.443	---	PASS
	2480	1.446	---	PASS
3DH1	2402	1.440	---	PASS
	2441	1.440	---	PASS
	2480	1.443	---	PASS

Test Mode	Channel[MHz]	99% Occupied Bandwidth [MHz]	Limit[MHz]	Verdict
DH1	2402	0.851	---	PASS
	2441	0.851	---	PASS
	2480	0.845	---	PASS
2DH1	2402	1.349	---	PASS
	2441	1.349	---	PASS
	2480	1.346	---	PASS
3DH1	2402	1.343	---	PASS
	2441	1.34	---	PASS
	2480	1.337	---	PASS

Please refer to the below plots:


20 dB EMISSION BANDWIDTH

DH1_Ant1_2402




Date: 14.OCT.2021 10:42:31

DH1_Ant1_2441




Date: 14.OCT.2021 10:44:15

DH1_Ant1_2480




Date: 14.OCT.2021 10:45:23

2DH1_Ant1_2402




Date: 14.OCT.2021 09:23:05

2DH1_Ant1_2441




Date: 14.OCT.2021 09:24:42

2DH1_Ant1_2480




Date: 14.OCT.2021 09:25:45

3DH1_Ant1_2402




Date: 14.OCT.2021 09:27:24

3DH1_Ant1_2441



Date: 14.OCT.2021 09:28:54


3DH1_Ant1_2480



Date: 14.OCT.2021 09:30:06


99% OCCUPIED BANDWIDTH

DH1_Ant1_2402




Date: 14.OCT.2021 10:42:54

DH1_Ant1_2441




Date: 14.OCT.2021 10:44:38

DH1_Ant1_2480




Date: 14.OCT.2021 10:45:44

2DH1_Ant1_2402




Date: 14.OCT.2021 09:23:25

2DH1_Ant1_2441




Date: 14.OCT.2021 09:25:03

2DH1_Ant1_2480




Date: 14.OCT.2021 09:26:06

3DH1_Ant1_2402




Date: 14.OCT.2021 09:27:45

3DH1_Ant1_2441



Date: 14.OCT.2021 09:29:16



Date: 14.OCT.2021 09:30:26

FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST**Applicable Standard**

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the max-hold function record the quantity of the channel.

Test Data**Environmental Conditions**

Temperature:	23 °C
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa


The testing was performed by Black Ding on 2021-10-14.

EUT operation mode: Transmitting

Test Result: Compliant.


TestMode	Channel	Result[Num]	Limit[Num]	Verdict
DH1	Hop	79	>=15	PASS
2DH1	Hop	79	>=15	PASS
3DH1	Hop	79	>=15	PASS

DH1_Ant1_Hop




Date: 14.OCT.2021 09:49:30

2DH1_Ant1_Hop



Date: 14.OCT.2021 09:57:05

3DH1_Ant1_Hop



Date: 14.OCT.2021 10:10:41

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)

Applicable Standard

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. The EUT was worked in channel hopping.
2. Set the RBW to: 1MHz.
3. Set the VBW $\geq 3 \times$ RBW.
4. Set the span to 0Hz.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Recorded the time of single pulses

Test Data

Environmental Conditions

Temperature:	23 °C
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa


The testing was performed by Black Ding on 2021-10-14.

EUT operation mode: Transmitting


Test Result: Compliant.

TestMode	Antenna	Channel	BurstWidth [ms]	TotalHops [Num]	Result[s]	Limit[s]	Verdict
DH1	Ant1	Hop	0.38	320	0.121	≤ 0.4	PASS
DH3	Ant1	Hop	1.63	180	0.293	≤ 0.4	PASS
DH5	Ant1	Hop	2.87	130	0.372	≤ 0.4	PASS
2DH1	Ant1	Hop	0.39	320	0.123	≤ 0.4	PASS
2DH3	Ant1	Hop	1.63	190	0.31	≤ 0.4	PASS
2DH5	Ant1	Hop	2.87	110	0.316	≤ 0.4	PASS
3DH1	Ant1	Hop	0.39	320	0.124	≤ 0.4	PASS
3DH3	Ant1	Hop	1.49	150	0.223	≤ 0.4	PASS
3DH5	Ant1	Hop	2.87	90	0.259	≤ 0.4	PASS

DH1_Ant1_Hop




Date: 14.OCT.2021 09:49:48




Date: 14.OCT.2021 09:49:53

DH3_Ant1_Hop




Date: 14.OCT.2021 09:50:35




Date: 14.OCT.2021 09:50:41

DH5_Ant1_Hop




Date: 14.OCT.2021 09:52:34




Date: 14.OCT.2021 09:52:40

2DH1_Ant1_Hop




Date: 14.OCT.2021 09:57:23




Date: 14.OCT.2021 09:57:28

2DH3_Ant1_Hop




Date: 14.OCT.2021 09:58:15




Date: 14.OCT.2021 09:58:20

2DH5_Ant1_Hop




Date: 14.OCT.2021 09:59:04




Date: 14.OCT.2021 09:59:10

3DH1_Ant1_Hop




Date: 14.OCT.2021 10:10:59




Date: 14.OCT.2021 10:11:04

3DH3_Ant1_Hop




Date: 14.OCT.2021 10:11:55




Date: 14.OCT.2021 10:12:01

3DH5_Ant1_Hop



Date: 14.OCT.2021 10:30:39



Date: 14.OCT.2021 10:30:45

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.

Test Data

Environmental Conditions

Temperature:	23 °C
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa


The testing was performed by Black Ding on 2021-10-14

EUT operation mode: Transmitting

Test Result: Compliant.


TestMode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
DH1	Ant1	2402	1.61	<=20.97	PASS
		2441	1.73	<=20.97	PASS
		2480	1.68	<=20.97	PASS
2DH1	Ant1	2402	3.01	<=20.97	PASS
		2441	2.99	<=20.97	PASS
		2480	2.94	<=20.97	PASS
3DH1	Ant1	2402	3.15	<=20.97	PASS
		2441	3.27	<=20.97	PASS
		2480	3.2	<=20.97	PASS

DH1_Ant1_2402




Date: 14.OCT.2021 10:31:45

DH1_Ant1_2441




Date: 14.OCT.2021 10:32:24

DH1_Ant1_2480




Date: 14.OCT.2021 10:33:03

2DH1_Ant1_2402




Date: 14.OCT.2021 10:46:47

2DH1_Ant1_2441




Date: 14.OCT.2021 10:35:44

2DH1_Ant1_2480




Date: 14.OCT.2021 10:36:19

3DH1_Ant1_2402




Date: 14.OCT.2021 10:37:05

3DH1_Ant1_2441



Date: 14.OCT.2021 10:38:13

3DH1_Ant1_2480



Date: 14.OCT.2021 10:38:53

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Data

Environmental Conditions

Temperature:	23°C
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa


The testing was performed by Black Ding on 2021-10-14.

EUT operation mode: Transmitting

Test Result: Compliant.


Conducted Band Edge Result:

DH1_Ant1_Low_2402




Date: 14.OCT.2021 10:43:09

DH1_Ant1_High_2480




Date: 14.OCT.2021 10:45:59

DH1_Ant1_Low_Hop_2402




Date: 14.OCT.2021 09:48:24

DH1_Ant1_High_Hop_2480




Date: 14.OCT.2021 09:53:21

2DH1_Ant1_Low_2402




Date: 14.OCT.2021 09:23:40

2DH1_Ant1_High_2480




Date: 14.OCT.2021 09:26:21

2DH1_Ant1_Low_Hop_2402




Date: 14.OCT.2021 09:54:21

2DH1_Ant1_High_Hop_2480




Date: 14.OCT.2021 10:00:00

3DH1_Ant1_Low_2402




Date: 14.OCT.2021 09:28:00

3DH1_Ant1_High_2480




Date: 14.OCT.2021 09:30:41

3DH1_Ant1_Low_Hop_2402



Date: 14.OCT.2021 10:04:56

3DH1_Ant1_High_Hop_2480



Date: 14.OCT.2021 10:17:17

***** END OF REPORT *****