

SPECIFICATION



Shenzhen Guandetong Electronic Limited

Copper tube antenna 1.13 black line total length 75mm with IPEX terminal (full coverage sleeve) According to 2.4G dual band

Product specification

Customers	深圳市丽欧	Frequency	2400-2500MHz
Name of wire rod		Version	A1
Customer data		GuandetongNo	
GuandetongNo			
R FDesign	肖彬	RF manager	刘亮
Structural design	王栋	Structure manager	王华
Technical Director	ANDY	Date	2024-12-09

Customer confirmation:

Whether the Assembly meets your requirements: ☐OK ☐NG

catalogue

Cover	1
catalogue.....	2
一、Product pictures	3
二、Product parameters	3
三、S11(VSWR、Return、Smith)	4
四、Structural drawings.....	4
五、Antenna gain and efficiency.....	4
六、3D graph.....	5
七、Environmental performance test.....	6

Confidentiality requirements of Shenzhen Guanditong Electronic Co. , Ltd. . The company has proprietary technology to provide the information, which should be strictly confidential, it shall not be disclosed to any person or company without the prior written consent of Shenzhen Guanditong Electronic Co. , Ltd. .

一、 Product pictures



二、 Product parameters


Product test parameters			
(Name)	2.4G copper tube antenna	(Model Type)	GDT-2.4G-75MM
(Electrical Specifications)			
(Frenquency Range)	2400-2500MHz	(Polarization)	perpendicular
(Impedance)	50 欧	Radiation	QXCOMM
(VSWR)	≤2.0	(Power)	50W
(Gain)	1.4dBi	(Bandwidth	100M
(Mechanical Specifications)			
(Copper tube dimensions)	24.5*4.4*75MM	(Chassis Color)	black
(Connector)	IPEX	(Cable Length)	75±2mm
(Chassis Material)	copper tube	(Wire specifications and colors)	1.13 black
(Working Temperature)	-40℃--+85℃	(Limit Temperature)	-40℃--+85℃

Address: 3/F, Tower D, Huanguan Nanmaoyuan Industrial Park, Guanhu Street, Longhua District, Shenzhen. Tel: 0755-88298396 fax: 0755-89733896

<http://www.szgdtrf.com>

Confidentiality requirements of Shenzhen Guanditong Electronic Co. , Ltd. . The company has proprietary technology to provide the information, which should be strictly confidential, it shall not be disclosed to any person or company without the prior written consent of Shenzhen Guanditong Electronic Co. , Ltd. .

四、Structural drawings



Address: 3/F, Tower D, Huanguan Nanmaoyuan Industrial Park, Guanhu Street,
Longhua District, Shenzhen. Tel: 0755-88298396 fax: 0755-89733896


<http://www.szgdtrf.com>

本公司已拥有专有技术所提供的资料，这些专有资料应严加保密，在未经深圳冠得通电子有限公司事先书面同意的时不允许透露给任何人或公司。

五、Antenna gain and efficiency

Test Point ID	Freq. (MHz)	TRP (dBm)	Gain (dBi)	Directivity (dBi)	Efficiency (%)	Efficiency (dB)	Max (dBm)	Theta of Max	Phi of Max	Min (dBm)	Theta of Min	Phi of Min	AVG (dBm)	Max/Min (dB)	Max/AVG (dB)	Min/AVG (dB)
1	2400.0	2400.00	0.65	4.96	37.1%	-4.31	0.65	7500	0	-95.99	0	0	-5.41	96.64	6.06	-90.58
2	2410.0	2410.00	0.44	4.86	36.1%	-4.42	0.44	7500	0	-95.99	0	0	-5.49	96.43	5.94	-90.50
3	2420.0	2420.00	0.02	4.70	34.1%	-4.67	0.02	7500	0	-95.99	0	0	-5.72	96.01	5.75	-90.27
4	2430.0	2430.00	0.26	4.73	35.7%	-4.47	0.26	9000	12000	-95.99	0	0	-5.52	96.25	5.78	-90.47
5	2440.0	2440.00	0.35	4.89	35.2%	-4.54	0.35	9000	13500	-95.99	0	0	-5.61	96.34	5.97	-90.38
6	2450.0	2450.00	0.25	4.98	33.7%	-4.73	0.25	9000	13500	-95.99	0	0	-5.82	96.24	6.06	-90.17
7	2460.0	2460.00	0.12	5.07	32.0%	-4.95	0.12	9000	13500	-95.99	0	0	-6.05	96.11	6.17	-89.94
8	2470.0	2470.00	0.20	5.10	32.3%	-4.90	0.20	9000	13500	-95.99	0	0	-6.00	96.18	6.20	-89.99
9	2480.0	2480.00	0.40	5.11	33.8%	-4.71	0.40	9000	13500	-95.99	0	0	-5.80	96.39	6.20	-90.19
10	2490.0	2490.00	0.60	5.16	35.0%	-4.56	0.60	9000	13500	-95.99	0	0	-5.65	96.59	6.25	-90.34
11	2500.0	2500.00	0.73	5.23	35.5%	-4.50	0.73	9000	13500	-95.99	0	0	-5.59	96.72	6.32	-90.40

六、3D graph



七、Environmental performance test

project	Project test conditions	Specifications
---------	-------------------------	----------------

深圳市冠得通电子有限公司

保 密 要 求

本公司已拥有专有技术所提供的资料，这些专有资料应严加保密，在未经深圳冠得通电子有限公司事先书面同意的时不允许透露给任何人或公司。

Storage environment	The test temperature, humidity and air pressure are as follows when there is no specific condition: 1. The temperature is $-30^{\circ}\text{C}\sim+80^{\circ}\text{C}$ 2. Relative humidity: 45% - 85% 3. The air pressure is 86kpa-106kpa	Normal electrical and mechanical performance
High and low temperature test	5 cycles between 70°C and 40°C , then under normal conditions 1-2H, check the appearance quality.	The size shall meet the requirements and Mechanical and electrical performance
Constant damp heat resistance test	Relative humidity: $95 \pm 3\%$, test temperature: 40°C. After lasting for 2h, The electrical performance shall be measured within 5 minutes after the test object is taken out, and the test object shall be within the normal range Part 1-2H, check the appearance quality	The size shall meet the requirements and Mechanical and electrical performance
vibration test	Vibration frequency range: 10-55HZ, displacement amplitude: 0.35MM, acceleration amplitude: 50.0M/s, frequency sweep cycles: 30 times	Normal electrical and mechanical performance
Drop test	Free fall for 3 times in the direction of mutually perpendicular axes at a height of 1M	Normal electrical and mechanical performance