



RF TEST REPORT

Product Name: LoRaWAN module

Model Name: LND915

FCC ID: Z5J-REACHLND915

Issued For : Xiamen Reach AIOT Technology Co., Ltd.

Rm.501,#51,Wanghai Road,Software Park II,Xiamen,China

Issued By : Shenzhen LGT Test Service Co., Ltd.

Room 205, Building 13, Zone B, Zhenxiong Industrial Park,
No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan
District, Shenzhen, Guangdong, China

Report Number: LGT23L002RF02

Sample Received Date: 01 Dec. 2023

Date of Test: 01 Dec. 2023 – 21 Feb. 2024

Date of Issue: 21 Feb. 2024

The test report is effective only with both signature and specialized stamp. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report only apply to the tested sample.



TEST REPORT CERTIFICATION

Applicant: Xiamen Reach AIOT Technology Co., Ltd.
Address: Rm.501,#51,Wanghai Road,Software Park II,Xiamen,China
Manufacturer: Xiamen Reach AIOT Technology Co., Ltd.
Address: Rm.501,#51,Wanghai Road,Software Park II,Xiamen,China
Product Name: LoRaWAN module
Trademark: RIV
Model Name: LND915
Sample Status: Normal

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC Part 15.247, Subpart C ANSI C63.10-2013	PASS

Prepared by:

Zane Shan

Zane Shan
Engineer

Approved by:

Vita Li

Vita Li
Technical Director





Table of Contents	Page
1. SUMMARY OF TEST RESULTS	6
1.1 TEST FACTORY	7
1.2 MEASUREMENT UNCERTAINTY	7
2. GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF THE EUT	8
2.2 DESCRIPTION OF THE TEST MODES	10
2.3 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING	10
2.4 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS	10
2.5 EQUIPMENTS LIST	11
3. EMC EMISSION TEST	12
3.1 CONDUCTED EMISSION MEASUREMENT	12
3.2 RADIATED EMISSION MEASUREMENT	16
4. CONDUCTED SPURIOUS & BAND EDGE EMISSION	31
4.1 LIMIT	31
4.2 TEST PROCEDURE	31
4.3 TEST SETUP	32
4.4 EUT OPERATION CONDITIONS	32
4.5 TEST RESULTS	33
5. NUMBER OF HOPPING CHANNEL	41
5.1 LIMIT	41
5.2 TEST PROCEDURE	41
5.3 TEST SETUP	41
5.4 EUT OPERATION CONDITIONS	41
5.5 TEST RESULTS	42
6. AVERAGE TIME OF OCCUPANCY	43
6.1 LIMIT	43
6.2 TEST PROCEDURE	43
6.3 TEST SETUP	43
6.4 EUT OPERATION CONDITIONS	43
6.5 TEST RESULTS	44
7. HOPPING CHANNEL SEPARATION MEASUREMEN	46
7.1 LIMIT	46
7.2 TEST PROCEDURE	46
7.3 TEST SETUP	46



Table of Contents	Page
7.4 EUT OPERATION CONDITIONS	46
7.5 TEST RESULTS	47
8. BANDWIDTH TEST	49
8.1 LIMIT	49
8.2 TEST PROCEDURE	49
8.3 TEST SETUP	49
8.4 EUT OPERATION CONDITIONS	49
8.5 TEST RESULTS	50
9. OUTPUT POWER TEST	52
9.1 LIMIT	52
9.2 TEST PROCEDURE	52
9.3 TEST SETUP	52
9.4 EUT OPERATION CONDITIONS	52
9.5 TEST RESULTS	53
10. ANTENNA REQUIREMENT	54
10.1 STANDARD REQUIREMENT	54
10.2 EUT ANTENNA	54



Revision History

Rev.	Issue Date	Contents
00	21 Feb. 2024	Initial Issue



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:
KDB 558074 D01 15.247 Meas Guidance v05r02.

FCC Part 15.247, Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	--
15.247(a)(1)	Hopping Channel Separation	PASS	--
15.247(b)(2)	Output Power	PASS	--
15.209	Radiated Spurious Emission	PASS	--
15.247(d)	Conducted Spurious & Band Edge Emission	PASS	--
15.247(a)(1)(i)	Number of Hopping Frequency	PASS	--
15.247(a)(1)(i)	Dwell Time	PASS	--
15.247(a)(1)(i)	Bandwidth	PASS	--
15.205	Restricted bands of operation	PASS	--
Part 15.247(d)/part 15.209(a)	Band Edge Emission	PASS	--
15.203	Antenna Requirement	PASS	--

NOTE:

- (1) 'N/A' denotes test is not applicable in this Test Report.
- (2) All tests are according to ANSI C63.10-2013.



1.1 TEST FACTORY

Company Name:	Shenzhen LGT Test Service Co., Ltd.
Address:	Room 205, Building 13, Zone B, Zhenxiong Industrial Park, No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan District, Shenzhen, Guangdong, China
Accreditation Certificate	A2LA Certificate No.: 6727.01
	FCC Registration No.: 746540
	CAB ID: CN0136

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95** %.

No.	Item	Uncertainty
1	RF output power, conducted	$\pm 0.68\text{dB}$
2	Unwanted Emissions, conducted	$\pm 2.988\text{dB}$
3	All emissions, radiated 9K-30MHz	$\pm 2.84\text{dB}$
4	All emissions, radiated 30M-1GHz	$\pm 4.39\text{dB}$
5	All emissions, radiated 1G-6GHz	$\pm 5.10\text{dB}$
6	All emissions, radiated >6G	$\pm 5.48\text{dB}$
7	Conducted Emission (9KHz-150KHz)	$\pm 2.79\text{dB}$
8	Conducted Emission (150KHz-30MHz)	$\pm 2.80\text{dB}$

Note: The measurement uncertainty is not included in the test result.



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

Product Name:	LoRaWAN module
Trademark:	RIV
Model Name:	LND915
Series Model:	N/A
Model Difference:	N/A
Channel List:	Please refer to the Note 3.
Frequency:	902 – 928 MHz
Modulation:	Lora
Rating:	DC 3.3V
Hardware Version:	LND470E_V1.0
Software Version:	FW_LNDxxxE_REACH-AT-CE&FCC_Release_1.0.2-20231124.bin
Connecting I/O Port(s):	Please refer to the Note 1.

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User Manual.
2. The antenna information refers to the manufacturer provide report, applicable only to the tested sample identified in the report. Due to the incorrect antenna information, a series of problems such as the accuracy of the test results will be borne by the customer.



3.

Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	902.3	22	906.7	44	911.1
01	902.5	23	906.9	45	911.3
02	902.7	24	907.1	46	911.5
03	902.9	25	907.3	47	911.7
04	903.1	26	907.5	48	911.9
05	903.3	27	907.7	49	912.1
06	903.5	28	907.9	50	912.3
07	903.7	29	908.1	51	912.5
08	903.9	30	908.3	52	912.7
09	904.1	31	908.5	53	912.9
10	904.3	32	908.7	54	913.1
11	904.5	33	908.9	55	913.3
12	904.7	34	909.1	56	913.5
13	904.9	35	909.3	57	913.7
14	905.1	36	909.5	58	913.9
15	905.3	37	909.7	59	914.1
16	905.5	38	909.9	60	914.3
17	905.7	39	910.1	61	914.5
18	905.9	40	910.3	62	914.7
19	906.1	41	910.5	63	914.9
20	906.1	42	910.7	/	/
21	906.5	43	910.9	/	/



2.2 DESCRIPTION OF THE TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Worst Mode	Description	Data Rate/Modulation
Mode 1	TX CH00	1Mbps/Lora
Mode 2	TX CH32	1Mbps/Lora
Mode 3	TX CH63	1Mbps/Lora
Mode 4	Hopping	Lora

Note:

We tested for all available U.S. voltage and frequencies (For 120V, 50/60Hz and 240V, 50/60Hz) for which the device is capable of operation, and the worst case of 120V/ 60Hz is shown in the report.

For AC Conducted Emission

Test Case	
AC Conducted Emission	Mode 5: Keeping TX

2.3 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS.

Test software Version	Test program: 902-928MHz	
sscom5.13.1	Mode Or Modulation type	Power setting
	Lora	14

2.4 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Accessories Equipment

Description	Manufacturer	Model	S/N	Rating
ANT	N/A	N/A	N/A	N/A
USB-A to Micro-USB Cable	N/A	N/A	N/A	1m, with ferrite core

Auxiliary Equipment

Description	Manufacturer	Model	S/N	Rating
Laptop	Lenovo	HKF-16	N/A	N/A

Note:

- (1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (2) “YES” is means “with core”; “NO” is means “without core”.



2.5 EQUIPMENTS LIST

Conducted Emission					
Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Until
EMI Test Receiver	R&S	ESU8	100372	2023.04.13	2024.04.12
LISN	COM-POWER	LI-115	02032	2023.04.07	2024.04.06
LISN	SCHWARZBECK	NNLK 8122	00160	2023.04.07	2024.04.06
Transient Limiter	CYBERTEK	EM5010A	E2250100049	2023.04.07	2024.04.06
Temperature & Humidity	KTJ	TA218B	N.A	2023.04.24	2024.04.23
Testing Software	EMC-I_V1.4.0.3_SKET				

Radiated Test equipment					
Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Until
EMI Test Receiver	R&S	ESU8	100372	2023.04.13	2024.04.12
Active loop Antenna	ETS	6502	00049544	2022.06.02	2025.06.01
Spectrum Analyzer	Keysight	N9010B	MY60242508	2023.04.10	2024.04.09
Bilog Antenna(30M-1G)	SCHWARZBECK	VULB 9168	2705	2022.06.05	2025.06.04
Horn Antenna(1-18G)	SCHWARZBECK	3115	10SL0060	2022.06.02	2025.06.01
Horn Antenna(18-40G)	A-INFO	LB-180400-K F	J211060273	2022.06.08	2025.06.07
Pre-amplifier(30M-1G)	EMtrace	RP01A	02019	2023.04.07	2024.04.06
Pre-amplifier(1-26.5G)	Agilent	8449B	3008A4722	2023.04.07	2024.04.06
Pre-amplifier(18-40G)	com-mw	LNPA_18-40- 01	18050003	2023.04.07	2024.04.06
Wireless Communications Test Set	R&S	CMW 500	137737	2023.04.13	2024.04.12
Temperature & Humidity	KTJ	TA218B	N.A	2023.04.24	2024.04.23
Testing Software	EMC-I_V1.4.0.3_SKET				

Conducted Test equipment					
Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Until
Signal Analyzer	Keysight	N9010B	MY60242508	2023.04.10	2024.04.09
Wireless Communications Test Set	R&S	CMW 500	137737	2023.04.13	2024.04.12
MXG Vector Signal Generator	Keysight	N5182B	MY59100717	2023.04.07	2024.04.06
Power Sensor	MW	MW100-RFCB	MW220324L G-33	2023.04.13	2024.04.12
Temperature & Humidity	KTJ	TA218B	N.A	2023.04.24	2024.04.23
Temperature& Humidity test chamber	AISRY	LX-1000L	171200018	2023.05.10	2024.05.09
Attenuator	eastsheep	90db	N.A	2023.04.10	2024.04.09
Testing Software	MTS8200_V2.0.0.0_MW				



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION LIMITS

The radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table.

FREQUENCY (MHz)	Conducted Emission limit (dBuV)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of “ * ” marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.1.2 TEST PROCEDURE

- The EUT is 0.8 m from the horizontal ground plane and 0.4 m from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments are powered from additional LISN(s). The LISN provides 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN is at least 80 cm from the nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 TEST SETUP



- Note:**
- Support units were connected to second LISN.
 - Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes support units.


3.1.4 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



3.1.5 TEST RESULT


Project: LGT23L002	Test Engineer: LiuH
EUT: LoRaWAN module	Temperature: 20.9°C
M/N: LND915	Humidity: 52%RH
Test Voltage: AC 120V/60Hz	Test Data: 2023-12-21
Test Mode: TX	
Note:	



No.	Frequency MHz	Reading dBuV	Factor dB	Level dBuV	Limit dBuV	Margin dB	Detector	Polar
1*	0.234	29.84	10.49	40.33	62.31	-21.98	QP	L1
2*	0.466	27.83	10.50	38.33	56.58	-18.25	QP	L1
3*	0.714	26.72	10.51	37.23	56.00	-18.77	QP	L1
4*	1.754	20.36	10.67	31.03	56.00	-24.97	QP	L1
5*	5.182	21.17	10.81	31.98	60.00	-28.02	QP	L1
6*	7.246	21.33	10.87	32.20	60.00	-27.80	QP	L1
7*	0.210	18.69	10.49	29.18	53.21	-24.03	AV	L1
8*	0.338	16.93	10.49	27.42	49.25	-21.83	AV	L1
9*	0.778	16.44	10.51	26.95	46.00	-19.05	AV	L1
10*	1.482	11.52	10.62	22.14	46.00	-23.86	AV	L1
11*	3.734	2.73	10.77	13.50	46.00	-32.50	AV	L1
12*	6.030	3.97	10.83	14.80	50.00	-35.20	AV	L1



Project: LGT23L002	Test Engineer: LiuH
EUT: LoRaWAN module	Temperature: 20.9°C
M/N: LND915	Humidity: 52%RH
Test Voltage: AC 120V/60Hz	Test Data: 2023-12-21
Test Mode: TX	
Note:	



No.	Frequency MHz	Reading dBuV	Factor dB	Level dBuV	Limit dBuV	Margin dB	Detector	Polar
1*	0.158	31.14	10.49	41.63	65.57	-23.94	QP	N
2*	0.382	27.02	10.49	37.51	58.24	-20.73	QP	N
3*	0.730	26.07	10.51	36.58	56.00	-19.42	QP	N
4*	1.158	23.08	10.55	33.63	56.00	-22.37	QP	N
5*	6.646	21.31	10.86	32.17	60.00	-27.83	QP	N
6*	9.410	20.74	10.99	31.73	60.00	-28.27	QP	N
7*	0.294	17.95	10.49	28.44	50.41	-21.97	AV	N
8*	0.782	16.15	10.51	26.66	46.00	-19.34	AV	N
9*	1.122	13.68	10.54	24.22	46.00	-21.78	AV	N
10*	2.246	7.13	10.73	17.86	46.00	-28.14	AV	N
11*	6.030	3.35	10.84	14.19	50.00	-35.81	AV	N
12*	11.330	1.63	10.99	12.62	50.00	-37.38	AV	N



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS

In any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the Restricted band specified on Part15.205 (a)&209(a) limit in the table and according to ANSI C63.10-2013 below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (0.009MHz - 1000MHz)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (1GHz-25 GHz)

FREQUENCY (MHz)	(dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

LIMITS OF RESTRICTED FREQUENCY BANDS

FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (GHz)
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			



For Radiated Emission

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/QP/AV
Start Frequency	9 KHz/150KHz (Peak/QP/AV)
Stop Frequency	150KHz/30MHz (Peak/QP/AV)
RB / VB (emission in restricted band)	200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz); 200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz)

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/QP
Start Frequency	30 MHz (Peak/QP)
Stop Frequency	1000 MHz (Peak/QP)
RB / VB (emission in restricted band)	120 KHz / 300 KHz

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak
Start Frequency	1000 MHz (Peak/AV)
Stop Frequency	10th carrier hamonic (Peak/AV)
RB / VB (emission in restricted band)	1 MHz / 3 MHz(Peak) 1 MHz/1/T MHz(AVG)

For Restricted band

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	880 to 930 MHz
RB / VB	1 MHz / 3 MHz(Peak) 1 MHz/1/T MHz(AVG)

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP



3.2.2 TEST PROCEDURE

- a. The measuring distance at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz, and above 1GHz.
- b. The EUT was placed on the top of a rotating table 0.8 m (above 1GHz is 1.5 m) above the ground at a 3 m anechoic chamber test site. The table was rotated 360 degree to determine the position of the highest radiation.
- c. The height of the equipment shall be 0.8 m (above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. Horizontal and vertical polarization of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and QuasiPeak detector mode will be re-measured.
- e. If the Peak Mode measured value is compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and no additional QP Mode measurement was performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

3.2.3 DEVIATION FROM TEST STANDARD


No deviation.

3.2.4 TESTSETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

Please refer to section 3.1.4 of this report.



3.2.6 FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where

FS = Field Strength

CL = Cable Attenuation Factor (Cable Loss)

RA = Reading Amplitude

AG = Amplifier Gain

AF = Antenna Factor

For example

Frequency	FS	RA	AF	CL	AG	Factor
(MHz)	(dBμV/m)	(dBμV/m)	(dB)	(dB)	(dB)	(dB)
300	40	58.1	12.2	1.6	31.9	-18.1

$$\text{Factor} = \text{AF} + \text{CL} - \text{AG}$$



3.2.7 TEST RESULTS

Results of Radiated Emissions (9 KHz~30MHz)

No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Remark
1*	-	-	-	-	-	-	-	See Note

Note:

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.




Results of Radiated Emissions (30MHz~1000MHz)

Project: LGT23L002	Test Engineer: Xiangdong Ma
EUT: LoRaWAN module	Temperature: 15.8°C
M/N: LND915	Humidity: 43%RH
Test Voltage: DC 3.3V	Test Data: 2023-12-21
Test Mode: 902.3MHz	
Note:	




No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	41.883	2.46	19.32	21.78	40.00	-18.22	QP	Hor
2*	117.543	2.72	17.43	20.15	43.50	-23.35	QP	Hor
3*	170.165	3.11	19.77	22.88	43.50	-20.62	QP	Hor
4*	277.714	2.95	19.48	22.43	46.00	-23.57	QP	Hor
5*	408.664	3.36	22.97	26.33	46.00	-19.67	QP	Hor
6*	615.274	3.86	28.25	32.11	46.00	-13.89	QP	Hor
!7*	902.273	37.13	33.25	70.38	--	--	QP	Hor




No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	35.456	2.89	18.62	21.51	40.00	-18.49	QP	Ver
2*	43.459	2.82	19.27	22.09	40.00	-17.90	QP	Ver
3*	115.603	1.97	17.26	19.23	43.50	-24.30	QP	Ver
4*	159.010	3.57	19.85	23.42	43.50	-20.10	QP	Ver
5*	405.148	3.63	22.92	26.55	46.00	-19.40	QP	Ver
6*	687.539	6.17	29.69	35.86	46.00	-10.10	QP	Ver
!7*	902.394	53.26	33.25	86.51	--	--	QP	Ver



Project: LGT23L002	Test Engineer: Xiangdong Ma
EUT: LoRaWAN module	Temperature: 15.8°C
M/N: LND915	Humidity: 43%RH
Test Voltage: DC 3.3V	Test Data: 2023-12-21
Test Mode: 908.7MHz	
Note:	




No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	42.731	2.60	19.29	21.89	40.00	-18.11	QP	Hor
2*	82.986	6.79	15.16	21.95	40.00	-18.05	QP	Hor
3*	151.371	3.74	19.97	23.71	43.50	-19.79	QP	Hor
4*	173.560	3.77	19.44	23.21	43.50	-20.29	QP	Hor
5*	569.684	2.67	26.63	29.30	46.00	-16.70	QP	Hor
6*	756.530	6.17	30.60	36.77	46.00	-9.23	QP	Hor
!7*	908.578	47.90	33.29	81.19	--	--	QP	Hor




No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	39.336	4.74	19.27	24.01	40.00	-15.99	QP	Ver
2*	86.260	4.79	15.11	19.90	40.00	-20.10	QP	Ver
3*	162.648	3.57	19.82	23.39	43.50	-20.11	QP	Ver
4*	260.375	4.70	18.73	23.43	46.00	-22.57	QP	Ver
5*	500.450	3.26	24.86	28.12	46.00	-17.88	QP	Ver
6*	616.729	5.17	28.30	33.47	46.00	-12.53	QP	Ver
!7*	908.456	53.34	33.29	86.63	--	--	QP	Ver



Project: LGT23L002	Test Engineer: Xiangdong Ma
EUT: LoRaWAN module	Temperature: 15.8°C
M/N: LND915	Humidity: 43%RH
Test Voltage: DC 3.3V	Test Data: 2023-12-21
Test Mode: 914.9MHz	
Note:	



No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	49.521	3.13	19.35	22.48	40.00	-17.52	PK	Hor
2*	85.533	7.15	15.12	22.27	40.00	-17.73	PK	Hor
3*	152.463	3.27	19.95	23.22	43.50	-20.28	PK	Hor
4*	184.473	4.50	18.31	22.81	43.50	-20.69	PK	Hor
5*	442.008	3.33	23.61	26.94	46.00	-19.06	PK	Hor
6*	844.800	4.26	32.21	36.47	46.00	-9.53	PK	Hor
!7*	915.004	46.08	33.32	79.40	46.00	33.40	PK	Hor




No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	36.063	4.60	18.72	23.32	40.00	-16.68	QP	Ver
2*	42.368	3.51	19.30	22.81	40.00	-17.19	QP	Ver
3*	64.556	2.95	18.36	21.31	40.00	-18.69	QP	Ver
4*	155.130	3.71	19.91	23.62	43.50	-19.88	QP	Ver
5*	387.203	1.97	22.45	24.42	46.00	-21.58	QP	Ver
6*	556.831	2.43	26.34	28.77	46.00	-17.23	QP	Ver
!7*	915.004	53.32	33.32	86.64	--	--	QP	Ver




Results of Radiated Emissions (Above 1000MHz)

Project: LGT23L002	Test Engineer: Xiangdong Ma
EUT: LoRaWAN module	Temperature: 15.8°C
M/N: LND915	Humidity: 43%RH
Test Voltage: DC 3.3V	Test Data: 2023-12-21
Test Mode: 902.3MHz	
Note:	




No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	1805.5000	63.49	-18.20	45.29	74.00	-28.71	PK	Hor
2*	2711.1000	60.66	-9.87	50.79	74.00	-23.21	PK	Hor
3*	8999.9000	58.01	-1.17	56.84	74.00	-17.16	PK	Hor
4*	1805.5000	50.10	-18.20	31.90	54.00	-22.10	AV	Hor
5*	2711.1000	46.57	-9.87	36.70	54.00	-17.30	AV	Hor
6*	8999.9000	47.47	-1.17	46.30	54.00	-7.70	AV	Hor




No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	1804.4000	61.80	-18.21	43.59	74.00	-30.41	PK	Ver
2*	2713.4000	56.78	-9.86	46.92	74.00	-27.08	PK	Ver
3*	8994.2000	56.94	-1.19	55.75	74.00	-18.25	PK	Ver
4*	1805.5000	56.71	-18.20	38.51	54.00	-15.49	AV	Ver
5*	2707.7000	50.24	-9.89	40.35	54.00	-13.65	AV	Ver
6*	8994.2000	47.29	-1.19	46.10	54.00	-7.90	AV	Ver



Project: LGT23L002	Test Engineer: Xiangdong Ma
EUT: LoRaWAN module	Temperature: 15.8°C
M/N: LND915	Humidity: 43%RH
Test Voltage: DC 3.3V	Test Data: 2023-12-21
Test Mode: 908.7MHz	
Note:	




No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	1816.7000	67.40	-18.08	49.32	74.00	-24.68	PK	Hor
2*	2725.7000	62.96	-9.79	53.17	74.00	-20.83	PK	Hor
3*	8900.9000	56.62	-1.45	55.17	74.00	-18.83	PK	Hor
4*	1817.9000	66.29	-18.07	48.22	54.00	-5.78	AV	Hor
5*	2726.9000	59.10	-9.78	49.32	54.00	-4.68	AV	Hor
6*	8900.9000	45.85	-1.45	44.40	54.00	-9.60	AV	Hor




No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	1816.7000	69.42	-18.08	51.34	74.00	-22.66	PK	Ver
2*	2725.7000	62.41	-9.79	52.62	74.00	-21.38	PK	Ver
3*	8863.7000	58.38	-1.56	56.82	74.00	-17.18	PK	Ver
4*	1817.9000	65.93	-18.07	47.86	54.00	-6.14	AV	Ver
5*	2726.9000	57.82	-9.78	48.04	54.00	-5.96	AV	Ver
6*	8863.7000	46.96	-1.56	45.40	54.00	-8.60	AV	Ver



Project: LGT23L002	Test Engineer: Xiangdong Ma
EUT: LoRaWAN module	Temperature: 15.8°C
M/N: LND915	Humidity: 43%RH
Test Voltage: DC 3.3V	Test Data: 2023-12-21
Test Mode: 914.9MHz	
Note:	



No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	1830.2000	68.22	-17.95	50.27	74.00	-23.73	PK	Hor
2*	2744.9000	60.85	-9.69	51.16	74.00	-22.84	PK	Hor
3*	8920.0000	56.39	-1.40	54.99	74.00	-19.01	PK	Hor
4*	1831.4000	64.36	-17.94	46.42	54.00	-7.58	AV	Hor
5*	2746.0000	56.80	-9.68	47.12	54.00	-6.88	AV	Hor
6*	8920.0000	46.70	-1.40	45.30	54.00	-8.70	AV	Hor



No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	1830.2000	67.82	-17.95	49.87	74.00	-24.13	PK	Ver
2*	2744.9000	62.89	-9.69	53.20	74.00	-20.80	PK	Ver
3*	9536.5000	56.93	-1.18	55.75	74.00	-18.25	PK	Ver
4*	1831.4000	63.39	-17.94	45.45	54.00	-8.55	AV	Ver
5*	2746.0000	60.31	-9.68	50.63	54.00	-3.37	AV	Ver
6*	9536.5000	45.78	-1.18	44.60	54.00	-9.40	AV	Ver


Remark:

In frequency ranges 10~25GHz no any other harmonic emissions detected which are tested to compliance with the limit. No recording in the test report. No any other emissions level which are attenuated less than 20dB below the limit. No recording in the test report.




3.2.8 TEST RESULTS (BAND EDGE REQUIREMENTS)

Project: LGT23L002	Test Engineer: Xiangdong Ma
EUT: LoRaWAN module	Temperature: 28.6°C
M/N: LND915	Humidity: 50%RH
Test Voltage: DC 3.3V	Test Data: 2023-12-21
Test Mode: 902.3MHz	
Note:	




No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	889.300	1.41	33.09	34.50	74.00	-39.50	PK	Hor
!2*	902.319	56.48	33.25	89.73	74.00	15.73	PK	Hor
3*	915.300	-0.32	33.32	33.00	74.00	-41.00	PK	Hor




No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	889.300	1.61	33.09	34.70	74.00	-39.30	PK	Ver
!2*	902.300	57.75	33.25	91.00	74.00	17.00	PK	Ver
3*	915.300	0.78	33.32	34.10	74.00	-39.90	PK	Ver



Project: LGT23L002	Test Engineer: Xiangdong Ma
EUT: LoRaWAN module	Temperature: 28.6°C
M/N: LND915	Humidity: 50%RH
Test Voltage: DC 3.3V	Test Data: 2023-12-21
Test Mode: 908.7MHz	
Note:	




No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	895.300	1.13	33.17	34.30	74.00	-39.70	PK	Hor
!2*	908.431	56.55	33.28	89.83	74.00	15.83	PK	Hor
3*	921.700	-1.06	33.36	32.30	74.00	-41.70	PK	Hor




No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	895.300	0.93	33.17	34.10	74.00	-39.90	PK	Ver
!2*	908.444	58.64	33.28	91.92	74.00	17.92	PK	Ver
3*	921.700	0.04	33.36	33.40	74.00	-40.60	PK	Ver



Project: LGT23L002	Test Engineer: Xiangdong Ma
EUT: LoRaWAN module	Temperature: 28.6°C
M/N: LND915	Humidity: 50%RH
Test Voltage: DC 3.3V	Test Data: 2023-12-21
Test Mode: 914.9MHz	
Note:	



No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	901.900	1.95	33.25	35.20	74.00	-38.80	PK	Hor
!2*	914.906	56.62	33.32	89.94	74.00	15.94	PK	Hor
3*	927.900	1.56	33.44	35.00	74.00	-39.00	PK	Hor



No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	901.900	2.55	33.25	35.80	74.00	-38.20	PK	Ver
!2*	914.919	59.15	33.32	92.47	74.00	18.47	PK	Ver
3*	927.900	1.26	33.44	34.70	74.00	-39.30	PK	Ver



4. CONDUCTED SPURIOUS & BAND EDGE EMISSION

4.1 LIMIT

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

4.2 TEST PROCEDURE

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	30 MHz to 10th carrier harmonic
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

For Band edge

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	Lower Band Edge: 886 – 917 MHz Upper Band Edge: 899 – 930 MHz
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

For Hopping Band edge

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	Lower Band Edge: 800 – 903 MHz Upper Band Edge: 914 – 1000 MHz
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold



4.3 TEST SETUP



The EUT is connected to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. Tune the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, the span is set to be greater than RBW.

4.4 EUT OPERATION CONDITIONS


Please refer to section 3.1.4 of this report.




4.5 TEST RESULTS

Reference Level for Conducted Spurious Emission and Band edge

CH 00




CH 32






CH 63






For Conducted Spurious Emission

CH 00




CH 32






CH 63






For Band edge

CH 00




CH 32






CH 63






Reference Level for Hopping Band edge

CH 00




CH 63






For Hopping Band edge

CH 00



CH 63





5. NUMBER OF HOPPING CHANNEL

5.1 LIMIT

FCC Part 15.247, Subpart C				
Section	Test Item	Limit	FrequencyRange (MHz)	Result
15.247 (a)(1)(i)	Number of Hopping Channel	≥ 50	902-928	PASS

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> Operating FrequencyRange
RB	100KHz
VB	300KHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

5.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- Spectrum Setting: RBW= 100KHz, VBW=300KHz, Sweep time = Auto.

5.3 TEST SETUP



5.4 EUT OPERATION CONDITIONS

Please refer to section 3.1.4 of this report.




5.5 TEST RESULTS

Number of Hopping Channel

64

Hopping channel





6. AVERAGE TIME OF OCCUPANCY

6.1 LIMIT

FCC Part 15.247, Subpart C				
Section	Test Item	Limit	FrequencyRange (MHz)	Result
15.247 (a)(1)(i)	Average Time of Occupancy	0.4sec	902-928	PASS

6.2 TEST PROCEDURE

- The transmitter output (antenna port) was connected to the spectrum analyzer.
- Set RBW =100KHz/VBW =300KHz.
- Use a video trigger with the trigger level set to enable triggering only on full pulses.
- Sweep Time is 2 second.
- Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- Measure the maximum time duration of one single pulse.

6.3 TEST SETUP



6.4 EUT OPERATION CONDITIONS


Please refer to section 3.1.4 of this report.




6.5 TEST RESULTS

Frequency	Dwell Time(s)	Limits(s)	result
902.3 MHz	0.390	0.4	Pass
908.7 MHz	0.390	0.4	Pass
914.9 MHz	0.390	0.4	Pass

CH00




CH32





CH63





7. HOPPING CHANNEL SEPARATION MEASUREMENT

7.1 LIMIT

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> 20 dB Bandwidth or Channel Separation
RB	30 kHz (20dB Bandwidth) / 30 kHz (Channel Separation)
VB	100 kHz (20dB Bandwidth) / 100 kHz (Channel Separation)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

7.2 TEST PROCEDURE

- The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
- The resolution bandwidth of 30 kHz and the video bandwidth of 100 kHz were utilised for 20 dB bandwidth measurement.
- The resolution bandwidth of 30 kHz and the video bandwidth of 100 kHz were utilised for channel separation measurement.

7.3 TEST SETUP




7.4 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.



CH32



CH63





8. BANDWIDTH TEST

8.1 LIMIT

FCC Part15.247, Subpart C				
Section	Test Item	Limit	FrequencyRange (MHz)	Result
15.247 (a)(1)(i)	Bandwidth	500KHz	902-928	PASS

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	30 kHz (20dB Bandwidth) / 3 kHz (Channel Separation)
VB	100 kHz (20dB Bandwidth) / 10 kHz (Channel Separation)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

8.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- Spectrum Setting: RBW= 3KHz, VBW=10KHz, Sweep time = Auto.

8.3 TEST SETUP



8.4 EUT OPERATION CONDITIONS


Please refer to section 3.1.4 of this report.



8.5 TEST RESULTS


Frequency	20dB Bandwidth(kHz)	Limit (KHz)	Result
902.3 MHz	137.00	500	PASS
908.7 MHz	137.80	500	PASS
914.9 MHz	137.90	500	PASS

CH00






CH32



CH63





9. OUTPUT POWER TEST

9.1 LIMIT

FCC Part 15.247, Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(2)	Output Power	1 W	902-928	PASS

9.2 TEST PROCEDURE

This is an RF-conducted test to evaluate maximum peak output power. Use a direct connection between the antenna port of the unlicensed wireless device and the spectrum analyzer, through suitable attenuation. The hopping shall be disabled for this test:

a) Use the following spectrum analyzer settings:

1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.

2) RBW > 20 dB bandwidth of the emission being measured.

3) VBW $\geq$ RBW.

4) Sweep: Auto.

5) Detector function: Peak.

6) Trace: Max hold.

b) Allow trace to stabilize.

c) Use the marker-to-peak function to set the marker to the peak of the emission.

d) The indicated level is the peak output power, after any corrections for external attenuators and cables.


e) A plot of the test results and setup description shall be included in the test report.

NOTE—A peak responding power meter may be used, where the power meter and sensor system video bandwidth is greater than the occupied bandwidth of the unlicensed wireless device, rather than a spectrum analyzer.

PKPM1 Peak power meter method:

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DSS bandwidth and shall use a fast-responding diode detector.

9.3 TEST SETUP



9.4 EUT OPERATION CONDITIONS

Please refer to section 3.1.4 of this report.



9.5 TEST RESULTS

Frequency (MHz)	Peak Power (dBm)	Average Power (dBm)	Limit (dBm)
902.3	5.05	1.72	30.00
908.7	4.91	1.54	30.00
914.9	4.71	1.29	30.00



10. ANTENNA REQUIREMENT

10.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

10.2 EUT ANTENNA

The EUT antenna is Dipole Antenna. It comply with the standard requirement.

※※※※※END OF THE REPORT※※※※※