

Radio Test Report FCC ID: Z5N-UHF01

This report concerns (check one) : Original Grant Class II Change

Issued Date : Nov. 15, 2011 **Project No.** : R1108001

Equipment: ON TOUCH RF Remote Controller

Model Name: SR06

Applicant: LOONG YEE Industry CO., LTD.

Address: No. 14, Lane 103, Sec. 2, Chung Hsing Rd.,

WuKu District, New Taipei City 24847,

Taiwan (R.O.C.)

Tested by: Neutron Engineering Inc. EMC Laboratory

Date of Receipt: Aug. 12, 2011

Date of Test: Aug. 12, 2011 ~ Oct. 03, 2011

Testing Engineer : Kush

(Rush Kao)

Technical Manager

(Jeff Yang

Authorized Signatory

(Andy Chiu)

Neutron Engineering Inc.

B1, No. 37, Lane 365, YangGuang St, NeiHu District 114, Taipei, Taiwan.

TEL: +886-2-2657-3299 FAX: +886-2-2657-3331







Declaration

Neutron represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with the standards traceable to National Measurement Laboratory (**NML**) of **R.O.C.**, or National Institute of Standards and Technology (**NIST**) of **U.S.A.**

Neutron's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **Neutron** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **Neutron** issued reports.

Neutron's reports must not be used by the client to claim product endorsement by the authorities or any agency of the Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **Neutron-self**, extracts from the test report shall not be reproduced except in full with **Neutron**'s authorized written approval.

Neutron's laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Report No.: NEI-FCCP-1-R1108001 Page 2 of 25

Table of Contents Page 1	age
1. CERTIFICATION	4
2 . SUMMARY OF TEST RESULTS	5
2.1 TEST FACILITY	6
2.2 MEASUREMENT UNCERTAINTY	6
3. GENERAL INFORMATION	7
3.1 GENERAL DESCRIPTION OF EUT	7
3.2 DESCRIPTION OF TEST MODES	8
3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	9
3.4 DESCRIPTION OF SUPPORT UNITS	10
4 . EMC EMISSION TEST	11
4.1 RADIATED EMISSION MEASUREMENT	11
4.1.1 RADIATED EMISSION LIMITS	11
4.1.2 MEASUREMENT INSTRUMENTS LIST 4.1.3 TEST PROCEDURE	12 12
4.1.4 DEVIATION FROM TEST STANDARD	14
4.1.5 TEST SETUP 4.1.6 EUT OPERATING CONDITIONS	14 14
4.1.6 EUT OPERATING CONDITIONS 4.1.7 TEST RESULTS (BETWEEN30 – 1000 MHz)	14 15
4.1.8 TEST RESULTS (BETWEEN30 – 5000 MHz)	17
4.2 20dB OCCUPIED BANDWIDTH MEASUREMENT	21
4.2.1 MEASUREMENT INSTRUMENTS LIST 4.2.2 TEST RESULTS	21 21
5 . TIMING TESTING	22
5.1 RADIATED EMISSION MEASUREMENT 5.1.1 LIMITS	22 22
5.1.2 MEASURING INSTRUMENTS LIST	22
5.1.3 TEST PROCEDURE	22
5.1.4 DEVIATION FROM TEST STANDARD	22
5.1.5 EUT OPERATING CONDITIONS 5.1.6 TEST RESULTS	22 23
6 . EUT TEST PHOTO	24

Report No.: NEI-FCCP-1-R1108001 Page 3 of 25

1. CERTIFICATION

Equipment: ON TOUCH RF Remote Controller

Brand Name: LOONG YEE

Model Name: SR06

Applicant: LOONG YEE Industry CO., LTD. Date of Test: Aug. 12, 2011 ~ Oct. 03, 2011

Standards: FCC Part15, Subpart C / ANCI C63.4: 2009

The above equipment has been tested and found compliance with the requirement of the relative standards by Neutron Engineering Inc. EMC Laboratory.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. NEI-FCCP-1-R1108001) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of NVLAP and TAF according to the ISO-17025 quality assessment standard and technical standard(s).

Report No.: NEI-FCCP-1-R1108001 Page 4 of 25

2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards: (Antenna to EUT distance is 3 m)

FCC Part15(15.231), Subpart C					
Standard	Standard Test Item				
15.207	Conducted Emission	N/A NOTE(1)			
15.209	Radiated Emission	PASS			
15.231(a)(1)	Transmitting Time	PASS			
15.231(b)	Radiated Emission	PASS NOTE(2)			
15.231(c)	20dB Occupied Bandwidth Measurement	PASS			

NOTE:

- (1)" N/A" denotes test is not applicable in this Test Report
- (2) The EUT is manually operated transmitter, not periodic transmissions.

Report No.: NEI-FCCP-1-R1108001 Page 5 of 25

2.1 TEST FACILITY

The test facilities used to collect the test data in this report:

CB08: (VCCI RN: G-91; FCC RN: 614388; FCC DN: TW1054;

IC Assigned Code: 4428C-1)

1F., No. 61, Ln. 77, Sing-ai Rd., Neihu Dist., Taipei City 114, Taiwan (R.O.C.)

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $\mathbf{y} \pm \mathbf{U}$, where expended uncertainty \mathbf{U} is based on a standard uncertainty multiplied by a coverage factor of $\mathbf{k=2}$, providing a level of confidence of approximately 95%.

The measurement instrumentation uncertainty considerations contained in CISPR 16-4-2.

Test Site	Method	Measurement Frequency Range	Ant. H / V	U,(dB)	NOTE
		30MHz ~ 200MHz	V	3.22	
		30MHz ~ 200MHz	Н	3.35	
	ANSI -	200MHz ~ 1,000MHz	V	3.24	
CB08		200MHz ~ 1,000MHz	Н	3.11	
CDUO		1000MHz ~ 18000MHz	V	4.05	
		1000MHz ~ 18000MHz	Η	3.97	
		18000MHz ~ 40000MHz	V	4.04	
		18000MHz ~ 40000MHz	Н	4.01	

Our calculated Measurement Instrumentation Uncertainty is shown in the tables above. These are our U_{lab} values in CISPR 16-4-2 terminology.

Since Table 1 of CISPR 16-4-2 has values of measurement instrumentation uncertainty, called U_{CISPR} , as follows:

Conducted Disturbance (mains port) - 150 kHz - 30 MHz : 3.6 dB

Radiated Disturbance (electric field strength on an open area test site or alternative test site) – 30 MHz – 1000 MHz : 5.2 dB

It can be seen that our U_{lab} values are smaller than U_{CISPR} .

Report No.: NEI-FCCP-1-R1108001 Page 6 of 25

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Equipment	ON TOUCH RF Remote Controller				
Brand Name	LOONG YEE				
Model Name	SR06				
OEM Brand/Model Name	N/A				
Model Difference	Please refer to Note 2.				
		CH RF Remote Controller.			
	Operation Frequency	433.95 MHz			
	Modulation Type	Pulse Modulation (ASK)			
	Antenna Designation	Printed Antenna			
	Number Of Channel	1			
Product Description	Transmitting Time	< 5 seconds			
·	Associated Receiver	FCC DOC			
	Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.				
Power Source	Battery supplied.				
Power Rating	I/P: DC 3V				
Connecting I/O Port(s)	Please refer to the User's Manual				
Products Covered	N/A				
EUT Modification(s)	N/A				

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

Report No.: NEI-FCCP-1-R1108001 Page 7 of 25


3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Test Mode	Description
Mode 1	TX 433.95MHz

For Radiated Test			
Final Test Mode	Description		
Mode 1	TX 433.95MHz		

Report No.: NEI-FCCP-1-R1108001 Page 8 of 25



Report No.: NEI-FCCP-1-R1108001 Page 9 of 25

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.	Note
E-1	ON TOUCH RF Remote Controller	LOONG YEE	SR06	Z5N-UHF001	N/A	EUT

Item	Shielded Type	Ferrite Core	Length	Note
N/A	-	-	-	-

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in <code>[Length]</code> column.

Report No.: NEI-FCCP-1-R1108001 Page 10 of 25

4. EMC EMISSION TEST

4.1 RADIATED EMISSION MEASUREMENT

4.1.1 RADIATED EMISSION LIMITS (Frequency Range 30MHz-1000MHz)

According to 15.231 the field strength of emissions from intentional radiators operated under these frequencies bands shall not exceed the following:

Fundamental	Field Strength of Fundamental		Field Strengt	h of Spurious
Frequency (MHz)	uV/meter	dBuV/meter	uV/meter	dBuV/meter
40.66 – 40.70	2250	67.04	225	48.04
70 – 130	1250	61.94	125	41.94
130 – 174	1250 to 3750	61.94 to 71.48	125 to 375	41.94 to 51.48
174 – 260	3750	71.48	75	37.50
260 – 470	3750 to 12500	71.48 to 81.94	375 to 1250	51.48 to 61.94
Above 470	12500	81.94	1250	61.94

Notes:

- (1) Emission level in dBuV/m=20 log (uV/m)
- (2) Measurement was performed at an antenna to the closed point of EUT distance of meters.
- (3) Fundamental frequency shall not be located within the Restricted Bands specified in provision of 15.205.
- (4) If spurious frequency which falls within the Restricted Bands specified in provision of 15.205, then the general radiated emission limits in 15.209 apply.

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Notes:

As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

Report No.: NEI-FCCP-1-R1108001 Page 11 of 25

4.1.2 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP-40	100129	Aug. 30, 2012
2	Horn Antenna	Schwarzbeck	BBHA 9120	D-325	Dec. 08, 2011
3	Microwave Pre_amplifier	Agilent	8449B	3008A01714	Apr. 18, 2012
4	Microflex Cable	N/A	N/A	1m	May. 18, 2012
5	Microflex Cable	AISI	S104-SMAP-1	10m	Aug. 21, 2012
6	Microflex Cable	N/A	N/A	3m	Aug. 21, 2012
7	Test Cable	N/A	LMR-400	966_12m	Jun. 16, 2012
8	Test Cable	N/A	LMR-400	966_3m	Jun. 16, 2012
9	Pre-Amplifier	EMC	EMC-330	980001	Jun. 02, 2012
10	Log-Bicon Antenna	Schwarzbeck	VULB9168-352	9168-352	Jun. 20, 2012

Remark: "N/A" denotes No Model Name / Serial No. and No Calibration specified.

4.1.3 TEST PROCEDURE

- a. The measuring distance of at 10 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3m or 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Remark:

- (1) Spectrum Setting:
 - 9 KHz 150 KHz, RBW= 1 KHz, VBW=1 KHz, Sweep time = 200 ms. 150 K Hz – 30 MHz, RBW= 9 KHz, VBW=9 KHz, Sweep time = 200 ms. 30 MHz – 1000 MHz, RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms.
- (2) All readings are Peak unless otherwise stated QP in column of \lceil Note $_{
 m l}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measure-ment didn't perform $_{
 m o}$

Report No.: NEI-FCCP-1-R1108001 Page 12 of 25



- (3) Measuring frequency range from 30MHz to 1000MHz o
- (4) If the peak scan value lower limit more than 20dB, then this signal data does not how in table \circ
- (5) The average value of fundamental frequency is: Average = Peak value + 20log(Duty cycle)
- (6) EUT Orthogonal Axes:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand


Report No.: NEI-FCCP-1-R1108001 Page 13 of 25

4.1.4 DEVIATION FROM TEST STANDARD


No deviation

4.1.5 TEST SETUP

(A) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(B) Radiated Emission Test Set-UP Frequency Over 1 GHz



4.1.6 EUT OPERATING CONDITIONS

Report No.: NEI-FCCP-1-R1108001 Page 14 of 25


4.1.7 TEST RESULTS (BETWEEN30 - 1000 MHz)

IF U I	ON TOUCH RF Remote Controller	Model Name :	SR06
Temperature:	26°C	Relative Humidity:	60%
Test Voltage :	DC 3V	Orthogonal Axis:	Υ
Test Mode :	TX 433.95MHz		

The following table lists worst case data from TX with various orthogonal planes on the EUT antenna.

Freq. (MHz)	Ant.Pol. H/V	DetectorMode (PK/AV)	Reading (dBuV)	Ant./CL/ Amp. CF(dB)	Actual FS (dBuV/m)	Limit-3m (dBuV/m)	Safe Margins (dBuV/m)	Note
45.52	V	Peak	34.47	- 12.22	22.25	40.00	- 17.75	
148.34	V	Peak	33.93	- 13.10	20.83	43.50	- 22.67	
608.12	V	Peak	33.41	- 5.88	27.53	46.00	- 18.47	
627.52	V	Peak	33.66	- 5.53	28.13	46.00	- 17.87	
806.00	V	Peak	34.27	- 2.83	31.44	46.00	- 14.56	
928.22	V	Peak	33.19	- 2.23	30.96	46.00	- 15.04	
47.46	Н	Peak	33.91	- 12.24	21.67	40.00	- 18.33	
163.86	Н	Peak	32.84	- 13.37	19.47	43.50	- 24.03	
293.84	Н	Peak	32.49	- 12.66	19.83	46.00	- 26.17	
392.78	Н	Peak	32.92	- 10.24	22.68	46.00	- 23.32	
582.90	Н	Peak	33.02	- 6.46	26.56	46.00	- 19.44	·
613.94	Н	Peak	33.53	- 5.77	27.76	46.00	- 18.24	

Report No.: NEI-FCCP-1-R1108001 Page 15 of 25



4.1.8 TEST RESULTS (BETWEEN30 - 5000 MHz)

FUI '	ON TOUCH RF Remote Controller	Model Name :	SR06
Temperature:	24°C	Relative Humidity:	36%
Test Voltage :	DC 3V	Orthogonal Axis:	Υ
Test Mode :	TX 433.95MHz		

The following table lists worst case data from TX with various orthogonal planes on the EUT antenna.

About the duty cycle correction factor calculated, please refer to the next page (Table-1).

Freq.	F/S	Ant.Pol.	Reading	Ant./CL	Duty Cycle	Peak	AV	Peak Limit	AV Limit	Safe Margins
(MHz)	1/3	HV	(dBuV)	CF(dB)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)
433.95	F	V	69.71	- 9.17	- 6.27	60.54	54.27	100.83	80.83	- 26.56
867.92	S	V	47.69	- 2.78	- 6.27	44.91	38.64	80.83	60.83	- 22.19
1301.81	S	V	48.99	- 6.65	- 6.27	42.34	36.07	74.00	54.00	- 17.93
1735.92	S	V	48.76	- 4.93	- 6.27	43.83	37.56	74.00	54.00	- 16.44

Report No.: NEI-FCCP-1-R1108001 Page 17 of 25



F J 1	ON TOUCH RF Remote Controller	Model Name :	SR06
Temperature:	24°C	Relative Humidity:	36%
Test Voltage :	DC 3V	Orthogonal Axis:	Υ
Test Mode :	TX 433.95MHz		

The following table lists worst case data from TX with various orthogonal planes on the EUT antenna.

About the duty cycle correction factor calculated, please refer to the next page (Table-1).

Freq.	F/S	Ant.Pol.	Reading	Ant./CL	Duty Cycle	Peak	AV	Peak Limit	AV Limit	Safe Margins
(MHz)	1/3	HV	(dBuV)	CF(dB)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)
433.95	F	V	80.91	- 9.17	- 6.27	71.74	65.47	100.83	80.83	- 15.36
867.92	S	V	56.04	- 2.78	- 6.27	53.26	46.99	80.83	60.83	- 13.84
1301.88	S	V	45.43	- 6.65	- 6.27	38.78	32.51	74.00	54.00	- 21.49
1735.79	S	V	44.65	- 4.93	- 6.27	39.72	33.45	74.00	54.00	- 20.55

Report No.: NEI-FCCP-1-R1108001 Page 18 of 25


Table - 1


Duty Cycle Correction Factor Calculated						
EUT:	ON TOUCH RF Remote Controller	Model Name :	SR06			
Temperature:	24°C	Relative Humidity:	58%			
Test Voltage:	DC 3V					

Frequency (MHz)	Pulse Train T _(on) (ms)	Total Duration of EUT at active state(T _(on+off)) (ms)	Factor = 20 log[T _(on) / T _(on+off)]
433.95	0.68 ms	1.4 ms	-6.27 dB


Plot For Pulse Train: T_(on)








-10



Center 433.9572 MHz

Neutron Engineering Inc.



Report No.: NEI-FCCP-1-R1108001 Page 20 of 25

4.2 20dB OCCUPIED BANDWIDTH MEASUREMENT

4.2.1 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP-40	100129	Aug. 30, 2012

Remark: "N/A" denotes No Model Name / Serial No. and No Calibration specified.


4.2.2 TEST RESULTS

I E U J I	ON TOUCH RF Remote Controller	Model Name :	SR06
Temperature:	15°C	Relative Humidity:	58%
Test Voltage:	DC 3V		
Test Mode :	TX 433.95MHz		

Frequency (MHz)	20dB Bandwidth (KHz)	99% Occupied BW (KHz)	Maximum Limit(KHz)	Result
433.95	41.60	62.00	1080.00	PASS

Note:

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for device operating above 70 MHz and below 900 MHz.



Report No.: NEI-FCCP-1-R1108001

Page 21 of 25

5. TIMING TESTING

5.1 RADIATED EMISSION MEASUREMENT

5.1.1 LIMITS

According to 15.231(a) (1), a manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

5.1.2 MEASURING INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP-40	100129	Aug. 30, 2012

5.1.3 TEST PROCEDURE

- a. The transmitter was used antenna to receive and measure the release time in peak hold mode.
- b. Spectrum Setting: RBW= 100 KHz, VBW=100 KHz, Sweep time = 10 s.

5.1.4 DEVIATION FROM TEST STANDARD

No deviation

5.1.5 EUT OPERATING CONDITIONS

The EUT was programmed to be in normal mode.

Report No.: NEI-FCCP-1-R1108001 Page 22 of 25

5.1.6 TEST RESULTS


EUT:	ON TOUCH RF Remote Controller	Model Name :	SR06
Temperature:	15°C	Relative Humidity:	58%
Test Voltage:	DC 3V		
Test Mode :	TX 433.95MHz		

Frequency (MHz)	Pulse Train T _(on+off) (ms)	Release Time (Second)	Result
433.95	220	< 5 Note(1)	PASS

Note:

(1) The EUT is a manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

Release Time



Report No.: NEI-FCCP-1-R1108001 Page 23 of 25