

EMC TEST REPORT

No. SH11080372-001

Applicant : Hangzhou Forever Technology Co., Ltd.
Hi-tech Development Park Building 3#, Binjiang District,
Zhejiang Province, P.R.China

Manufacturer : Hangzhou Forever Technology Co., Ltd.
Hi-tech Development Park Building 3#, Binjiang District,
Zhejiang Province, P.R.China

Equipment : Remote control transmitter

Type/Model : KSI-393 (TX)

SUMMARY

The equipment complies with the requirements according to the following standard(s):

47CFR Part 15 (2010): Radio Frequency Devices


ANSI C63.4 (2003): American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

RSS-210 Issue 8 (December 2010): Low-power Licence-exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment

RSS-Gen Issue 3 (December 2010): General Requirements and Information for the Certification of Radiocommunication Equipment

Date of issue: Dec 19, 2011

Prepared by:



Wakeyou Wang (*Project Engineer*)

Reviewed by:



Daniel Zhao (*Reviewer*)

Description of Test Facility

Name: Intertek Testing Services Limited Shanghai
Address: Building No.86, 1198 Qinzhou Road(North), Shanghai 200233, P.R. China

FCC Registration Number: 236597
IC Assigned Code: 2042B-1

Name of contact: Steve Li
Tel: +86 21 64956565 ext. 214
Fax: +86 21 54262335 ext. 214

Content

| | |
|---|-----------|
| SUMMARY..... | 1 |
| DESCRIPTION OF TEST FACILITY..... | 2 |
| 1. GENERAL INFORMATION | 4 |
| 1.1 Applicant Information..... | 4 |
| 1.2 Identification of the EUT | 4 |
| 1.3 Technical specification | 5 |
| 1.4 Mode of operation during the test / Test peripherals used..... | 5 |
| 2. TEST SPECIFICATION | 6 |
| 2.1 Instrument list | 6 |
| 2.2 Test Standard | 6 |
| 3. FUNDAMENTAL & SPURIOUS EMISSION & RESTRICT BAND RADIATED EMISSION | 8 |
| 3.1 Test limit..... | 8 |
| 3.2 Test Configuration | 9 |
| 3.3 Test procedure and test setup..... | 9 |
| 3.4 Test protocol | 10 |
| 4. DEACTIVATING TIME | 11 |
| 4.1 Test limit..... | 11 |
| 4.2 Test Configuration | 12 |
| 4.3 Test procedure and test setup..... | 12 |
| 4.4 Test protocol | 12 |
| 5. POWER LINE CONDUCTED EMISSION | 13 |
| 5.1 Limit..... | 13 |
| 5.2 Test configuration | 13 |
| 5.3 Test procedure and test set up | 14 |
| 5.4 Test protocol | 15 |
| 6. EMISSION BANDWIDTH | 16 |
| 6.1 Test limit..... | 16 |
| 6.2 Test Configuration | 16 |
| 6.3 Test procedure and test setup..... | 16 |
| 6.4 Test protocol | 17 |
| 7. OCCUPIED BANDWIDTH | 18 |
| 7.1 Test limit..... | 18 |
| 7.2 Test Configuration | 18 |
| 7.3 Test procedure and test setup..... | 18 |
| 7.4 Test protocol | 19 |

1. General Information

1.1 Applicant Information

Applicant: Hangzhou Forever Technology Co., Ltd.
Hi-tech Development Park Building 3#, Binjiang
District, Zhejiang Province, P.R.China

Name of contact: Mr. Hu

Tel: 86 571 87804199
Fax: 86 571 87862235

Manufacturer: Hangzhou Forever Technology Co., Ltd.
Hi-tech Development Park Building 3#, Binjiang
District, Zhejiang Province, P.R.China

Sample received date : Aug 12, 2011
Date of test : Aug 12, 2011 ~ Nov 26, 2011

1.2 Identification of the EUT

Equipment: Remote control transmitter

Type/model: KSI-393 (TX)

FCC ID: Z5T-991109

IC: Not applied

1.3 Technical specification

| | |
|---------------------------|---|
| Operation Frequency Band: | 315MHz |
| Modulation: | ASK |
| Antenna Designation: | PCB antenna, non-user removable. |
| Rating: | Battery DC 12V Working frequency: 315MHz |
| Description of EUT: | There is one model only. The EUT is a transmitter to transmit wireless signal so as to control the on/off condition of receiver. |
| Channel Description: | There is one channel only and working at the central frequency of 315MHz. |

1.4 Mode of operation during the test / Test peripherals used

Within this test report, EUT was tested with modulation and tested under its rating voltage and frequency.

The EUT is a portable device, so three axes were observed. The three axes were tested one by one while the test receiver worked as “max hold” continuously and the highest reading among the whole test procedure was recorded.

2. Test Specification

2.1 Instrument list

| Equipment | Type | Manu. | Internal no. | Cal. Date | Due date |
|-----------------------|------------|-------------------|--------------|------------|------------|
| Test Receiver | ESIB 26 | R&S | EC 3045 | 2011-10-21 | 2012-10-20 |
| Semi-anechoic chamber | - | Albatross project | EC 3048 | 2011-5-21 | 2012-5-20 |
| Bilog Antenna | CBL 6112D | TESEQ | EC 4206 | 2011-5-16 | 2013-5-15 |
| Horn antenna | HF 906 | R&S | EC 3049 | 2011-5-13 | 2013-5-12 |
| Pre-amplifier | Pre-amp 18 | R&S | EC 3222 | 2011-4-12 | 2012-4-11 |

2.2 Test Standard

47CFR Part 15 (2010): Radio Frequency Devices

ANSI C63.4 (2003): American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

RSS-210 Issue 8 (December 2010): Low-power Licence-exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment

RSS-Gen Issue 3 (December 2010): General Requirements and Information for the Certification of Radiocommunication Equipment

2.3 Test Summary

This report applies to tested sample only. This report shall not be reproduced in part without written approval of Intertek Testing Service Shanghai Limited.

| TEST ITEM | FCC REFERANCE | IC REFERANCE | RESULT |
|---------------------------------|---------------|------------------------------|--------|
| Fundamental & spurious emission | 15.231(b) | RSS-210 Issue 8 Annex A1.1.2 | Pass |
| Restrict band radiated emission | 15.205 | RSS-210 Issue 8 Clause 2.2 | Pass |
| Power line conducted emission | 15.207 | RSS-Gen Issue 3 Clause 7.2.4 | NA |
| Emission bandwidth | 15.231(c) | RSS-210 Issue 8 Annex A1.1.3 | Pass |
| Deactivating time | 15.231(a)(1) | RSS-210 Issue 8 Annex A1.1.1 | Pass |
| Occupied bandwidth | - | RSS-Gen Issue 3 Clause 4.6.1 | Tested |

3. Fundamental & Spurious Emission & Restrict band radiated emission

Test result: PASS

3.1 Test limit

3.1.1 The emission shall test through the 10th harmonic or to 40GHz, whichever is lower. It must comply with the limits below:

| Fundamental Frequency (MHz) | Fundamental limit (uV/m) | Spurious limit (uV/m) |
|---|-----------------------------|--------------------------|
| <input type="checkbox"/> 40.66 – 40.70 | 2250 | 225 |
| <input type="checkbox"/> 70 – 130 | 1250 | 125 |
| <input type="checkbox"/> 130 - 174 | 1250 to 3750 | 125 to 375 |
| <input type="checkbox"/> 174 - 260 | 3750 | 375 |
| <input checked="" type="checkbox"/> 260 – 470 | 3750 to 12500 | 375 to 1250 |
| <input type="checkbox"/> Above 470 | 12500 | 1250 |

The formulas for calculating the maximum permitted fundamental field strengths are as follows: for the band 130-174 MHz, uV/m at 3 meters = $56.81818(\text{Frequency}) - 6136.3636$; for the band 260-470 MHz, uV/m at 3 meters = $41.6667(\text{Frequency}) - 7083.3333$. The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.

For that the EUT use fundamental frequency of 315MHz, after calculation, the limit is:

$$\text{Fundamental limit} = 41.6667 * 315 - 7083.3333 = 6041.68 \text{uV/m} = 75.60 \text{dBuV/m}$$


$$\text{Spurious limit} = 75.60 - 20 = 55.60 \text{dBuV/m}$$

//////////

3.1.2 The radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) showed as below:

| Frequency (MHz) | Field Strength (dBuV/m) | Measurement Distance (m) |
|--------------------|----------------------------|-----------------------------|
| 30 - 88 | 40.0 | 3 |
| 88 - 216 | 43.5 | 3 |
| 216 - 960 | 46.0 | 3 |
| Above 960 | 54.0 | 3 |

3.2 Test Configuration



3.3 Test procedure and test setup

The measurement was applied in a semi-anechoic chamber. While testing for spurious emission higher than 1GHz, the pre-amplifier is equipped just at the output terminal of the antenna.

The EUT and simulators were placed on a 0.8m high wooden turntable above the horizontal metal ground plane. The turn table rotated 360 degrees to determine the position of the maximum emission level. The EUT was set 3 meters away from the receiving antenna which was mounted on an antenna mast. The antenna moved up and down between from 1meter to 4 meters to find out the maximum emission level.

The radiated emission was measured using the Spectrum Analyzer with the resolutions bandwidth set as:

RBW = 100kHz, VBW = 300kHz (30MHz~1GHz)
RBW = 1MHz, VBW = 3MHz (>1GHz for PK);

3.4 Test protocol

| Antenna | Frequency (MHz) | Correct Factor (dB/m) | Corrected Reading (dBuV/m) | Emission Type | AV Limit (dBuV/m) | Margin (dB) | Detector |
|---------|-----------------|-----------------------|----------------------------|---------------|-------------------|-------------|----------|
| H | 315.04 | 15.50 | 66.80 | Fundamental | 75.60 | 8.80 | PK |
| H | 945.57 | 24.00 | 59.30 | Harmonics | 75.60 (PK limit) | 16.30 | PK |
| V | 1258.52 | -13.50 | 42.40 | Harmonics | 55.60 | 13.20 | PK |
| V | 2520.36 | -8.80 | 37.30 | Harmonics | 55.60 | 19.30 | PK |
| H | 322.00 | 15.90 | 31.60 | Restrict | 46.00 | 14.40 | PK |
| H | 334.79 | 16.20 | 31.90 | Restrict | 46.00 | 14.10 | PK |
| V | 1571.14 | -12.40 | 45.30 | Restrict | 54.00 | 8.70 | PK |
| V | 1889.78 | -10.70 | 41.80 | Restrict | 54.00 | 12.20 | PK |

Remark: 1. Correct Factor = Antenna Factor + Cable Loss (+ Amplifier, for higher than 1GHz)

2. Corrected Reading = Original Receiver Reading + Correct Factor
3. If the PK reading is lower than the AV limit, the AV assessment is not conducted any longer.

Example: Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB, Gain of Preamplifier = 32.00dB, Original Receiver Reading = 10dBuV. Then Correct Factor = $30.20 + 2.00 - 32.00 = 0.20$ dB/m; Corrected Reading = 10 dBuV + 0.20dB/m = 10.20dBuV/m

Calculating the AV value of spurious emission according to the duty cycle

| Antenna | Frequency (MHz) | PK Reading (dBuV/m) | Correct Factor (dB) | AV Reading (dBuV/m) | Limit (dBuV/m) | Margin (dB) |
|---------|-----------------|---------------------|---------------------|---------------------|----------------|-------------|
| H | 945.57 | 59.30 | -7.60 | 51.70 | 55.60 | 3.90 |

Remark: 1. Correct Factor = $20\lg(\text{duty cycle}) = 20\lg(41.9\%) = -7.60$

2. AV Reading = PK Reading + Correct Factor
3. Margin = limit - AV Reading


4. Deactivating time

Test result: PASS

4.1 Test limit

- (1) A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.
- (2) A transmitter activated automatically shall cease transmission within 5 seconds after activation.
- (3) Periodic transmissions at regular predetermined intervals are not permitted. However, polling or supervision transmissions, including data, to determine system integrity of transmitters used in security or safety applications are allowed if the total duration of transmissions does not exceed more than two seconds per hour for each transmitter. There is no limit on the number of individual transmissions, provided the total transmission time does not exceed two seconds per hour.
- (4) Intentional radiators which are employed for radio control purposes during emergencies involving fire, security, and safety of life, when activated to signal an alarm, may operate during the pendency of the alarm condition.
- (5) Transmission of set-up information for security systems may exceed the transmission duration limits in (1) and (2) above, provided such transmission are under the control of a professional installer and do not exceed ten seconds after a manually operated switch is released or a transmitter is activated automatically. Such set-up information may include data.

4.2 Test Configuration



4.3 Test procedure and test setup

The measurement was applied in a semi-anechoic chamber.

The central frequency of test receiver was set as the operating frequency of EUT and the Span was set as 0.

The EUT was switched once. The test receiver recorded the whole time from the triggered moment to the time of stopping radiating. For manual switching, to avoid uncertainty, the operating above would be repeated five times and the worst data is recorded.

4.4 Test protocol

Whole time from the triggered moment to the time of stopping radiating: 140ms.
As a result, the EUT complies with the limit of 5s' deactivating time.

5. Power line conducted emission


Test result: **NA**

5.1 Limit

| Frequency of Emission (MHz) | Conducted Limit (dBuV) | |
|-----------------------------|------------------------|------------|
| | QP | AV |
| 0.15-0.5 | 66 to 56* | 56 to 46 * |
| 0.5-5 | 56 | 46 |
| 5-30 | 60 | 50 |

* Decreases with the logarithm of the frequency.

5.2 Test configuration



- For table top equipment, wooden support is 0.8m height table
- For floor standing equipment, wooden support is 0.1m height rack.

5.3 Test procedure and test set up

The EUT are connected to the main power through a line impedance stabilization network (LISN). This provides a $50\Omega/50\mu\text{H}$ coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a $50\Omega/50\mu\text{H}$ coupling impedance with 50Ω termination.

Both sides (Line and Neutral) of AC line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4 on conducted measurement. The bandwidth of the test receiver is set at 9 kHz.

5.4 Test protocol

Power line: L

| Frequency | Correct Factor (dB) | Corrected Reading (dBuV) | | Limit (dBuV) | | Margin (dB) | |
|-----------|------------------------|-----------------------------|----|-----------------|----|----------------|----|
| | | QP | AV | QP | AV | QP | AV |
| - | - | - | - | - | - | - | - |
| - | - | - | - | - | - | - | - |
| - | - | - | - | - | - | - | - |
| - | - | - | - | - | - | - | - |
| - | - | - | - | - | - | - | - |
| - | - | - | - | - | - | - | - |
| - | - | - | - | - | - | - | - |

Remark: 1. Correction Factor (dB) = LISN Factor (dB) + Cable Loss (dB).

2. Margin (dB) = Limit - Corrected Reading.

3. If the margin higher than 20dB, it would be marked as *.

Power line: N

| Frequency | Correct Factor (dB) | Corrected Reading (dBuV) | | Limit (dBuV) | | Margin (dB) | |
|-----------|------------------------|-----------------------------|----|-----------------|----|----------------|----|
| | | QP | AV | QP | AV | QP | AV |
| - | - | - | - | - | - | - | - |
| - | - | - | - | - | - | - | - |
| - | - | - | - | - | - | - | - |
| - | - | - | - | - | - | - | - |
| - | - | - | - | - | - | - | - |
| - | - | - | - | - | - | - | - |

Remark: 1. Correction Factor (dB) = LISN Factor (dB) + Cable Loss (dB).

2. Margin (dB) = Limit - Corrected Reading.

3. If the margin higher than 20dB, it would be marked as *.

6. Emission Bandwidth


Test Status: Pass

6.1 Test limit

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20dB down from the modulated carrier.

The limit for the EUT = $0.25\% * 315\text{MHz} = 788\text{kHz}$

6.2 Test Configuration



6.3 Test procedure and test setup

The EUT and simulators were placed on a 0.8m high wooden turntable above the horizontal metal ground plane. The turn table rotated 360 degrees to determine the position of the maximum emission level. The EUT was set 3 meters away from the receiving antenna which was mounted on an antenna mast. The antenna moved up and down between from 1meter to 4 meters to find out the maximum emission level.

The central frequency of test receiver was set near the operating frequency of EUT.

Spectrum Analyzer with the resolutions bandwidth set at 10kHz, the video bandwidth set at 30kHz.

6.4 Test protocol

Temperature : 25 °C
Relative Humidity : 55 %

| Channel | Emission Bandwidth (kHz) | Limit (kHz) |
|---------|-----------------------------|----------------|
| 1 | 33.43 | 788 |


7. Occupied Bandwidth

Test Status: Tested

7.1 Test limit

None

7.2 Test Configuration



7.3 Test procedure and test setup

The occupied bandwidth per RSS-Gen Issue 3 Clause 4.6.1 was measured using the Spectrum Analyzer with the resolutions bandwidth set at 10kHz, the video bandwidth set at 30kHz.

7.4 Test protocol

Temperature : 25 °C

Relative Humidity : 55 %

| Channel | Occupied Bandwidth (kHz) | Max. Value (kHz) |
|---------|--------------------------|------------------|
| 1 | 64.13 | 64.13 |

Remark: “Max. Value” is the maximum test result of all the measured occupied bandwidth.