


Prüfbericht-Nr.: Test Report No.:	50049367 001	Auftrags-Nr.: Order No.:	164066056	Seite 1 von 38 Page 1 of 38
Kunden-Referenz-Nr.: Client Reference No.:	429028	Auftragsdatum: Order date:	13.06.2016	
Auftraggeber: Client:	Compupal (Group) Corporation. No.1555 Jiashan Avenue, Jiashan 314113, Zhejiang, China			
Prüfgegenstand: Test item:	Portable Bluetooth Speaker			
Bezeichnung / Typ-Nr.: Identification / Type No.:	NS-CSPBTHOL16			
Auftrags-Inhalt: Order content:	FCC Certification and Verification			
Prüfgrundlage: Test specification:	CFR47 FCC Part 15: Subpart C Section 15.247 CFR47 FCC Part 15: Subpart C Section 15.207 CFR47 FCC Part 15: Subpart C Section 15.209 FCC KDB Publication 447498 v06 CFR47 FCC Part 15: Subpart B Section 15.107 CFR47 FCC Part 15: Subpart B Section 15.109 RSS-247 Issue 1 May 2015 RSS-102 Issue 5 March 2015 RSS-Gen Issue 4 November 2014			
Wareneingangsdatum: Date of receipt:	13.06.2016			
Prüfmuster-Nr.: Test sample No.:	A000375695-001, 002, 004			
Prüfzeitraum: Testing period:	26.06.2016 - 27.06.2016			
Ort der Prüfung: Place of testing:	Shenzhen Accurate Technology Co., Ltd.			
Prüflaboratorium: Testing laboratory:	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüfergebnis*: Test result*:	Pass			
geprüft von / tested by: 		kontrolliert von / reviewed by: 		
11.07.2016 Datum Date	Winnie Hou / Senior Project Manager Name / Stellung Name / Position	20.07.2016 Datum Date	Owen Tian / Technical Certifier Name / Stellung Name / Position	Unterschrift Signature
Sonstiges / Other: FCC ID: Z5Y-CSPBTHOL16, IC: 10828A-CSPBTHOL16				
Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:		Prüfmuster vollständig und unbeschädigt Test item complete and undamaged		
* Legende: 1 = sehr gut 2 = gut 3 = befriedigend 4 = ausreichend 5 = mangelhaft P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet Legend: 1 = very good 2 = good 3 = satisfactory 4 = sufficient 5 = poor P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested				
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.				

V04

TEST SUMMARY

5.1.1 ANTENNA REQUIREMENT

RESULT: *Passed*

5.1.2 PEAK OUTPUT POWER

RESULT: *Passed*

5.1.3 CONDUCTED POWER SPECTRAL DENSITY

RESULT: *Passed*

5.1.4 -6dB BANDWIDTH

RESULT: *Passed*

5.1.5 99% BANDWIDTH

RESULT: *Passed*

5.1.6 CONDUCTED SPURIOUS EMISSIONS MEASURED IN 100KHZ BANDWIDTH

RESULT: *Passed*

5.1.7 SPURIOUS EMISSION

RESULT: *Passed*

5.1.8 20dB BANDWIDTH

RESULT: *Passed*

5.1.9 FREQUENCY SEPARATION

RESULT: *Passed*

5.1.10 NUMBER OF HOPPING FREQUENCY

RESULT: *Passed*

5.1.11 TIME OF OCCUPANCY

RESULT: *Passed*

5.1.12 CONDUCTED EMISSIONS

RESULT: *Passed*

5.1.13 RADIATED EMISSION

RESULT: *Passed*

Contents

1.	GENERAL REMARKS	4
1.1	COMPLEMENTARY MATERIALS	4
2.	TEST SITES	4
2.1	TEST FACILITIES	4
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS	5
2.3	TRACEABILITY	6
2.4	CALIBRATION	6
2.5	MEASUREMENT UNCERTAINTY	6
2.6	LOCATION OF ORIGINAL DATA	6
2.7	STATUS OF FACILITY USED FOR TESTING	6
3.	GENERAL PRODUCT INFORMATION	7
3.1	PRODUCT FUNCTION AND INTENDED USE	7
3.2	RATINGS AND SYSTEM DETAILS	7
3.3	INDEPENDENT OPERATION MODES	9
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS	9
3.5	SUBMITTED DOCUMENTS	9
4.	TEST SET-UP AND OPERATION MODES	10
4.1	PRINCIPLE OF CONFIGURATION SELECTION	10
4.2	TEST OPERATION AND TEST SOFTWARE	10
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	10
4.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE	10
4.5	TEST SETUP DIAGRAM	11
5.	TEST RESULTS	13
5.1	TRANSMITTER REQUIREMENT & TEST SUITES	13
5.1.1	<i>Antenna Requirement</i>	<i>13</i>
5.1.2	<i>Peak Output Power</i>	<i>14</i>
5.1.3	<i>Conducted Power Spectral Density</i>	<i>15</i>
5.1.4	<i>-6dB Bandwidth</i>	<i>16</i>
5.1.5	<i>99% Bandwidth</i>	<i>17</i>
5.1.6	<i>Conducted spurious emissions measured in 100kHz Bandwidth</i>	<i>18</i>
5.1.7	<i>Spurious Emission</i>	<i>27</i>
5.1.8	<i>20dB Bandwidth</i>	<i>28</i>
5.1.9	<i>Frequency Separation</i>	<i>29</i>
5.1.10	<i>Number of hopping frequency</i>	<i>30</i>
5.1.11	<i>Time of Occupancy</i>	<i>31</i>
5.1.12	<i>Conducted emissions</i>	<i>32</i>
5.1.13	<i>Radiated Emission</i>	<i>33</i>
6.	PHOTOGRAPHS OF THE TEST SET-UP	34
7.	LIST OF TABLES	38
8.	LIST OF PHOTOGRAPHS	38

1. General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:
Appendix 1: Test Result

2. Test Sites

2.1 Test Facilities

Shenzhen Accurate Technology Co., Ltd.

F1, Bldg. A, Changyuan New Material Port, Keyuan Rd., Science & Industry Park Nanshan District, Shenzhen 518057, P.R. China

FCC Registration No.: 752051

Test site Industry Canada No.: 5077A-2

The tests at the test site have been conducted under the supervision of a TÜV engineer.

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

Kind of Equipment	Manufacturer	Type	S/N	Calibrated until
Spurious emission and Radiated emission				
Spectrum Analyzer	Rohde&Schwarz	FSV40	101495	2017-01-01
Test Receiver	Rohde&Schwarz	ESCS30	100307	2017-01-01
Bilog Antenna	Schwarzbeck	VULB9163	9163-323	2017-01-01
Loop Antenna	Schwarzbeck	FMZB1516	1516131	2017-01-01
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	2017-01-01
Horn Antenna	Schwarzbeck	BBHA9170	9170-359	2017-01-01
RF Switching Unit+PreAMP	Compliance Direction	RSU-M2	38322	2017-01-01
Pre-Amplifier	Rohde&Schwarz	CBLU11835 40-01	3791	2017-01-01
Radio Spectrum Test				
Spectrum Analyzer	Rohde & Schwarz	ESPI3	100396/003	2017-01-09
Spectrum Analyzer	Agilent	E7405A	MY45115511	2017-01-09
Conducted Emission				
Test Receiver	Rohde & Schwarz	ESCS30	100307	2017-01-09
L.I.S.N.	Schwarzbeck	NLSK8126	8126431	2017-01-09
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100815	2017-01-09
50 ⁺ Coaxial Switch	Anritsu Corp	MP59B	6200283933	2017-01-09

2.3 Traceability

All measurement equipment calibrations are traceable to NIM (National Institute of Metrology) or where calibration is performed in other countries, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements are $\pm 3\text{dB}$.

2.6 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendix 1 of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) file for certification follow-up purposes.

2.7 Status of Facility Used for Testing

The Shenzhen Accurate Technology Co., Ltd. test facility located at F1, Bldg. A, Changyuan New Material Port, Keyuan Rd., Science & Industry Park Nanshan District, Shenzhen 518057, P.R. China is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

3. General Product Information

3.1 Product Function and Intended Use

The EUT is Bluetooth Portable Speaker which supports Bluetooth 4.0 dual mode. Sub-models are used for EUT to distinguish different enclosure color. NS-CSPBTHOL16-BK, NS-CSPBTHOL16-BL, NS-CSPBTHOL16-G, NS-CSPBTHOL16-P, NS-CSPBTHOL16-PR, NS-CSPBTHOL16-R are identical in function, circuit design and components except different enclosure color. For details refer to the User Manual, Technical Description and Circuit Diagram.

3.2 Ratings and System Details

Table 2: Rating of EUT

Kind of Equipment:	Portable Bluetooth Speaker
Type Designation:	NS-CSPBTHOL16
FCC ID	Z5Y-CSPBTHOL16
IC	10828A-CSPBTHOL16

Table 3: Technical Specification of Bluetooth (BDR & EDR)

Technical Specification	Value
Operating Frequency band	2402 – 2480 MHz
Bluetooth Core Version	4.1
Channel Number	79 channels
Channel separation	1MHz
Extreme Temperature Range	-10°C to +50°C
Operation Voltage	DC5V via USB port
Modulation	GFSK, 8DPSK, $\pi/4$ DQPSK
Antenna Type	Internal Antenna, Non-User Replaceable
Antenna Gain	1dBi
RF Output Power	0.00043W (-3.7dBm)

Table 4: RF channel and frequency of Bluetooth (BDR & EDR mode)

RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)
0	2402.00	20	2422.00	40	2442.00	60	2462.00
1	2403.00	21	2423.00	41	2443.00	61	2463.00
2	2404.00	22	2424.00	42	2444.00	62	2464.00
3	2405.00	23	2425.00	43	2445.00	63	2465.00
4	2406.00	24	2426.00	44	2446.00	64	2466.00
5	2407.00	25	2427.00	45	2447.00	65	2467.00
6	2408.00	26	2428.00	46	2448.00	66	2468.00
7	2409.00	27	2429.00	47	2449.00	67	2469.00
8	2410.00	28	2430.00	48	2450.00	68	2470.00
9	2411.00	29	2431.00	49	2451.00	69	2471.00
10	2412.00	30	2432.00	50	2452.00	70	2472.00
11	2413.00	31	2433.00	51	2453.00	71	2473.00
12	2414.00	32	2434.00	52	2454.00	72	2474.00
13	2415.00	33	2435.00	53	2455.00	73	2475.00
14	2416.00	34	2436.00	54	2456.00	74	2476.00
15	2417.00	35	2437.00	55	2457.00	75	2477.00
16	2418.00	36	2438.00	56	2458.00	76	2478.00
17	2419.00	37	2439.00	57	2459.00	77	2479.00
18	2420.00	38	2440.00	58	2460.00	78	2480.00
19	2421.00	39	2441.00	59	2461.00		

Table 5: Technical Specification of Bluetooth (low energy)

Technical Specification	Value
Operating Frequency band	2402 – 2480 MHz
Bluetooth Core Version	4.1
Channel Number	40 channels
Channel separation	2MHz
Extreme Temperature Range	-10°C to +50°C
Operation Voltage	DC5V via USB port
Modulation	GFSK
Antenna Type	Internal Antenna, Non-User Replaceable
Antenna Gain	1dBi
RF Output Power	0.00014W (-8.5dBm)

Table 6: RF channel and frequency of Bluetooth low energy

RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)
0	2402.00	10	2422.00	20	2442.00	30	2462.00
1	2404.00	11	2424.00	21	2444.00	31	2464.00
2	2406.00	12	2426.00	22	2446.00	32	2466.00
3	2408.00	13	2428.00	23	2448.00	33	2468.00
4	2410.00	14	2430.00	24	2450.00	34	2470.00
5	2412.00	15	2432.00	25	2452.00	35	2472.00
6	2414.00	16	2434.00	26	2454.00	36	2474.00
7	2416.00	17	2436.00	27	2456.00	37	2476.00
8	2418.00	18	2438.00	28	2458.00	38	2478.00
9	2420.00	19	2440.00	29	2460.00	39	2480.00

3.3 Independent Operation Modes

The basic operation modes are:

- A. On, Bluetooth mode (BDR & EDR)
 - 1. Transmitting on low channel
 - 2. Transmitting on middle channel
 - 3. Transmitting on high channel
- B. On, Bluetooth low energy mode
 - 1. Transmitting on low channel
 - 2. Transmitting on middle channel
 - 3. Transmitting on high channel
- C. On, Bluetooth hopping mode
- D. Charging mode
- E. Play with Aux in
- F. Off

3.4 Noise Generating and Noise Suppressing Parts

Refer to the Circuit Diagram.

3.5 Submitted Documents

- Bill of Material
- PCB Layout
- Photo Document
- Technical Description
- Circuit Diagram
- Instruction Manual
- Rating Label

4. Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

The equipment under test (EUT) was configured to measure its maximum power level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All testing were performed according to the procedures in ANSI C63.4: 2014 and ANSI C63.10: 2013.

4.3 Special Accessories and Auxiliary Equipment

The EUT was tested with following accessories:

Description	Manufacturer	Type	S/N
iPhone6S PLUS	Apple	ML6D2 CH/A	C35QJ76JGRWM
Notebook	LENOVO	ThinkPad X240	N/A
Printer	HP	1015	CNFG030424

4.4 Countermeasures to achieve EMC Compliance

The test sample, which has been tested, contained the noise suppression parts as described in the Constructional Data Form or the Technical Construction File. No additional measures were employed to achieve compliance.

4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test (Below 1GHz)




Diagram of Measurement Configuration for Radiation Test (Above 1GHz)




Diagram of Measurement Equipment Configuration for Mains Conduction Measurement




Diagram of Measurement Equipment Configuration for Conducted Transmitter Measurement



5. Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

RESULT:**Passed**

Test standard	:	FCC Part 15.247(b)(4) and Part 15.203 RSS-Gen 6.7
Limit	:	the use of antennas with directional gains that do not exceed 6 dBi

According to the manufacturer declared, the EUT has an internal antenna, the directional gain of antenna is 1dBi, and the antenna connector is designed with permanent attachment and no consideration of replacement. Therefore the EUT is considered sufficient to comply with the provision.

Refer to EUT photo for details.

5.1.2 Peak Output Power

RESULT:
Passed

Test date : 2016-06-26
 Test standard : FCC Part 15.247(b)(1)&(3)
 RSS-247 Clause 5.4(2)&(4)
 Basic standard : ANSI C63.10: 2013
 Limit : FHSS < 0.125 Watts, DSSS < 1.0 Watts
 Kind of test site : Shielded room

Test setup

Test Channel : Low/ Middle/ High
 Operation Mode : A, B
 Ambient temperature : 25°C
 Relative humidity : 55%
 Atmospheric pressure : 101 kPa

Table 7: Test result of Peak Output Power

Test Mode	Channel Frequency (MHz)	Measured Peak Output Power		Limit (W)
		(dBm)	(W)	
BDR	2402	-4.2	0.00038	< 0.125
	2441	-6.0	0.00025	
	2480	-8.3	0.00015	
EDR	2402	-3.7	0.00043	< 0.125
	2441	-5.2	0.00030	
	2480	-7.0	0.00020	
Low Energy	2402	-8.5	0.00014	< 1.0
	2440	-11.3	0.00007	
	2480	-14.1	0.00004	

Note: The cable loss is taken into account in results.

5.1.3 Conducted Power Spectral Density

RESULT:**Passed**

Test date : 2016-06-26
Test standard : FCC Part 15.247(e)
RSS-247 Clause 5.2(2)
Basic standard : ANSI C63.10: 2013
Limit : 8dBm/3kHz
Kind of test site : Shielded room

Test setup

Test Channel : Low/ Middle/ High
Operation Mode : B
Ambient temperature : 25°C
Relative humidity : 55%
Atmospheric pressure : 101 kPa

Table 8: Test result of Power Spectral Density, low energy

Channel	Channel Frequency (MHz)	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)
Low Channel	2402	-25.61	< 8
Middle Channel	2440	-27.84	< 8
High Channel	2480	-30.67	< 8

Note: The cable loss is taken into account in results.

5.1.4 -6dB Bandwidth**RESULT:****Passed**

Date of testing : 2015-01-07
Test standard : FCC Part 15.247(a)(2)
RSS-247 Clause 5.2(1)
Basic standard : ANSI C63.10: 2013
Kind of test site : Shielded room

Test setup

Test Channel : Low/ Middle/ High
Operation Mode : B
Ambient temperature : 25°C
Relative humidity : 55%
Atmospheric pressure : 101 kPa

Table 9: Test result of 6dB Bandwidth, low energy

Channel	Channel Frequency (MHz)	-6dB Bandwidth (kHz)	Limit (kHz)
Low Channel	2402	751	> 500
Mid Channel	2440	755	> 500
High Channel	2480	768	> 500

5.1.5 99% Bandwidth

RESULT:
Passed

Date of testing : 2015-01-07
 Test standard : RSS-Gen clause 6.6
 Basic standard : ANSI C63.10: 2013
 Kind of test site : Shielded room

Test setup

Test Channel : Low/ Middle/ High
 Operation Mode : A, B
 Ambient temperature : 25°C
 Relative humidity : 55%
 Atmospheric pressure : 101 kPa

Table 10: Test result of 99% Bandwidth

Test Mode	Channel Frequency (MHz)	99% Bandwidth (kHz)	Limit (kHz)
BDR	2402	1007.24	/
	2441	985.53	
	2480	968.16	
EDR	2402	1523.87	/
	2441	1332.85	
	2480	1536.90	
Low Energy	2402	1072.36	/
	2440	1081.04	
	2480	1085.38	

Note: The cable loss is taken into account in results.

5.1.6 Conducted spurious emissions measured in 100kHz Bandwidth

RESULT:**Passed**

Date of testing	:	2016-06-26
Test standard	:	FCC part 15.247(d) RSS-247 Clause 5.5
Basic standard	:	ANSI C63.10: 2013
Limit	:	20dB (below that in the 100kHz bandwidth within the band that contains the highest level of the desired power); In addition, radiated emissions which fall in the restricted bands, must also comply with the radiated emission limits specified in 15.209(a)
Kind of test site	:	Shield room

Test setup


Test Channel	:	Low/ High
Operation mode	:	A, B
Ambient temperature	:	25°C
Relative humidity	:	55%
Atmospheric pressure	:	101 kPa

All emissions are more than 20dB below fundamental, details refer to following test plot, and compliance is achieved as well.

Test Plot of 100kHz Bandwidth of Frequency Band Edge


BDR mode

Low Channel




Date: 26.JUN.2016 18:12:04


Low Channel, Band Edge




Date: 26.JUN.2016 18:02:32

Middle Channel



Date: 26.JUN.2016 18:13:20

High Channel



Date: 26.JUN.2016 18:14:17

High Channel, Band Edge



Date: 26.JUN.2016 18:00:52

EDR mode
Low Channel



Date: 26.JUN.2016 18:10:51

Low Channel, Band Edge



Date: 26.JUN.2016 18:04:26

Middle Channel



Date: 26.JUN.2016 18:09:32

High Channel



Date: 26.JUN.2016 18:08:04

High Channel, Band Edge



Date: 26.JUN.2016 18:05:55

Low energy
Low Channel



Date: 26.JUN.2016 17:28:54

Low Channel, Band Edge



Date: 26.JUN.2016 17:23:10

Middle Channel


Date: 26.JUN.2016 17:27:48

High Channel


Date: 26.JUN.2016 17:26:40

High Channel, Band Edge


Date: 26.JUN.2016 17:24:58

5.1.7 Spurious Emission

RESULT:**Passed**

Date of testing	:	2016-06-26 to 2016-06-27
Test standard	:	FCC part 15.247(d) FCC Part 15.205 RSS-247 Clause 3.3
Basic standard	:	ANSI C63.10: 2013
Limits	:	Refer to 15.209(a) of FCC part 15.247(d) RSS-Gen Table 4 & Table 5
Kind of test site	:	3m Semi-Anechoic Chamber

Test setup

Test Channel	:	Low/ Middle/ High
Operation mode	:	A, B
Ambient temperature	:	25°C
Relative humidity	:	55%
Atmospheric pressure	:	101 kPa

Remark:

During the pretest the EUT was rotated through three orthogonal axes to determine the attitude that maximizes the emissions. After that the EUT was manually handled to find the orientation that has the maximum emission, which is the orientation shown in the test setup photos.

Testing was carried out within frequency range 9kHz to the tenth harmonics.

For details refer to Appendix 1.

Test Mode	Channel Frequency (MHz)	20dB Bandwidth (kHz)	2/3 of 20dB Bandwidth (kHz)	Limit (MHz)
BDR	2402	1033.3	688.867	/
	2441	1029.0	686.000	
	2480	1028.9	685.933	
EDR	2402	1364.7	909.800	/
	2441	1406.7	937.800	
	2480	1411.0	940.667	

Channel	Channel Frequency (MHz)	Measured Channel Separation (MHz)	Limit (kHz)	Result
Low Channel	2402	1	≥ 25kHz or 2/3 of 20dB bandwidth	Pass
Adjacency Channel	2403			
Mid Channel	2441	1	≥ 25kHz or 2/3 of 20dB bandwidth	Pass
Adjacency Channel	2442			
High Channel	2480	1	≥ 25kHz or 2/3 of 20dB bandwidth	Pass
Adjacency Channel	2479			

5.1.10 Number of hopping frequency**RESULT:****Passed**

Date of testing : 2016-06-26
Test standard : FCC part 15.247(a)(1)(iii)
RSS-247 Clause 5.1(4)
Basic standard : ANSI C63.10: 2013
Limits : ≥ 15 non-overlapping channels
Kind of test site : Shield room

Test setup

Test Channel : Low/ Middle/ High
Operation Mode : C
Ambient temperature : 25°C
Relative humidity : 55%
Atmospheric pressure : 101 kPa

Table 13: Test result of Number of hopping frequency

Frequency Range	Measured Quantity of Hopping Channel	Limit	Result
<u>2400</u> to <u>2483.5</u> MHz	79	≥ 15	Pass

5.1.11 Time of Occupancy

RESULT:
Passed

Date of testing : 2016-06-27
 Test standard : FCC part 15.247(a)(1)(iii)
 RSS-247 Clause 5.1(4)
 Basic standard : ANSI C63.10: 2013
 Limits : <0.4s
 Kind of test site : Shield room

Test setup

Test Channel : Low/ Middle/ High
 Operation Mode : A
 Ambient temperature : 25°C
 Relative humidity : 55%
 Atmospheric pressure : 101 kPa

Table 14: Test result of Time of Occupancy

Test Mode	Channel	Data Packet	Pulse width (ms)	Measured Dwell time(s)	Limit (s)
BDR mode	2402	DH1	0.420	0.134	< 0.4s
		DH3	1.696	0.271	
		DH5	2.956	0.315	
	2441	DH1	0.413	0.132	
		DH3	1.696	0.271	
		DH5	2.956	0.315	
	2480	DH1	0.420	0.134	
		DH3	1.681	0.269	
		DH5	2.956	0.315	
EDR mode	2402	3DH1	0.427	0.137	
		3DH3	1.703	0.272	
		3DH5	2.949	0.315	
	2441	3DH1	0.427	0.137	
		3DH3	1.688	0.270	
		3DH5	2.949	0.315	
	2480	3DH1	0.420	0.134	
		3DH3	1.688	0.270	
		3DH5	2.971	0.317	

Note:

Dwell time = Pulse width x (Hopping rate / Number of channels) x Period

Period = 0.4 (seconds/ channel) x 79 (channel) = 31.6 seconds

5.1.12 Conducted emissions

RESULT:**Passed**

Date of testing	:	2016-06-27
Test standard	:	FCC Part 15.107(a) & FCC Part 15.207(a) RSS-Gen Clause 8.8
Basic standard	:	ANSI C63.10: 2013 & ANSI C63.4: 2014
Frequency range	:	0.15 – 30MHz
Limits	:	FCC Part 15.207(a) & FCC Part 15.207(a) RSS-Gen Table 3
Kind of test site	:	Shield room

Test setup

Input Voltage	:	AC 120V, 60Hz via AC input of PC
Operation Mode	:	C, D
Earthing	:	Not connected
Ambient temperature	:	25°C
Relative humidity	:	55%
Atmospheric pressure	:	101 kPa

For details refer to Appendix 1.

5.1.13 Radiated Emission

RESULT:**Passed**

Date of testing	:	2016-06-26
Test standard	:	FCC Part 15.109(a) & FCC Part 15.209(a) RSS-Gen 8.9
Basic standard	:	ANSI C63.4: 2014
Frequency range	:	30 - 6000MHz
Classification	:	Class B
Limit	:	FCC Part 15.109(a) & FCC Part 15.209(a) RSS-Gen Table 4
Kind of test site	:	3m Semi-Anechoic Chamber

Test setup

Input Voltage	:	AC 120V, 60Hz via AC input of PC
Operation mode	:	D, E
Earthing	:	Not connected
Ambient temperature	:	Refer to Appendix 1
Relative humidity	:	Refer to Appendix 1
Atmospheric pressure	:	Refer to Appendix 1

Test data refer to Appendix 1.

7. List of Tables

Table 1: List of Test and Measurement Equipment	5
Table 2: Rating of EUT	7
Table 3: Technical Specification of Bluetooth (BDR & EDR)	7
Table 4: RF channel and frequency of Bluetooth (BDR & EDR mode)	8
Table 5: Technical Specification of Bluetooth (low energy)	8
Table 6: RF channel and frequency of Bluetooth low energy	9
Table 7: Test result of Peak Output Power	14
Table 8: Test result of Power Spectral Density, low energy	15
Table 9: Test result of 6dB Bandwidth, low energy	16
Table 10: Test result of 99% Bandwidth	17
Table 11: Test result of 20dB Bandwidth	28
Table 12: Test result of Frequency Separation	29
Table 13: Test result of Number of hopping frequency	30
Table 14: Test result of Time of Occupancy	31

8. List of Photographs

Photograph 1: Set-up for Spurious Emissions (9kHz-30MHz)	34
Photograph 2: Set-up for Spurious Emissions (30MHz-1GHz)	34
Photograph 3: Set-up for Spurious Emissions (1GHz-18GHz)	35
Photograph 4: Set-up for Spurious Emissions (18GHz-26GHz)	35
Photograph 5: Set-up for Conducted Emissions	36
Photograph 6: Set-up for Radiated Emissions, below 1GHz	36
Photograph 7: Set-up for Radiated Emissions, above 1GHz	37

List of Figures

Figure 1: Test figure of spurious emissions, mode A.1, Horizontal polarity (9kHz – 30MHz)	3
Figure 2: Test figure of spurious emissions, mode A.1, Vertical polarity (9kHz – 30MHz)	4
Figure 3: Test figure of spurious emissions, mode A.1, Horizontal polarity (30MHz – 1GHz)	5
Figure 4: Test figure of spurious emissions, mode A.1, Vertical polarity (30MHz – 1GHz)	6
Figure 5: Test figure of spurious emissions, mode A.1, Horizontal polarity (1GHz – 18GHz)	7
Figure 6: Test figure of spurious emissions, mode A.1, Vertical polarity (1GHz – 18GHz)	8
Figure 7: Test figure of spurious emissions, mode A.1, Horizontal polarity (18GHz – 25GHz)	9
Figure 8: Test figure of spurious emissions, mode A.1, Vertical polarity (18GHz – 25GHz)	10
Figure 9: Test figure of spurious emissions, mode A.2, Horizontal polarity (9kHz – 30MHz)	11
Figure 10: Test figure of spurious emissions, mode A.2, Vertical polarity (9kHz – 30MHz)	12
Figure 11: Test figure of spurious emissions, mode A.2, Horizontal polarity (30MHz – 1GHz)	13
Figure 12: Test figure of spurious emissions, mode A.2, Vertical polarity (30MHz – 1GHz)	14
Figure 13: Test figure of spurious emissions, mode A.2, Horizontal polarity (1GHz – 18GHz)	15
Figure 14: Test figure of spurious emissions, mode A.2, Vertical polarity (1GHz – 18GHz)	16
Figure 15: Test figure of spurious emissions, mode A.2, Horizontal polarity (18GHz – 25GHz)	17
Figure 16: Test figure of spurious emissions, mode A.2, Vertical polarity (18GHz – 25GHz)	18
Figure 17: Test figure of spurious emissions, mode A.3, Horizontal polarity (9kHz – 30MHz)	19
Figure 18: Test figure of spurious emissions, mode A.3, Vertical polarity (9kHz – 30MHz)	20
Figure 19: Test figure of spurious emissions, mode A.3, Horizontal polarity (30MHz – 1GHz)	21
Figure 20: Test figure of spurious emissions, mode A.3, Vertical polarity (30MHz – 1GHz)	22
Figure 21: Test figure of spurious emissions, mode A.3, Horizontal polarity (1GHz – 18GHz)	23
Figure 22: Test figure of spurious emissions, mode A.3, Vertical polarity (1GHz – 18GHz)	24
Figure 23: Test figure of spurious emissions, mode A.3, Horizontal polarity (18GHz – 25GHz)	25
Figure 24: Test figure of spurious emissions, mode A.3, Vertical polarity (18GHz – 25GHz)	26
Figure 25: Test figure of spurious emissions, mode B.1, Horizontal polarity (9kHz – 30MHz)	27
Figure 26: Test figure of spurious emissions, mode B.1, Vertical polarity (9kHz – 30MHz)	28
Figure 27: Test figure of spurious emissions, mode B.1, Horizontal polarity (30MHz – 1GHz)	29
Figure 28: Test figure of spurious emissions, mode B.1, Vertical polarity (30MHz – 1GHz)	30
Figure 29: Test figure of spurious emissions, mode B.1, Horizontal polarity (1GHz – 18GHz)	31
Figure 30: Test figure of spurious emissions, mode B.1, Vertical polarity (1GHz – 18GHz)	32
Figure 31: Test figure of spurious emissions, mode B.1, Horizontal polarity (18GHz – 25GHz)	33
Figure 32: Test figure of spurious emissions, mode B.1, Vertical polarity (18GHz – 25GHz)	34
Figure 33: Test figure of spurious emissions, mode B.2, Horizontal polarity (9kHz – 30MHz)	35
Figure 34: Test figure of spurious emissions, mode B.2, Vertical polarity (9kHz – 30MHz)	36
Figure 35: Test figure of spurious emissions, mode B.2, Horizontal polarity (30MHz – 1GHz)	37
Figure 36: Test figure of spurious emissions, mode B.2, Vertical polarity (30MHz – 1GHz)	38
Figure 37: Test figure of spurious emissions, mode B.2, Horizontal polarity (1GHz – 18GHz)	39
Figure 38: Test figure of spurious emissions, mode B.2, Vertical polarity (1GHz – 18GHz)	40
Figure 39: Test figure of spurious emissions, mode B.2, Horizontal polarity (18GHz – 25GHz)	41
Figure 40: Test figure of spurious emissions, mode B.2, Vertical polarity (18GHz – 25GHz)	42
Figure 41: Test figure of spurious emissions, mode B.3, Horizontal polarity (9kHz – 30MHz)	43
Figure 42: Test figure of spurious emissions, mode B.3, Vertical polarity (9kHz – 30MHz)	44
Figure 43: Test figure of spurious emissions, mode B.3, Horizontal polarity (30MHz – 1GHz)	45
Figure 44: Test figure of spurious emissions, mode B.3, Vertical polarity (30MHz – 1GHz)	46
Figure 45: Test figure of spurious emissions, mode B.3, Horizontal polarity (1GHz – 18GHz)	47
Figure 46: Test figure of spurious emissions, mode B.3, Vertical polarity (1GHz – 18GHz)	48
Figure 47: Test figure of spurious emissions, mode B.3, Horizontal polarity (18GHz – 25GHz)	48
Figure 48: Test figure of spurious emissions, mode B.3, Vertical polarity (18GHz – 25GHz)	50
Figure 49: Test figure of Radiated emissions in restricted bands, Mode A.1, Horizontal	51
Figure 50: Test figure of Radiated emissions in restricted bands, Mode A.1, Vertical	52
Figure 51: Test figure of Radiated emissions in restricted bands, Mode A.3, Horizontal	53
Figure 52: Test figure of Radiated emissions in restricted bands, Mode A.3, Vertical	54

Figure 53: Test figure of Radiated emissions in restricted bands, Mode B.1, Horizontal	55
Figure 54: Test figure of Radiated emissions in restricted bands, Mode B.1, Vertical	56
Figure 55: Test figure of Radiated emissions in restricted bands, Mode B.3, Horizontal	57
Figure 56: Test figure of Radiated emissions in restricted bands, Mode B.3, Vertical	58
Figure 57: Test figure of Conducted emissions, Mode C, line live	59
Figure 58: Test figure of Conducted emissions, Mode C, line neutral	60
Figure 59: Test figure of Conducted emissions, Mode D, line live	61
Figure 60: Test figure of Conducted emissions, Mode D, line neutral	62
Figure 61: Test figure of Radiated emissions, Mode D, Below 1GHz, Horizontal	63
Figure 62: Test figure of Radiated emissions, Mode D, Below 1GHz, Vertical	64
Figure 63: Test figure of Radiated emissions, Mode D, Above 1GHz, Horizontal	65
Figure 64: Test figure of Radiated emissions, Mode D, Above 1GHz, Vertical	66
Figure 65: Test figure of Radiated emissions, Mode E, Below 1GHz, Horizontal	67
Figure 66: Test figure of Radiated emissions, Mode E, Below 1GHz, Vertical	68
Figure 67: Test figure of Radiated emissions, Mode E, Above 1GHz, Horizontal	69
Figure 68: Test figure of Radiated emissions, Mode E, Above 1GHz, Vertical	70

Figure 1: Test figure of spurious emissions, mode A.1, Horizontal polarity (9kHz – 30MHz)


ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3M Radiated

EUT: Portable Bluetooth Speaker M/N: NS-CSPBTHOL16
 Manufacturer:
 Operating Condition: TX 2402MHz
 Test Site: 2# Chamber
 Operator: LGWADE
 Test Specification: DC 3.7V
 Comment: X
 Start of Test: 2016-6-27 /

SCAN TABLE: "LFRE Fin"

Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M



**Figure 2: Test figure of spurious emissions, mode A.1, Vertical polarity
(9kHz – 30MHz)**

ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3M Radiated

EUT: Portable Bluetooth Speaker M/N: NS-CSPBTHOL16
 Manufacturer:
 Operating Condition: TX 2402MHz
 Test Site: 2# Chamber
 Operator: LGWADE
 Test Specification: DC 3.7V
 Comment: Y
 Start of Test: 2016-6-27 /

SCAN TABLE: "LFRE Fin"

Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




Figure 3: Test figure of spurious emissions, mode A.1, Horizontal polarity (30MHz – 1GHz)



Figure 4: Test figure of spurious emissions, mode A.1, Vertical polarity (30MHz – 1GHz)



Figure 5: Test figure of spurious emissions, mode A.1, Horizontal polarity (1GHz –18GHz)




Figure 6: Test figure of spurious emissions, mode A.1, Vertical polarity (1GHz – 18GHz)




Figure 7: Test figure of spurious emissions, mode A.1, Horizontal polarity (18GHz –25GHz)




Figure 8: Test figure of spurious emissions, mode A.1, Vertical polarity (18GHz – 25GHz)




Figure 9: Test figure of spurious emissions, mode A.2, Horizontal polarity (9kHz – 30MHz)


ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3M Radiated

EUT: Portable Bluetooth Speaker M/N: NS-CSPBTHOL16
 Manufacturer:
 Operating Condition: TX 2441MHz
 Test Site: 2# Chamber
 Operator: LGWADE
 Test Specification: DC 3.7V
 Comment: X
 Start of Test: 2016-6-27 /

SCAN TABLE: "LFRE Fin"

Short Description:				_SUB_STD_VTERM2 1.70			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer	
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M	
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M	



**Figure 10: Test figure of spurious emissions, mode A.2, Vertical polarity
(9kHz – 30MHz)**

ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3M Radiated

EUT: Portable Bluetooth Speaker M/N: NS-CSPBTHOL16
 Manufacturer:
 Operating Condition: TX 2441MHz
 Test Site: 2# Chamber
 Operator: LGWADE
 Test Specification: DC 3.7V
 Comment: Y
 Start of Test: 2016-6-27 /

SCAN TABLE: "LFRE Fin"

Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




Figure 11: Test figure of spurious emissions, mode A.2, Horizontal polarity (30MHz – 1GHz)



Figure 12: Test figure of spurious emissions, mode A.2, Vertical polarity (30MHz – 1GHz)




Figure 13: Test figure of spurious emissions, mode A.2, Horizontal polarity (1GHz – 18GHz)




Figure 14: Test figure of spurious emissions, mode A.2, Vertical polarity (1GHz – 18GHz)




Figure 15: Test figure of spurious emissions, mode A.2, Horizontal polarity (18GHz – 25GHz)




Figure 16: Test figure of spurious emissions, mode A.2, Vertical polarity (18GHz – 25GHz)




Figure 17: Test figure of spurious emissions, mode A.3, Horizontal polarity (9kHz – 30MHz)


ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3M Radiated

EUT: Portable Bluetooth Speaker M/N: NS-CSPBTHOL16
 Manufacturer:
 Operating Condition: TX 2480MHz
 Test Site: 2# Chamber
 Operator: LGWADE
 Test Specification: DC 3.7V
 Comment: X
 Start of Test: 2016-6-27 /

SCAN TABLE: "LFRE Fin"

Short Description:			_SUB_STD_VTERM2 1.70			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M



**Figure 18: Test figure of spurious emissions, mode A.3, Vertical polarity
(9kHz – 30MHz)**

ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3M Radiated

EUT: Portable Bluetooth Speaker M/N: NS-CSPBTHOL16
 Manufacturer:
 Operating Condition: TX 2480MHz
 Test Site: 2# Chamber
 Operator: LGWADE
 Test Specification: DC 3.7V
 Comment: Y
 Start of Test: 2016-6-27 /

SCAN TABLE: "LFRE Fin"

Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




Figure 19: Test figure of spurious emissions, mode A.3, Horizontal polarity (30MHz – 1GHz)



Figure 20: Test figure of spurious emissions, mode A.3, Vertical polarity (30MHz – 1GHz)




Figure 21: Test figure of spurious emissions, mode A.3, Horizontal polarity (1GHz –18GHz)




Figure 22: Test figure of spurious emissions, mode A.3, Vertical polarity (1GHz – 18GHz)




Figure 23: Test figure of spurious emissions, mode A.3, Horizontal polarity (18GHz –25GHz)




Figure 24: Test figure of spurious emissions, mode A.3, Vertical polarity (18GHz – 25GHz)




Figure 25: Test figure of spurious emissions, mode B.1, Horizontal polarity (9kHz – 30MHz)

ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3M Radiated

EUT: Portable Bluetooth Speaker M/N: NS-CSPBTHOL16
 Manufacturer:
 Operating Condition: TX 2402MHz
 Test Site: 2# Chamber
 Operator: LGWADE
 Test Specification: DC 3.7V
 Comment: X
 Start of Test: 2016-6-27 /

SCAN TABLE: "LFRE Fin"

Short Description:				_SUB_STD_VTERM2 1.70			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer	
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M	
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M	




Figure 26: Test figure of spurious emissions, mode B.1, Vertical polarity (9kHz – 30MHz)

ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3M Radiated

EUT: Portable Bluetooth Speaker M/N: NS-CSPBTHOL16
 Manufacturer:
 Operating Condition: TX 2402MHz
 Test Site: 2# Chamber
 Operator: LGWADE
 Test Specification: DC 3.7V
 Comment: Y
 Start of Test: 2016-6-27 /

SCAN TABLE: "LFRE Fin"

Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




Figure 27: Test figure of spurious emissions, mode B.1, Horizontal polarity (30MHz – 1GHz)



Figure 28: Test figure of spurious emissions, mode B.1, Vertical polarity (30MHz – 1GHz)



Figure 29: Test figure of spurious emissions, mode B.1, Horizontal polarity (1GHz –18GHz)



Figure 30: Test figure of spurious emissions, mode B.1, Vertical polarity (1GHz – 18GHz)




Figure 31: Test figure of spurious emissions, mode B.1, Horizontal polarity (18GHz –25GHz)




Figure 32: Test figure of spurious emissions, mode B.1, Vertical polarity (18GHz – 25GHz)




Figure 33: Test figure of spurious emissions, mode B.2, Horizontal polarity (9kHz – 30MHz)

ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3M Radiated

EUT: Portable Bluetooth Speaker M/N: NS-CSPBTHOL16
 Manufacturer:
 Operating Condition: TX 2440MHz
 Test Site: 2# Chamber
 Operator: LGWADE
 Test Specification: DC 3.7V
 Comment: X
 Start of Test: 2016-6-27 /

SCAN TABLE: "LFRE Fin"

Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




Figure 34: Test figure of spurious emissions, mode B.2, Vertical polarity (9kHz – 30MHz)

ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3M Radiated

EUT: Portable Bluetooth Speaker M/N: NS-CSPBTHOL16
 Manufacturer:
 Operating Condition: TX 2440MHz
 Test Site: 2# Chamber
 Operator: LGWADE
 Test Specification: DC 3.7V
 Comment: Y
 Start of Test: 2016-6-27 /

SCAN TABLE: "LFRE Fin"

Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




Figure 35: Test figure of spurious emissions, mode B.2, Horizontal polarity (30MHz – 1GHz)




Figure 36: Test figure of spurious emissions, mode B.2, Vertical polarity (30MHz – 1GHz)




Figure 37: Test figure of spurious emissions, mode B.2, Horizontal polarity (1GHz – 18GHz)



Figure 38: Test figure of spurious emissions, mode B.2, Vertical polarity (1GHz – 18GHz)




Figure 39: Test figure of spurious emissions, mode B.2, Horizontal polarity (18GHz – 25GHz)




Figure 40: Test figure of spurious emissions, mode B.2, Vertical polarity (18GHz – 25GHz)




Figure 41: Test figure of spurious emissions, mode B.3, Horizontal polarity (9kHz – 30MHz)


ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3M Radiated

EUT: Portable Bluetooth Speaker M/N: NS-CSPBTHOL16
 Manufacturer:
 Operating Condition: TX 2480MHz
 Test Site: 2# Chamber
 Operator: LGWADE
 Test Specification: DC 3.7V
 Comment: X
 Start of Test: 2016-6-27 /

SCAN TABLE: "LFRE Fin"

Short Description: _SUB_STD_VTERM2 1.70				Detector	Meas. Time	IF Bandw.	Transducer
Start Frequency	Stop Frequency	Step Width					
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M	
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M	



**Figure 42: Test figure of spurious emissions, mode B.3, Vertical polarity
(9kHz – 30MHz)**

ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3M Radiated

EUT: Portable Bluetooth Speaker M/N: NS-CSPBTHOL16
 Manufacturer:
 Operating Condition: TX 2480MHz
 Test Site: 2# Chamber
 Operator: LGWADE
 Test Specification: DC 3.7V
 Comment: Y
 Start of Test: 2016-6-27 /

SCAN TABLE: "LFRE Fin"

Short Description:			_SUB_STD_VTERM2 1.70			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




Figure 43: Test figure of spurious emissions, mode B.3, Horizontal polarity (30MHz – 1GHz)




Figure 44: Test figure of spurious emissions, mode B.3, Vertical polarity (30MHz – 1GHz)



Figure 45: Test figure of spurious emissions, mode B.3, Horizontal polarity (1GHz –18GHz)




Figure 46: Test figure of spurious emissions, mode B.3, Vertical polarity (1GHz – 18GHz)





Figure 47: Test figure of spurious emissions, mode B.3, Horizontal polarity (18GHz –25GHz)



ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: LGWADE #2416	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 3.7V
Test item: Radiation Test	Date: 16/06/26/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: Portable Bluetooth Speaker	Engineer Signature: LGWADE
Mode: TX 2480MHz	Distance: 3m
Model: NS-CSPBTHOL16	
Manufacturer:	
Note: Bluetooth 4.0	



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26275.468	33.74	16.50	50.24	74.00	-23.76	peak			
2	26275.468	24.35	16.50	40.85	54.00	-13.15	AVG			

Figure 48: Test figure of spurious emissions, mode B.3, Vertical polarity (18GHz – 25GHz)




Figure 49: Test figure of Radiated emissions in restricted bands, Mode A.1, Horizontal




Figure 50: Test figure of Radiated emissions in restricted bands, Mode A.1, Vertical




Figure 51: Test figure of Radiated emissions in restricted bands, Mode A.3, Horizontal




Figure 52: Test figure of Radiated emissions in restricted bands, Mode A.3, Vertical




Figure 53: Test figure of Radiated emissions in restricted bands, Mode B.1, Horizontal




Figure 54: Test figure of Radiated emissions in restricted bands, Mode B.1, Vertical




Figure 55: Test figure of Radiated emissions in restricted bands, Mode B.3, Horizontal




Figure 56: Test figure of Radiated emissions in restricted bands, Mode B.3, Vertical




Figure 57: Test figure of Conducted emissions, Mode C, line live


ACCURATE TECHNOLOGY CO.,LTD

CONDUCTED EMISSION STANDARD FCC PART 15 B

EUT: Portable Bluetooth Speaker M/N:NS-CSPBTHOL16
Manufacturer:
Operating Condition: TX
Test Site: 1#Shielding Room
Operator: LGWADE
Test Specification: L 120V/60Hz
Comment: Mains Port
Start of Test: 6/27/2016 /

SCAN TABLE: "V 9K-30MHz fin"

Short Description: _SUB STD_VTERM2 1.70
Start Stop Step Detector Meas. IF Transducer
Frequency Frequency Width Time Bandw.
9.0 kHz 150.0 kHz 100.0 Hz QuasiPeak 1.0 s 200 Hz NSLK8126 2008
Average
150.0 kHz 30.0 MHz 5.0 kHz QuasiPeak 1.0 s 9 kHz NSLK8126 2008
Average



MEASUREMENT RESULT: "BBY-0627-8_fin"

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.160000	42.90	10.5	66	22.6	QP	L1	GND
0.195000	55.00	10.5	64	8.8	QP	L1	GND
3.470000	38.10	11.1	56	17.9	QP	L1	GND

MEASUREMENT RESULT: "BBY-0627-8_fin2"

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.200000	38.60	10.5	54	15.0	AV	L1	GND
0.270000	32.30	10.6	51	18.8	AV	L1	GND
3.440000	29.90	11.1	46	16.1	AV	L1	GND

Figure 58: Test figure of Conducted emissions, Mode C, line neutral

ACCURATE TECHNOLOGY CO., LTD


CONDUCTED EMISSION STANDARD FCC PART 15 B

EUT: Portable Bluetooth Speaker M/N: NS-CSPBTHOL16
 Manufacturer:
 Operating Condition: TX
 Test Site: 1#Shielding Room
 Operator: LGWADE
 Test Specification: N 120V/60Hz
 Comment: Mains Port
 Start of Test: 6/27/2016 /

SCAN TABLE: "V 9K-30MHz fin"

Short Description: _SUB STD_VTERM2 1.70

Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	NSLK8126 2008
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	NSLK8126 2008
			Average			



MEASUREMENT RESULT: "BBY-0627-7_fin"

6/27/2016

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.150000	47.60	10.5	66	18.4	QP	N	GND
0.190000	54.90	10.5	64	9.1	QP	N	GND
3.410000	39.70	11.1	56	16.3	QP	N	GND

MEASUREMENT RESULT: "BBY-0627-7_fin2"

6/27/2016

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.195000	39.90	10.5	54	13.9	AV	N	GND
0.265000	33.10	10.6	51	18.2	AV	N	GND
3.570000	31.00	11.1	46	15.0	AV	N	GND

Figure 59: Test figure of Conducted emissions, Mode D, line live


ACCURATE TECHNOLOGY CO., LTD

CONDUCTED EMISSION STANDARD FCC PART 15 B

EUT: Portable Bluetooth Speaker M/N: NS-CSPBTHOL16
Manufacturer:
Operating Condition: Charging
Test Site: 1#Shielding Room
Operator: LGWADE
Test Specification: L 120V/60Hz
Comment: Mains Port
Start of Test: 6/27/2016 /

SCAN TABLE: "V 9K-30MHz fin"

Short Description: _SUB STD_VTERM2 1.70
Start Stop Step Detector Meas. IF Transducer
Frequency Frequency Width Time Bandw.
9.0 kHz 150.0 kHz 100.0 Hz QuasiPeak 1.0 s 200 Hz NSLK8126 2008
Average
150.0 kHz 30.0 MHz 5.0 kHz QuasiPeak 1.0 s 9 kHz NSLK8126 2008
Average



MEASUREMENT RESULT: "BBY-0627-5_fin"

6/27/2016

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.150000	49.70	10.5	66	16.3	QP	L1	GND
0.190000	55.50	10.5	64	8.5	QP	L1	GND
3.580000	42.10	11.1	56	13.9	QP	L1	GND

MEASUREMENT RESULT: "BBY-0627-5_fin2"

6/27/2016

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.195000	41.70	10.5	54	12.1	AV	L1	GND
0.260000	33.10	10.6	51	18.3	AV	L1	GND
3.560000	33.40	11.1	46	12.6	AV	L1	GND

Figure 60: Test figure of Conducted emissions, Mode D, line neutral


ACCURATE TECHNOLOGY CO.,LTD

CONDUCTED EMISSION STANDARD FCC PART 15 B

EUT: Portable Bluetooth Speaker M/N:NS-CSPBTHOL16
Manufacturer:
Operating Condition: Charging
Test Site: 1#Shielding Room
Operator: LGWADE
Test Specification: N 120V/60Hz
Comment: Mains Port
Start of Test: 6/27/2016 /

SCAN TABLE: "V 9K-30MHz fin"

Short Description: SUB STD_VTERM2 1.70
Start Stop Step Detector Meas. IF Transducer
Frequency Frequency Width Time Bandw.
9.0 kHz 150.0 kHz 100.0 Hz QuasiPeak 1.0 s 200 Hz NSLK8126 2008
Average
150.0 kHz 30.0 MHz 5.0 kHz QuasiPeak 1.0 s 9 kHz NSLK8126 2008
Average



MEASUREMENT RESULT: "BBY-0627-6_fin"

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.150000	48.60	10.5	66	17.4	QP	N	GND
0.190000	55.40	10.5	64	8.6	QP	N	GND
3.500000	41.40	11.1	56	14.6	QP	N	GND

MEASUREMENT RESULT: "BBY-0627-6_fin2"

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.200000	41.00	10.5	54	12.6	AV	N	GND
0.275000	32.80	10.6	51	18.2	AV	N	GND
3.580000	32.70	11.1	46	13.3	AV	N	GND

Figure 61: Test figure of Radiated emissions, Mode D, Below 1GHz, Horizontal




Figure 62: Test figure of Radiated emissions, Mode D, Below 1GHz, Vertical




Figure 63: Test figure of Radiated emissions, Mode D, Above 1GHz, Horizontal




Figure 64: Test figure of Radiated emissions, Mode D, Above 1GHz, Vertical




Figure 65: Test figure of Radiated emissions, Mode E, Below 1GHz, Horizontal




Figure 66: Test figure of Radiated emissions, Mode E, Below 1GHz, Vertical




Figure 67: Test figure of Radiated emissions, Mode E, Above 1GHz, Horizontal




Figure 68: Test figure of Radiated emissions, Mode E, Above 1GHz, Vertical

