


FCC PART 15.247  
TEST REPORT

For

**Compupal Group Corporation**

No.1555 Jiashan Avenue, Jiashan, Zhejiang, China

**FCC ID: Z5YHS-BT06**

<b>Report Type:</b> Original Report	<b>Product Type:</b> Bluetooth 4.0 Headphone
<b>Test Engineer:</b> Matt Yao	<i>Matt Yao</i>
<b>Report Number:</b> RKS150806001-00A	
<b>Report Date:</b> 2015-08-06	
<b>Reviewed By:</b> EMC Manager	Jesse Huang <i>Jesse Huang</i>
<b>Prepared By:</b> Bay Area Compliance Laboratories Corp. (Kunshan) Chenghu Road, Kunshan Development Zone No.248, Kunshan, Jiangsu, China Tel: +86-0512-86175000 Fax: +86-0512-88934268 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>	

**Note:** This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

## TABLE OF CONTENTS

<b>GENERAL INFORMATION</b> .....	<b>4</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE.....	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY.....	4
TEST FACILITY.....	5
<b>SYSTEM TEST CONFIGURATION</b> .....	<b>6</b>
DESCRIPTION OF TEST CONFIGURATION.....	6
EUT EXERCISE SOFTWARE.....	6
SPECIAL ACCESSORIES.....	6
EQUIPMENT MODIFICATIONS.....	6
SUPPORT EQUIPMENT LIST AND DETAILS.....	6
EXTERNAL I/O CABLE.....	6
BLOCK DIAGRAM OF TEST SETUP.....	7
<b>SUMMARY OF TEST RESULTS</b> .....	<b>8</b>
<b>FCC§15.247 (i), §1.1310&amp; §2.1091 –MAXIMUM PERMISSIBLE</b> .....	<b>9</b>
<b>EXPOSURE (MPE)</b> .....	<b>9</b>
APPLICABLE STANDARD.....	9
<b>FCC §15.203 – ANTENNA REQUIREMENT</b> .....	<b>10</b>
APPLICABLE STANDARD.....	10
ANTENNA CONNECTOR CONSTRUCTION.....	10
<b>FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS</b> .....	<b>11</b>
APPLICABLE STANDARD.....	11
MEASUREMENT UNCERTAINTY.....	11
EUT SETUP.....	11
EMI TEST RECEIVER SETUP.....	12
TEST PROCEDURE.....	12
TEST EQUIPMENT LIST AND DETAILS.....	12
CORRECTED FACTOR & MARGIN CALCULATION.....	12
TEST RESULTS SUMMARY.....	13
TEST DATA.....	13
<b>FCC §15.205, §15.209 &amp; §15.247(d) – RADIATED EMISSIONS</b> .....	<b>16</b>
APPLICABLE STANDARD.....	16
MEASUREMENT UNCERTAINTY.....	16
EUT SETUP.....	16
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP.....	17
TEST PROCEDURE.....	17
CORRECTED AMPLITUDE & MARGIN CALCULATION.....	18
TEST EQUIPMENT LIST AND DETAILS.....	18
TEST RESULTS SUMMARY.....	18
TEST DATA.....	19
<b>FCC §15.247(a) (1)-CHANNEL SEPARATION TEST</b> .....	<b>24</b>
APPLICABLE STANDARD.....	24
TEST PROCEDURE.....	24

TEST EQUIPMENT LIST AND DETAILS.....	24
TEST DATA .....	24
<b>FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH.....</b>	<b>31</b>
APPLICABLE STANDARD .....	31
TEST PROCEDURE .....	31
TEST EQUIPMENT LIST AND DETAILS.....	31
TEST DATA .....	31
<b>FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST .....</b>	<b>37</b>
APPLICABLE STANDARD .....	37
TEST PROCEDURE .....	37
TEST EQUIPMENT LIST AND DETAILS.....	37
TEST DATA .....	37
<b>FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME).....</b>	<b>40</b>
APPLICABLE STANDARD .....	40
TEST PROCEDURE .....	40
TEST EQUIPMENT LIST AND DETAILS.....	40
TEST DATA .....	40
<b>FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT .....</b>	<b>56</b>
APPLICABLE STANDARD .....	56
TEST PROCEDURE .....	56
TEST EQUIPMENT LIST AND DETAILS.....	56
TEST DATA .....	56
<b>FCC §15.247(d) - BAND EDGES TESTING .....</b>	<b>62</b>
APPLICABLE STANDARD .....	62
TEST PROCEDURE .....	62
TEST EQUIPMENT LIST AND DETAILS.....	62
TEST DATA .....	62

---

## GENERAL INFORMATION

---

### Product Description for Equipment under Test (EUT)

The Compupal Group Corporation's product, model number: 8037606 (FCC ID: Z5YHS-BT06) or the "EUT" in this report was a Bluetooth 4.0 Headphone, which was measured approximately: 180 mm(L)\* 165 mm(W)\* 72 mm(H), rated with input voltage: DC 4.2 V.

*Note: The series product, model: HS-BT06. They have the same hardware, PCB layout, antenna and component, the different is the profile software, and the profile software does not affect the RF power and parameter..*

*\*All measurement and test data in this report was gathered from production sample serial number: 150714 (Assigned by BACL, Kunshan). The EUT supplied by the applicant was received on 2015-07-14.*

### Objective

This test report is prepared on behalf of Compupal Group Corporation in accordance with Part 2-Subpart J, Part 15-Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

### Related Submittal(s)/Grant(s)

N/A

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement uncertainty with radiated emission is 5.91 dB for 30MHz-1GHz, and 4.92 dB for above 1GHz, 1.95dB for conducted measurement.

## **Test Facility**

The Test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the Chenghu Road, Kunshan Development Zone No.248, Kunshan, Jiangsu, China.

Test site at Bay Area Compliance Laboratories Corp. (Kunshan) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2014. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 815570. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

The system was configured for testing in an engineering mode which was controlled by the equipment Bluetooth tester.

### EUT Exercise Software

N/A

### Special Accessories

No special accessory.

### Equipment Modifications

No modification was made to the EUT tested.


### Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
N/A			

### External I/O Cable

Cable Description	Length (m)	From Port	To
Un-shielding Detachable USB Cable	0.9	EUT	PC

### Block Diagram of Test Setup



**SUMMARY OF TEST RESULTS**

<b>FCC Rules</b>	<b>Description of Test</b>	<b>Result</b>
§15.247 (i), §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209 & §15.247(d)	Radiated Emissions	Compliance
§15.247(a)(1)	20 dB Emission Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band edges	Compliance



**FCC§15.247 (i), §1.1310& §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE)**

**Applicable Standard**

According to subpart 15.247(i)and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
<b>Frequency Range (MHz)</b>	<b>Electric Field Strength (V/m)</b>	<b>Magnetic Field Strength (A/m)</b>	<b>Power Density (mW/cm<sup>2</sup>)</b>	<b>Averaging Time (minutes)</b>
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/		f/1500	30
1500-100,000	/		1.0	30

f = frequency in MHz; \* = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

**Calculated Formulary:**

Predication of MPE limit at a given distance

$S = PG/4 \pi R^2$  = power density (in appropriate units, e.g. mW/cm<sup>2</sup>);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

**Calculated Data:**

<b>Mode</b>	<b>Frequency (MHz)</b>	<b>Antenna Gain</b>		<b>Conducted Power</b>		<b>Evaluation Distance (cm)</b>	<b>Power Density (mW/cm<sup>2</sup>)</b>	<b>MPE Limit (mW/cm<sup>2</sup>)</b>
		<b>(dBi)</b>	<b>(numeric)</b>	<b>(dBm)</b>	<b>(mW)</b>			
<b>GFSK</b>	2480	2	1.585	5.34	3.42	20	0.0011	1.0
<b>π/4-DQPSK</b>	2441	2	1.585	4.17	2.61	20	0.0008	1.0
<b>8DPSK</b>	2441	2	1.585	4.42	2.77	20	0.0009	1.0

**Result:** The device meet FCC MPE at 20 cm distance

---

## **FCC §15.203 – ANTENNA REQUIREMENT**

---

### **Applicable Standard**

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

### **Antenna Connector Construction**

The EUT has one integral antenna arrangement for bluetooth, which was permanently attached and the antenna gain is 2 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

**Result:** Compliance.

## FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

### Applicable Standard

FCC §15.207(a)


### Measurement Uncertainty

Input quantities to be considered for conducted disturbance measurements maybe receiver reading, attenuation of the connection between LISN and receiver, LISN voltage division factor, LISN VDF frequency interpolation and receiver related input quantities, etc.

Based on CISPR 16-4-2:2011, the expanded combined standard uncertainty of conducted disturbance test at Bay Area Compliance Laboratories Corp. (Shenzhen) is shown as below. And the uncertainty will not be taken into consideration for the test data recorded in the report.

Port	Expanded Measurement uncertainty
AC Mains	3.26 dB (k=2, 95% level of confidence)
CAT 3	3.70 dB (k=2, 95% level of confidence)
CAT 5	3.86 dB (k=2, 95% level of confidence)
CAT 6	4.64 dB (k=2, 95% level of confidence)

### EUT Setup



- Note: 1. Support units were connected to second LISN.  
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.4-2009. The related limit was specified in FCC Part 15.207.

The adapter was connected to a 120 VAC/60 Hz power source.

### EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

### Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS30	831294/005	2014-09-16	2015-09-16
Rohde & Schwarz	LISN	ESH3-Z5	12005	2014-09-16	2015-09-16
Rohde & Schwarz	LISN	ESH3-Z5	12008	2014-09-16	2015-09-16
Rohde & Schwarz	CE Test software	EMC 32	V 09.10.0	--	--

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

### Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Correction Factor} = \text{LISN VDF} + \text{Cable Loss} + \text{Transient Limiter Attenuation}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

## Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, the worst margin reading as below:

**11.01 dB at 0.186 M in the Neutral** conducted mode

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(L_m)} \leq L_{lim} + U_{cispr}$$

In BACL,  $U_{(L_m)}$  is less than  $U_{cispr}$ , if  $L_m$  is less than  $L_{lim}$ , it implies that the EUT complies with the limit.

## Test Data


### Environmental Conditions

<b>Temperature:</b>	27 °C
<b>Relative Humidity:</b>	56 %
<b>ATM Pressure:</b>	101.0 kPa

*The testing was performed by Matt Yao on 2015-07-31.*

*EUT operation mode: Charging & Transmitting*


AC 120V/60 Hz, Line



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.390000	34.81	9.000	L1	11.0	23.25	58.06	Compliance
1.046000	33.40	9.000	L1	11.1	22.60	56.00	Compliance
2.030000	35.73	9.000	L1	11.2	20.27	56.00	Compliance
4.846000	39.77	9.000	L1	11.3	16.23	56.00	Compliance
7.338000	28.13	9.000	L1	11.4	27.87	56.00	Compliance
15.998000	35.12	9.000	L1	11.3	20.88	56.00	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.390000	20.33	9.000	L1	11.0	27.73	48.06	Compliance
1.046000	22.65	9.000	L1	11.1	23.35	46.00	Compliance
2.030000	28.15	9.000	L1	11.2	17.85	46.00	Compliance
4.846000	31.19	9.000	L1	11.3	14.81	46.00	Compliance
7.338000	23.46	9.000	L1	11.4	22.54	46.00	Compliance
15.998000	32.81	9.000	L1	11.3	13.19	46.00	Compliance

**AC 120V/60 Hz, Neutral**



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.186000	53.2	9.000	N	0.6	11.01	64.21	Compliance
0.258000	42.76	9.000	N	0.6	18.74	61.50	Compliance
0.362000	33.86	9.000	N	0.7	24.82	58.68	Compliance
1.890000	33.52	9.000	N	0.7	22.48	56.00	Compliance
4.970000	39.42	9.000	N	0.8	16.58	56.00	Compliance
26.790000	20.79	9.000	N	0.6	39.21	60.00	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.186000	41.16	9.000	N	0.6	13.05	54.21	Compliance
0.258000	28.10	9.000	N	0.6	23.40	51.50	Compliance
0.362000	18.40	9.000	N	0.7	30.28	48.68	Compliance
1.890000	21.94	9.000	N	0.9	24.06	46.00	Compliance
4.970000	33.44	9.000	N	0.8	12.56	46.00	Compliance
26.790000	22.91	9.000	N	0.8	27.09	50.00	Compliance

**FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS**

**Applicable Standard**

FCC §15.205; §15.209; §15.247(d)


**Measurement Uncertainty**

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on CISPR 16-4-2:2011, the expanded combined standard uncertainty of radiation emissions at Bay Area Compliance Laboratories Corp. (Shenzhen) is 5.91 dB for 30MHz-1GHz, and 4.92 dB for above 1GHz. And this uncertainty will not be taken into consideration for the test data recorded in the report.


**EUT Setup**

**Below 1 GHz:**





**Above 1GHz:**



The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC 15.209 and FCC 15.247 limits.

The adapter was connected to a 120 VAC/60 Hz power source.

**EMI Test Receiver & Spectrum Analyzer Setup**

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1 MHz	3 MHz	/	PK
	1 MHz	10 Hz	/	Ave.

**Test Procedure**

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

## Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

## Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sonoma Instrument	Amplifier	330	171377	2014-09-16	2015-09-16
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2014-09-16	2015-09-16
Sunol Sciences	Broadband Antenna	JB3	A090314-1	2014-09-12	2015-09-12
ETS	Horn Antenna	3115	6229	2014-09-12	2015-09-12
Rohde & Schwarz	Signal Analyzer	FSIQ26	100048	2014-09-16	2015-09-16
Mini	Pre-amplifier	ZVA-183-S+	857001418	2014-09-16	2015-09-16
champrotek	Chamber	Chamber A	1#	2014-09-17	2015-09-17
R&S	Auto test Software	EMC32	V 09.10.0	-	-

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

## Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

**2.84 dB at 7323 MHz** in the **Horizontal** polarization for Middle channel

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(L_m)} \leq L_{lim} + U_{cispr}$$

In BACL,  $U_{(L_m)}$  is less than  $+ U_{cispr}$ , if  $L_m$  is less than  $L_{lim}$ , it implies that the EUT complies with the limit.

**Test Data**


**Environmental Conditions**

<b>Temperature:</b>	27 °C
<b>Relative Humidity:</b>	56 %
<b>ATM Pressure:</b>	101.0 kPa

The testing was performed by Matt Yao on 2015-07-31.

EUT operation mode: Normal operation

**30MHz-1GHz:**



Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBµV/m)	FCC Part 15.247/205/209	
	Reading (dBµV)	Detector (PK/QP/Ave.)		Height (cm)	Polar (H/V)			Limit (dB µ V/m)	Margin (dB)
40.088250	21.43	QP	342.0	100.0	V	-10.3	11.13	40.00	28.87
43.540100	25.6	QP	166.0	100.0	V	-12.5	13.10	40.00	26.90
49.858300	28.03	QP	318.0	100.0	V	-16.4	11.63	40.00	28.37
72.755600	26.24	QP	251.0	200.0	V	-17.1	9.14	40.00	30.86
184.013400	36.14	QP	0.0	200.0	H	-11.8	24.34	43.50	19.16
319.997300	32.35	QP	292.0	100.0	H	-9.8	22.55	46.00	23.45

**30 MHz -25 GHz:** (Scan with GFSK,  $\pi/4$ -DQPSK, 8-DPSK mode, the worst case is BDR Mode (GFSK))

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dB $\mu$ V/m)	FCC Part 15.247/205/209	
	Reading (dB $\mu$ V)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dB $\mu$ V/m)	Margin (dB)
Low Channel (2402 MHz)									
2402.00	87.49	PK	54	1.9	H	3.0	90.49	/	/
2402.00	77.34	Ave.	54	1.9	H	3.0	80.34	/	/
2402.00	86.51	PK	43	2.0	V	3.0	89.51	/	/
2402.00	77.52	Ave.	43	2.0	V	3.0	80.52	/	/
2312.89	36.69	PK	148	1.3	H	2.9	39.59	74	34.41
2312.89	23.52	Ave.	148	1.3	H	2.9	26.42	54	27.58
2495.40	37.96	PK	232	1.0	H	4.2	42.16	74	31.84
2495.40	23.53	Ave.	232	1.0	H	4.2	27.73	54	26.27
2489.36	35.79	PK	320	2.1	H	4.2	39.99	74	34.01
2489.36	25.17	Ave.	320	2.1	H	4.2	29.37	54	24.63
4804.00	53.49	PK	282	1.6	H	11.66	65.15	74	8.85
4804.00	37.3	Ave.	282	1.6	H	11.66	48.96	54	5.04
7206.00	53.71	PK	342	1.4	H	17.20	70.91	74	3.09
7206.00	32.34	Ave.	342	1.4	H	17.20	49.54	54	4.46
9608.00	30.94	PK	299	1.7	H	19.12	50.06	74	23.94
9608.00	14.72	Ave.	299	1.7	H	19.12	33.84	54	20.16

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBµV/m)	FCC Part 15.247/205/209	
	Reading (dBµV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBµV/m)	Margin (dB)
Middle Channel (2441 MHz)									
2441.00	93.79	PK	38	2.1	H	2.6	96.79	/	/
2441.00	82.67	Ave.	38	2.1	H	2.6	85.67	/	/
2441.00	92.28	PK	54	2.2	V	2.6	95.28	/	/
2441.00	81.17	Ave.	54	2.2	V	2.6	84.17	/	/
2334.53	37.74	PK	131	1.6	H	3.0	40.64	74	33.36
2334.53	23.52	Ave.	131	1.6	H	3.0	26.42	54	27.58
2490.64	37.63	PK	172	1.0	H	4.2	41.83	74	32.17
2490.64	23.53	Ave.	172	1.0	H	4.2	27.73	54	26.27
2485.70	36.26	PK	249	2.5	H	4.2	40.46	74	33.54
2485.70	25.92	Ave.	249	2.5	H	4.2	30.12	54	23.88
4882.00	47.59	PK	329	1.6	H	11.6	59.25	74	14.75
4882.00	37.00	Ave.	329	1.6	H	11.6	48.66	54	5.34
7323.00	45.45	PK	231	2.1	H	17.5	62.65	74	11.35
7323.00	33.96	Ave.	231	2.1	H	17.5	51.16	54	2.84
9764.00	34.09	PK	146	1.8	H	19.3	53.39	74	20.61
9764.00	16.32	Ave.	146	1.8	H	19.3	35.62	54	18.38
High Channel (2480 MHz)									
74.69	53.25	QP	187	1.2	V	-19.3	33.95	40	6.05
2480.00	93.46	PK	191	1.1	H	3.2	96.46	/	/
2480.00	82.33	Ave.	191	1.1	H	3.2	85.33	/	/
2480.00	91.37	PK	306	2.5	V	3.2	94.37	/	/
2480.00	79.24	Ave.	306	2.5	V	3.2	82.24	/	/
2314.80	37.09	PK	71	2.2	H	2.9	39.99	74	34.01
2314.80	23.52	Ave.	71	2.2	H	2.9	26.42	54	27.58
2483.50	49.85	PK	247	1.5	H	3.2	54.05	74	19.95
2483.50	31.6	Ave.	247	1.5	H	3.2	35.80	54	18.2
2496.32	45.47	PK	47	1.2	H	3.3	49.67	74	24.33
2496.32	28.18	Ave.	47	1.2	H	3.3	32.38	54	21.62
4960.00	52.85	PK	65	2.2	H	11.9	64.51	74	9.49
4960.00	36.18	Ave.	65	2.2	H	11.9	47.84	54	6.16
7440.00	49.08	PK	242	1.0	H	17.7	66.28	74	7.72
7440.00	32.86	Ave.	242	1.0	H	17.7	50.06	54	3.94
9920.00	34.29	PK	229	1.7	H	19.42	53.41	74	20.59
9920.00	15.11	Ave.	229	1.7	H	19.42	34.23	54	19.77

Note:

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor


Corrected Amplitude = Corrected Factor + Reading

Margin = Limit - Corrected. Amplitude


### Conducted Spurious Emissions at Antenna Port

#### BDR Mode (GFSK)


#### Low Channel



### Middle Channel



### High Channel



Note: TDF = Cable loss (1dB) + attenuation (10dB) = 11dB

## FCC §15.247(a) (1)-CHANNEL SEPARATION TEST

### Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

### Test Procedure

1. Set the EUT in transmitting mode, maxhold the channel.
2. Set the adjacent channel of the EUT and maxhold another trace.
3. Measure the channel separation.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	100048	2014-09-16	2015-09-16

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions

Temperature:	26 °C
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa

*The testing was performed by Matt Yao on 2015-07-31.*

*EUT operation mode: Transmitting*


*Test Result: Compliance. Please refer to following tables and plots*




Mode	Channel	Frequency (MHz)	Channel Separation (MHz)	≥Limit (MHz)	Result
<b>BDR (GFSK)</b>	Low	2402	1.002	0.617	Pass
	Adjacent	2403			
	Middle	2441	1.002	0.599	Pass
	Adjacent	2442			
	High	2480	1.002	0.596	Pass
	Adjacent	2479			
<b>EDR (π/4-DQPSK)</b>	Low	2402	1.002	0.801	Pass
	Adjacent	2403			
	Middle	2441	1.002	0.804	Pass
	Adjacent	2442			
	High	2480	1.002	0.812	Pass
	Adjacent	2479			
<b>EDR (8DPSK)</b>	Low	2402	1.002	0.809	Pass
	Adjacent	2403			
	Middle	2441	1.002	0.807	Pass
	Adjacent	2442			
	High	2480	1.002	0.807	Pass
	Adjacent	2479			

Note: Limit = 20 dB bandwidth \*2/3


**BDR (GFSK): Low Channel**




**BDR (GFSK): Middle Channel**




**BDR (GFSK): High Channel**




**EDR ( $\pi/4$ -DQPSK): Low Channel**




**EDR ( $\pi/4$ -DQPSK): Middle Channel**




**EDR ( $\pi/4$ -DQPSK): High Channel**




### EDR (8DPSK): Low Channel



### EDR (8DPSK): Middle Channel



**EDR (8DPSK): High Channel**



*Note: TDF=Cable loss (1dB) +attenuation (10dB) =11dB*

## FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH

### Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

### Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	100048	2014-09-16	2015-09-16

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions

Temperature:	26 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa


*The testing was performed by Matt Yao on 2017-07-31.*

*EUT operation mode: Transmitting*

*Test Result: Compliance. Please refer to following tables and plots*


Mode	Channel	Frequency (MHz)	20 dB Emission Bandwidth (MHz)
<b>BDR (GFSK)</b>	Low	2402	0.926
	Middle	2441	0.898
	High	2480	0.894
<b>EDR (<math>\pi/4</math>-DQPSK)</b>	Low	2402	1.202
	Middle	2441	1.206
	High	2480	1.218
<b>EDR (8DPSK)</b>	Low	2402	1.214
	Middle	2441	1.210
	High	2480	1.210

**BDR (GFSK): Low Channel**







**BDR (GFSK): Middle Channel**




**BDR (GFSK): High Channel**




**EDR ( $\pi/4$ -DQPSK): Low Channel**




**EDR ( $\pi/4$ -DQPSK): Middle Channel**




**EDR ( $\pi/4$ -DQPSK): High Channel**




**EDR (8DPSK): Low Channel**



**EDR (8DPSK): Middle Channel**



**EDR (8DPSK): High Channel**



Note: TDF=Cable loss (1dB) +attenuation (10dB) =11dB

## **FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST**

### **Applicable Standard**

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

### **Test Procedure**

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the max-hold function record the quantity of the channel.

### **Test Equipment List and Details**

<b>Manufacturer</b>	<b>Description</b>	<b>Model</b>	<b>Serial Number</b>	<b>Calibration Date</b>	<b>Calibration Due Date</b>
Rohde & Schwarz	Signal Analyzer	FSIQ26	100048	2014-09-16	2015-09-16

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

### **Test Data**

#### **Environmental Conditions**

<b>Temperature:</b>	26 °C
<b>Relative Humidity:</b>	55 %
<b>ATM Pressure:</b>	101.0 kPa


*The testing was performed by Matt Yao on 2015-07-30.*

*EUT operation mode: Transmitting*


*Test Result: Compliance. Please refer to following tables and plots*

Mode	Frequency Range (MHz)	Number of Hopping Channel (CH)	Limit (CH)
BDR (GFSK)	2400-2483.5	79	≥15
EDR (π/4-DQPSK)	2400-2483.5	79	≥15
EDR (8DPSK)	2400-2483.5	79	≥15


**BDR (GFSK): Number of Hopping Channels**



**EDR ( $\pi/4$ -DQPSK): Number of Hopping Channels**



**EDR (8DPSK): Number of Hopping Channels**



Note: TDF=Cable loss (1dB) +attenuation (10dB) =11dB

## **FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)**

### **Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

### **Test Procedure**

The EUT was worked in channel hopping; Spectrum SPAN was set as 0. Sweep was set as 0.4 X channel no. (s), the quantity of pulse was get from single sweep. In addition, the time of single pulses was tested.

### **Test Equipment List and Details**

<b>Manufacturer</b>	<b>Description</b>	<b>Model</b>	<b>Serial Number</b>	<b>Calibration Date</b>	<b>Calibration Due Date</b>
Rohde & Schwarz	Signal Analyzer	FSIQ26	100048	2014.09.16	2015-09-16

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

### **Test Data**

#### **Environmental Conditions**

<b>Temperature:</b>	26 °C
<b>Relative Humidity:</b>	55 %
<b>ATM Pressure:</b>	101.0 kPa

*The testing was performed by Matt Yao on 2015-07-30.*


*EUT operation mode: Transmitting*

*Test Result: Compliance. Please refer to following tables and plots*




Mode		Channel	Pulse Width (ms)	Dwell Time (S)	Limit (S)	Result	
BDR (GFSK)	DH 1	Low	0.411	0.132	0.4	Pass	
		Middle	0.431	0.141	0.4	Pass	
		High	0.431	0.141	0.4	Pass	
	Note: DH1:Dwell time = Pulse time*(1600/2/79)*31.6S						
	DH 3	Low	1.673	0.269	0.4	Pass	
		Middle	1.684	0.269	0.4	Pass	
		High	1.684	0.269	0.4	Pass	
	Note: DH3:Dwell time = Pulse time*(1600/4/79)*31.6S						
	DH 5	Low	2.926	0.312	0.4	Pass	
		Middle	2.936	0.313	0.4	Pass	
		High	2.936	0.313	0.4	Pass	
	Note: DH5:Dwell time = Pulse time*(1600/6/79)*31.6S						
	EDR (π/4-DQPSK)	DH 1	Low	0.431	0.141	0.4	Pass
Middle			0.445	0.142	0.4	Pass	
High			0.445	0.142	0.4	Pass	
Note: DH1:Dwell time = Pulse time*(1600/2/79)*31.6S							
DH 3		Low	1.683	0.269	0.4	Pass	
		Middle	1.688	0.270	0.4	Pass	
		High	1.698	0.272	0.4	Pass	
Note: DH3:Dwell time = Pulse time*(1600/4/79)*31.6S							
DH 5		Low	2.936	0.313	0.4	Pass	
		Middle	2.950	0.315	0.4	Pass	
		High	2.940	0.314	0.4	Pass	
Note: DH5:Dwell time = Pulse time*(1600/6/79)*31.6S							
EDR (8DPSK)		DH 1	Low	0.421	0.134	0.4	Pass
	Middle		0.445	0.142	0.4	Pass	
	High		0.435	0.139	0.4	Pass	
	Note: DH1:Dwell time = Pulse time*(1600/2/79)*31.6S						
	DH 3	Low	1.673	0.268	0.4	Pass	
		Middle	1.698	0.272	0.4	Pass	
		High	1.688	0.270	0.4	Pass	
	Note: DH3:Dwell time = Pulse time*(1600/4/79)*31.6S						
	DH 5	Low	2.936	0.313	0.4	Pass	
		Middle	2.950	0.315	0.4	Pass	
		High	2.950	0.315	0.4	Pass	
	Note: DH5:Dwell time = Pulse time*(1600/6/79)*31.6S						


### BDR (GFSK): Pulse time, Low Channel, DH1




### Pulse time, Middle Channel, DH1




### Pulse time, High Channel, DH1



### Pulse time, Low Channel, DH3




**Pulse time, Middle Channel, DH3**




Date: 30.JUL.2015 18:07:20

**Pulse time, High Channel, DH3**




Date: 30.JUL.2015 18:07:53

**Pulse time, Low Channel, DH5**




Date: 30.JUL.2015 17:10:20

**Pulse time, Middle Channel, DH5**




Date: 30.JUL.2015 18:09:05


**Pulse time, High Channel, DH5**




**EDR ( $\pi/4$ -DQPSK):  
Pulse time, Low Channel, DH1**




**Pulse time, Middle Channel, DH1**



**Pulse time, High Channel, DH1**




### Pulse time, Low Channel, DH3



Date: 30.JUL.2015 17:11:56


### Pulse time, Middle Channel, DH3



Date: 30.JUL.2015 18:12:30




**Pulse time, High Channel, DH3**




Date: 30.JUL.2015 18:12:02

**Pulse time, Low Channel, DH5**




Date: 30.JUL.2015 17:12:33


**Pulse time, Middle Channel, DH5**




Pulse time, High Channel, DH5




**EDR (8DPSK):  
Pulse time, Low Channel, DH1**



**Pulse time, Middle Channel, DH1**




**Pulse time, High Channel, DH1**




Date: 30.JUL.2015 18:14:37

**Pulse time, Low Channel, DH3**




Date: 30.JUL.2015 17:14:05

### Pulse time, Middle Channel, DH3




Date: 30.JUL.2015 18:15:42

### Pulse time, High Channel, DH3




Date: 30.JUL.2015 18:16:05


**Pulse time, Low Channel, DH5**



**Pulse time, Middle Channel, DH5**



**Pulse time, High Channel, DH5**



Date: 30.JUL.2015 18:17:00

Note: TDF = Cable loss (1dB) + attenuation (10dB) = 11dB

## FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

### Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

### Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	100048	2014.09.16	2015-09-16

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions

<b>Temperature:</b>	26 °C
<b>Relative Humidity:</b>	55 %
<b>ATM Pressure:</b>	101.0 kPa

*The testing was performed by Matt Yao on 2015-07-30.*


*EUT operation mode: Transmitting*

*Test Result: Compliance. Please refer to following tables and plots*




Mode	Channel	Frequency (MHz)	Peak Output Power		Limit (mW)
			(dBm)	(mW)	
<b>BDR (GFSK)</b>	Low	2402	1.86	1.53	1000
	Middle	2441	4.96	3.13	1000
	High	2480	5.34	3.42	1000
<b>EDR (<math>\pi/4</math>-DQPSK)</b>	Low	2402	0.61	1.15	1000
	Middle	2441	4.17	2.61	1000
	High	2480	3.89	2.45	1000
<b>EDR (8DPSK)</b>	Low	2402	0.94	1.24	1000
	Middle	2441	4.42	2.77	1000
	High	2480	4.19	2.62	1000


**BDR (GFSK): Low Channel**




**BDR (GFSK): Middle Channel**




**BDR (GFSK): High Channel**




**EDR( $\pi/4$ -DQPSK): Low Channel**




**EDR( $\pi/4$ -DQPSK): Middle Channel**




**EDR( $\pi/4$ -DQPSK): High Channel**




**EDR(8DPSK): Low Channel**



**EDR(8DPSK): Middle Channel**



**EDR(8DPSK): High Channel**



Note: TDF = Cable loss (1dB) + attenuation (10dB) = 11dB

## FCC §15.247(d) - BAND EDGES TESTING

### Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	100048	2014.09.16	2015-09-16

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions


Temperature:	26 °C
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa

*The testing was performed by Matt Yao on 2015-07-30*


*EUT operation mode: Transmitting*

Test Result: Compliance. Please refer to following plots.


**BDR (GFSK): Band Edge-Left Side**




**BDR (GFSK): Band Edge-Right Side**



**EDR ( $\pi/4$ -DQPSK): Band Edge-Left Side**




**EDR ( $\pi/4$ -DQPSK): Band Edge-Right Side**






**EDR (8DPSK): Band Edge-Left Side**



Date: 31.JUL.2015 12:51:02

**BDR (8DPSK): Band Edge-Right Side**



Date: 31.JUL.2015 12:45:55

Note: TDF=Cable loss (1dB) +attenuation (10dB) =11dB

\*\*\*\*\* **END OF REPORT** \*\*\*\*\*