

TEST REPORT

Report No.: SHATBL2406009W02

Applicant : Shenzhen Aoni Electronic Co., Ltd

Product Name : Indoor Wi-Fi IP Plug In 1080p Deterrence Camera with 2-Way Audio-White

Brand Name : Night Owl

Model Name : WCM-FWIP2-I-V2

FCC ID : Z63-FWIP2-I-V2

Test Standard : FCC CFR Title 47 Part 15 Subpart C Section 15.247

Date of Test : 2024.06.17~2024.09.03

Report Prepared by :

Chris Xu

(Chris Xu)

Report Approved by :

Ghost Li.

(Ghost Li)

Authorized Signatory :

Terry Yang

(Terry Yang)



TABLE OF CONTENTS

REVISION HISTORY	3
DECLARATION OF REPORT	4
1. GENERAL DESCRIPTION	5
1.1. Applicant	5
1.2. Manufacturer	5
1.3. Factory	5
1.4. General Information of EUT	6
1.5. Laboratory Information	6
2. FCC 47CFR §2.1091 Requirement	7
2.1. Test Standards	7
2.2. Limit	7
2.3. MPE Calculation Method	8
2.4. Antenna Information	8
2.5. Manufacturing Tolerance	8
2.6. Test Result	10

REVISION HISTORY

Rev.	Issue Date	Revisions	Revised by
A0	2024.09.03	Initial Release	N/A

DECLARATION OF REPORT

1. The device has been tested by ATBL, and the test results show that the equipment under test (EUT) is in compliance with the requirements of 47 CFR Part 2.1091. And it is applicable only to the tested sample identified in the report.
2. This report shall not be reproduced except in full, without the written approval of ATBL, this document only be altered or revised by ATBL, personal only, and shall be noted in the revision of the document.
3. The general information of EUT in this report is provided by the customer or manufacture, ATBL is only responsible for the test data but not for the information provided by the customer or manufacture.
4. The results in this report is only apply to the sample as tested under conditions. The customer or manufacturer is responsible for ensuring that the additional production units of this model have the same electrical and mechanical components.
5. In this report, '☐' indicates that EUT does not support content after '☐', and '☑' indicates that it supports content after '☑'.

1. GENERAL DESCRIPTION

1.1. Applicant

Name : Shenzhen Aoni Electronic Co., Ltd
Address : No.5,Bldg.,Honghui Industrial Park,2nd Liuxian Road,Xin'An streets, Bao'an District, ShenZhen, China

1.2. Manufacturer

Name : Aoni Intelligent Technology (Zhongshan) Co., LTD
Address : Floor 4,5,6,7,8,9, Building 2, NO. 138, Lefeng South Road, Lianfeng, Xiaolan Town, Zhongshan City, Guangdong Province

1.3. Factory

Name : Aoni Intelligent Technology (Zhongshan) Co., LTD
Address : Floor 4,5,6,7,8,9, Building 2, NO. 138, Lefeng South Road, Lianfeng, Xiaolan Town, Zhongshan City, Guangdong Province

1.4. General Information of EUT

General Information	
Equipment Name	Indoor Wi-Fi IP Plug In 1080p Deterrence Camera with 2-Way Audio-White
Brand Name	Night Owl
Model Name	WCM-FWIP2-I-V2
Series Model	CAM-FWIP2-IN;CAM-2PK-FWIP2-IN;1PK-WCM-FWIP2-I-WA;2PK-WCM-FWIP2-I-WA;WCM-FWIP2-I-WA;WCM-FWIP2-I-CN13
Model Difference	All models are identical except model name.
Operation Frequency	2400MHz - 2483.5MHz
Modulation Type	802.11b: DSSS (DBPSK/DQPSK/CCK) 802.11g/n/ax(HT): OFDM 802.11ax:OFDMA
Antenna gain	3.66dBi
Antenna Designation	FPC Antenna
Power supply	Input:100-240V~ 50/60Hz Output:DC5V 1A
Hardware Version	V1.1
Software Version	V1.0.28

1.5. Laboratory Information

Company Name	:	Shanghai ATBL Technology Co., Ltd.
Address	:	Building 8,No.160 Basheng Road, Waigaoqiao Free Trade Zone, Pudong New Area, Shanghai
Telephone	:	+86(0)21-51298625

2. FCC 47CFR §2.1091 Requirement

2.1. Test Standards

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

KDB447498 D01: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

2.2. Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

2.3. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

2.4. Antenna Information

EUT can only use antennas certificated as follows provided by manufacturer;

Antenna	Model No. of antenna:	Type of antenna:	Gain of the antenna (Max.)	Frequency range: (MHz)
WIFI	/	FPC antenna	3.66dBi	2400-2500

2.5. Manufacturing Tolerance

Frequency (MHz)	ANT0_11b(AVG)		
	2412	2437	2462
Target (dBm)	16.0	16.0	16.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

Frequency (MHz)	ANT0_11G(AVG)		
	2412	2437	2462
Target (dBm)	14.0	14.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

Frequency (MHz)	ANT0_11N20(AVG)		
	2412	2437	2462
Target (dBm)	13.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

Frequency (MHz)	ANT0_11N40(AVG)		
	2422	2437	2452
Target (dBm)	12.0	12.0	12.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

Frequency (MHz)	ANT0_11AX20(AVG)		
	2412	2437	2462
Target (dBm)	13.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

Frequency (MHz)	ANT0_11AX40(AVG)		
	2422	2437	2452
Target (dBm)	12.0	12.0	12.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

2.6. Test Result

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r = 20\text{cm}$, as well as the gain of the used antenna is refer to section 4, the RF power density can be obtained.

Modulation Type	Output power (Target)		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
2.4G WIFI	17.0	50.119	3.66	2.32	0.023	1.0000

Note:

- 1.The Maximum power is less than the limit, complies with the exemption requirements.
- 2.Output power (AVG) including turn-up tolerance;
- 3.The calculated distance is 20 cm.

*****END OF THE REPORT*****