





TEST REPORT

Applicant	GUANGDONG FEILUN TECHNOLOGY INDUSTRIAL CO., LTD.
Address	Haisheng Road,Laimei Industrial District,Fengxiang Chenghai,Shantou city, Guangdong,China

Manufacturer or Supplier	GUANGDONG FEILUN TECHNOLOGY INDUSTRIAL CO., LTD.
Address	Haisheng Road,Laimei Industrial District,Fengxiang Chenghai,Shantou city, Guangdong,China
Product	Toy RC Monster Rockslide 1:24
Brand Name	N/A
Model	FL2019A
Additional Model & Model Difference:	N/A
Date of tests	Jan. 16 to 23, 2019

the tests have been carried out according to the requirements of the following standards:

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Evans He	Approved by David Huang
Project Engineer / EMC Department	Supervisor / EMC Department

mas. He

Date: Mar. 11, 2019

David Huang

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/ and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute you unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080



TABLE OF CONTENTS

K	ELEA	SE CONTROL RECORD	3
1	SU	MMARY OF TEST RESULTS	4
	2	MEASUREMENT UNCERTAINTY	4
3	GE	NERAL INFORMATION	5
	3.1	GENERAL DESCRIPTION OF EUT	5
	3.2	DESCRIPTION OF TEST MODES	6
	3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS	6
	3.4	DESCRIPTION OF SUPPORT UNITS	6
4	TE	ST TYPES AND RESULTS	7
	4.1	RADIATED EMISSION MEASUREMENT	7
	4.	1.1 LIMITS OF RADIATED EMISSION MEASUREMENT	7
	4	1.2 TEST INSTRUMENTS	8
	4	1.3 TEST PROCEDURES	9
	4.	1.4 DEVIATION FROM TEST STANDARD	9
	4	1.5 TEST SETUP	
	4	1.6 EUT OPERATING CONDITIONS	
	4	1.7 TEST RESULTS	
	4.2	BANDWIDTH MEASUREMENT	16
	4.2.1	LIMITS OF BANDWIDTH MEASUREMENT	16
	4.2.2	TEST INSTRUMENTS	16
	4.2.3	TEST PROCEDURE	18
	4.2.4	DEVIATION FROM TEST STANDARD	18
	4.2.5	TEST SETUP	18
	4.2.6	EUT OPERATING CONDITIONS	18
	4.2.7	TEST RESULTS	19
5	PH	OTOGRAPHS OF THE TEST CONFIGURATION	20
6 R		PENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES T	

Fax: +86 769 8593 1080
Email: DGservice@cn.bureauveritas.com



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF190115N002	O115N002 Original release	
RF190115N002-V1	Changed The FCC Site Registration No.	Mar. 11,2019

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080 Email: <u>DGservice@cn.bureauveritas.com</u>

Page 3 of 21



SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C , SECTION 15.227(2015-10)					
STANDARD SECTION TEST TYPE AND LIMIT RESULT REMARK					
§15.207 (a)	AC Power Conducted Emission	N/A	EUT is powered by battery		
§15.209 §15.227	Radiated Emission	PASS	Compliant		
§15.215(c)	20dB Bandwidth Test	PASS	Compliant		
§15.203	Antenna Requirement	N/A	No antenna connector is used		

NOTE: Test Lab Information:

Lab: Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch

Test Lab Address: Zone A, Floor 1, Building 2 Wan Ye Long Technology

Park South Side of Zhoushi Road, Bao'an District Shenzhen,

Guangdong, 518108, People's Republic of China

2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY	
	9KHz ~ 30MHz	3.11dB	
Radiated emissions	30MHz ~ 1GHz	5.12dB	
Radiated efflissions	1GHz ~ 18GHz	5.34dB	
	18GHz ~ 40GHz	5.20dB	

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k = 2.

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080



3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Toy RC Monster Rockslide 1:24
MODEL NO.	FL2019A
ADDITIONAL MODEL	N/A
FCC ID	Z6QFC15527A
NOMINAL VOLTAGE	DC 9V From Battery
MODULATION TYPE	FM
OPERATING FREQUENCY	27.145MHz
NUMBER OF CHANNEL	1
ANTENNA TYPE	Radial, external spring Antenna with 0dBi gain
I/O PORTS	Refer to user's manual

NOTE:

- 1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- 2. For the test results, the EUT had been tested with all conditions, but only the worst case was shown in test report.
- 3. Please refer to the EUT photo document (Reference No.: 190115N002) for detailed product photos.

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080



3.2 DESCRIPTION OF TEST MODES

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and packet type. The worst case was found when the EUT was positioned on Y axis for radiated emission. The EUT was tested under the following mode.

FREQUENCY	TEST MODES	
27.145 MHz	Transmitting	

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C, 15.227 ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit without any other necessary accessories or support units.

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080

Email: DGservice@cn.bureauveritas.com

Page 6 of 21



4 TEST TYPES AND RESULTS

RADIATED EMISSION MEASUREMENT 4.1

4.1.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)	
0.009 ~ 0.490	2400/F(kHz)	300	
0.490 ~ 1.705 24000/F(kHz)		30	
1.705 ~ 30.0	30	30	
30 ~ 88	100	3	
88 ~ 216	150	3	
216 ~ 960	200	3	
Above 960	500	3	

According to §15.227(a), the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Frequency Range of Fundamental [MHz]	Field Strength of Fundamental Emission [Peak] [µV/m]	Field Strength of Fundamental Emission [Average] [µV/m]
26.96 – 27.28	100,000 (100 dBμV/m)	10,000 (80 dBμV/m)

NOTE:

- 1. The lower limit shall apply at the transition frequencies.
- 2. Emission level $(dBuV/m) = 20 \log Emission level (uV/m)$.
- 3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

Dongguan Branch

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080



4.1.2 TEST INSTRUMENTS

Instrument	Model	Serial #	Cal Date	Cal Due
Agilent ESA-E SERIES SPECTRUM ANALYZER	E4407B	MY45108319	Feb 11, 18	Feb. 10, 19
EMI test receiver	ESL6	1300.5001K06- 100262-eQ	Jan, 05, 19	Jan. 04, 20
SYNTHESIZED SIGNAL GENERATOR	8665B	3744A01293	Jan, 05, 19	Jan. 04, 20
Bilog Antenna (30MHz~6GHz)	JB6	A110712	Feb 08, 18	Feb. 07, 19
Bilog Antenna (30MHz~2GHz)	JB1	A112017	Jan 26, 18	Jan. 25, 19
A-INFOMW Horn Antenna (1~18GHz)	AH-118	71259	Jan 26, 18	Jan. 25, 19
Pre-Amplifier (100MHz-26.5GHz)	EMC 012645	980077	May 18, 18	May 17, 19
Pre-Amplifier (18GHz-40GHz)	EMC 184045	980102	Nov. 08,18	Nov. 07,19
EMCO Horn Antenna (1~18GHz)	AH-118	71283	Feb 02, 18	Feb. 01, 19
OPT 010 AMPLIFIER (0.1~1300MHz)	8447E	2727A02430	Dec. 09, 18	Dec. 08, 19
Horn Antenna	BBHA 9170	BBHA9170147	Mar. 14, 18	Mar. 13, 19
Microwave Preamplifier (0.5 ~ 18GHz)	PAM-118	443008	Dec. 09, 18	Dec. 08, 19
Large Loop Antenna	RF300	Rf300	Dec. 09, 18	Dec. 08, 19
Universal Radio Communication Tester	CMU200	121393	Feb 11, 18	Feb. 10, 19
Positioning Controller	UC3000	MF780208282	Dec. 09, 18	Dec. 08, 19
Test Software	EZ-EMC	ver.lcp-03A1	N/A	N/A

NOTE:

- 1. The test was performed in 966 Chamber (a 3m Semi-anechoic chamber).
- 2. The calibration interval of the above test instruments are 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
- 3. The horn antenna is used only for the measurement of emission frequency above1GHz if tested.
- 4. The FCC Site Registration No. is 749762.

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080



4.1.3 TEST PROCEDURES

The basic test procedure was in accordance with ANSI C63.10 (section 6).

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3m chamber room. The table was rotated 360 degrees to determine the position of the highest radiation. (Below 1000MHz)
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10m chamber room. The table was rotated 360 degrees to determine the position of the highest radiation. (Below 30MHz)
- c. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- g. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position Y, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using new battery. The turntable was rotated to maximize the emission level.
- h. For below 30MHz, a loop antenna with its vertical plane is place 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1m above the ground.

NOTE:

- 1. The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
- 2. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
- 3. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
- 4. Margin value = Emission level Limit value.
- 5. Fundamental AV value =PK Emission +AV Factor.

4.1.4 DEVIATION FROM TEST STANDARD


No deviation.

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080




4.1.5 TEST SETUP

Below 30MHz



30MHz~1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080



4.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power of equipment.
- b. Hold down the TX of button, then the EUT was operating.
- c. EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.

4.1.7 TEST RESULTS

FIELD STRENGTH OF FUNDAMENTAL

ANTENNA POLARITY: 0°

	Freq.	Correction	Raw	Emission	Limit	Margin
No.	(MHz)	Factor	Value	Level	(dBuV/m)	(dB)
		(dB/m)	(dBuV)	(dBuV/m)		
*	27.145(PK)	-11.75	66.85	55.1	100	-44.9
*	27.145(AV)	-4.4	-	50.7	80	-29.3

ANTENNA POLARITY: 90°

	Freq.	Correction	Raw	Emission	Limit	Margin
No.	(MHz)	Factor	Value	Level	(dBuV/m)	(dB)
		(dB/m)	(dBuV)	(dBuV/m)		
*	27.145(PK)	-11.75	66.25	54.5	100	-45.5
*	27.145(AV)	-4.4	-	50.1	80	-29.9

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).

- 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
- 3. Margin value = Emission level Limit value.
- 4. " * ": Fundamental frequency.
- 5. The average value of fundamental frequency is: Average value = Peak value +AV factor, where the AV factor is calculated from following formula: AV factor=20 log (Duty cycle) = 20 log (60.242%) = -4.40dB, Please see page 12~13 for plotted duty.

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080




Duty Cycle:

Tp = 18.16ms

Ton = Ton1 * Number + Ton2 * Number = 4*1.51+10*0.49 = 10.94ms

Duty Cycle = Ton / Tp * 100% = 10.94/18.16= 60.242%


Tp=18.16ms




Tel: +86 769 8998 2098 Fax: +86 769 8593 1080



Ton1=1.51ms



Ton2= 0.4901ms



Tel: +86 769 8998 2098 Fax: +86 769 8593 1080




FREQUENCY RANGE	IUKH7 ~ 1(4H7	DETECTOR FUNCTION	Quasi-Peak (QP)
-----------------	---------------	----------------------	-----------------

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 m									
No.	Frequency	Reading	Ant_F	PA_G	Cab_L	Result	Limit	Margin	Height	Degree
	(MHz)	(dBuV/m)	(dB/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(°)
1	790.6188	29.16	21.29	21.17	2.94	32.22	46.00	-13.78	100	297
2	492.4685	26.45	17.55	21.83	2.38	24.55	46.00	-21.45	200	151
3	204.9551	26.86	12.03	22.37	1.56	18.08	43.50	-25.42	100	113
4	121.9755	26.29	13.77	22.36	1.17	18.87	43.50	-24.63	100	262
5	95.7622	27.93	9.38	22.32	1.01	16.00	43.50	-27.50	100	204
6	38.7518	28.48	14.81	22.27	0.78	21.80	40.00	-18.20	100	104

REMARKS:

- 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
- 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
- 3. The emission levels of other frequencies were less than 20dB margin against the limit.
- 4. Margin value = Emission level Limit value.



Tel: +86 769 8998 2098 Fax: +86 769 8593 1080




FREQUENCY RANGE	9KHz ~ 1GHz	DETECTOR FUNCTION	Quasi-Peak (QP)
-----------------	-------------	----------------------	-----------------

	ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 m									
No.	Frequency	Reading	Ant_F	PA_G	Cab_L	Result	Limit	Margin	Height	Degree
	(MHz)	(dBuV/m)	(dB/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(°)
1	99.8777	32.34	10.37	22.32	1.12	21.51	43.50	-21.99	200	138
2	166.6514	29.58	12.07	22.26	1.37	20.76	43.50	-22.74	100	350
3	334.8589	26.96	14.33	22.19	1.96	21.06	46.00	-24.94	100	309
4	539.4775	27.76	18.25	21.72	2.47	26.76	46.00	-19.24	100	237
5	790.6188	29.62	21.29	21.17	2.94	32.68	46.00	-13.32	100	237
6	57.9993	38.45	7.52	22.40	0.76	24.33	40.00	-15.67	100	360

REMARKS:

- 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
- 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
- 3. The emission levels of other frequencies were less than 20dB margin against the limit.
- 4. Margin value = Emission level Limit value.



Tel: +86 769 8998 2098 Fax: +86 769 8593 1080



4.2 BANDWIDTH MEASUREMENT

4.2.1 LIMITS OF BANDWIDTH MEASUREMENT

The field strength of any emissions appearing between the band edges and out of band shall be attenuated at least 20 dB below the level of the unmodulated carrier or to the general limits in Section 15.209.

FREQUENCY	Limits	
(MHz)	[MHz]	
27.145	within 26.96-27.28	

4.2.2 TEST INSTRUMENTS

Instrument	Model	Serial #	Cal Date	Cal Due
Power Sensor	Dare RPR3006C/P/W	N/A	Jan. 05, 19	Jan. 04, 20
Power Sensor	Dare RPR3006C/P/W	N/A	Jan. 05, 19	Jan. 04, 20
Agilent ESA-E SERIES SPECTRUM ANALYZER	E4407B	MY45108319	Feb. 11, 18	Feb. 10, 19
EMI test receiver	ESL6	1300.5001K06- 100262-eQ	Jan. 05, 19	Jan. 04, 20
Power Splitter	1#	1#	Dec. 09, 18	Dec. 08, 19
SYNTHESIZED SIGNAL GENERATOR	8665B	3744A01293	Jan. 05, 19	Jan. 04, 20
DC Power Supply	E3640A	MY40004013	Jan. 05, 19	Jan. 04, 20
Bilog Antenna (30MHz~6GHz)	JB6	A110712	Feb. 08, 18	Feb. 07, 19
Bilog Antenna (30MHz~2GHz)	JB1	A112017	Jan. 26, 18	Jan. 25, 19
A-INFOMW Horn Antenna (1~18GHz)	AH-118	71259	Jan. 26, 18	Jan. 25, 19
Pre-Amplifier (100MHz-26.5GHz)	EMC 012645	980077	May 18, 18	May 17, 19
Pre-Amplifier (18GHz-40GHz)	EMC 184045	980102	Nov. 08, 18	Nov. 07, 19
EMCO Horn Antenna (1~18GHz)	AH-118	71283	Feb. 02, 18	Feb. 01, 19
OPT 010 AMPLIFIER (0.1~1300MHz)	8447E	2727A02430	Dec. 09, 18	Dec. 08, 19
Horn Antenna	BBHA 9170	BBHA9170147	Mar. 14, 18	Mar. 13, 19
Microwave Preamplifier (0.5 ~ 18GHz)	PAM-118	443008	Dec. 09, 18	Dec. 08, 19
Attenuator	MINI	N/A	Dec. 09, 18	Dec. 08, 19

Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie Town, Dongguan City, Guangdong 523942, China

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080



Test Software	EZ-EMC	ver.lcp-03A1	N/A	N/A
---------------	--------	--------------	-----	-----

NOTE:

- 1. The test was performed in RF Oven room.
- 2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

Fax: +86 769 8593 1080 Email: DGservice@cn.bureauveritas.com

Tel: +86 769 8998 2098

Page 17 of 21 Report Version 1




4.2.3 TEST PROCEDURE

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- d. Repeat above procedures until all frequencies measured were complete.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

4.2.5 TEST SETUP



4.2.6 EUT OPERATING CONDITIONS

Same as item 4.1.6


Tel: +86 769 8998 2098 Fax: +86 769 8593 1080



4.2.7 TEST RESULTS

Lower & Upper Test Frequency Point (MHz)	Test Frequency (MHz)	P/F
Lower	27.11	PASS
Upper	27.17	PASS

Test Data:



Tel: +86 769 8998 2098 Fax: +86 769 8593 1080



5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).

Fax: +86 769 8593 1080

Tel: +86 769 8998 2098



6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080