



FCC AND IC RADIO TEST REPORT

FCC ID: Z6RSMFB201

IC ID: 11423A-FB201

Product : GSM MOBILE PHONE

Trade Name : Roam

Model Name : FB201

Serial Model : N/A

Report No. : 2013NT1212201F1

Prepared for

Social Mobile Telecommunications

801 NE 167th, St. Suite#314, North Miami Beach, FL33162, USA

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street
Bao'an District, Shenzhen P.R. China

Tel.: +86-0755-61156588 Fax.: +86-0755-61156599
Website: www.ntek.org.cn

TEST RESULT CERTIFICATION

Applicant's name : Social Mobile Telecommunications

Address : 801 NE 167th, St. Suite#314, North Miami Beach, FL33162, USA

Manufacture's Name : Skynet Technology Limited

Address : Room 2906, Block C, Royal Plaza, Yitian Road, Futian District, Shenzhen, China

Local Representative : Roam Mobility

Address : #200-10451 Shellbridge Way, Richmond, British Columbia, Canada

Product description

Product name : GSM MOBILE PHONE

Model and/or type reference : FB201

Band name : Roam

Standards : FCC Part 22H and 24E
RSS 132 Issue 3 and RSS 133 Issue 6

Test procedure ANSI C63.4-2003

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personal only, and shall be noted in the revision of the document.

Date of Test :

Date (s) of performance of tests : November 25, 2013 ~January 2, 2014

Date of Issue : January 3, 2014

Test Result : **Pass**

Testing Engineer : Apple Huang
(Apple Huang)

Technical Manager : Tom Zhang
(Tom Zhang)

Authorized Signatory : Bovey Yang
(Bovey Yang)

Table of Contents	Page
1 . SUMMARY OF TEST RESULTS	4
1.1 TEST FACILITY	5
1.2 MEASUREMENT UNCERTAINTY	5
2 . GENERAL INFORMATION	6
2.1 GENERAL DESCRIPTION OF EUT	6
2.2 DESCRIPTION OF TEST MODES	7
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	8
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	9
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	10
3 . TEST RESULT	11
3.1 OUTPUT POWER	11
3.1.1 CONDUCTED OUTPUT POWER	11
3.1.2 RADIATED OUTPUT POWER	12
3.2 SPURIOUS EMISSION	15
3.2.1 CONDUCTED SPURIOUS EMISSION	15
3.2.2 RADIATED SPURIOUS EMISSION	17
3.3 FREQUENCY STABILITY	21
3.3.1 MEASUREMENT METHOD	21
3.3.2 PROVISIONS APPLICABLE	21
3.4 OCCUPIED BANDWIDTH	23
3.4.1 MEASUREMENT METHOD	23
3.4.2 PROVISIONS APPLICABLE	23
3.4.3 MEASUREMENT RESULT	23
3.5 EMISSION BANDWIDTH	24
3.5.1 MEASUREMENT METHOD	24
3.5.2 PROVISIONS APPLICABLE	24
3.5.3 MEASUREMENT RESULT	24
3.6 BAND EDGE	25
3.6.1 MEASUREMENT METHOD	25
3.6.2 PROVISIONS APPLICABLE	25
3.6.3 MEASUREMENT RESULT	25
APPENDIX I	26
APPENDIX II	29
APPENDIX III	35
APPENDIX IV	39
4 . EUT TEST PHOTO	45
APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

Item Description	FCC Rules	IC Rules	Result
Conducted Output Power	22.913(a) / 24.232 (b)	RSS 132 § 5.4/ RSS133 § 6.4	Pass
Radiated Output Power			
Conducted Spurious Emission	2.1051 / 22.917 / 24.238	RSS-132 § 5.5/ RSS-133 § 6.5	Pass
Radiated Spurious Emission			
Frequency Stability	2.1055 /24.235	RSS-132 § 5.3/ RSS-133 § 6.3	Pass
Occupied Bandwidth	2.1049 (h)(i)	RSS-Gen 4.6.1	Pass
Emission Bandwidth	22.917(b) / 24.238 (b)	RSS-132 § 5.5/ RSS-133 § 6.5	Pass
Band Edge	22.917(b) / 24.238 (b)	RSS-132 § 5.5/ RSS-133 § 6.5	Pass

1.1 TEST FACILITY

NETK Testing Technology Co., Ltd

Add. : 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen P.R. China.

The **FCC** Registration Number is **238937**.

The **IC** Registration Number is **9270A-1**

The **CNAS** Registration Number is **CNAS L5516**.

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty **U** is based on a standard uncertainty multiplied by a coverage factor of **k=2**, providing a level of confidence of approximately **95 %** .

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	Radiated Emission Test	$\pm 3.17\text{dB}$
3	RF power,conducted	$\pm 0.16\text{dB}$
4	Spurious emissions,conducted	$\pm 0.21\text{dB}$
5	All emissions,radiated(<1G)	$\pm 4.68\text{dB}$
6	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	GSM MOBILE PHONE
Trade Name	Roam
Model Name	FB201
Serial Model	N/A
Model Difference	N/A
Frequency:	GSM 850 MHz: 824.2-848.4MHz PCS 1900 MHz: 1850.2-1909.8MHz
Antenna Gains	GSM 850 MHz : 1.5 dBi PCS 1900 MHz : 1.9 dBi
Output Power:	GSM850(Class 4) : 1.990 W (32.84dBm) GPRS850(Multislot Class 8) : 1.853W (32.68 dBm) GSM1900 (Class 1) : 1.025 W (30.11 dBm) GPRS1900 (Multislot Class 8) : 0.961 W (29.83 dBm)
SIM card:	SIM 1 and SIM2 is a chipset unit and tested as single chipset
Type of Modulation	GMSK
Antenna Type	PIFA Antenna
Bluetooth	Frequency: 2402 – 2480 MHz Modulation: GFSK Output Power: 0 dBm
Ratings	DC 3.7V
Adapter	Power Supply Model No.: PC201 Input: 100-240V~ 50/60Hz 150mA Output: DC5.0V, 600mA
Battery	Rated Voltage: 3.7V Charge Limit: 4.2V Capacity: 600mAh
Connecting I/O Port(s)	Please refer to the User's Manual

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.


For Radiated Emission	
Final Test Mode	Description
GSM850	TX1
PCS1900	TX2
GPRS850	TX3
GPRS1900	TX4

Note:


- (1) During the testing, the EUT (GSM Dual Band GPRS Digital Mobile Phone) was controlled via Rhode & Schwarz Digital Radio Communication Tester (CMU 200) to ensure max power transmission and proper modulation. Three channels (The top channel, the middle channel and the bottom channel) were chosen for testing on both GSM and PCS frequency band.
- (2) The EUT use new battery.

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

CONDUCTED METHOD:



RADIATED METHOD:



2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Mobile Phone	Roam	FB201	N/A	EUT

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2013.07.06	2014.07.05	1 year
2	Test Receiver	R&S	ESPI	101318	2013.06.07	2014.06.06	1 year
3	Bilog Antenna	TESEQ	CBL6111D	31216	2013.07.06	2014.07.05	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2013.06.07	2014.06.06	1 year
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	2013.06.07	2014.06.06	1 year
6	Horn Antenna	EM	EM-AH-10180	2011071402	2013.07.06	2014.07.05	1 year
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2013.07.06	2014.07.05	1 year
8	Amplifier	EM	EM-30180	060538	2012.12.22	2014.12.21	1 year
9	Loop Antenna	ARA	PLA-1030/B	1029	2013.06.08	2014.06.07	1 year
10	Power Meter	R&S	NRVS	100696	2013.07.06	2014.07.05	1 year
11	Power Sensor	R&S	URV5-Z4	0395.1619.05	2013.07.06	2014.07.05	1 year
12	Communication Tester	R&S	CMU200	A0304247	2013.07.06	2014.07.05	1 year
13	Power Splitter	Agilent	11636A	N/A	2013.07.06	2014.07.05	1 year

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2013.06.06	2014.06.05	1 year
2	LISN	R&S	ENV216	101313	2013.08.24	2014.08.23	1 year
3	LISN	EMCO	3816/2	00042990	2013.08.24	2014.08.23	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	2013.06.07	2014.06.06	1 year
5	Passive Voltage Probe	R&S	ESH2-Z3	100196	2013.06.07	2014.06.06	1 year
6	Absorbing clamp	R&S	MOS-21	100423	2013.06.08	2014.06.07	1 year

3. TEST RESULT

3.1 OUTPUT POWER

3.1.1 CONDUCTED OUTPUT POWER

Requirement

According to FCC §2.1046 (a), for transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, power output shall be measured at the RF output terminals when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified in §2.1033 (c)(8). The electrical characteristics of the radio frequency load attached to the output terminals when this test is made shall be stated.

MEASUREMENT METHOD

The EUT was setup for the max output power with pseudo random data modulation. Power was measured with Spectrum Analyzer. The measurements were performed on all modes(GSM, GPRS) at 3 typical channels(the Top Channel, the Middle Channel and the Bottom Channel) for both GSM band and PCS band

MEASUREMENT RESULT

Conducted Output Power for GSM 850 MHZ					
Mode	Frequency	Power Step	Result		Conclusion
			Peak Power (dBm)	W	
GSM	824.2	5	32.71	1.901	Pass
	836.6	5	32.84	1.990	Pass
	848.8	5	32.08	1.940	Pass
GPRS Class 12	824.2	3	32.54	1.794	Pass
	836.6	3	32.68	1.853	Pass
	848.8	3	32.14	1.636	Pass

Conducted Output Power for PCS 1900 MHZ					
Mode	Frequency	Power Step	Result		Conclusion
			Peak Power(dBM)		
GSM	1850.2	0	29.81	0.957	Pass
	1880.0	0	30.11	1.025	Pass
	1909.8	0	29.77	0.948	Pass
GPRS Class 12	1850.2	3	29.57	0.905	Pass
	1880.0	3	29.83	0.961	Pass
	1909.8	3	29.46	0.883	Pass

3.1.2 RADIATED OUTPUT POWER MEASUREMENT METHOD

The measurements procedures specified in TIA-603C-2004 were applied.

- 1 In an anechoic antenna test chamber, a half-wave dipole antenna for the frequency band of interest is placed at the reference centre of the chamber. An RF Signal source for the frequency band of interest is connected to the dipole with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A known (measured) power (P_{in}) is applied to the input of the dipole, and the power received (P_r) at the chamber's probe antenna is recorded.
- 2 The substitution method is used. Substitution values at each frequency are measured before and saved to the test software. A "reference path loss" is established as $AR_{pl} = P_{in} + 2.15 - P_r$. The AR_{pl} is the attenuation of "reference path loss", and including the gain of receive antenna, the cable loss and the air loss. The measurement results are obtained as described below: $Power = P_{Mea} + AR_{pl}$
- 3 The EUT is substituted for the dipole at the reference centre of the chamber and a scan is performed to obtain the radiation pattern.
- 4 From the radiation pattern, the co-ordinates where the maximum antenna gain occurs are identified.
- 5 The EUT is then put into continuously transmitting mode at its maximum power level.
- 6 Power mode measurements are performed with the receiving antenna placed at the coordinates determined in Step 3 to determine the output power as defined in Rule 24.232 (b) and (c). The "reference path loss" from Step 1 is added to this result.
- 7 This value is EIRP since the measurement is calibrated using a half-wave dipole antenna of known gain (2.15 dBi) and known input power (P_{in}).

ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dBi}$.

PROVISIONS APPLICABLE

This is the test for the maximum radiated power from the EUT. Rule Part 24.232(b) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage." Rule Part 22.913(a) specifies "Maximum ERP. The effective radiated power (ERP) of base transmitters and cellular repeaters must not exceed 500 Watts. The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."

Radiated Power Limits for GSM 850 MHZ (ERP)		
Mode	Power Step	Nominal Peak Power
GSM	5	<=38.45 dBm (7W)
GPRS	3	<=38.45 dBm (7W)

Radiated Power Limits for PCS 1900 MHZ (E.I.R.P.)		
Mode	Power Step	Nominal Peak Power
GSM	0	<=33 dBm (2W)
GPRS	3	<=33 dBm (2W)

MEASUREMENT RESULT

Radiated Power (ERP) for GSM 850 MHZ					
Mode	Frequency	Power Step	Result		Conclusion
			Max. Peak ERP (dBm)	Polarization Of Max. ERP	
GSM	824.2	5	31.43	Horizontal	Pass
	836.6	5	31.69	Horizontal	Pass
	848.8	5	31.12	Horizontal	Pass
GPRS	824.2	3	29.56	Horizontal	Pass
	836.6	3	29.72	Horizontal	Pass
	848.8	3	29.35	Horizontal	Pass

Radiated Power (E.I.R.P) for PCS 1900 MHZ

Mode	Frequency	Power Step	Result		Conclusion
			Max. Peak E.I.R.P.(dBm)	Polarization Of Max. E.I.R.P.	
GSM	1850.2	0	29.24	Horizontal	Pass
	1880.0	0	29.37	Horizontal	Pass
	1909.8	0	29.15	Horizontal	Pass
GPRS	1850.2	3	27.69	Horizontal	Pass
	1880.0	3	27.78	Horizontal	Pass
	1909.8	3	27.33	Horizontal	Pass

NOTE: DUE TO THE CONDUCTED OUTPUT POWER, GPRS WAS PERFORMED AT CLASS8

3.2 SPURIOUS EMISSION

3.2.1 CONDUCTED SPURIOUS EMISSION

MEASUREMENT METHOD

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1, Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment of PCS1900 band, this equates to a frequency range of 30 MHz to 19.1 GHz, data taken from 30 MHz to 20 GHz. For GSM850, data taken from 30 MHz to 9 GHz.

2, Determine EUT transmit frequencies: the following typical channels were chosen to conducted emissions testing.

Typical Channels for testing of GSM 850 MHz	
Channel	Frequency (MHz)
128	824.2
190	836.6
251	848.8

Typical Channels for testing of PCS 1900 MHz	
Channel	Frequency (MHz)
512	1850.2
661	1880.0
810	1909.8

PROVISIONS APPLICABLE

On any frequency outside frequency band of the USPCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least $43+10\log(P)$ dB. For all power levels +30 dBm to 0 dBm, this becomes a constant specification limit of -13 dBm.

MEASUREMENT RESULT

Conducted Spurious Emission for GSM 850 MHz						
Harmonic	Tx ch. 128	Level	Tx ch. 190	Level	Tx ch. Freq.	Level
c	Freq. (MHz)	(dBm)	Freq. (MHz)	(dBm)	(MHz) 251	(dBm)
2	1648.4	B.I.N.F	1673.2	nf	1697.6	B.I.N.F
3	2472.6	B.I.N.F	2509.8	nf	2546.4	B.I.N.F
4	3296.8	B.I.N.F	3346.4	nf	3395.2	B.I.N.F
5	4121	B.I.N.F	4183	nf	4244	B.I.N.F
6	4945.2	B.I.N.F	5019.6	nf	5092.8	B.I.N.F
7	5769.4	B.I.N.F	5856.2	nf	5941.6	B.I.N.F
8	6593.6	B.I.N.F	6692.8	nf	6790.4	B.I.N.F
9	7417.8	B.I.N.F	7529.4	nf	7639.2	B.I.N.F
10	8242	B.I.N.F	8366	nf	8488	B.I.N.F

● B.I.N.F: Below Instruments Noise floor

Conducted Spurious Emission for PCS 1900 MHz						
Harmonic	Tx ch. 512	Level	Tx ch. 661	Level	Tx ch. 810	Level
c	Freq. (MHz)	(dBm)	Freq. (MHz)	(dBm)	Freq. (MHz)	(dBm)
2	3700.4	B.I.N.F	3760	nf	3819.6	B.I.N.F
3	5550.6	B.I.N.F	5640	nf	5729.4	B.I.N.F
4	7400.8	B.I.N.F	7520	nf	7639.2	B.I.N.F
5	9251.0	B.I.N.F	9400	nf	9549.0	B.I.N.F
6	11101.2	B.I.N.F	11280	nf	11458.8	B.I.N.F
7	12951.4	B.I.N.F	13160	nf	13368.6	B.I.N.F
8	14801.6	B.I.N.F	15040	nf	15278.4	B.I.N.F
9	16651.8	B.I.N.F	16920	nf	17188.2	B.I.N.F
10	18502.0	B.I.N.F	18800	nf	19098.0	B.I.N.F

B.I.N.F: Below Instruments Noise floor

Please refers to Appendix I for compliance test plots for Conducted Spurious Emission


3.2.2 RADIATED SPURIOUS EMISSION

MEASUREMENT METHOD


The measurements procedures specified in TIA-603C-2004 were used for testing. The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment. The resolution bandwidth is set 1MHz as outlined in Part 24.238. The measurements were performed on all modes(GSM, GPRS,) at 3 typical channels(the Top Channel, the Middle Channel and the Bottom Channel) for both GSM band and PCS band.

The procedure of radiated spurious emissions is as follows:

a) Pre-calibration With pre-calibration method, the Radiated Spurious Emissions(RSE) is calculated as, $RSE = Rx \text{ (dBuV)} + CL \text{ (dB)} + SA \text{ (dB)} + Gain \text{ (dBi)} - 107$ (dBuV to dBm) The SA is calibrated using following setup.



b) EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the test item for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the test item and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector and 1MHz bandwidth.



Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the PCS band (1850.2 MHz, 1880 MHz and 1909.8 MHz), GSM850 band (824.2MHz, 836.6MHz, 848.8MHz). It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the PCS1900, GSM850 into any of the other blocks.

The substitution method is used. Substitution values at each frequency are measured before and saved to the test software. A "reference path loss" is established and the A_{Rpl} is the attenuation of "reference path loss", and including the gain of receive antenna, the gain of the preamplifier, the cable loss and the air loss. The measurement results are obtained as described below: $\text{Power} = P_{\text{Mea}} + A_{Rpl}$

PROVISIONS APPLICABLE

(a) On any frequency outside a licensee's frequency block (e.g. A, D, B, etc.) within the USPCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least $43 + 10\log(P)$ dB. The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log (P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

MEASUREMENT RESULT

The Worst Test Results for Channel 128 / 824.2 MHz					
Frequency(MHz)	Power(dBm)	ARpl (dBm)	PMea(dBm)	Limit (dBm)	Polarity
1648.00	-41.54	-2.95	-38.59	-13.00	Horizontal
1752.00	-45.28	-0.35	-44.93	-13.00	Vertical
2472.00	-39.57	0.12	-39.69	-13.00	Horizontal
9086.00	-39.45	8.45	-47.90	-13.00	Horizontal

The Worst Test Results for Channel 190/836.6 MHz					
Frequency(MHz)	Power(dBm)	ARpl (dBm)	PMea(dBm)	Limit (dBm)	Polarity
1673.00	-34.97	-2.09	-32.88	-13.00	Horizontal
1903.00	-50.40	-0.25	-50.15	-13.00	Vertical
9089.00	-39.99	8.52	-48.51	-13.00	Vertical

The Worst Test Results for Channel 251/848.8 MHz					
Frequency(MHz)	Power(dBm)	ARpl (dBm)	PMea(dBm)	Limit(dBm)	Polarity
1698.00	-45.11	-2.25	-42.86	-13.00	Horizontal
1888.50	-38.58	-0.29	-38.29	-13.00	Vertical
2131.00	-47.35	-0.87	-46.48	-13.00	Vertical
9089.00	-48.45	8.52	-39.93	-13.00	Horizontal

The Worst Test Results for Channel 512/1850.2 MHz					
Frequency(MHz)	Power(dBm)	ARpl (dBm)	PMea(dBm)	Limit(dBm)	Polarity
1999.00	-36.20	9.60	-45.80	-13.00	Horizontal
3700.00	-33.50	10.50	-44.00	-13.00	Horizontal
12950.40	-32.70	12.30	-45.00	-13.00	Vertical
17919.60	-31.74	18.70	-50.44	-13.00	Vertical

The Worst Test Results for Channel 661/1880.0 MHz					
Frequency(MHz)	Power(dBm)	ARpl (dBm)	PMea(dBm)	Limit(dBm)	Polarity
2000.50	-35.70	9.80	-45.50	-13.00	Vertical
9399.00	-33.70	11.80	-45.50	-13.00	Vertical
13160.40	-29.50	14.40	-43.90	-13.00	Horizontal
15039.60	-31.20	14.90	-46.10	-13.00	Vertical
17941.20	-37.80	19.90	-57.70	-13.00	Horizontal

The Worst Test Results for Channel 810/1909.8 MHz					
Frequency(MHz)	Power(dBm)	ARpl (dBm)	PMea(dBm)	Limit(dBm)	Polarity
2000.00	-30.00	9.80	-39.80	-13.00	Vertical
9548.50	-38.10	11.30	-49.40	-13.00	Horizontal
13367.40	-41.20	12.40	-53.60	-13.00	Horizontal
15277.80	-34.80	14.80	-49.60	-13.00	Vertical
17931.60	-37.70	19.00	-56.70	-13.00	Horizontal

3.3 FREQUENCY STABILITY

3.3.1 MEASUREMENT METHOD

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

- (1) Measure the carrier frequency at room temperature.
- (2) Subject the EUT to overnight soak at -30°C.
- (3) With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on channel 661 for PCS 1900, channel 190 for GSM850 measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
- (4) Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
- (5) Re-measure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1 Volt increments re-measuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.
- (6) Subject the EUT to overnight soak at +50°C.
- (7) With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
- (8) Repeat the above measurements at 10°C increments from +50°C to -30°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
- (9) At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

3.3.2 PROVISIONS APPLICABLE

For Hand carried battery powered equipment

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.5VDC and 4.2VDC, with a nominal voltage of 3.8VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages represent a tolerance of -10 % and +12.5 %. For the purposes of measuring frequency stability these voltage limits are to be used.

For equipment powered by primary supply voltage

MEASUREMENT RESULT

1. GSM 850MHz Band

Test Conditions		Frequency Deviation						Verdict	
Power (VDC)	Temperatur e (°C)	Channel = 128 (824.2MHz)		Channel = 190 (836.6MHz)		Channel = 251 (848.8MHz)			
		Hz	Limits	Hz	Limits	Hz	Limits		
3.7	-30	18.75	±2060.5	-29.36	±209 1.5	25.15	±212 2	PASS	
	-20	-12.12		-2.15		28.31			
	-10	16.28		40.06		-12.90			
	0	-22.03		1.99		12.66			
	+10	-12.02		-19.86		5.05			
	+20	-11.39		-2.32		3.02			
	+30	26.75		23.12		-13.01			
	+40	6.31		-2.15		0.51			
	+50	-22.19		35.31		-12.90			
	4.2	+25		29.35		23.11			
3.6	+25	27.19		-27.15		-34.03			

2. GSM 1900MHz Band

Test Conditions		Frequency Deviation						Verdict	
Power (VDC)	Temperatur e (°C)	Channel = 512 (1850.2MHz)		Channel = 661 (1880.0MHz)		Channel = 810 (1909.8MHz)			
		Hz	Limits	Hz	Limits	Hz	Limits		
3.7	-30	-17.39	±1850.2	38.28	±1880.0	29.22	±1909.8	PASS	
	-20	-3.10		-2.15		19.31			
	-10	38.28		35.06		-17.92			
	0	-2.15		1.99		17.36			
	+10	40.06		-19.86		5.05			
	+20	1.99		-2.32		3.02			
	+30	-19.86		23.12		-13.01			
	+40	39.56		11.33		0.51			
	+50	46.60		-17.55		21.45			
	4.2	+25		38.10		-15.09			
3.6	+25	12.32		-21.07		-22.16			

3.4 OCCUPIED BANDWIDTH

3.4.1 MEASUREMENT METHOD

The test set up and general procedure is similar to conducted peak output power test. Only different for setting the measurement configuration of the measuring instrument of Spectrum Analyzer.

3.4.2 PROVISIONS APPLICABLE

The occupied bandwidth (99%) shall not exceed 300 KHz.

3.4.3 MEASUREMENT RESULT

Occupied Bandwidth (99%) for GSM 850 MHz		
Mode	Frequency(MHz)	Occupied Bandwidth (99%)(kHz)
GSM	824.2	247.2376kHz
	836.6	244.6592kHz
	848.8	252.0262kHz
GPRS	824.2	246.4016KHz
	836.6	245.9659KHz
	848.8	249.1315KHz

Occupied Bandwidth (99%) for PCS 1900 MHz		
Mode	Frequency(MHz)	Occupied Bandwidth (99%)(kHz)
GSM	1850.2	248.4985kHz
	1880.0	245.1971kHz
	1909.8	244.4805kHz
GPRS	1850.2	240.1771KHz
	1880.0	249.1503KHz
	1909.8	245.1028KHz

Please refers to Appendix II for compliance test plots for Occupied Bandwidth (99%)

3.5 EMISSION BANDWIDTH

3.5.1 MEASUREMENT METHOD

The test set up and general procedure is similar to conducted peak output power test. Only different for setting the measurement configuration of the measuring instrument of Spectrum Analyzer.

3.5.2 PROVISIONS APPLICABLE

The emission bandwidth is defined as two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26dB below the transmitter power

3.5.3 MEASUREMENT RESULT

Emission Bandwidth (-26dBc) for GSM 850 MHz		
Mode	Frequency(MHz)	Occupied Bandwidth (-26dBc)(kHz)
GSM	824.2	326.738kHz
	836.6	328.148kHz
	848.8	322.847kHz
GPRS	824.2	316.304KHz
	836.6	325.272KHz
	848.8	323.506KHz

Emission Bandwidth (-26dBc) for PCS 1900 MHz		
Mode	Frequency(MHz)	Occupied Bandwidth (-26dBc)(kHz)
GSM	1850.2	311.339kHz
	1880.0	315.206kHz
	1909.8	311.450kHz
GPRS	1850.2	316.189KHz
	1880.0	312.833KHz
	1909.8	322.452KHz

Please refers to Appendix II for compliance test plots for Emission Bandwidth (-26dBc)

3.6 BAND EDGE

3.6.1 MEASUREMENT METHOD

The test set up and general procedure is similar to conducted peak output power test. Only different for setting the measurement configuration of the measuring instrument of Spectrum Analyzer.

3.6.2 PROVISIONS APPLICABLE

as Specified in FCC rules of 22.917(b) and 24.238(b)

3.6.3 MEASUREMENT RESULT


Please refers to Appendix III for compliance test plots for band edges

APPENDIX I


TEST PLOTS FOR CONDUCTED SPURIOUS EMISSION

CONDUCTED EMISSION IN GSM BAND


Conducted Emission Transmitting Mode CH 128




Conducted Emission Transmitting Mode CH 190




Conducted Emission Transmitting Mode CH 251




Conducted Emission Transmitting Mode CH 512



Conducted Emission Transmitting Mode CH 661




Conducted Emission Transmitting Mode CH 810




APPENDIX II

TEST PLOTS FOR OCCUPIED BANDWIDTH (99%)
EMISSION BANDWIDTH (-26dBc)


Occupied Bandwidth (99%) GSM 850 BAND CH 128




Occupied Bandwidth (99%) GSM 850 BAND CH 190




Occupied Bandwidth (99%) GSM 850 BAND CH 251




Occupied Bandwidth (99%) GPRS 850 BAND CH 128




Occupied Bandwidth (99%) GPRS 850 BAND CH 190




Occupied Bandwidth (99%) GPRS 850 BAND CH 251




Occupied Bandwidth (99%) PCS 1900 BAND CH 512




Occupied Bandwidth (99%) PCS 1900 BAND CH 661




Occupied Bandwidth (99%) PCS 1900 BAND CH 810




Occupied Bandwidth (99%) GPRS 1900 BAND CH 512



Occupied Bandwidth (99%) GPRS 1900 BAND CH 661




Occupied Bandwidth (99%) GPRS 1900 BAND CH 810




APPENDIX III

TEST PLOTS FOR BAND EDGES


Low Band Edge GSM 850 BAND CH 128




High Band Edge GSM 850 BAND CH 251




Low Band Edge GPRS 850 BAND CH 128




High Band Edge GPRS 850 BAND CH 251




Low Band Edge PCS 1900 BAND CH 512




High Band Edge PCS 1900 BAND CH 810



Low Band Edge GPRS 1900 BAND CH 512




High Band Edge GPRS 1900 BAND CH 810




APPENDIX IV

CONDUCTED OUTPUT POWER


GSM 850MHz Channel = 128




GSM 850MHz Channel = 190




GSM 850MHz Channel = 251




GPRS 850MHz Channel = 128




GPRS 850MHz Channel = 190




GPRS 850MHz Channel = 251




GSM 1900MHz Channel = 512




GSM 1900MHz Channel = 661




GSM 1900MHz Channel = 810




GPRS 1900MHz Channel = 512




GPRS 1900MHz Channel = 661



GPRS 1900MHz Channel = 810



4. EUT TEST PHOTO**Radiated Measurement Photos**

-----END OF REPORT-----