

MANUAL

AE1103RC-C is my company's conventional remote control, 3 keys, With a pcb antenna, Low power consumption, meet the various aspects of the application.

Scope:

- 1, Automobile, motorcycle alarm
- 2, Anti-theft alarm system.
- 3, A variety of remote control, electric curtains, roller shutter doors, car park Road illustrates control;

Specifications:

- 1,Current: 9mA..
- 2,Oscillation mode: SAW Oscillation.
- 3,RF Frequency :433.92MHz

Performance characteristics :

- 1,3 keys
- 2, High stability
- 3, Imported SMD components
- 4, The remote control will not transmit the command to receiver when multiple buttons are pressed down at the same time.
- 5,If no key is pressed, the remote control is in energy-saving state.

FCC NOTE:

THE MANUFACTURER IS NOT RESPONSIBLE FOR ANY RADIO OR TV INTERFERENCE CAUSED BY UNAUTHORIZED MODIFICATIONS TO THIS EQUIPMENT. SUCH MODIFICATIONS COULD VOID THE USER'S AUTHORITY TO OPERATE THE EQUIPMENT.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: 1. This device may not cause harmful interference, and 2. This device must accept any interference received, including interference that may cause undesired operation.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.