



Shenzhen CTL Electromagnetic Technology Co., Ltd.
Tel: +86-755-89486194 Fax: +86-755-26636041

FCC PART 15 SUBPART C TEST REPORT

FCC Part 15.247

Report Reference No.....: **CTL1312121961-WW**

Compiled by

(position+printed name+signature) : File administrators Jacky Chen

Jacky Chen

Name of the organization performing
the tests Test Engineer Tracy Qi

Tracy Qi

(position+printed name+signature) :

Approved by
(position+printed name+signature) : Manager Tracy Qi

Tracy Qi

Date of issue.....: Dec. 28, 2013

Representative Laboratory Name : **Shenzhen CTL Electromagnetic Technology Co., Ltd.**

Address: Floor 1-A, Baisha Technology Park, No.3011, Shahexi Road,
Nanshan District, Shenzhen, China 518055

Test Firm: **Bontek Compliance Testing Laboratory Ltd**

Address: 1/F, Block East H-3, OCT Eastern Ind. Zone, Qiaocheng East
Road, Nanshan, Shenzhen, China

Applicant's name: **DORRY ELECTRONICS INTERNATIONAL CO.,LTD**

Address: F/2, 3-4 Lane, Guangya Yuan, Bantian Town, Longgang District,
Shenzhen City, China

Test specification:

Standard: FCC Part 15.247: Operation within the bands 902–928 MHz, 2400–
2483.5 MHz, and 5725–5850 MHz.

TRF Originator: Shenzhen CTL Electromagnetic Technology Co., Ltd.

Master TRF: Dated 2011-01

Shenzhen CTL Electromagnetic Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTL Electromagnetic Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTL Electromagnetic Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description: **2G Phone Tablet PC**

FCC ID: **Z75TB650**

Trade Mark: N/A

Model/Type reference: TB-650, TB-726G, TB-782G, TB-M77, TB-798M, TB-677M,
TB-720M, TB-A31G


GSM

Transmit: GSM 850: 824~849MHz, PCS 1900: 1850~1910MHz

Receive: GSM 850: 869~894MHz, PCS 1900: 1930~1990MHz

Release Version: R99

Type of modulation	GMSK for GSM/GPRS 8PSK for EDGE
GPRS Type	Class B
GPRS Class	Class 12
Bluetooth	
Work frequency	2402~2480MHz
Version	V3.0 + HS
Type of modulation	FHSS
Data Rate	1Mbps(GFSK), 2Mbps(Pi/4 DQPSK), 3Mbps(8DPSK)
Wi-Fi	
Work frequency	802.11b/g/n(20MHz): 2412~2462MHz
Type of modulation	802.11b DSSS, 802.11g/n: OFDM
Data Rate	802.11b: 1/2/5.5/11 Mbps 802.11g: 6/9/12/18/24/36/48/54 Mbps 802.11n: up to 65 Mbps
Antenna Gain	0 dBi for GSM850 and PCS1900 -2.0 dBi for Bluetooth and Wi-Fi
Antenna type	Internal
Result	Positive



TEST REPORT

Test Report No. :	CTL1312121961-WW	Dec. 28, 2013
		Date of issue

Equipment under Test : 2G Phone Tablet PC

Model /Type : TB-650

Listed Models : TB-726G, TB-782G, TB-M77, TB-798M, TB-677M, TB-720M, TB-A31G

Different Description : Only model's name and colour are different based on marketing requirement.

Applicant : DORRY ELECTRONICS INTERNATIONAL CO.,LTD

Address : F/2, 3-4 Lane,Guangya Yuan,Bantian Town, Longgang District, Shenzhen City, China

Manufacturer : DORRY ELECTRONICS INTERNATIONAL CO.,LTD

Address : F/2, 3-4 Lane,Guangya Yuan,Bantian Town, Longgang District, Shenzhen City, China

Test Result according to the standards on page 5:	Positive
--	-----------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

<u>1.</u>	<u>TEST STANDARDS</u>	5
<u>2.</u>	<u>SUMMARY</u>	6
2.1.	General Remarks	6
2.2.	Equipment Under Test	6
2.3.	Short description of the Equipment under Test (EUT)	6
2.4.	EUT operation mode	6
2.5.	EUT configuration	7
2.6.	NOTE	7
2.7.	Related Submittal(s) / Grant (s)	7
2.8.	Modifications	7
<u>3.</u>	<u>TEST ENVIRONMENT</u>	8
3.1.	Address of the test laboratory	8
3.2.	Test Facility	8
3.3.	Environmental conditions	8
3.4.	Configuration of Tested System	8
3.5.	Statement of the measurement uncertainty	9
3.6.	Equipments Used during the Test	10
3.7.	Summary of Test Result	11
<u>4.</u>	<u>TEST CONDITIONS AND RESULTS</u>	12
4.1.	Conducted Emissions Test	12
4.2.	Radiated Emission Test	15
4.3.	6dB Bandwidth Measurement	22
4.4.	Maximum Peak Output Power	29
4.5.	Band Edge Measurement	31
4.6.	Power Spectral Density Measurement	56
4.7.	Spurious RF Conducted Emission	63
4.8.	Operation Frequency Range of 20dB Bandwidth	69
4.9.	Antenna Requirement	73
4.10.	RF Exposure	74
<u>5.</u>	<u>TEST SETUP PHOTOS OF THE EUT</u>	75
<u>6.</u>	<u>EXTERNAL AND INTERNAL PHOTOS OF THE EUT</u>	77

1. TEST STANDARDS

The tests were performed according to following standards:

FCC Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

ANSI C63.10-2009: American National Standard for Testing Unlicensed Wireless Devices.

ANSI C63.4-2003

KDB Publication No. 558074 D01 v03r01 Guidance on Measurements for Digital Transmission Systems



2. SUMMARY

2.1. General Remarks

Date of receipt of test sample	:	Dec. 18, 2013
	:	
Testing commenced on	:	Dec. 18, 2013
	:	
Testing concluded on	:	Dec. 27, 2013

2.2. Equipment Under Test

Power supply system utilised

Power supply voltage	:	<input checked="" type="radio"/> 120V / 60 Hz	<input type="radio"/> 115V / 60Hz
	:	<input type="radio"/> 12 V DC	<input type="radio"/> 24 V DC
	:	<input checked="" type="radio"/> Other (specified in blank below)	

DC 3.7V from battery

Description of the test mode

IEEE 802.11b/g/n: Thirteen channels are provided to the EUT, but only eleventh channels used for USA.

Channel	Frequency(MHz)	Channel	Frequency(MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432		
6	2437		
7	2442		

2.3. Short description of the Equipment under Test (EUT)

The EUT 2G Phone Tablet PC with GSM850/1900MHz, Bluetooth and wifi function.

For more details, refer to the user's manual of the EUT.

Serial number: Prototype

2.4. EUT operation mode

Test Mode:

1. The EUT has been tested under normal operating condition.
2. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed. Channel low (2412MHz), mid (2442MHz) and high (2462MHz) with highest data rate are chosen for full testing.
3. Test Mode:

Test Mode(TM)	Description	Remark
1	Transmitting	802.11 b
2	Transmitting	802.11 g
3	Transmitting	802.11 n HT20
4	Transmitting	802.11 n HT40

2.5. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- supplied by the manufacturer

- supplied by the lab

Notebook PC

Manufacturer : DELL

Model No. : PP18L

2.6. NOTE

1. The EUT is an 802.11b/g/n Tablet PC, The functions of the EUT listed as below:

	Test Standards	Reference Report
WLAN 802.11b/g, 802.11n	FCC Part 15 Subpart C (Section15.247)	CTL1312121961-WW
WLAN 802.11b/g, 802.11n	FCC Per 47 CFR 2.1091(b)	13C0557R-HP-US-P03V01

2. The frequency bands used in this EUT are listed as follows:

Frequency Band(MHz)	2400-2483.5	5150-5350	5470-5725	5725-5850
802.11b	✓	—	—	—
802.11g	✓	—	—	—
802.11n(20MHz)	✓	—	—	—

3. The EUT incorporates a SISO function, Physically, the EUT provides two completed transmitter and two completed receivers.

Modulation Mode	TX Function
802.11b	1TX
802.11g	1TX
802.11n (20MHz)	1TX

2.7. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: Z75TB650 filing to comply with of the FCC Part 15.247 Rules.

2.8. Modifications

No modifications were implemented to meet testing criteria.

3. TEST ENVIRONMENT

3.1. Address of the test laboratory

Bontek Compliance Testing Laboratory Ltd
1/F, Block East H-3, OCT Eastern Ind. Zone, Qiaocheng East Road, Nanshan, Shenzhen, China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 (2003) and CISPR Publication 22.

3.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

IC Registration No.: 7631A

The 3m alternate test site of Bontek Compliance Testing Laboratory Ltd EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration NO.: 7631A on March, 2011.

FCC-Registration No.: 338263

Bontek Compliance Testing Laboratory Ltd EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 338263, March 24, 2008.

3.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:


Temperature: 15-35 °C

Humidity: 30-60 %

Atmospheric pressure: 950-1050mbar

3.4. Configuration of Tested System

Fig. 2-1 Configuration of Tested System



3.5. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Bontek Compliance Testing Laboratory Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Bontek laboratory is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.10dB	(1)
Radiated Emission	Above 1GHz	4.32dB	(1)
Conducted Disturbance	0.15~30MHz	3.20dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.



3.6. Equipments Used during the Test

Item	Test Equipment	Manufacturer	Model No.	Last Cal.	Due. Date
1	EMI Test Receiver	ROHDE & SCHWARZ	ESCI	2013/04/14	2014/04/13
2	Radio Communication Tester	ROHDE & SCHWARZ	CMU200	2013/04/14	2014/04/13
3	Dual Directional Coupler	Agilent	778D	2013/04/14	2014/04/13
4	10dB attenuator	SCHWARZBECK	MTA1MP-136	2013/04/14	2014/04/13
5	Tunable Bandreject filter	K&L	3TNF-800	2013/04/14	2014/04/13
6	Tunable Bandreject filter	K&L	5TNF-1700	2013/04/14	2014/04/13
7	High-Pass Filter	K&L	9SH10-2700/X12750-O/O	2013/04/14	2014/04/13
8	High-Pass Filter	K&L	41H10-1375/U12750-O/O	2013/04/14	2014/04/13
9	Coaxial Cable	Huber+Suhner	AC4-RF-H	2013/04/14	2014/04/13
10	AC Power Supply	IDRC	CF-500TP	2013/04/14	2014/04/13
11	DC Power Supply	IDRC	CD-035-020PR	2013/04/14	2014/04/13
12	RF Current Probe	FCC	F-33-4	2013/04/14	2014/04/13
13	Temperature /Humidity Meter	zhicheng	ZC1-2	2013/04/14	2014/04/13
14	MICROWAVE AMPLIFIER	HP	8349B	2013/04/14	2014/04/13
15	Amplifier	HP	8447D	2013/04/14	2014/04/13
16	SIGNAL GENERATOR	HP	8647A	2013/04/14	2014/04/13
17	Log Periodic Antenna	ELECTRO-METRICS	EM-6950	2013/04/14	2014/04/13
18	Horn Antenna	Schwarzbeck	BBHA9120A	2013/04/14	2014/04/13
19	EMI Test Receiver	R&S	ESPI	2013/04/14	2014/04/13
20	Loop Antenna	ZHINAN	ZN30900A	2013/04/14	2014/04/13
21	Horn Antenna	Schwarzbeck	BBHA9120D	2013/04/14	2014/04/13
22	Horn Antenna	Schwarzbeck	BBHA9170	2013/04/14	2014/04/13
23	Spectrum Analyzer	Agilent	E4446A	2013/04/14	2014/04/13
24	Wideband Peak Power Meter	Anritsu	ML2495A	2013/04/14	2014/04/13
25	Power Sensor	Anritsu	MA2411B	2013/04/14	2014/04/13

3.7. Summary of Test Result

FCC PART 15		
FCC Part 15.207	AC Power Conducted Emission	PASS
FCC Part 15.247(a)(2)	6dB Bandwidth	PASS
FCC Part 15.247(d)	Spurious RF Conducted Emission	PASS
FCC Part 15.247(b)	Maximum Peak Output Power	PASS
FCC Part 15.247(e)	Power Spectral Density	PASS
FCC Part 15.109/ 15.205/ 15.209	Radiated Emissions	PASS
FCC Part 15.247(d)	Band Edge Compliance of RF Emission	PASS
FCC Part 15.203/15.247 (b)	Antenna Requirement	PASS
FCC Per 47 CFR 2.1091(b)	MPE Evaluation	PASS

Remark: The measurement uncertainty is not included in the test result.

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.


Test Items	Mode	Data Rate	Channel
AC Power Conducted Emission	Normal Link	11 Mbps	1
	11b/DSSS	11 Mbps	1/6/11
Maximum Peak Conducted Output Power	11g/OFDM	54 Mbps	1/6/11
Power Spectral Density	11n(20MHz)/OFDM	65Mbps	1/6/11
6dB Bandwidth	11b/DSSS	11 Mbps	1/6/11
Spurious RF conducted emission	11g/OFDM	54 Mbps	1/6/11
Radiated Emission 30MHz~1GHz	11n(20MHz)/OFDM	65Mbps	1/6/11
	11b/DSSS	11 Mbps	1/6/11
	11g/OFDM	54 Mbps	1/6/11
Radiated Emission 1GHz~10th Harmonic	11n(20MHz)/OFDM	65Mbps	1/6/11
	11b/DSSS	11 Mbps	1/11
	11g/OFDM	54 Mbps	1/11
Band Edge Compliance of RF Emission	11n(20MHz)/OFDM	65Mbps	1/11

Note1: According exploratory test, EUT will have maximum output power in those data rate, so those data rate were used for all test.

4. TEST CONDITIONS AND RESULTS

4.1. Conducted Emissions Test

TEST CONFIGURATION



TEST PROCEDURE

For unintentional device, according to § 15.107(a) Line Conducted Emission Limits is as following:

Frequency (MHz)	Maximum RF Line Voltage (dB μ V)			
	CLASS A		CLASS B	
	Q.P.	Ave.	Q.P.	Ave.
0.15 - 0.50	79	66	66-56*	56-46*
0.50 - 5.00	73	60	56	46
5.00 - 30.0	73	60	60	50

* Decreasing linearly with the logarithm of the frequency


For intentional device, according to §15.207(a) Line Conducted Emission Limit is same as above table.

1. Please follow the guidelines in ANSI C63.4-2003.
2. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN).
4. All the support units are connecting to the other LISN.
5. The LISN provides 50 ohm coupling impedance for the measuring instrument.
6. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
7. Both sides of AC line were checked for maximum conducted interference.
8. The frequency range from 150 kHz to 30 MHz was searched.
9. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

The RBW/VBW for 150KHz to 30MHz: 9KHz

TEST RESULTS

SCAN TABLE: "Voltage (9K-30M) FIN"
 Short Description: 150K-30M Voltage


**MEASUREMENT RESULT: "CTL131227615_fin"**

12/27/2013 5:10PM	Frequency	Level	Transd	Limit	Margin	Detector	Line	PE
	MHz	dB μ V	dB	dB μ V	dB			
	0.420000	40.70	9.8	57	16.7	QP	N	GND
	0.514500	48.00	9.8	56	8.0	QP	N	GND
	1.239000	39.70	9.8	56	16.3	QP	N	GND
	1.266000	40.00	9.8	56	16.0	QP	N	GND
	1.297500	39.80	9.8	56	16.2	QP	N	GND

MEASUREMENT RESULT: "CTL131227615_fin2"

12/27/2013 5:10PM	Frequency	Level	Transd	Limit	Margin	Detector	Line	PE
	MHz	dB μ V	dB	dB μ V	dB			
	0.420000	32.70	9.8	47	14.7	AV	N	GND
	0.424500	32.70	9.8	47	14.7	AV	N	GND
	0.514500	40.00	9.8	46	6.0	AV	N	GND
	1.117500	29.00	9.8	46	17.0	AV	N	GND
	1.266000	30.50	9.8	46	15.5	AV	N	GND
	1.356000	30.10	9.8	46	15.9	AV	N	GND

SCAN TABLE: "Voltage (9K-30M) FIN"
 Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "CTL131227616_fin"

12/27/2013 5:13PM	Frequency	Level	Transd	Limit	Margin	Detector	Line	PE
	MHz	dB μ V	dB	dB μ V	dB			
	0.510000	43.20	9.8	56	12.8	QP	L1	GND
	1.203000	34.40	9.8	56	21.6	QP	L1	GND
	1.293000	34.80	9.8	56	21.2	QP	L1	GND
	1.320000	32.60	9.8	56	23.4	QP	L1	GND
	1.356000	34.30	9.8	56	21.7	QP	L1	GND
	2.175000	32.20	9.9	56	23.8	QP	L1	GND


MEASUREMENT RESULT: "CTL131227616_fin2"

12/27/2013 5:13PM	Frequency	Level	Transd	Limit	Margin	Detector	Line	PE
	MHz	dB μ V	dB	dB μ V	dB			
	0.393000	27.30	9.8	48	20.7	AV	L1	GND
	0.420000	27.60	9.8	47	19.8	AV	L1	GND
	0.510000	33.80	9.8	46	12.2	AV	L1	GND
	1.266000	24.70	9.8	46	21.3	AV	L1	GND
	1.324500	24.60	9.8	46	21.4	AV	L1	GND


4.2. Radiated Emission Test

TEST CONFIGURATION


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

TEST PROCEDURE

1. The testing follows FCC KDB Publication No. 558074 (Measurement Guidelines of DTS), the EUT was setup according to ANSI C63.4: and tested according to ANSI C63.10 for compliance to FCC 47CFR 15.247 requirements.
2. The EUT was placed on a turn table which is 0.8m above ground plane.
3. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0°C to 360°C to acquire the highest emissions from EUT
4. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
5. Span = wide enough to fully capture the emission being measured; RBW = 1 MHz for $f > 1$ GHz, 120 kHz for $f < 1$ GHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. Repeat above procedures until all frequency measurements have been completed.

Note:

When doing emission measurement above 1GHz, the horn antenna will be bended down a little (as horn antenna has the narrow beamwidth) in order to keeping the antenna in the “cone of radiation” of EUT. The 3dB beamwidth is 60 degrees for H-plane and 90 degrees for E-plane.

LIMIT

For unintentional device, according to § 15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency (MHz)	Distance (Meters)	Radiated (dB μ V/m)	Radiated (μ V/m)
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table. According to § 15.247(d), in any 100kHz bandwidth outside the frequency band in which the EUT is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of desired power.

TEST RESULTS

Mode1: Transmit at 802.11b

CH	Antenna	Frequency (MHz)	Reading Level (dBuV/m)	Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	H	2411.9	71.3	27.8	99.1	Fundamental	/	PK
	H	350.6	1.0	16.3	17.3	46	-28.7	QP
	H	569.7	0.8	21.2	22.0	46	-24.0	QP
	V	3042.1	43.9	-5.6	38.3	54(note3)	-15.7	PK
	H	4825.0	55.8	-2.5	53.3	54(note3)	-0.7	PK
	H	7236.0	39.9	2.6	42.5	54(note3)	-31.5	PK
	H	24000.0	34.1	18.8	50.2	54(note3)	-3.8	PK
6	H	2437.0	70.5	27.7	98.2	Fundamental	/	PK
	V	349.7	0.2	16.3	16.5	46	-29.5	QP
	V	539.0	2.6	20.9	23.5	46	-22.5	QP
	H	3114.4	43.9	-5.7	38.2	54(note3)	-15.8	PK
	H	4873.9	55.2	-2.3	52.9	54(note3)	-1.1	PK
	V	7311.0	40.4	2.7	43.1	54(note3)	-10.9	PK
	H	24000.0	34.1	18.8	50.2	54(note3)	-3.8	PK
11	H	2462.1	69.4	27.9	97.3	Fundamental	/	PK
	H	367.3	1.1	16.7	17.8	46	-28.2	QP
	H	539.1	3.3	20.9	24.2	46	-21.8	QP
	V	3057.0	44.3	-5.6	38.7	54(note3)	-15.3	PK
	H	4924.9	53.4	-2.2	51.2	54(note3)	-2.8	PK
	H	7386.0	39.6	2.8	42.4	54(note3)	-11.6	PK
	H	24000.0	34.1	18.8	50.2	54(note3)	-3.8	PK

Note: 1. Measure Level = Reading Level + Factor.

2. The test results which are attenuated more than 20 dB below the permissible value limit (the test frequency range: 9kHz~30MHz, 18GHz~25GHz), therefore no data appear in the report.

3. This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.

Mode2: Transmit at 802.11g

CH	Antenna	Frequency (MHz)	Reading Level (dBuV/m)	Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	H	2412.1	74.2	27.8	102.0	Fundamental	/	PK
	V	345.7	0.3	16.2	16.5	46	-29.5	QP
	V	539.1	3.0	20.9	23.9	46	-22.1	QP
	V	3129.3	44.7	-5.7	39.0	54(note3)	-15.0	PK
	H	4825.0	54.1	-2.5	51.6	54(note3)	-2.4	PK
	V	7236.0	40.0	2.6	42.6	54(note3)	-31.4	PK
	H	24000.0	34.1	18.8	50.2	54(note3)	-3.8	PK
6	H	2437.0	73.5	27.8	101.3	Fundamental	/	PK
	H	355.1	0.4	16.4	16.8	46	-29.2	QP
	H	539.1	2.5	21	23.5	46	-22.5	QP
	V	3129.3	44.9	-5.6	39.3	54(note3)	-14.7	PK
	H	4873.9	53.9	-2.3	51.6	54(note3)	-2.4	PK
	V	7311.0	40.2	2.7	42.9	74	-11.1	PK
	H	24000.0	34.1	18.8	50.2	54(note3)	-3.8	PK
11	H	2461.8	73.0	27.9	100.9	Fundamental	/	PK
	V	346.9	0.9	16.1	17.0	46	-29.0	QP
	V	539.1	3.9	20.9	24.8	46	-21.2	QP
	V	3112.3	44.2	-5.6	38.6	54(note3)	-15.4	PK
	H	4920.6	55.2	-2.2	53.0	54(note3)	-1.0	PK
	V	7386.0	40.7	2.7	43.4	54(note3)	-10.6	PK
	H	24000.0	34.1	18.8	50.2	54(note3)	-3.8	PK

Note: 1. Measure Level = Reading Level + Factor.

2. The test results which are attenuated more than 20 dB below the permissible value limit (the test frequency range: 9kHz~30MHz, 18GHz~25GHz), therefore no data appear in the report.

3. This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.

Mode3: Transmit at 802.11n(20MHz)

CH	Antenna	Frequency (MHz)	Reading Level (dBuV/m)	Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	H	2411.6	71.3	27.7	99.0	Fundamental	/	PK
	H	353.6	0.9	16.3	17.2	46	-28.8	QP
	H	539.1	1.7	20.9	22.6	46	-23.4	QP
	V	3044.3	44.3	-5.7	38.6	54(note3)	-15.4	PK
	H	4820.8	50.2	-2.5	47.7	54(note3)	-6.3	PK
	V	7236.0	40.5	2.6	43.1	54(note3)	-30.9	PK
	H	24000.0	34.1	18.8	50.2	54(note3)	-3.8	PK
6	H	2437.0	70.3	28.3	98.6	Fundamental	/	PK
	V	347.2	0.3	16.2	16.5	46	-29.5	QP
	V	539.1	3.1	20.9	24.0	46	-22.0	QP
	H	3095.3	44.3	-5.6	38.7	54(note3)	-15.3	PK
	H	4873.9	50.8	-2.3	48.5	54(note3)	-5.5	PK
	H	7311.0	39.8	2.7	42.5	54(note3)	-11.5	PK
	H	24000.0	34.1	18.8	50.2	54(note3)	-3.8	PK
11	H	2461.6	69.7	27.9	97.6	Fundamental	/	PK
	H	353.3	0.3	16.4	16.7	46	-29.3	QP
	H	539.1	1.7	20.9	22.6	46	-23.4	QP
	V	3012.4	44.7	-5.7	39.0	54(note3)	-15.0	PK
	H	4929.1	49.5	-2.2	47.3	54(note3)	-6.7	PK
	V	7386.0	39.8	2.8	42.6	74	-11.4	PK
	H	24000.0	34.1	18.8	50.2	54(note3)	-3.8	PK

Note: 1. Measure Level = Reading Level + Factor.


2. The test results which are attenuated more than 20 dB below the permissible value limit (the test frequency range: 9kHz~30MHz, 18GHz~25GHz), therefore no data appear in the report.

3. This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.

The worst case of Radiated Emission below 1GHz:

SWEEP TABLE: "test (30M-1G)"

Short Description:		Field Strength		
Start	Stop	Detector	Meas.	IF
Frequency	Frequency		Time	Bandw.
30.0 MHz	1.0 GHz	MaxPeak	300.0 ms	120 kHz
				JB1




MEASUREMENT RESULT: "CTL131227014_red"

12/27/2013 5:24PM									
Frequency	Level	Transd	Limit	Margin	Det.	Height	Azimuth	Polarization	
MHz	dB μ V/m	dB	dB μ V/m	dB		cm	deg		
30.000000	37.10	21.1	40.0	2.9	---	0.0	0.00	VERTICAL	
64.920000	34.20	8.4	40.0	5.8	---	0.0	0.00	VERTICAL	
148.340000	39.00	14.2	43.5	4.5	---	0.0	0.00	VERTICAL	
165.800000	36.00	13.8	43.5	7.5	---	0.0	0.00	VERTICAL	
716.760000	37.70	23.7	46.0	8.3	---	0.0	0.00	VERTICAL	
749.740000	36.20	24.3	46.0	9.8	---	0.0	0.00	VERTICAL	

Electromagnetic Tech

SWEEP TABLE: "test (30M-1G)"

Short Description:		Field Strength			
Start Frequency	Stop Frequency	Detector	Meas.	IF	Transducer
30.0 MHz	1.0 GHz	MaxPeak	300.0 ms	120 kHz	JB1

***MEASUREMENT RESULT: "CTL131227013_red"***


12/27/2013 5:22PM

Frequency MHz	Level dB μ V/m	Transd dB	Limit dB μ V/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
198.780000	39.10	14.2	43.5	4.4	---	0.0	0.00	HORIZONTAL
383.080000	41.20	17.8	46.0	4.8	---	0.0	0.00	HORIZONTAL
532.460000	38.80	20.6	46.0	7.2	---	0.0	0.00	HORIZONTAL
866.140000	40.70	25.5	46.0	5.3	---	0.0	0.00	HORIZONTAL
883.600000	40.10	25.8	46.0	5.9	---	0.0	0.00	HORIZONTAL
934.040000	39.50	26.4	46.0	6.5	---	0.0	0.00	HORIZONTAL



4.3. 6dB Bandwidth Measurement

TEST CONFIGURATION



TEST PROCEDURE

1. The testing follows FCC KDB Publication No. 558074 (Measurement Guidelines of DTS).
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW. The 6 dB bandwidth must be greater than 500 kHz.
4. The marker-delta reading at this point is the 6 dB bandwidth of the emission.

LIMIT


For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

TEST RESULTS


Product	:	2G Phone Tablet PC
Test Item	:	6dB Occupied Bandwidth
Test Site	:	TR-3
Test Mode	:	Mode 1: Transmit by 802.11b

Channel No.	Frequency (MHz)	Occupied Bandwidth (kHz)	Limit (kHz)	Result
01	2412	9030	500	Pass
06	2437	8530	500	Pass
11	2462	8530	500	Pass


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




Product	:	2G Phone Tablet PC
Test Item	:	6dB Occupied Bandwidth
Test Site	:	TR-3
Test Mode	:	Mode 2: Transmit by 802.11g


Channel No.	Frequency (MHz)	Occupied Bandwidth (kHz)	Limit (kHz)	Result
01	2412	15510	500	Pass
06	2437	15130	500	Pass
11	2462	15310	500	Pass



Channel 06 (2437MHz)




Channel 11 (2462MHz)




Product	:	2G Phone Tablet PC
Test Item	:	6dB Occupied Bandwidth
Test Site	:	TR-3
Test Mode	:	Mode 3: Transmit by 802.11n(20MHz)


Channel No.	Frequency (MHz)	Occupied Bandwidth (kHz)	Limit (kHz)	Result
01	2412	16010	500	Pass
06	2437	16880	500	Pass
11	2462	16010	500	Pass



Channel 06 (2437MHz)




Channel 11 (2462MHz)



4.4. Maximum Peak Output Power

TEST CONFIGURATION



TEST PROCEDURE

According to C63.10 -2009 and KDB558074, The EUT was directly connected to the power meter / spectrum analyzer and antenna output port as show in the block diagram as TEST CONFIGURATION shows.

Use the wideband power meter to test peak power and record the result.

LIMIT

The Peak Output Power Measurement limits are 30dBm.

TEST RESULTS

Product	:	2G Phone Tablet PC
Test Item	:	Power Output
Test Site	:	TR3
Test Mode	:	Mode 1: Transmit by 802.11b

Channel No.	Frequency (MHz)	Measurement Power Output (dBm)	Limit (dBm)	Result
1	2412	9.66	30.00	Pass
6	2437	9.34	30.00	Pass
11	2462	9.25	30.00	Pass

Product	:	2G Phone Tablet PC
Test Item	:	Power Output
Test Site	:	TR3
Test Mode	:	Mode 2: Transmit by 802.11g

Channel No.	Frequency (MHz)	Measurement Power Output (dBm)	Limit (dBm)	Result
1	2412	9.43	30.00	Pass
6	2437	9.49	30.00	Pass
11	2462	9.25	30.00	Pass


Product	:	2G Phone Tablet PC
Test Item	:	Power Output
Test Site	:	TR3
Test Mode	:	Mode 3: Transmit by 802.11n(20MHz)

Channel No.	Frequency (MHz)	Measurement Power Output (dBm)	Limit (dBm)	Result
1	2412	8.86	30.00	Pass
6	2437	8.75	30.00	Pass
11	2462	8.63	30.00	Pass



4.5. Band Edge Measurement

TEST CONFIGURATION



TEST PROCEDURE

The band edge compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10 and FCC KDB Publication No. 558074 (Measurement Guidelines of DTS) with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=100kHz and VBM= 300KHz to measure the peak field strength and set RBW to 1MHz and VBW to 10Hz to measure the average radiated field strength.

The conducted RF band edge was measured by using a spectrum analyzer. Set span wide enough to capture the highest in-band emission and the emission at the band edge. Set RBW and VBW to 100 kHz, to measure the conducted peak band edge.

Connect the spectrum analyzer to the EUT using an appropriate RF cable connected to the EUT output. Configure the spectrum analyzer settings as described below (be sure to enter all losses between the unlicensed wireless device output and the spectrum analyzer).

- Span: Set Span for minimum 50 MHz - Reference Level: 110 dB μ V (corrected for gains and losses of test antenna factor, preamp gain and cable loss) - Attenuation: 10 dB
- Sweep Time: Coupled - Resolution Bandwidth: Up to and including 1 GHz = ≥ 100 kHz
- Resolution Bandwidth: Above 1 GHz = 1 MHz - Video Bandwidth: Below 1 GHz = 300 kHz
- Video Bandwidth: Up to and including 1 GHz = ≥ 3 MHz for peak and 10 Hz for average
- Detector: Peak

Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel.


LIMIT

1. Below -20dB of the highest emission level in operating band.
2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209(see Section 15.205(c)).


Frequency (MHz)	Limit Average (dB μ V/m)	Limit Peak (dB μ V/m)
Below 2390 or Above 2483.5	54	74

TEST RESULTS

Engineer: Milo	Time: 2013/12/24 - 22:20
Site: AC1	
Limit: FCC_Part15.209 RE(3m)	Margin: 0
Probe: BBHA9120D-737(1-18GHz)	Polarity: Horizontal
EUT: 2G Phone Tablet PC	Power: By battery
Note: Mode 1: Transmit at channel 2412MHz by 802.11b	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	52.258	24.576	-21.742	74.000	27.682	PK
2	*	2411.892	99.062	71.292	N/A	N/A	27.769	PK



Engineer: Milo	Time: 2013/12/24 - 22:39
Site: AC1	
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-737(1-18GHz)	Polarity: Horizontal
EUT: 2G Phone Tablet PC	Power: By battery

Note: Mode 1: Transmit at channel 2412MHz by 802.11b




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	40.954	13.272	-13.046	54.000	27.682	AV
2	*	2411.066	94.402	66.636	N/A	N/A	27.766	AV



Engineer: Milo	Time: 2013/12/24 - 22:41
Site: AC1	
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-737(1-18GHz)	Polarity: Vertical
EUT: 2G Phone Tablet PC	Power: By battery

Note: Mode 1: Transmit at channel 2412MHz by 802.11b




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	52.378	24.696	-21.622	74.000	27.682	PK
2	*	2411.892	97.544	69.774	N/A	N/A	27.769	PK



Engineer: Milo	Time: 2013/12/24 - 22:58
Site: AC1	
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-737(1-18GHz)	Polarity: Vertical
EUT: 2G Phone Tablet PC	Power: By battery

Note: Mode 1: Transmit at channel 2412MHz by 802.11b




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	40.477	12.795	-13.523	54.000	27.682	AV
2	*	2411.248	93.139	65.372	N/A	N/A	27.767	AV



Engineer: Milo	Time: 2013/12/24 - 23:00
Site: AC1	
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-737(1-18GHz)	Polarity: Horizontal
EUT: 2G Phone Tablet PC	Power: By battery

Note: Mode 1: Transmit at channel 2462MHz by 802.11b



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2462.104	97.341	69.365	N/A	N/A	27.976	PK
2		2483.500	52.333	24.276	-21.667	74.000	28.057	PK



Engineer: Milo	Time: 2013/12/24 - 23:07
Site: AC1	
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-737(1-18GHz)	Polarity: Horizontal
EUT: 2G Phone Tablet PC	Power: By battery

Note: Mode 1: Transmit at channel 2462MHz by 802.11b




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2461.186	92.528	64.555	N/A	N/A	27.973	AV
2		2483.500	39.809	11.752	-14.191	54.000	28.057	AV



Engineer: Milo	Time: 2013/12/24 - 23:08
Site: AC1	
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-737(1-18GHz)	Polarity: Vertical
EUT: 2G Phone Tablet PC	Power: By battery

Note: Mode 1: Transmit at channel 2462MHz by 802.11b



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2462.032	96.574	68.598	N/A	N/A	27.976	PK
2		2483.500	51.096	23.039	-22.904	74.000	28.057	PK



Engineer: Milo	Time: 2013/12/24 - 23:10
Site: AC1	
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-737(1-18GHz)	Polarity: Vertical
EUT: 2G Phone Tablet PC	Power: By battery

Note: Mode 1: Transmit at channel 2462MHz by 802.11b




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2461.354	91.713	63.740	N/A	N/A	27.974	AV
2		2483.500	39.792	11.735	-14.208	54.000	28.057	AV



Engineer: Milo	Time: 2013/12/24 - 23:11
Site: AC1	
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-737(1-18GHz)	Polarity: Horizontal
EUT: 2G Phone Tablet PC	Power: By battery

Note: Mode 2: Transmit at channel 2412MHz by 802.11g




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	64.722	37.040	-9.278	74.000	27.682	PK
2	*	2412.116	101.962	74.191	N/A	N/A	27.770	PK



Engineer: Milo	Time: 2013/12/24 - 23:25
Site: AC1	
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-737(1-18GHz)	Polarity: Horizontal
EUT: 2G Phone Tablet PC	Power: By battery

Note: Mode 2: Transmit at channel 2412MHz by 802.11g




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	46.839	19.157	-7.161	54.000	27.682	AV
2	*	2411.248	83.924	56.157	N/A	N/A	27.767	AV



Engineer: Milo	Time: 2013/12/24 - 23:26
Site: AC1	
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-737(1-18GHz)	Polarity: Vertical
EUT: 2G Phone Tablet PC	Power: By battery


Note: Mode 2: Transmit at channel 2412MHz by 802.11g



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	63.364	35.682	-10.636	74.000	27.682	PK
2	*	2411.766	100.433	72.664	N/A	N/A	27.769	PK




Engineer: Milo	Time: 2013/12/24 - 23:29
Site: AC1	
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-737(1-18GHz)	Polarity: Vertical
EUT: 2G Phone Tablet PC	Power: By battery
Note: Mode 2: Transmit at channel 2412MHz by 802.11g	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	45.870	18.188	-8.130	54.000	27.682	AV
2	*	2410.968	81.969	54.203	N/A	N/A	27.766	AV




Engineer: Milo	Time: 2013/12/24 - 23:30
Site: AC1	
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-737(1-18GHz)	Polarity: Horizontal
EUT: 2G Phone Tablet PC	Power: By battery
Note: Mode 2: Transmit at channel 2462MHz by 802.11g	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2461.792	100.942	72.967	N/A	N/A	27.975	PK
2		2483.500	68.540	40.483	-5.460	74.000	28.057	PK
3		2484.088	71.130	43.071	-2.870	74.000	28.059	PK



Engineer: Milo	Time: 2013/12/24 - 23:41
Site: AC1	
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-737(1-18GHz)	Polarity: Horizontal
EUT: 2G Phone Tablet PC	Power: By battery
Note: Mode 2: Transmit at channel 2462MHz by 802.11g	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2461.282	81.521	53.548	N/A	N/A	27.973	AV
2		2483.500	47.724	19.667	-6.276	54.000	28.057	AV



Engineer: Milo	Time: 2013/12/24 - 23:42
Site: AC1	
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-737(1-18GHz)	Polarity: Vertical
EUT: 2G Phone Tablet PC	Power: By battery

Note: Mode 2: Transmit at channel 2462MHz by 802.11g




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2461.624	99.306	71.331	N/A	N/A	27.975	PK
2		2483.500	67.647	39.590	-6.353	74.000	28.057	PK
3		2483.752	70.236	42.178	-3.764	74.000	28.058	PK



Engineer: Milo	Time: 2013/12/24 - 23:44
Site: AC1	
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-737(1-18GHz)	Polarity: Vertical
EUT: 2G Phone Tablet PC	Power: By battery


Note: Mode 2: Transmit at channel 2462MHz by 802.11g



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2461.438	81.660	53.686	N/A	N/A	27.974	AV
2		2483.500	47.880	19.823	-6.120	54.000	28.057	AV




Engineer: Milo	Time: 2013/12/24 - 23:46
Site: AC1	
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-737(1-18GHz)	Polarity: Horizontal
EUT: 2G Phone Tablet PC	Power: By battery
Note: Mode 3: Transmit at channel 2412MHz by 802.11n(20MHz)	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	65.288	37.606	-8.712	74.000	27.682	PK
2	*	2411.612	99.036	71.267	N/A	N/A	27.768	PK




Engineer: Milo	Time: 2013/12/24 - 23:58
Site: AC1	
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-737(1-18GHz)	Polarity: Horizontal
EUT: 2G Phone Tablet PC	Power: By battery
Note: Mode 3: Transmit at channel 2412MHz by 802.11n(20MHz)	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	45.122	17.440	-8.878	54.000	27.682	AV
2	*	2411.234	81.400	53.633	N/A	N/A	27.767	AV



Engineer: Milo	Time: 2013/12/24 - 23:59
Site: AC1	
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-737(1-18GHz)	Polarity: Vertical
EUT: 2G Phone Tablet PC	Power: By battery
Note: Mode 3: Transmit at channel 2412MHz by 802.11n(20MHz)	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	65.761	38.079	-8.239	74.000	27.682	PK
2	*	2411.360	97.935	70.167	N/A	N/A	27.767	PK



Engineer: Milo	Time: 2013/12/25 - 00:01
Site: AC1	
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-737(1-18GHz)	Polarity: Vertical
EUT: 2G Phone Tablet PC	Power: By battery


Note: Mode 3: Transmit at channel 2412MHz by 802.11n(20MHz)




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	43.590	15.908	-10.410	54.000	27.682	AV
2	*	2411.234	79.810	52.043	N/A	N/A	27.767	AV




Engineer: Milo	Time: 2013/12/25 - 00:02
Site: AC1	
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-737(1-18GHz)	Polarity: Horizontal
EUT: 2G Phone Tablet PC	Power: By battery
Note: Mode 3: Transmit at channel 2462MHz by 802.11n(20MHz)	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2461.648	97.647	69.672	N/A	N/A	27.975	PK
2		2483.500	63.916	35.859	-10.084	74.000	28.057	PK
3		2485.702	68.684	40.618	-5.316	74.000	28.066	PK




Engineer: Milo	Time: 2013/12/25 - 00:07
Site: AC1	
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-737(1-18GHz)	Polarity: Horizontal
EUT: 2G Phone Tablet PC	Power: By battery
Note: Mode 3: Transmit at channel 2462MHz by 802.11n(20MHz)	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2462.722	79.199	51.220	N/A	N/A	27.979	AV
2		2483.500	44.077	16.020	-9.923	54.000	28.057	AV



Engineer: Milo	Time: 2013/12/25 - 00:08
Site: AC1	
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-737(1-18GHz)	Polarity: Vertical
EUT: 2G Phone Tablet PC	Power: By battery
Note: Mode 3: Transmit at channel 2462MHz by 802.11n(20MHz)	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2461.396	96.476	68.502	N/A	N/A	27.974	PK
2		2483.500	63.543	35.486	-10.457	74.000	28.057	PK
3		2484.232	67.839	39.779	-6.161	74.000	28.060	PK



Engineer: Milo	Time: 2013/12/25 - 00:10
Site: AC1	
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-737(1-18GHz)	Polarity: Vertical
EUT: 2G Phone Tablet PC	Power: By battery

Note: Mode 3: Transmit at channel 2462MHz by 802.11n(20MHz)




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2461.294	78.231	50.258	N/A	N/A	27.973	AV
2		2483.500	42.725	14.668	-11.275	54.000	28.057	AV



4.6. Power Spectral Density Measurement

TEST CONFIGURATION



TEST PROCEDURE

The EUT was tested according to KDB558074 D01 v03r01 for compliance to FCC 47CFR 15.247 requirements.

Set RBW= 3 kHz, VBW \geq 10KHz, SPAN to 1.5 times greater than the EBW,.

LIMIT


For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

TEST RESULTS


Product	:	2G Phone Tablet PC
Test Item	:	Power Spectral Density
Test Site	:	TR-3
Test Mode	:	Mode 1: Transmit by 802.11b

Channel No.	Frequency (MHz)	PSD (dBm/3KHz)	Limit (dBm/3KHz)	Result
01	2412	-5.89	8	Pass
06	2437	-4.48	8	Pass
11	2462	-6.62	8	Pass


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




Product	:	2G Phone Tablet PC
Test Item	:	Power Spectral Density
Test Site	:	TR-3
Test Mode	:	Mode 2: Transmit by 802.11g


Channel No.	Frequency (MHz)	Reading Value (dBm/3KHz)	Limit (dBm/3KHz)	Result
01	2412	-10.83	8	Pass
06	2437	-11.05	8	Pass
11	2462	-10.54	8	Pass



Channel 06 (2437MHz)




Channel 11 (2462MHz)




Product	:	2G Phone Tablet PC
Test Item	:	Power Spectral Density
Test Site	:	TR-3
Test Mode	:	Mode 3: Transmit by 802.11n (20MHz)


Channel No.	Frequency (MHz)	PSD (dBm/3KHz)	Limit (dBm/3KHz)	Result
01	2412	-12.30	8	Pass
06	2437	-12.40	8	Pass
11	2462	-12.08	8	Pass



Channel 06 (2437MHz)




Channel 11 (2462MHz)



4.7. Spurious RF Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE


The EUT was tested according to KDB558074 D01 v03r01 for compliance to FCC 47CFR 15.247 requirements. The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10-2009 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=100kHz and VBM= 300KHz to measure the peak field strength , and measure frequeny range from 30MHz to 26.5GHz.

LIMIT


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

TEST RESULTS


Product	:	2G Phone Tablet PC
Test Item	:	RF Antenna Conducted Spurious
Test Site	:	TR-3
Test Mode	:	Mode 1: Transmit by 802.11b




Channel 06 (2437MHz)




Channel 11 (2462MHz)




Product	:	2G Phone Tablet PC
Test Item	:	RF Antenna Conducted Spurious
Test Site	:	TR-3
Test Mode	:	Mode 2: Transmit by 802.11g




Channel 06 (2437MHz)




Channel 11 (2462MHz)




Product	:	2G Phone Tablet PC
Test Item	:	RF Antenna Conducted Spurious
Test Site	:	TR-3
Test Mode	:	Mode 3: Transmit by 802.11n (20MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)



4.8. Operation Frequency Range of 20dB Bandwidth

TEST CONFIGURATION



TEST PROCEDURE


The EUT was tested according to KDB558074 D01 v03r01 for compliance to FCC 47CFR 15.247 requirements. Set RBW = 100 kHz, Span greater than RBW.


LIMIT

20 dB bandwidth of the emission is contained within the operation frequency band.



TEST RESULT

Product	:	2G Phone Tablet PC
Test Item	:	Operation Frequency Range of 20dB Bandwidth
Test Site	:	TR-3
Test Mode	:	Mode 1: Transmit by 802.11b







Product	:	2G Phone Tablet PC
Test Item	:	Operation Frequency Range of 20dB Bandwidth
Test Site	:	TR-3
Test Mode	:	Mode 2: Transmit by 802.11g



Product	:	2G Phone Tablet PC
Test Item	:	Operation Frequency Range of 20dB Bandwidth
Test Site	:	TR-3
Test Mode	:	Mode 3: Transmit by 802.11n (20MHz)



4.9. Antenna Requirement

STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.


And according to FCC 47 CFR Section 15.247 (c), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

Refer to statement below for compliance.

The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

ANTENNA CONNECTED CONSTRUCTION

The directional gains of antenna used for transmitting is -2.0 dBi, and the antenna connector is designed with permanent attachment and no consideration of replacement. Please see EUT photo for details.



4.10. RF Exposure

STANDARD APPLICABLE

According to § 1.1307 (b)(1), system operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

This is a portable device. Per KDB 447498 D01 v05, the device used distance is 5mm from body.

LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30


F= Frequency in MHz

MEASUREMENT RESULTS


Per KDB 447498 D01 V05

This is a bluetooth function and the Max peak output power is 9.66 dBm (9.25 mW) lower than low threshold 10 mW in general population category.

The SAR measurement is not necessary.



5. Test Setup Photos of the EUT





6. External and Internal Photos of the EUT



External Photos of EUT











Internal Photos of EUT







.....End of Report.....

