

Shenzhen CTL Electromagnetic Technology Co., Ltd. Tel: +86-755-89486194 Fax: +86-755-89486187

Analy Zhang Kendy Wang Lung Cri

FCC PART 15 SUBPART C TEST REPORT

FCC Part 15.249

Report Reference No...... CTL120508400-WF

Compiled by

(position+printed name+signature)..: File administrators Andy Zhang

Name of the organization performing

the tests

Test Engineer Kendy Wang

(position+printed name+signature)...

Approved by

(position+printed name+signature)..: Manager Tracy Qi

Date of issue...... May 21, 2012

Representative Laboratory Name .: Shenzhen CTL Electromagnetic Technology Co., Ltd.

Nanshan, Shenzhen 518055 China.

Test Firm...... Bontek Compliance Testing Laboratory Ltd

Road, Nanshan, Shenzhen, China

Applicant's name...... HongKong AtoB Co. Ltd.

Address....... The 1st Floor, Shisheng Building, Shangkeng Industrial District

Changping Town, DongGuan City, GuangDong, China

Test specification:

Standard FCC Part 15.249: Operation within the bands 920-928 MHz, 2400-

2483.5 MHz. 5725-5850 MHz and 24.0 - 24.25 GHz.

TRF Originator...... Shenzhen CTL Electromagnetic Technology Co., Ltd.

Master TRF...... Dated 2011-01

Shenzhen CTL Electromagnetic Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTL Electromagnetic Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTL Electromagnetic Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description: Bluetooth Handset

Trade Mark /

Models/Type reference...... TK5, TK6, TK7, TK8, IS-MP02, IS-MP03

Modulation GFSK

Work Frequency...... 2402 MHz~2480 MHz

Antenna Type...... PCB Antenna

FCC ID **Z79-TK5**

Result...... Positive

TEST REPORT

Test Report No. :	CTL120508400-WF	May 21, 2012
	C1L120300400-VVI	Date of issue

Equipment under Test : Bluetooth Handset

Model /Type : TK5

Listed Models : TK6, TK7, TK8, IS-MP02, IS-MP03

Applicant : HongKong AtoB Co. Ltd.

Address : The 1st Floor, Shisheng Building, Shangkeng Industrial

District Changping Town, DongGuan City, GuangDong,

Report No.: CTL120508400-WF

China

Manufacturer HongKong AtoB Co. Ltd.

Address The 1st Floor, Shisheng Building, Shangkeng Industrial

District Changping Town, DongGuan City, GuangDong,

China

Test Result according to the standards on page 4:	Positive
---	----------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Report No.: CTL120508400-WF

Contents

SUMMARY	
General Remarks	
Equipment Under Test	
Short description of the Equipment under Test (EUT) EUT operation mode	
EUT configuration	
Related Submittal(s) / Grant (s)	
Modifications	
TEST ENVIRONMENT	<u></u>
11 11	
Address of the test laboratory	
Test Facility	
Environmental conditions	
Configuration of Tested System Statement of the measurement uncertainty	
Equipments Used during the Test	
Equipments oded during the rest	
TEST CONDITIONS AND RESULTS	3
	ed.
Conducted Emissions Test	d.
Radiated Emission Test	3
Band Edge Measurement	7
3 200	5
TEST SETUP PHOTOS OF THE EUT	?.
EGI GEIGI IIIGIGG GI IIIE EGI IIIIIIIIII	

V1.0 Page 4 of 21 Report No.: CTL120508400-WF

1. TEST STANDARDS

The tests were performed according to following standards:

ANSI C63.4-2003



V1.0 Page 5 of 21 Report No.: CTL120508400-WF

2. <u>SUMMAR</u>Y

2.1. General Remarks

Date of receipt of test sample May 13, 2012

Testing commenced on May 15, 2012

Testing concluded on May 21, 2012

2.2. Equipment Under Test

Power supply system utilised

o 115V / 60Hz Power supply voltage 120V / 60 Hz

24 V DC

Other (specified in blank below)

DC 3.7V from battery

2.3. Short description of the Equipment under Test (EUT)

Wireless Bluetooth Handset work at 2400~2483.5 MHz.

For more details, refer to the user's manual of the EUT.

Serial number: Prototype

2.4. EUT operation mode

The EUT has been tested under typical operating condition.

2.5. EUT configuration

omagnetic Tech The following peripheral devices and interface cables were connected during the measurement:

o - supplied by the manufacturer

- supplied by the lab

Manufacturer: DELL Mouse

Model No.: MOC5UO

Manufacturer: DELL Notebook Computer

Model No.: PP26L

V1.0 Page 6 of 21 Report No.: CTL120508400-WF

2.6. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: **Z79-TK5** filing to comply with Section 15.249 of the FCC Part 15, Subpart C Rules.

2.7. Modifications

No modifications were implemented to meet testing criteria.



3. TEST ENVIRONMENT

3.1. Address of the test laboratory

Bontek Compliance Testing Laboratory Ltd 1/F, Block East H-3, OCT Eastern Ind. Zone, Qiaocheng East Road, Nanshan, Shenzhen, China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 (2003) and CISPR Publication 22.

3.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

IC Registration No.: 7631A

The 3m alternate test site of Bontek Compliance Testing Laboratory Ltd EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration NO.: 7631A on March, 2011.

FCC-Registration No.: 338263

Bontek Compliance Testing Laboratory Ltd EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 338263, March 24, 2008.

3.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges


Temperature: 15-35 ° C

Humidity: 30-60 %

Atmospheric pressure: 950-1050mbar

3.4. Configuration of Tested System

Fig. 2-1 Configuration of Tested System



3.5. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements" and is documented in the Bontek Compliance Testing Laboratory Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Bontek laboratory is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.10dB	(1)
Radiated Emission	1~12.75GHz	4.32dB	(1)
Conducted Disturbance	0.15~30MHz	3.20dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3.6. Equipments Used during the Test


Item	Test Equipment	Manufacturer	Model No.	Last Cal.	Due. Date
1	EMI Test Receiver	ROHDE & SCHWARZ	ESCI	2012/04/14	2013/04/13
2	Radio Communication Tester	ROHDE & SCHWARZ	CMU200	2012/04/14	2013/04/13
3	Dual Directional Coupler	Agilent	778D	2012/04/14	2013/04/13
4	10dB attenuator	SCHWARZBECK	MTAIMP-136	2012/04/14	2013/04/13
5	Tunable Bandreject filter	K&L	3TNF-800	2012/04/14	2013/04/13
6	Tunable Bandreject filter	K&L	5TNF-1700	2012/04/14	2013/04/13
7	High-Pass Filter	K&L	9SH10- 2700/X12750- O/O	2012/04/14	2013/04/13
8	High-Pass Filter	K&L Ctromagne	41H10- 1375/U12750- O/O	2012/04/14	2013/04/13
9	Coaxial Cable	Huber+Suhner	AC4-RF-H	2012/04/14	2013/04/13
10	AC Power Supply	IDRC	CF-500TP	2012/04/14	2013/04/13
11	DC Power Supply	IDRC	CD-035-020PR	2012/04/14	2013/04/13
12	RF Current Probe	FCC	F-33-4	2012/04/14	2013/04/13
13	Temperature /Humidity Meter	zhicheng	ZC1-2	2012/04/14	2013/04/13
14	MICROWAVE AMPLIFIER	HP	8349B	2012/04/14	2013/04/13
15	Amplifier	HP	8447D	2012/04/14	2013/04/13
16	SIGNAL GENERATOR	HP	8647A	2012/04/14	2013/04/13
17	Log Periodic Antenna	ELECTRO-METRICS	EM-6950	2012/04/14	2013/04/13
18	Horn Antenna	Schwarzbeck	BBHA9120A	2012/04/14	2013/04/13
19	EMI Test Receiver	R&S	ESPI	2012/04/14	2013/04/13
20	Loop Antenna	ZHINAN	ZN30900A	2012/04/14	2013/04/13
21	Horn Antenna	Schwarzbeck	BBHA9120D	2012/4/14	2013/04/13
22	Horn Antenna	Schwarzbeck	BBHA9170	2012/4/14	2013/04/13

V1.0 Page 9 of 21 Report No.: CTL120508400-WF

4. TEST CONDITIONS AND RESULTS

4.1. Conducted Emissions Test

TEST CONFIGURATION



TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4.
- 2 Support equipment, if needed, was placed as per ANSI C63.4.
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- 4 If a EUT received DC power from the USB Port of Notebook PC, the PC's adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

Conducted Power Line Emission Limit

For unintentional device, according to § 15.107(a) Line Conducted Emission Limits is as following:


F=====================================	Maximum RF Line Voltage (dBμV)				
Frequency (MHz)	CLASS A		C	CLASS B	
(141112)	Q.P.	Ave. Q.P.		Ave.	
0.15 - 0.50	79	66	66-56*	56-46*	
0.50 - 5.00	73	60	56	46	
5.00 - 30.0	73	60	60	50	

^{*} Decreasing linearly with the logarithm of the frequency

For intentional device, according to §15.207(a) Line Conducted Emission Limit is same as above table.

TEST RESULTS

SCAN TABLE: "Voltage (9K-30M) FIN" Short Description: 150K-30M Voltage




MEASUREMENT RESULT: "CTL120521304 fin"

5/21/2012 9	:34AM						
Frequency	Level	Transd	Limit	Margin	Detector	Line	PΕ
MHz	dBµV	dB	dΒμV	dB			
0.307500	54.70	10.2	60	5.3	QP	N	GND
0.591000	50.50	10.2	56	5.5	QP	N	GND
0.654000	46.90	10.2	56	9.1	QP	N	GND

MEASUREMENT RESULT: "CTL120521304_fin2"

5/21/2012	9:34	AM						
Freque	ency	Level	Transd	Limit	Margin	Detector	Line	PΕ
	MHz	dΒμV	dB	dΒμV	dB			
	. =							
0.289	9500	47.30	10.2	51	3.2	AV	N	GND
0.609	9000	40.00	10.2	46	6.0	AV	N	GND
0.613	3500	40.00	10.2	46	6.0	AV	N	GND

SCAN TABLE: "Voltage (9K-30M)FIN"
Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "CTL120521305 fin"

5/21/2012 9	:37AM						
Frequency MHz	_		Limit dBµV	Margin dB	Detector	Line	PE
0.316500 0.613500 0.937500	49.60	10.2 10.2 10.3	56	4.7 6.4 10.0	ÕР	L1 L1 L1	GND GND GND

MEASUREMENT RESULT: "CTL120521305 fin2"


5/21/2012 9	:37AM						
Frequency	Level	Transd	Limit	Margin	Detector	Line	PΕ
MHz	dΒμV	dB	dΒμV	dB			
0.289500	47.60	10.2	51	2.9	AV	L1	GND
0.609000	40.20	10.2	46	5.8	AV	L1	GND
0.613500	40.60	10.2	46	5.4	AV	L1	GND

V1.0 Page 12 of 21 Report No.: CTL120508400-WF


4.2. Radiated Emission Test

TEST CONFIGURATION


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

Radiation Limit

For unintentional device, according to § 15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency (MHz)	Distance (Meters)	Radiated (dBµV/m)	Radiated (μV/m)
// -	AVIANI	70 17 1	. ,
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500
N			

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table.

Test Procedure

- 1. The EUT is placed on a turntable, which is 0.8m above ground plane.
- 2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
- EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- 4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 6. Repeat above procedures until the measurements for all frequencies are complete.

Note:

Three axes are chosen for pretest, the Z axis is the worst mode for final test. For battery operated equipment, the equipment tests shall be performed using a new battery.


TEST RESULTS

Below 1GHz Test Results:

SWEEP TABLE: "test (30M-1G)"
Short Description: Fi

, Field Strength Detector Meas. Stop ÍF Transducer Start Bandw. Frequency Frequency Time

1.0 GHz Coupled 30.0 MHz MaxPeak 100 kHz VULB9163 NEW




MEASUREMENT RESULT: "CTL051512 red"

5/15/2012 18: Frequency MHz	36 Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
243.400000	34.80	17.0	46.0	11.2		100.0	0.00	VERTICAL
425.760000	40.80	22.0	46.0	5.2		100.0	0.00	VERTICAL
567.380000	41.20	25.3	46.0	4.8		100.0	0.00	VERTICAL
664.380000	38.20	26.3	46.0	7.8		100.0	0.00	VERTICAL
712.880000	38.10	26.7	46.0	7.9		100.0	0.00	VERTICAL
928.220000	44.10	29.4	46.0	1.9		100.0	0.00	VERTICAL



SWEEP TABLE: "test (30M-1G)"
Short Description: Fi Field Strength Start Stop Detector Meas. ΙF

Transducer Frequency Frequency Time Bandw. 30.0 MHz 1.0 GHz MaxPeak Coupled 100 kHz VULB9163 NEW



MEASUREMENT RESULT: "CTL051513_red"

5/15/2012	18:40							
Frequenc MH	4	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
264.74000	0 34.30	17.5	46.0	11.7		100.0	0.00	HORIZONTAL
284.14000	0 39.50	18.3	46.0	6.5		100.0	0.00	HORIZONTAL
332.64000	0 35.20	19.8	46.0	10.8		100.0	0.00	HORIZONTAL
427.70000	0 40.20	22.0	46.0	5.8		100.0	0.00	HORIZONTAL
712.88000	0 39.30	26.7	46.0	6.7		100.0	0.00	HORIZONTAL
928.22000	0 37.90	29.4	46.0	8.1		100.0	0.00	HORIZONTAL

Remark:

- Measuring frequencies from 9 KHz to the 1 GHz, Loop Antenna used below 30MHz. (1) See Section 3.6 table item 20.
- (2)* denotes emission frequency which appearing within the Restricted Bands specified in provision of 15.205, then the general radiated emission limits in 15.209 apply.
- The IF bandwidth of EMI Test Receiver was 120KHz for measuring from 30 MHz to 1 (3)GHz and 1 MHz for measuring above 1 GHz. Below 30MHz was 10KHz.

V1.0 Page 16 of 21 Report No.: CTL120508400-WF

Above 1 GHz Test Results:

Top Channel

Freq.	Ant.Pol.	DetectorMode	e Reading	Ant./CL/	Actual FS	Limit3m	Safe Margin	Note
(MHz)	H/V	(PK/AV)	(dBuV)	Amp. CF(dB	(dBuV/m)	(dBuV/m)	(dB)	
2480	V	Peak	76.48	-3.30	73.18	93.98	-20.80	F
2480	Н	Peak	70.62	-3.30	67.32	93.98	-26.66	F
4960	V	Peak	48.90	3.90	52.80	73.98	-21.18	Н
4960	Н	Peak	42.49	3.90	46.39	73.98	-27.59	Н
7440	V							Н
7440	Н							Н
Others								

Middle Channel:

Freq.	Ant.Pol.	DetectorMode	Reading	Ant./CL/	Actual FS	Limit3m	Safe Margin	Note
(MHz)	H/V	(PK/AV)	(dBuV)	Amp. CF(dB)	(dBuV/m)	(dBuV/m)	(dB)	
2441	V	Peak	74.69	-3.40	71.29	93.98	-22.69	F
2441	Н	Peak	68.70	-3.40	65.30	93.98	-28.68	F
4882	V	Peak	47.63	3.70	51.33	73.98	-22.65	H
4882	Н	Peak	40.51	3.70	44.21	73.98	-29.77	Н
7323	V	00		MIN				H
7323	Н	3 A	10			3		Н
Others		0	TANK T		I WE			

E CONTRACTOR S

Bottom Channel:

Freq.	Ant.Pol.	DetectorMode	e Reading	Ant./CL/	Actual FS	Limit3m	Safe Margin	Note
(MHz)	H/V	(PK/AV)	(dBuV)	Amp. CF(dE	(dBuV/m)	(dBuV/m)	(dB)	
2402	V	Peak	73.85	-3.50	70.35	93.98	-23.63	F
2402	Н	Peak	65.83	-3.50	62.33	93.98	-31.65	F
4804	V	Peak	46.65	3.80	50.45	73.98	-23.53	Н
4804	Н	Peak	38.22	3.80	42.02	73.98	-31.96	Н
7206	V			ragile				H
7206	Н							Н
Others								

Remark:

- (1) Measuring frequencies from 1 GHz to the 25 GHz, Horn Antenna used above 1 GHz. See Section 3.6 table item 18 and 21.
- (2) "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency.
- (3) * denotes emission frequency which appearing within the Restricted Bands specified in provision of 15.205, then the general radiated emission limits in 15.209 apply.
- (4) Data of measurement within this frequency range shown "--- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) The IF bandwidth of EMI Test Receiver was 120KHz for measuring from 30 MHz to 1 GHz and 1 MHz for measuring above 1 GHz

4.3. Band Edge Measurement

TEST CONFIGURATION

Same as Section 4.2

TEST PROCEDURE

The band edge compliance of RF radiated emission should be measured by following the guidance in ANSI C63.4 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW to 100KHz and VBM to 300KHz to measure the peak field strength and set RBW to 1MHz and VBW to 10Hz to measure the average radiated field strength.


The conducted RF band edge was measured by using a spectrum analyzer. Set span wide enough to capture the highest in-band emission and the emission at the band edge. Set RBW to 100 KHz and VBM to 300 KHz, to measure the conducted peak band edge.

LIMIT


FCC PART 15.249(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

TEST RESULTS

Band-Edge Compliance: 2310MHz - 2390MHz Restricted Band, Low Channel,



Band-Edge: 2483.5MHz - 2500MHz Restricted Band, High Channel



Note:

- 1. The field strength of any emissions which appear outside of this band shall not exceed the general radiated emission limits in Section 15.209.
- 2. The average measurement was not performed when the peak measured data under the limit of average detection.

5. Test Setup Photos of the EUT







6. External and Internal Photos of the EUT

External Photos



Internal Photos







.....End of Report.....