RF
TEST REPORT

ISSUED BY Shenzhen BALUN Technology Co., Ltd.




FOF

Card Printer

ISSUED TO

Jiangmen Dascom Computer Peripherals Co., Ltd.

No.399, Jin Xing Road, Jiang Hai District, Jiangmen City, Guang Dong Province, P.R. China





Report No.: BL-SZ1920155-401

EUT Name: Card Printer

Model Name: DC-3300 (refer section 2.4)
Brand Name: TALLY/DASCOM, DASCOM

Test Standard: 47 CFR Part 15 Subpart C

FCC ID: Z7ODC3300

Test Conclusion: Pass

Test Date: Feb. 21, 2019 ~ Apr. 08, 2019

Date of Issue: Apr. 09, 2019

NOTE: This test report of test results only related to testing samples, which can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen BALUN Technology Co., Ltd. Any objections should be raised within thirty days from the date of issue. To validate the report, please contact us.



Revision History

VersionIssue DateRevisions ContentRev. 01Mar. 11, 2019Initial IssueRev. 02Apr. 09, 2019Update the Frequency Stability Test in

section 5.4 and Conducted Emissions
Test in section 5.5 and test data in

ANNEX A TEST RESULT

TABLE OF CONTENTS

1	AD	MINISTRATIVE DATA (GENERAL INFORMATION)	4
	1.1	Identification of the Testing Laboratory	4
	1.2	Identification of the Responsible Testing Location	4
	1.3	Laboratory Condition	4
	1.4	Announce	4
2	PR	ODUCT INFORMATION	5
	2.1	Applicant Information	5
	2.2	Manufacturer Information	5
	2.3	Factory Information	5
	2.4	General Description for Equipment under Test (EUT)	5
	2.5	Ancillary Equipment	6
	2.6	Technical Information	6
3	SU	MMARY OF TEST RESULTS	7
	3.1	Test Standards	7
	3.2	Verdict	7
4	GE	NERAL TEST CONFIGURATIONS	8
	4.1	Test Environments	8
	4.2	Test Equipment List	8
	4.3	Description of Test Setup	9
	4.3	.1 For Radiated Test (Below 30 MHz)	9
	4.3	.2 For Radiated Test (30 MHz-1 GHz)	9
	4.3	.3 For AC Power Supply Port Test	10
5	TES	ST ITEMS	11
	5.1	Antenna Requirements	11
	5.1	.1 Relevant Standards	11



5.1	.2	Antenna Anti-Replacement Construction	12
5.2	Emi	ssion Bandwidth	13
5.2	.1	Definition	13
5.2	2	Test Setup	13
5.2	3	Test Procedure	13
5.2	.4	Test Result	14
5.3	Fiel	d Strength of Fundamental Emissions and Radiated Emissions	15
5.3	.1	Limit	15
5.3	.2	Test Setup	16
5.3	.3	Test Procedure	16
5.3	.4	Test Result	16
5.4	Free	quency Tolerance	17
5.4	.1	Limit	17
5.4	.2	Test Setup	17
5.4	.3	Test Procedure	17
5.4	.4	Test Result	17
5.5	Cor	nducted Emission	18
5.5	5.1	Limit	18
5.5	.2	Test Setup	18
5.5	.3	Test Procedure	18
5.5	.4	Test Result	18
ANNEX	Α	TEST RESULT	19
A.1	Emi	ssion Bandwidth	19
A.2	Fiel	d Strength of Fundamental Emissions	20
A.3	Rac	liated Emissions	21
A.4	Free	quency Stability	24
A.5	Cor	nducted Emissions	25
ANNEX	C	TEST SETUP PHOTOS	29
ANNEX	D	EUT EXTERNAL PHOTOS	29
ANNEX	Έ	EUT INTERNAL PHOTOS	29



1 ADMINISTRATIVE DATA (GENERAL INFORMATION)

1.1 Identification of the Testing Laboratory

Company Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road,
Address	Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Identification of the Responsible Testing Location

dentification of the Responsible resting Location			
Test Location	Shenzhen BALUN Technology Co., Ltd.		
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road,		
Address	Nanshan District, Shenzhen, Guangdong Province, P. R. China		
	The laboratory has been listed by Industry Canada to perform		
	electromagnetic emission measurements. The recognition numbers of		
	test site are 11524A-1.		
	The laboratory is a testing organization accredited by FCC as a		
Accreditation	accredited testing laboratory. The designation number is CN1196.		
Certificate	The laboratory is a testing organization accredited by American		
Certificate	Association for Laboratory Accreditation(A2LA) according to ISO/IEC		
	17025.The accreditation certificate is 4344.01.		
	The laboratory is a testing organization accredited by China National		
	Accreditation Service for Conformity Assessment (CNAS) according to		
	ISO/IEC 17025. The accreditation certificate number is L6791.		
	All measurement facilities used to collect the measurement data are		
Description	located at Block B, FL 1, Baisha Science and Technology Park, Shahe		
Description	Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R.		
	China 518055		

1.3 Laboratory Condition

Ambient Temperature	20°C to 25°C
Ambient Relative Humidity	45% to 55%
Ambient Pressure	100 kPa to 102 kPa

1.4 Announce

- (1) The test report reference to the report template version v6.2.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
- (5) This document may not be altered or revised in any way unless done so by BALUN and all revisions are duly noted in the revisions section.
- (6) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.



2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant Jiangmen Dascom Computer Peripherals Co., Ltd.	
A ddroop	No.399, Jin Xing Road, Jiang Hai District, Jiangmen City, Guang
Address	Dong Province, P.R. China

2.2 Manufacturer Information

	Manufacturer	Jiangmen Dascom Computer Peripherals Co., Ltd.
	Addraga	No.399, Jin Xing Road, Jiang Hai District, Jiangmen City, Guang
	Address	Dong Province, P.R. China

2.3 Factory Information

Factory	Jiangmen Dascom Computer Peripherals Co., Ltd.	
Addross	No.399, Jin Xing Road, Jiang Hai District, Jiangmen City, Guang	
Address	Dong Province, P.R. China	

2.4 General Description for Equipment under Test (EUT)

EUT Name	Card Printer
Under Test Model Name	DC-3300
Series Model Name	DC-3350, DC-340, DC-350
Description of Model	All models are same with electrical parameters and internal circuit
name differentiation	structure, but only different on model number.
Hardware Version	27011217
Software Version	DC-3300v01.01.00.00
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A



2.5 Ancillary Equipment

	Adapter	
	Brand Name	N/A
Ancillary Equipment 1	Model No.	GST120A24
	Serial No.	N/A
	Rated Input	100-240 V~, 50 / 60 Hz, Max. 1.4A
	Rated Output	24 V= 5 A
Ancillary Equipment 2	Power Line	
Ancillary Equipment 2	Length (Approx.)	1.5 m
Ancillant Fauinment 2	USB Cable	
Ancillary Equipment 3	Length (Approx.)	1.5 m

2.6 Technical Information

Network and Wireless	RFID
connectivity	מו וט

The requirement for the following technical information of the EUT was tested in this report:

Modulation Type	ASK
	☐ Mobile
Product Type	☐ Portable
Frequency Range	13.56 MHz
Receiver	3
Categorization	3
Number of channel	1
Tested Channel	1
Antenna Type	PCB Antenna



3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title		
	47 CFR Part 15,			
1	Subpart C	Miscellaneous Wireless Communications Services		
	(10-1-17 Edition)			
2	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless		
2	ANSI C03. 10-2013	Devices		

3.2 Verdict

No.	Description	FCC Part No.	Test Result	Verdict
1	Antenna Requirement	15.203	-	Pass Note
2	Emissions Bandwidth	15.215	ANNEX A.1	Pass
3	Field Strength of Fundamental Emissions	15.225(a)	ANNEX A.2	Pass
4	Radiated Emissions	15.225(d) 15.209	ANNEX A.3	Pass
5	Frequency Stability	15.225(e)	ANNEX A.4	Pass
6	Conducted Emission	15.207	ANNEX A.5	Pass

Note: The EUT has a permanently and irreplaceable attached antenna, which complies with the requirement FCC 15.203 & RSS-Gen 8.3.



4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	45% to 55%	
Atmospheric Pressure	100 kPa to 102 kPa	
Temperature	NT (Normal Temperature)	+22°C to +25°C
Working Voltage of the EUT	NV (Normal Voltage)	120 V


4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	ROHDE&SCHWARZ	FSV-30	103118	2018.06.11	2019.06.10
Vector Signal Generator	ROHDE&SCHWARZ	SMBV100A	260592	2018.06.11	2019.06.10
Signal Generator	ROHDE&SCHWARZ	SMB100A	177746	2018.06.11	2019.06.10
Switch Unit with OSP- B157	ROHDE&SCHWARZ	OSP120	101270	2018.06.11	2019.06.10
Spectrum Analyzer	AGILENT	E4440A	MY45304434	2018.11.06	2019.11.05
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2018.06.13	2019.06.12
LISN	SCHWARZBECK	NSLK 8127	8127-687	2018.06.13	2019.06.12
Bluetooth Tester	ROHDE&SCHWARZ	CBT	101005	2018.06.11	2019.06.10
Power Splitter	KMW	DCPD-LDC	1305003215	-	
Power Sensor	ROHDE&SCHWARZ	NRP-Z21	103971	2018.06.11	2019.06.10
Attenuator (20 dB)	KMW	ZA-S1-201	110617091		
Attenuator (6 dB)	KMW	ZA-S1-61	1305003189		
DC Power Supply	ROHDE&SCHWARZ	HMP2020	018141664	2018.06.21	2019.06.20
Temperature Chamber	ANGELANTIONI SCIENCE	NTH64-40A	1310	2018.06.26	2019.06.25
Test Antenna- Rod(9 kHz-30 MHz)	SCHWARZBECK	VAMP 9243	9243-556	2017.11.07	2019.11.08
Test Antenna- Loop(9 kHz-30 MHz)	SCHWARZBECK	FMZB 1519	1519-037	2017.07.22	2019.07.21
Test Antenna- Bi-Log(30 MHz-3 GHz)	SCHWARZBECK	VULB 9163	9163-624	2018.07.11	2019.07.10
Test Antenna- Horn(1-18 GHz)	SCHWARZBECK	BBHA 9120D	9120D-1148	2018.06.21	2019.06.20
Test Antenna- Horn(15-26.5 GHz)	SCHWARZBECK	BBHA 9170	9170-305	2018.06.21	2019.06.20
Anechoic Chamber	EMC TECHNOLOGY LTD	21.1m*11.6 m*7.35m	N/A	2017.02.21	2020.02.20
Shielded Enclosure	ChangNing	CN-130701	130703		
Test Software	BALUN	BL410_E	V18.626		




4.3 Description of Test Setup

4.3.1 For Radiated Test (Below 30 MHz)



(Diagram 1)


4.3.2 For Radiated Test (30 MHz-1 GHz)



(Diagram 2)



4.3.3 For AC Power Supply Port Test



(Diagram 3)



5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Relevant Standards

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

RSS-Gen 6.8

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer. The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

This radio transmitter [enter the device's ISED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.


Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.



5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is embedded in the product.	An embedded-in antenna design is used.





5.2 Emission Bandwidth

5.2.1 Definition

15.215(c);

Intentional radiators operating under the alternative provisions to the general emission limits must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

RSS-Gen 6.7

The occupied bandwidth or the "99% emission bandwidth" is defined as the frequency range between two points, one above and the other below the carrier frequency, within which 99% of the total transmitted power of the fundamental transmitted emission is contained. The occupied bandwidth shall be reported for all equipment in addition to the specified bandwidth required in the applicable RSSs.

In some cases, the "x dB bandwidth" is required, which is defined as the frequency range between two points, one at the lowest frequency below and one at the highest frequency above the carrier frequency, at which the maximum power level of the transmitted emission is attenuated x dB below the maximum in-band power level of the modulated signal, where the two points are on the outskirts of the in-band emission.

The following conditions shall be observed for measuring the occupied bandwidth and x dB bandwidth:

- The transmitter shall be operated at its maximum carrier power measured under normal test conditions.
- The span of the spectrum analyzer shall be set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.
- The detector of the spectrum analyzer shall be set to "Sample". However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or "Max Hold") may be necessary to determine the occupied / x dB bandwidth if the device is not transmitting continuously.
- The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the actual occupied / x dB bandwidth and the video bandwidth (VBW) shall not be smaller than three times the RBW value. Video averaging is not permitted.

Note: It may be necessary to repeat the measurement a few times until the RBW and VBW are in compliance with the above requirement.

For the 99% emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99% emission bandwidth).

5.2.2 Test Setup

See section 4.1.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.2.3 Test Procedure

The 20dB bandwidth is measured with a spectrum analyzer connected via a receiver antenna placed near the EUT



while the EUT is operating in transmission mode.

Use the following spectrum analyzer settings:

Span = approximately 2 to 3 times the 20 dB bandwidth

RBW ≥ 1% of the 20 dB bandwidth & RBW = 1% to 5% OBW

VBW ≥ RBW & VBW = 3* RBW

Sweep = auto

Detector function = peak

Trace = max hold

5.2.4 Test Result

Please refer to ANNEX A.1



5.3 Field Strength of Fundamental Emissions and Radiated Emissions

5.3.1 Limit

FCC §15.225(a), (b), (c); RSS-210 B.6

According to FCC section 15.225, for <30 MHz, Radiated emissions were measured according to ANSI C63.4. The EUT was set to transmit at the highest output power. The EUT was set 10 meter away from the measuring antenna. The loop antenna was positioned 1 meter above the ground from the center of the loop. The measuring bandwidth was set to 10 KHz. (Note: During testing the receive antenna was rotated about its axis to maximize the emission from the EUT)

There was no detected Restricted bands and Radiated suprious emission below 30MHz. The 30m limit was converted to 3m Limit using square factor(x) as it was found by measurements as follows; 3 m Limit(dBuV/m) = $20\log(X)+40\log(30/3)=20\log(15848)+40\log(30/3)=124dBuV$

Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Erogueney rango (MUz)	Field Stren	gth@30m	Field Strength@10m	Field Strength@3m
Frequency range (MHz)	μV/m	dBµV/m	dBμV/m	dBµV/m
Below 13.110	30	29.5	48.58	69.5
13.110 ~ 13.410	106	40.5	59.58	80.5
13.410 ~ 13.553	334	50.5	69.58	90.5
13.553 ~13.567	15848	84	103.08	124
13.567 ~ 13.710	334	50.5	69.58	90.5
13.710 ~14.010	106	40.5	59.58	80.5
Above 14.010	30	29.5	48.58	69.5

NOTE:

- 1. Field Strength ($dB\mu V/m$) = 20*log[Field Strength ($\mu V/m$)].
- 2. In the emission tables above, the tighter limit applies at the band edges.

FCC §15.225(d)

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μV/m)
0.009 - 0.490	2400/F(kHz)
0.490 - 1.705	24000/F(kHz)
1.705 - 30.0	30
30 - 88	100
88 - 216	150
216 - 960	200
Above 960	500



Note:

- 1. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit.
- 2. For above 1000 MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).

5.3.2 Test Setup

See section 4.1.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented. The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \ge 1$ GHz, 100 kHz for f < 1 GHz

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

5.3.4 Test Result

Please refer to ANNEX A.2

NOTE:

1. Results (dBuV/m) = Reading (dBuV) + Factor (dB/m)

The reading level is calculated by software which is not shown in the sheet

- 2. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) Amplifier Gain (dB)
- 3. Over limit = Results Limit.



5.4 Frequency Tolerance

5.4.1 Limit

FCC §15.225(e)

The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

RSS-210 B.6

- (a) at the temperatures of -30°C (-22°F), +20°C (+68°F) and +50°C (+122°F), and at the manufacturer's rated supply voltage; and
- (b) at the temperature of +20° C (+68° F) and at $\pm 15\%$ of the manufacturer's rated supply voltage.

If the frequency stability limits are only met within a temperature range that is smaller than the -30° C to +50° C range specified in (a), the frequency stability requirement will be deemed to be met if the transmitter is automatically prevented from operating outside this smaller temperature range and if the published operating characteristics for the equipment are revised to reflect this restricted temperature range.

5.4.2 Test Setup

See section 4.1.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

- 1. The test is performed in a Temperature Chamber.
- The EUT is configured as MS + DC Power Supply.

5.4.4 Test Result

Please refer to ANNEX A.4.



5.5 Conducted Emission

5.5.1 Limit

FCC §15.207; RSS-Gen

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a $50\mu\text{H}/50\Omega$ line impedance stabilization network (LISN).

Frequency range	Conducted Limit (dBµV)				
(MHz)	Quai-peak	Average			
0.15 - 0.50	66 to 56	56 to 46			
0.50 - 5	56	46			
0.50 - 30	60	50			

5.5.2 Test Setup

See section 4.1.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.5.4 Test Result

Please refer to ANNEX A.5.

NOTE:

1. Results (dBuV/m) = Reading (dBuV) + Factor (dB/m)

The reading level is calculated by software which is not shown in the sheet

- 2. Factor = Insertion loss + Cable loss
- 3. Over limit = Results Limit.



ANNEX A TEST RESULT


A.1 Emission Bandwidth

Test Data

Frequency	Emission Bandwidth(20dB down)	Occupied Bandwidth(99%)
(MHz)	(kHz)	(kHz)
13.56	24.834	21.099


Test plots

Emission Bandwidth



Date: 26.FEB.2019 20:25:54

99% Occupied Bandwidth



Date: 26.FEB.2019 20:26:46




A.2 Field Strength of Fundamental Emissions

Test Data

Field Strength of Fundamental Emissions Value							
Frequency (MHz)	Detector	Field Strength (dBuV/m)	Limit @10m (dBuV/m)	Antenna	Margin (dB)		
13.56	PEAK	56.42	103.0	Vertical	46.58		

Test Plot






A.3 Radiated Emissions

Note: This frequency which near 13.560 MHz with circle should be ignored because they are NFC carrier frequency.


The Data and Plots (9 kHz ~ 30 MHz)(at 10m chamber)



No.	Frequency	Results	Factor (dB)	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(0)	(cm)		
1	0.028	49.98	20.20	97.7	-47.72	Peak	356.00	100	V	Pass
2	0.396	39.63	20.18	74.7	-35.07	Peak	289.00	100	V	Pass
3	0.725	37.00	20.41	49.4	-12.40	Peak	210.00	100	V	Pass
4	5.127	33.12	20.81	48.5	-15.38	Peak	60.00	100	V	Pass
5	13.560	56.26	20.86	48.5	7.76	Peak	325.00	100	V	N/A
6	19.888	32.86	21.15	48.5	-15.64	Peak	254.00	100	V	Pass




Test Data and Plots (30 MHz ~ 1 GHz)



No.	Frequency	Results	Factor (dB)	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(0)	(cm)		
1	40.670	23.40	-26.79	30.0	-6.60	Peak	249.00	200	V	Pass
2	128.212	25.90	-27.34	33.5	-7.60	Peak	67.00	300	V	Pass
3	257.707	23.91	-27.26	36.0	-12.09	Peak	275.00	100	V	Pass
4	299.902	23.13	-25.89	36.0	-12.87	Peak	199.00	100	V	Pass
5	398.358	25.79	-23.21	36.0	-10.21	Peak	359.00	300	V	Pass
6	597.450	31.95	-17.74	36.0	-4.05	Peak	180.00	300	٧	Pass





No.	Frequency	Results	Factor (dB)	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(o)	(cm)		
1	198.295	23.97	-29.47	33.5	-9.53	Peak	41.00	300	Н	Pass
2	249.947	28.42	-27.39	36.0	-7.58	Peak	161.00	300	Н	Pass
3	398.358	32.09	-23.21	36.0	-3.91	Peak	180.00	200	Н	Pass
4	516.213	25.03	-20.34	36.0	-10.97	Peak	243.00	200	Н	Pass
5	599.633	31.19	-18.21	36.0	-4.81	Peak	23.00	200	Н	Pass
6	998.787	30.90	-11.36	44.0	-13.10	Peak	211.00	100	Н	Pass



A.4 Frequency Stability

OPERATING FREQUENCY:	13560000 Hz
REFERENCE VOLTAGE:	120V
DEVIATION LIMIT:	±0.01%

VOLTAGE	Test	Conditions			
VOLTAGE (%)	Power (VDC)	Temperature (°C)	Frequency(MHz)	Deviation(ppm)	Verdict
100		+20°C(Ref)	13.560421	0.0031%	
100		-30	13.560421	0.0031%	
100		-20	13.560366	0.0027%	
100		-10	13.559071	0.0068%	
100		0	13.559199	0.0059%	
100	120	+10	13.560612	0.0045%	
100		+20	13.558952	0.0077%	
100		+25	13.559267	0.0054%	
100		+30	13.559289	0.0052%	Pass
100		+40	13.560800	0.0059%	
100		+50	13.560658	0.0049%	
MAX(Battery End Point, 85)	102	+20	13.560357	0.0026%	
MIN(Battery End Point, 115)	138	+20	13.559477	0.0039%	




A.5 Conducted Emissions

Note 1: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 60 Hz and 240 VAC, 50 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz) shown here.

Note 2: This frequency which near 13.560 MHz with circle should be ignored because they are NFC carrier frequency.


Note 3: After removing the NFC antenna and replacing it with a corresponding impedance, test result is pass.

Test Data and Plots (Original state)



No.	Frequency	Results	Factor (dB)	Limit	Over	Detector	Line	Verdict
	(MHz)	(dBuV)		(dBuV)	Limit			
					(dB)			
1	0.164	44.7	10.01	65.3	-20.60	Peak	L Line	Pass
1**	0.164	37.5	10.01	55.3	-17.80	AV	L Line	Pass
2	0.326	41.0	10.03	59.6	-18.60	Peak	L Line	Pass
2**	0.326	37.0	10.03	49.6	-12.60	AV	L Line	Pass
3	0.982	32.1	10.03	56.0	-23.90	Peak	L Line	Pass
3**	0.982	22.1	10.03	46.0	-23.90	AV	L Line	Pass
4	12.354	43.5	10.19	60.0	-16.50	Peak	L Line	Pass
4**	12.354	29.9	10.19	50.0	-20.10	AV	L Line	Pass
5	13.558	80.7	10.19	60.0	20.70	Peak	L Line	N/A
5**	13.558	77.1	10.19	50.0	27.10	AV	L Line	N/A
6	27.120	34.9	10.32	60.0	-25.10	Peak	L Line	Pass
6**	27.120	27.3	10.32	50.0	-22.70	AV	L Line	Pass






No.	Frequency	Results	Factor (dB)	Limit	Over	Detector	Line	Verdict
	(MHz)	(dBuV)		(dBuV)	Limit			
					(dB)			
1	0.164	45.0	10.01	65.3	-20.30	Peak	N Line	Pass
1**	0.164	38.1	10.01	55.3	-17.20	AV	N Line	Pass
2	0.326	41.2	10.03	59.6	-18.40	Peak	N Line	Pass
2**	0.326	38.9	10.03	49.6	-10.70	AV	N Line	Pass
3	7.736	37.2	10.15	60.0	-22.80	Peak	N Line	Pass
3**	7.736	21.9	10.15	50.0	-28.10	AV	N Line	Pass
4	12.232	47.9	10.19	60.0	-12.10	Peak	N Line	Pass
4**	12.232	34.4	10.19	50.0	-15.60	AV	N Line	Pass
5	13.560	82.1	10.19	60.0	22.10	Peak	N Line	N/A
5**	13.560	78.3	10.19	50.0	28.30	AV	N Line	N/A
6	27.120	35.0	10.32	60.0	-25.00	Peak	N Line	Pass
6**	27.120	27.9	10.32	50.0	-22.10	AV	N Line	Pass



Test Data and Plots (After removiong the NFC antenna state)




Freq	uency	(MHz

No.	Frequency	Results	Factor (dB)	Limit	Over	Detector	Line	Verdict
	(MHz)	(dBuV)		(dBuV)	Limit			
					(dB)			
1	0.170	41.9	10.01	65.0	-23.10	Peak	L Line	Pass
1**	0.170	38.2	10.01	55.0	-16.80	AV	L Line	Pass
2	0.316	38.0	10.03	59.8	-21.80	Peak	L Line	Pass
2**	0.316	33.1	10.03	49.8	-16.70	AV	L Line	Pass
3	0.342	42.2	10.03	59.2	-17.00	Peak	L Line	Pass
3**	0.342	40.1	10.03	49.2	-9.10	AV	L Line	Pass
4	2.606	30.6	10.08	56.0	-25.40	Peak	L Line	Pass
4**	2.606	19.4	10.08	46.0	-26.60	AV	L Line	Pass
5	12.410	42.7	10.19	60.0	-17.30	Peak	L Line	Pass
5**	12.410	32.6	10.19	50.0	-17.40	AV	L Line	Pass
6	25.228	31.4	10.31	60.0	-28.60	Peak	L Line	Pass
6**	25.228	20.1	10.31	50.0	-29.90	AV	L Line	Pass



PHASE N



					, , , , , ,			
No.	Frequency	Results	Factor (dB)	Limit	Over	Detector	Line	Verdict
	(MHz)	(dBuV)		(dBuV)	Limit			
					(dB)			
1	0.172	43.3	10.01	64.9	-21.60	Peak	N Line	Pass
1**	0.172	38.3	10.01	54.9	-16.60	AV	N Line	Pass
2	0.312	38.2	10.03	59.9	-21.70	Peak	N Line	Pass
2**	0.312	36.0	10.03	49.9	-13.90	AV	N Line	Pass
3	0.340	42.9	10.03	59.2	-16.30	Peak	N Line	Pass
3**	0.340	40.9	10.03	49.2	-8.30	AV	N Line	Pass
4	0.966	31.5	10.03	56.0	-24.50	Peak	N Line	Pass
4**	0.966	26.3	10.03	46.0	-19.70	AV	N Line	Pass
5	4.148	31.3	10.10	56.0	-24.70	Peak	N Line	Pass
5**	4.148	20.1	10.10	46.0	-25.90	AV	N Line	Pass
6	12.352	47.7	10.19	60.0	-12.30	Peak	N Line	Pass
6**	12.352	37.2	10.19	50.0	-12.80	AV	N Line	Pass



ANNEX B TEST SETUP PHOTOS

Please refer the document "BL-SZ1920155-AE.PDF".

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document "BL-SZ1920155--AW.PDF".

ANNEX D EUT INTERNAL PHOTOS

Please refer the document "BL-SZ1920155--AI.PDF".

--END OF REPORT--