ABBA INNOVATION S.A.S

MOBILE PHONE

Main Model: 5300

Serial Model: 5130, A1, A2, A3, A5, A7, A6, A8

March 15, 2013

Report No.: 13070052-FCC-R2 (This report supersedes NONE)



Modifications made to the product: None This Test Report is Issued Under the Authority of: Alan Lv Alex Liu **Compliance Engineer Technical Manager**

This test report may be reproduced in full only. Test result presented in this test report is applicable to the representative sample only.





Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 2 of 62

Laboratory Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to <u>testing</u> and <u>certification</u>, SIEMIC provides initial design reviews and <u>compliance</u> <u>management</u> through out a project. Our extensive experience with <u>China</u>, <u>Asia Pacific</u>, <u>North America</u>, <u>European</u>, <u>and international</u> compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Accreditation Body	Scope		
USA	FCC, A2LA	EMC, RF/Wireless, Telecom		
Canada	IC, A2LA, NIST	EMC, RF/Wireless, Telecom		
Taiwan	BSMI , NCC , NIST	EMC, RF, Telecom, Safety		
Hong Kong	OFTA , NIST	RF/Wireless ,Telecom		
Australia	NATA, NIST	EMC, RF, Telecom, Safety		
Korea	KCC/RRA, NIST	EMI, EMS, RF, Telecom, Safety		
Japan	VCCI, JATE, TELEC, RFT	EMI, RF/Wireless, Telecom		
Mexico	NOM, COFETEL, Caniety	Safety, EMC, RF/Wireless, Telecom		
Europe	A2LA, NIST	EMC, RF, Telecom, Safety		

Accreditations for Product Certifications

Country/Region	Accreditation Body	Scope
USA	FCC TCB, NIST	EMC, RF, Telecom
Canada	IC FCB , NIST	EMC, RF, Telecom
Singapore	iDA, NIST	EMC, RF, Telecom
EU	NB	EMC & R&TTE Directive
Japan	MIC, (RCB 208)	RF, Telecom
Hong Kong	OFTA (US002)	RF, Telecom



Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 3 of 62

This page has been left blank intentionally.



Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 4 of 62

CONTENTS

1	EXECUTIVE SUMMARY & EUT INFORMATION	5
2	TECHNICAL DETAILS	6
3	MODIFICATION	7
4	TEST SUMMARY	8
5	MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	9
ANI	NEX A. TEST INSTRUMENT & METHOD	39
ANI	NEX B. EUT AND TEST SETUP PHOTOGRAPHS	45
ANI	NEX C. TEST SETUP AND SUPPORTING EQUIPMENT	57
ANI	NEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PART LIST	61
ANI	NEX E. DECLARATION OF SIMILARITY	62



Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 5 of 62

1 EXECUTIVE SUMMARY & EUT INFORMATION

The purpose of this test programme was to demonstrate compliance of the ABBA INNOVATION S.A.S, MOBILE PHONE and model: 5300 against the current Stipulated Standards. The MOBILE PHONE has demonstrated compliance with the FCC 15.247: 2012, ANSI C63.4: 2009.

EUT Information

EUT

: **MOBILE PHONE**

Description Main Model

5300

Serial Model

5130, A1, A2, A3, A5, A7, A6, A8

Antenna Gain

GSM850: 0.5 dBi PCS1900: 1 dBi

Bluetooth: 0 dBi

Adapter:

Model: 5300

Input: AC110-240V 50/60Hz 200mA

Input Power

Output: DC5.0V-500mA

Li-ion Battery:

Model:BL-5C

Voltage: 3.7V, 800mAh

Classification

Per Stipulated

Test Standard : FCC 15.247: 2012, ANSI C63.4: 2009

Revision Number	Report Number	Description of Revision	Date of Revision	
0	12070199-FCC-R2	Original Report	September 26, 2012	
1	13070052-FCC-R2	Amended Report	March 15, 2013	

Note1: This is the amended report application (13070052-FCC-R2) of the device, the original submission (12070199-FCC-R2) was granted on September 26, 2012. The differences between the original device and the current one were only changed the **applicant name**, **trade name**, **color** and **model name**. The **circuit** and **PCB LAYOUT** are all the same. All above were explained in the attached Declaration Letter.

Note2: The only difference between main model 5300 and serial modes in this report is the **model name**.



Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 6 of 62 www.siemic.com.cr

	2 TECHNICAL DETAILS
Purpose	Compliance testing of MOBILE PHONE with stipulated standard
Applicant / Client	ABBA INNOVATION S.A.S Calle 76 No. 52-40 Local 1,Alto Prado Barranquilla ,Colombia
Manufacturer	Movicom technology co., limited Room 1207 Zhan Tao Technology Bldg ,Long Hua Shenzhen ,China
Laboratory performing the tests	SIEMIC Nanjing (China) Laboratories NO.2-1,Longcang Dadao, Yuhua Economic Development Zone, Nanjing, China Tel:+86(25)86730128/86730129 Fax:+86(25)86730127 Email:info@siemic.com
Test report reference number	13070052-FCC-R2
Date EUT received	September 13, 2012
Standard applied	FCC 15.247: 2012, ANSI C63.4: 2009
Dates of test (from - to)	September 19 to September 25, 2012
No of Units	#1
Equipment Category	DSS
Trade Name	Taxcel, Airus
RF Operating Frequency (ies)	GSM850 TX : 824.2 ~ 848.8 MHz; RX :869.2 ~ 893.8 MHz PCS1900 TX : 1850.2 ~ 1909.8 MHz; RX :1930.2 ~ 1989.8 MHz Bluetooth: 2402-2480MHz
Number of Channels	299CH (PCS1900) and 124CH (GSM850) Bluetooth: 79 CH
Modulation	GSM / GPRS: GMSK Bluetooth: GFSK
FCC ID	Z87ABBA5300



Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 7 of 62

3 MODIFICATION

NONE

Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 8 of 62

www.siemic.com.cn

4 TEST SUMMARY

The product was tested in accordance with the following specifications. All testing has been performed according to below product classification:

Spread Spectrum System/Device

Test Results Summary

Test Standard	Description	Product Class	Pass / Fail
§15.247(i), §2.1093	RF Exposure	See Above	Pass
§15.203	Antenna Requirement	See Above	Pass
§15.207(a)	AC Line Conducted Emissions	See Above	Pass
§15.205, §15.209, §15.247(d)	Radiated Emissions	See Above	Pass
§15.247(a)(1)	20 dB Bandwidth	See Above	Pass
§15.247(a)(1)	Channel Separation	See Above	Pass
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	See Above	Pass
§15.247(a)(1)(iii)	Quantity of Hopping Channel	See Above	Pass
§15.247(b)(1)	Peak Output Power	See Above	Pass
§15.247(d)	Band Edge	See Above	Pass

Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page:

MEASUREMENTS, EXAMINATION AND DERIVED RESULTS

5.1 §15.247 (i) and §2.1093 – RF Exposure

Standard Requirement:

According to §15.247 (i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Table 2 - Summary of SAR Evaluation Requirements for a Cell Phone with Multiple Transmitters

	Individual Transmitter	Simultaneous Transmission
Licensed Transmitters Unlicensed Transmitters	$\begin{tabular}{ll} \hline \textbf{Routine evaluation required} \\ \hline \textbf{When there is no simultaneous transmission} - \\ \hline \textbf{0} & \textbf{output} \leq 60/\text{f: SAR not required} \\ \hline \textbf{0} & \textbf{output} \geq 60/\text{f: stand-alone SAR required} \\ \hline \textbf{When there is simultaneous transmission} - \\ \hline \textbf{Stand-alone SAR not required when} \\ \hline \textbf{0} & \textbf{output} \leq 2 \cdot P_{Ref} \text{ and antenna is } \geq 5.0 \text{ cm} \\ \hline \textbf{from other antennas} \\ \hline \textbf{0} & \textbf{output} \leq P_{Ref} \text{ and antenna is } \geq 2.5 \text{ cm from other antennas} \\ \hline \textbf{0} & \textbf{output} \leq P_{Ref} \text{ and antenna is } \leq 2.5 \text{ cm from other antennas}, \\ \hline \textbf{0} & \textbf{output} \leq P_{Ref} \text{ and antenna is } \leq 2.5 \text{ cm from other antennas}, \\ \hline \textbf{0} & \textbf{output} \leq P_{Ref} \text{ or } 1\text{-g SAR} \leq 1.2 \text{ W/kg} \\ \hline \hline \textbf{Otherwise stand-alone SAR is required} \\ \hline \hline \textbf{0} & \textbf{test SAR on highest output channel for each} \\ \hline \end{tabular}$	SAR not required: Unlicensed only o when stand-alone 1-g SAR is not required and antenna is ≥ 5 cm from other antennas Licensed & Unlicensed o when the sum of the 1-g SAR is < 1.6 W/kg for all simultaneous transmitting antennas o when SAR to peak location separation ratio of simultaneous transmitting antenna pair is < 0.3 SAR required: Licensed & Unlicensed antenna pairs with SAR to peak location separation ratio ≥ 0.3; test is only required for the configuration that results in the highest SAR in stand-alone configuration for each
	o test SAR on highest output channel for each wireless mode and exposure condition o if SAR for highest output channel is > 50% of SAR limit, evaluate all channels according to normal procedures	wireless mode and exposure condition Note: simultaneous transmission exposure conditions for head and body can be different for different style phones; therefore, different test requirements may apply
Jaw, Mouth and Nose	Flat phantom SAR required o when measurement is required in tight regions of SAM and it is not feasible or the results can be questionable due to probe tilt, calibration, positioning and orientation issues o position rectangular and clam-shell phones according to flat phantom procedures and conduct SAR measurements for these specific locations	When simultaneous transmission SAR testing is required, contact the FCC Laboratory for interim guidance.

Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page:

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

Two antennas are available for the EUT, (GSM antenna, and Bluetooth antenna).

BT and GSM Antenna separation is 8.0 cm>5 cm, and the maximum EIRP is 3.92mW<2Pref(24 mW). According to KDB 648474, no stand-alone required for BT

Test Result: Pass

The SAR measurement is exempt.

Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 11 of 62

5.2 §15.203 – Antenna Requirement

Standard Requirement:

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.
- c. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has 2 antennas, one is a monopole antenna for Bluetooth, the gain is 0 dBi; one is a PIFA antenna for GSM, the gain are 0.5 dBi for GSM and 1 dBi for PCS which in accordance to section 15.203, please refer to the internal photos.

Test Result: Pass

Note: the following test data please refer to report 12070199-FCC-R2.

Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 12 of 62

5.3 §15.207 (a) – AC Line Conducted Emissions

Standard Requirement:

	Conducted lin	Conducted limit (dBµV)			
Frequency of emission (MHz)	Quasi-peak	Average			
0.15–0.5	66 to 56*	56 to 46*			
0.5–5	56	46			
5–30	60	50			

^{*}Decreases with the logarithm of the frequency.

Procedures:

- 1. All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR and Average detectors, are reported. All other emissions were relatively insignificant.
- 2. A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
- 3. Conducted Emissions Measurement Uncertainty

 All test measurements carried out are traceable to nation
 - All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 9kHz 30MHz (Average & Quasi-peak) is $\pm 3.5dB$.

4. Environmental Conditions Temperature 22°C
Relative Humidity 50%
Atmospheric Pressure 1019mbar

5. Test date: September 19, 2012

Tested By : Alan Lv


Test Result: Pass

Note: the following test data please refer to report 12070199-FCC-R2.

Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 13 of 62

Test Mode: charging & GFSK transmitting





Test Data


Phase Line Plot at 120Vac, 60Hz

Frequency (MHz)	Quasi Peak (dBµV)	Limit (dBµV)	Margin (dB)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Factors (dB)
0.49	35.97	56.10	-20.13	30.85	46.10	-15.25	10.17
0.54	36.35	56.00	-19.65	31.03	46.00	-14.97	10.16
0.67	28.33	56.00	-27.67	23.51	46.00	-22.49	10.13
0.78	29.10	56.00	-26.90	23.79	46.00	-22.21	10.15
0.43	31.67	57.27	-25.60	26.11	47.27	-21.16	10.17
2.17	27.61	56.00	-28.39	19.34	46.00	-26.66	10.20

Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 14 of 62

www.siemic.com.cn

Test Mode: charging & GFSK transmitting



Test Data

Phase Neutral Plot at 120Vac, 60Hz

Frequency (MHz)	Quasi Peak (dBµV)	Limit (dBµV)	Margin (dB)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Factors (dB)
0.52	34.46	56.00	-21.54	29.06	46.00	-16.94	10.16
0.53	30.97	56.00	-25.03	26.29	46.00	-19.71	10.16
2.11	28.70	56.00	-27.30	19.85	46.00	-26.15	10.20
2.05	28.75	56.00	-27.25	19.69	46.00	-26.31	10.20
1.21	27.05	56.00	-28.95	21.87	46.00	-24.13	10.17
2.18	28.33	56.00	-27.67	19.45	46.00	-26.55	10.20

Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 15 of 62

5.4 §15.209, §15.205 & §15.247(d) - Spurious Emissions

- 1. All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR detectors, are reported. All other emissions were relatively insignificant.
- A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
- 3. Radiated Emissions Measurement Uncertainty

All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 1GHz (3m & 10m) & 1GHz above (3m) is +5.6/-4.5dB.

4. Environmental Conditions Temperature 22°C
Relative Humidity 50%
Atmospheric Pressure 1019mbar

5. Test date: September 19, 2012

Tested By: Alan Lv

Standard Requirement:

The emissions from the Low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges.


Test Result: Pass

Note: the following test data please refer to report 12070199-FCC-R2.

Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 16 of 62 www.siemic.com.cr

Test Mode: charging & GFSK transmitting

Below 1GHz



Test Data

Horizontal Polarity Plot @3m


11011201100110, 1100 000111							
Frequency (MHz)	Peak (dBuV/m)	Azimuth	Polarity (H/V)	Height (cm)	Factors (dB)	Limit (dBuV/m)	Margin (dB)
117.91	26.87	182.90	Н	200.00	-31.14	43.50	-16.63
158.40	25.72	192.70	Н	200.00	-32.24	43.50	-17.78
117.18	25.37	186.80	Н	200.00	-31.24	43.50	-18.13
912.58	27.70	0.30	Н	200.00	-20.54	46.00	-18.30
950.89	27.22	37.30	Н	100.00	-21.04	46.00	-18.78
959.38	26.78	218.10	Н	200.00	-20.69	46.00	-19.22

Note: Fast QP measurement performed, more than 10dB below limit so QP test data was not presented.

Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 17 of 62

Test Mode: charging & GFSK transmitting

Below 1GHz



Test Data

Vertical Polarity Plot @3m

, er erent i erent ty i i er erent							
Frequency (MHz)	Peak (dBuV/m)	Azimuth	Polarity (H/V)	Height (cm)	Factors (dB)	Limit (dBuV/m)	Margin (dB)
117.30	29.63	232.40	V	100.00	-31.09	43.50	-13.87
30.00	25.73	104.20	V	100.00	-20.43	40.00	-14.27
113.54	29.09	181.90	V	100.00	-31.57	43.50	-14.41
735.19	29.32	352.90	V	200.00	-19.86	46.00	-16.68
727.91	29.12	45.30	V	200.00	-20.21	46.00	-16.88
810.37	29.08	318.00	V	200.00	-18.91	46.00	-16.92

Note: Fast QP measurement performed, more than 10dB below limit so QP test data was not presented.

Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 18 of 62 www.siemic.com.cr

Test Mode: charging & GFSK transmitting

Above 1 GHz

Note: Other Bluetooth modes were verified; only the result of worst case DH5 mode was presented.

Low Channel (2402 MHz)

Frequen cy (MHz)	S.A. Reading (dBµV)	Detector (PK/AV)	Direction (degree)	Height (cm)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre- Amp. Gain (dB)	Cord. Amp. (dBµV/ m)	Limit (dBµV/ m)	Margin (dB)
4804	51.29	AV	142	120	V	32.7	8.17	55	37.16	54	-16.84
4804	71.26	PK	142	120	V	32.7	8.17	55	57.13	74	-16.87
2388	50.17	AV	76	140	V	30.1	7.2	55	32.47	54	-21.53
2388	69.71	PK	76	140	V	30.1	7.2	55	52.01	74	-21.99
4804	50.12	AV	142	130	Н	32.7	8.17	55	35.99	54	-18.01
4804	70.47	PK	142	130	Н	32.7	8.17	55	56.34	74	-17.66
2389	51.46	AV	273	110	Н	30.1	7.2	55	33.76	54	-20.24
2389	70.12	PK	273	110	Н	30.1	7.2	55	52.42	74	-21.58

Middle Channel (2441 MHz)

Frequen cy (MHz)	S.A. Reading (dBµV)	Detector (PK/AV)	Direction (degree)	Height (cm)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre- Amp. Gain (dB)	Cord. Amp. (dBµV/ m)	Limit (dBµV/ m)	Margin (dB)
4880	51.01	AV	132	150	V	32.8	9	55	37.81	54	-16.19
4880	70.19	PK	132	150	V	32.8	9	55	56.99	74	-17.01
7320	46.32	AV	193	140	V	35.6	11.16	55	38.08	54	-15.92
7320	61.72	PK	193	140	V	35.6	11.16	55	53.48	74	-20.52
4880	50.43	AV	154	110	Н	32.8	9	55	37.23	54	-16.77
4880	69.43	PK	154	110	Н	32.8	9	55	56.23	74	-17.77
7320	44.19	AV	193	120	Н	35.6	11.16	55	35.95	54	-18.05
7320	62.81	PK	193	120	Н	35.6	11.16	55	54.57	74	-19.43

High Channel (2480 MHz)

Frequen cy (MHz)	S.A. Reading (dBµV)	Detector (PK/AV)	Direction (degree)	Height (cm)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre- Amp. Gain (dB)	Cord. Amp. (dBµV/ m)	Limit (dBµV/ m)	Margin (dB)
4960	51.26	AV	152	150	V	32.9	10.16	55	39.32	54	-14.68
4960	68.25	PK	152	150	V	32.9	10.16	55	56.31	74	-17.69
2485	53.72	AV	215	130	V	30.6	7.2	55	36.52	54	-17.48
2485	67.49	PK	215	130	V	30.6	7.2	55	50.29	74	-23.71
4960	50.27	AV	94	120	Н	32.9	10.16	55	38.33	54	-15.67
4960	69.11	PK	94	120	Н	32.9	10.16	55	57.17	74	-16.83
2486	52.46	AV	193	140	Н	30.6	7.2	55	35.26	54	-18.74
2486	69.33	PK	193	140	Н	30.6	7.2	55	52.13	74	-21.87

Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 19 of 62

5.5 §15.247(a) (1)-Channel Separation

1. Conducted Measurement

EUT was set for low, mid, high channel with modulated mode and highest RF output power.

The spectrum analyzer was connected to the antenna terminal.

2. Environmental Conditions Temperature 22°C

Relative Humidity 50% Atmospheric Pressure 1019mbar

3. Conducted Emissions Measurement Uncertainty

All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30 MHz - 40 GHz is $\pm 1.5 dB$.

4. Test date: September 25, 2012

Tested By: Alan Lv

Standard Requirement:

According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Procedures:

- 1. Place the EUT on the table and set it in hopping function transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set center frequency of spectrum analyzer = middle of hopping channel.
- 4. Set the spectrum analyzer as Resolution (or IF) Bandwidth (RBW) ≥ 1% of the span, Video (or Average) Bandwidth (VBW) ≥ RBW, Sweep = auto, Detector function = peak, Trace = max hold.
- 5. Max hold, mark 2 peaks of hopping channel and record the 2 peaks frequency.

Test Result: Pass

Note: the following test data please refer to report 12070199-FCC-R2.

Test Mode: GFSK Transmitting


Channel	Channel Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)	Result
Low Channel	2402	1.000	0.699	Pass
Adjacency Channel	2403	1.000	*****	
Mid Channel	2440	1.000	0.693	Pass
Adjacency Channel	2441	1.000		1 435
High Channel	2480	1.000	0.699	Pass
Adjacency Channel	2479	1.000	0.099	1 433

Please refer to the following plots.

Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 20 of 62




Date: 25.SEP.2012 00:17:57



Date: 25.SEP.2012 00:19:22

Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 21 of 62



Date: 25.SEP.2012 00:20:40

Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 22 of 62

www.siemic.com.cn

§15.247(a) (1) – 20dB Bandwidth

1. Conducted Measurement

EUT was set for low, mid, high channel with modulated mode and highest RF output power.

The spectrum analyzer was connected to the antenna terminal.

2. Environmental Conditions Temperature 22°C Relative Humidity 50%

Atmospheric Pressure 1019mbar

3. Conducted Emissions Measurement Uncertainty

All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz - 40GHz is $\pm 1.5\text{dB}$.

4. Test date: September 25, 2012

Tested By: Alan Lv

Standard Requirement:

According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Procedures:

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set the spectrum analyzer as Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel, RBW ≥ 1% of the 20 dB bandwidth, VBW ≥ RBW, Sweep = auto, Detector function = peak, Trace = max hold.
- 4. Set the measured low, middle and high frequency and test 20dB bandwidth with spectrum analyzer.

Test Result: Pass


Note: the following test data please refer to report 12070199-FCC-R2.

Test Mode: GFSK Transmitting


Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
Low	2402	1.048
Middle	2441	1.040
High	2480	1.048

Please refer to the following plots.

Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 23 of 62




Date: 25.SEP.2012 00:15:08



Date: 25.SEP.2012 00:02:20

Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 24 of 62 www.siemic.com.cr



Date: 25.SEP.2012 00:04:35

Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 25 of 62

50%

1019mbar

5.6 §15.247(a) (1) (iii)-Number of Hopping Channels

1. Conducted Measurement

EUT was set for low, mid, high channel with modulated mode and highest RF output power.

The spectrum analyzer was connected to the antenna terminal.

2. Conducted Emissions Measurement Uncertainty

All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30 MHz - 40 GHz is $\pm 1.5 dB$.

3. Environmental Conditions

Temperature
Relative Humidity
Atmospheric Pressure

4. Test date: September 24, 2012

Tested By: Alan Lv

Standard Requirement:

According to §15.247(a)(1)(iii), Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.

Procedures:

- 1. Place the EUT on the table and set it in hopping function transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set the spectrum analyzer as Start=2400MHz, Stop = 2483.5MHz, Span = the frequency band of operation, RBW ≥1% of the span, VBW ≥ RBW, Sweep = auto, Detector function = peak, Trace = max hold.
- 4. Count the quantity of peaks to get the number of hopping channels.

Test Result: Pass

Note: the following test data please refer to report 12070199-FCC-R2.


Test Mode:	Hopping Mode With GFSK Modulation
------------	-----------------------------------

Frequency Range (MHz)	Number of Hopping Channels	Limit	
2400-2483.5	79	≥15	

Please refer to following tables and plots

Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 26 of 62 www.siemic.com.cr

Number of Hopping Channels



Date: 24.SEP.2012 23:55:46

Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 27 of 62

5.7 §15.247(a) (1) (iii) -Time of Occupancy (Dwell Time)

1. Conducted Measurement

EUT was set for low, mid, high channel with modulated mode and highest RF output power.

The spectrum analyzer was connected to the antenna terminal.

2. Conducted Emissions Measurement Uncertainty

All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz - 40GHz is $\pm 1.5dB$.

3. Environmental Conditions

Temperature 22°C
Relative Humidity 50%
Atmospheric Pressure 1019mbar

4. Test date: September 25, 2012

Tested By: Alan Lv

Standard Requirement:

According to §15.247(a)(1)(iii), The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Procedures:

- 1. Place the EUT on the table and set it in transmitting mode and switch on frequency hopping function.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set the spectrum analyzer as Span = zero span, centered on a hopping channel, RBW=1MHz, VBW ≥ RBW, Sweep = as necessary to capture the entire dwell time per hopping channel, Detector function = peak, Trace = max hold.
- 4. Calculate the time of occupancy in a period with time occupancy of a burst and quantity of bursts.

Test Result: Pass


Note: the following test data please refer to report 12070199-FCC-R2.

Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 28 of 62 www.siemic.com.cr

Test Mode: Hopping Mode With GFSK Modulation

Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result		
	Low	0.430	0.13760	0.4	Pass		
DH 1	Middle	0.430	0.13760	0.4	Pass		
DILI	High	0.430	0.13760	0.4	Pass		
	<i>Note:</i> Dwell time=Pulse time (ms) × $(1600 \div 2 \div 79) \times 31.6$ Second						
	Low	1.730	0.27680	0.4	Pass		
DH 3	Middle	1.710	0.27360	0.4	Pass		
DH 3	High	1.710	0.26360	0.4	Pass		
	<i>Note:</i> Dwell time=Pulse time (ms) × $(1600 \div 4 \div 79) \times 31.6$ Second						
	Low	2.970	0.31680	0.4	Pass		
DH 5	Middle	2.970	0.31680	0.4	Pass		
DH 5	High	2.970	0.31680	0.4	Pass		
	Note: Dwell	time=Pulse Time (m	$(1600 \div 6 \div 6)$	79) ×31.6 Sec	cond		


Please refer to the following plots.




Date: 25.SEP.2012 00:33:43

Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 29 of 62

Middle Channel for DH1




Date: 25.SEP.2012 00:35:33



Date: 25.SEP.2012 00:36:49


Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 30 of 62

Low Channel for DH3



Date: 25.SEP.2012 00:31:37

Middle Channel for DH3



Date: 25.SEP.2012 00:30:53

%

10


-20--30-

-40--50-

-90

Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 31 of 62

MUNUM




Center 2.48 GHz 1 ms/

Date: 25.SEP.2012 00:30:00

hey who have who


Low Channel for DH5 RBW 1 MHz *VBW 3 MHz 10 dBm



Date: 25.SEP.2012 00:26:11


Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 32 of 62

Middle Channel for DH5



Date: 25.SEP.2012 00:27:21

High Channel for DH5



Date: 25.SEP.2012 00:28:25

Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 33 of 62

5.8 §15.247(b) (1) - Peak Output Power

1. Conducted Measurement

EUT was set for low, mid, high channel with modulated mode and highest RF output power.

The spectrum analyzer was connected to the antenna terminal.

2. Conducted Emissions Measurement Uncertainty

All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz - 40GHz is $\pm 1.5\text{dB}$.

3. Environmental Conditions

Temperature 22°C
Relative Humidity 50%
Atmospheric Pressure 1019mbar

4. Test date: September 25, 2012

Tested By: Alan Lv

Standard Requirement:

According to §15.247(b)(2), For frequency hopping systems in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5MHz band: 0.125watts.

Procedures:

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set the spectrum analyzer as Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel, RBW > the 20 dB bandwidth of the emission being measured, VBW ≥ RBW, Sweep=auto, Detector function=peak, Trace = max hold.
- 4. Then set the EUT to transmit at low, middle and high channel and measure the conducted output power separately.

Test Result: Pass

Note: the following test data please refer to report 12070199-FCC-R2.

Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 34 of 62

www.siemic.com.cn

Test Mode: GFSK Transmitting

Channel	Channel frequency (MHz)	Peak output power (dBm)	Power output (mW)	Limit (mW)
Low channel	2402	5.47	3.52	125
Middle channel	2441	5.78	3.78	125
High channel	2480	5.93	3.92	125

Please refer to the following plots.


Note: The data above was tested in conducted mode.




Date: 25.SEP.2012 00:22:49

Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 35 of 62

Middle Channel



Date: 25.SEP.2012 00:22:10



Date: 25.SEP.2012 00:21:41

Report No: 13070052-FCC-R2
Issue Date: March 15, 2013
Page: 36 of 62
www.siemic.com.cn

5.9 §15.247(d) - Band Edge

Standard Requirement:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Procedures:

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
- 3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, for Radiated emissions restricted band RBW=1MHz, VBW=3MHz.
- 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- 5. Repeat above procedures until all measured frequencies were complete.

Test Result: Pass


Note: the following test data please refer to report 12070199-FCC-R2.

Test Mode:	GFSK Transmitting
------------	-------------------


Frequency (MHz)	Delta Peak to Band Emission (dBc)	Limit (dBc)	
2399.78	49.61	20	
2484.12	46.10	20	

Note: The point fall into the strict band was recorded in FCC 15.209, please refer to the restrict band testing.

Issue Date: March 15, 2013 Page: 37 of 62 Page:



Date: 25.SEP.2012 00:16:01



Date: 25.SEP.2012 00:12:56

Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 38 of 62

www.siemic.com.cn

Radiated Band Edge Measurements

Distance of Measurements: 3 Meters
Operating Frequency: 2402MHz

Frequency (MHz)	S.A. Reading (dBµV)	Detector (PK/AV)	Direction (degree)	Height (cm)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre- Amp. Gain (dB)	Cord. Amp. (dBµV/m)	Limit (dBμV/m)	Margin (dB)
2399.77	58.12	AV	124	127	V	28.5	0.5	55	32.12	54	-19.24
2399.77	75.63	PK	124	127	V	28.5	0.5	55	49.63	54	-17.59
2399.77	60.24	AV	115	152	Н	28.5	0.5	55	34.24	74	-23.36
2399.77	74.58	PK	115	152	Н	28.5	0.5	55	48.58	74	-22.21

Distance of Measurements: 3 Meters
Operating Frequency: 2480MHz

Frequency (MHz)	S.A. Reading (dBµV)	Detector (PK/AV)	Direction (degree)	Height (cm)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre- Amp. Gain (dB)	Cord. Amp. (dBµV/m)	Limit (dBµV/m)	Margin (dB)
2484.12	60.46	AV	112	121	V	28.7	0.7	55	38.46	54	-19.14
2484.12	59.79	PK	112	121	V	28.7	0.7	55	50.19	54	-23.81
2484.12	59.72	AV	120	145	Н	28.7	0.7	55	34.12	74	-19.88
2484.12	74.93	PK	120	145	Н	28.7	0.7	55	49.33	74	-24.67

Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 39 of 62

Annex A. TEST INSTRUMENT & METHOD


Annex A.i. TEST INSTRUMENTATION & GENERAL PROCEDURES

Instrument	Model	Serial #	Calibration Date	Calibration Due Date
AC Line Conducted Emissions				
R&S EMI Test Receiver	ESPI3	101216	08/26/2012	08/25/2013
Com-Power LISN	LI-115	241090	05/26/2012	05/25/2013
Com-Power Transient Limiter	LIT-153	531021	05/26/2012	05/25/2013
Universal Radio Communication Tester	CMU200	104031	03/01/2012	02/28/2013
A- INFOMW Antenna	JXTXLB-	J2031081120	06/25/2012	06/24/2013
(1~18GHz)	10180	092		
Radiated Emissions	05625	2021 4 00022	01/10/2012	01/00/2012
Hp Spectrum Analyzer	8563E	3821A09023	01/10/2012	01/09/2013
R&S EMI Receiver	ESPI3	101216	08/26/2012	08/25/2013
Antenna (30MHz~6GHz)	JB6	A121411	12/28/2011	12/27/2012
ETS-Lindgren Antenna(1 ~18GHz)	3115	N/A	10/04/2011	10/03/2012
A- INFOMW Antenna (1~18GHz)	JXTXLB- 10180	J2031081120 092	06/25/2012	06/24/2013
Horn Antenna (18~40GHz)	AH-840	N/A	07/23/2012	07/22/2013
Microwave Pre-Amp (18~40GHz)	PA-840	N/A	Every 2000 Hours	
Hp Agilent Pre-Amplifier	8447F	1937A01160	05/26/2012	05/25/2013
MITEQ Pre-Amplifier	AMF-7D-			
$(0.1 \sim 18 \text{GHz})$	00101800-	1451710	05/26/2012	05/25/2013
, ,	30-10P			
Universal Radio Communication Tester	CMU200	104031	03/01/2012	02/28/2013
Chamber	3m	N/A	04/13/2012	04/12/2013

Annex A.ii. CONDUCTED EMISSIONS TEST DESCRIPTION

Test Set-up

- 1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table, as shown in <u>Annex B</u>.
- 2. The power supply for the EUT was fed through a $50\Omega/50\mu$ H EUT LISN, connected to filtered mains.
- 3. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss coaxial cable.
- 4. All other supporting equipments were powered separately from another main supply.



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration1.

Test Method

- 1. The EUT was switched on and allowed to warm up to its normal operating condition.
- 2. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver.
- 3. High peaks, relative to the limit line, were then selected.
- 4. The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz. For FCC tests, only Quasi-peak measurements were made; while for CISPR/EN tests, both Quasi-peak and Average measurements were made.
- 5. Steps 2 to 4 were then repeated for the LIVE line (for AC mains) or DC line (for DC power).

Description of Conducted Emission Program

This EMC Measurement software run LabView automation software and offers a common user interface for electromagnetic interference (EMI) measurements. This software is a modern and powerful tool for controlling and monitoring EMI test receivers and EMC test systems. It guarantees reliable collection, evaluation, and documentation of measurement results. Basically, this program will run a pre-scan measurement before it proceeds with the final measurement. The pre-scan routine will run the common scan range from 150 kHz to 30 MHz; the program will first start a peak and average scan on selectable measurement time and step size. After the program complete the pre-scan, this program will perform the Quasi Peak and Average measurement, based on the pre-scan peak data reduction result.

Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 41 of 62

Sample Calculation Example

At 20 MHz $limit = 250 \mu V = 47.96 dB\mu V$

Transducer factor of LISN, pulse limiter & cable loss at 20 MHz = 11.20 dB

Q-P reading obtained directly from EMI Receiver = $40.00 \text{ dB}\mu\text{V}$

(Calibrated for system losses)

i.e. 7.96 dB below limit Therefore, Q-P margin = 47.96 - 40.00 = 7.96

Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 42 of 62

Annex A. iii. RADIATED EMISSIONS TEST DESCRIPTION

Limit

1. Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (mV/m)	Measurement Distance (m)	
30-88	100*	3	
88-216	150*	3	
216-960	200*	3	
Above 960	500	3	

Remark: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

2. In the above emission table, the tighter limit applies at the band edges.

Frequency (Hz)	Field Strength (μV/m at 3-meter)	Field Strength (dBµV/m at 3-meter)	
30-88	100	40	
88-216	150	43.5	
216-960	200	46	
Above 960	500	54	

EUT Characterisation


EUT characterisation, over the frequency range from 30MHz to 10th Harmonic, was done in order to minimise radiated emissions testing time while still maintaining high confidence in the test results.

The EUT was placed in the chamber, at a height of about 0.8m on a turntable. Its radiated emissions frequency profile was observed, using a spectrum analyzer /receiver with the appropriate broadband antenna placed 3m away from the EUT. Radiated emissions from the EUT were maximised by rotating the turntable manually, changing the antenna polarisation and manipulating the EUT cables while observing the frequency profile on the spectrum analyzer / receiver. Frequency points at which maximum emissions occurred, clock frequencies and operating frequencies were then noted for the formal radiated emissions test at the Open Area Test Site (OATS) or 3m EMC chamber.



Test Set-up

- 1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m X 1.0m X 0.8m high, non-metallic table.
- 2. The filtered power supply for the EUT and supporting equipment were tapped from the appropriate power sockets located on the turntable.
- 3. The relevant broadband antenna was set at the required test distance away from the EUT and supporting equipment boundary.



Test Method

The following procedure was performed to determine the maximum emission axis of EUT:

- 1. With the receiving antenna is H polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
- 2. With the receiving antenna is V polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
- 3. Compare the results derived from above two steps. So, the axis of maximum emission from EUT was determined and the configuration was used to perform the final measurement.

Final Radiated Emission Measurement

- 1. Setup the configuration according to figure 1. Turn on EUT and make sure that it is in normal function.
- 2. For emission frequencies measured below 1 GHz, a pre-scan is performed in a shielded chamber to determine the accurate frequencies of higher emissions will be checked on an open test site. As the same purpose, for emission frequencies measured above 1 GHz, a pre-scan also be performed with a 1 meter measuring distance before final test.
- 3. For emission frequencies measured below and above 1 GHz, set the spectrum analyzer on a 100 kHz and 1 MHz resolution bandwidth respectively for each frequency measured in step 2.
- 4. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from $0 \circ to 360 \circ with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading.$
- 5. Repeat step 4 until all frequencies need to be measured was complete.
- 6. Repeat step 5 with search antenna in vertical polarized orientations.

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth	
30 to 1000	Peak	100 kHz	100 kHz	
Above 1000	Peak	1 MHz	1 MHz	
Above 1000	Average	1 MHz	10 Hz	

Description of Radiated Emissions Program

This EMC Measurement software run LabView automation software and offers a common user interface for electromagnetic interference (EMI) measurements. This software is a modern and powerful tool for controlling and monitoring EMI test receivers and EMC test systems. It guarantees reliable collection, evaluation, and documentation of measurement results. Basically, this program will run a pre-scan measurement before it proceeds with the final measurement. The pre-scan routine will run the scan on four different antenna heights, 2 antenna polarity, and 360 degrees table rotation. For example, the program was set to run 30 MHz to 1 GHz scan; the program will first start from a meter antenna height and divide the 30 MHz to 1 GHz into 10 separate parts of maximum hold sweeps. Each parts of maximum hold sweep, the program will collect the data from 0 degree to 360 degrees table rotation. After the program complete the 1m scan, the antenna continues to rise to 2m and continue the scan. The step will repeated for all specified antenna height and polarity. This program will perform the Quasi Peak measurement after the signal maximization process and pre-scan routine. The final measurement will be base on the pre-scan data reduction result.

Sample Calculation Example

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. For the limit is employed average value, therefore the peak value can be transferred to average value by subtracting the duty factor. The basic equation with a sample calculation is as follows:

Peak = Reading + Corrected Factor

where

Corr. Factor = Antenna Factor + Cable Factor - Amplifier Gain (if any)

And the average value is

Average = Peak Value + Duty Factor or Set RBW = 1MHz, VBW = <math>10Hz.

If the measured frequencies are fall in the restricted frequency band, the limit employed must be quasi peak value when frequencies are below or equal to 1 GHz. And the measuring instrument is set to quasi peak detector function.

Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 45 of 62

Annex B. EUT AND TEST SETUP PHOTOGRAPHS

Annex B.i. Photograph 1: EUT External Photo



EUT – The Whole Package View



Adapter - Front View



Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 46 of 62




EUT - Front View



EUT - Rear View



Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 47 of 62



EUT - Top View



EUT - Bottom View



Report No: 13070052-FCC-R2
Issue Date: March 15, 2013
Page: 48 of 62



EUT - Left View



EUT - Right View

Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 49 of 62

Annex B.ii. Photograph 2: EUT Internal Photo



Cover Off - Top View



Cover Off - Bottom View

SIEMIC, INC.

Accessing global markets

Title: RF Test Report for MOBILE PHONE
Main Model: 5300
Serial Model: 5130, A1, A2, A3, A5, A7, A6, A8
To: FCC 15.247: 2012, ANSI C63.4: 2009

Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 50 of 62

1/AXCEL
5300 800mAh

20 INCH 1 2 3 3 64

Battery - Top View




Battery - Bottom View

SIEMIC, INC.
Accessing global markets

Title: RF Test Report for MOBILE PHONE
Main Model: 5300
Serial Model: 5130, A1, A2, A3, A5, A7, A6, A8
To: FCC 15.247: 2012, ANSI C63.4: 2009

Report No: 13070052-FCC-R2
Issue Date: March 15, 2013
Page: 51 of 62



LCD - Top View




LCD - Bottom View


SIEMIC, INC.
Accessing global markets

Title: RF Test Report for MOBILE PHONE
Main Model: 5300
Serial Model: 5130, A1, A2, A3, A5, A7, A6, A8
To: FCC 15.247: 2012, ANSI C63.4: 2009

Report No: 13070052-FCC-R2
Issue Date: March 15, 2013
Page: 52 of 62




Uncover - Front View




Uncover - Rear View



Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 53 of 62




Uncover without LCD - Top View




Uncover Without Shielding - Top View



Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 54 of 62



GSM Antenna - Top View



Bluetooth Antenna - Top View

Bluetooth Antenna

Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 55 of 62

Annex B.iii. Photograph 3: Test Setup Photo




Conducted Emissions Test Setup Front View




Conducted Emissions Test Setup Side View

Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 56 of 62 www.siemic.com.cr



Radiated Spurious Emissions Test Setup Below 1GHz - Front View



Radiated Spurious Emissions Test Setup Above 1GHz - Front View

Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 57 of 62

Annex C. TEST SETUP AND SUPPORTING EQUIPMENT


EUT TEST CONDITIONS

Annex C. i. SUPPORTING EQUIPMENT DESCRIPTION


The following is a description of supporting equipment and details of cables used with the EUT.

Manufacturer	Equipment Description (Including Brand Name)	Model	Calibration Date	Calibration Due Date
A-INFOMW	Horn Antenna	JXTXLB-10180	06/25/2012	06/24/2013
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	03/01/2012	02/28/2013

Block Configuration Diagram for Conducted Emissions



Block Configuration Diagram for Radiated Emissions



Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 60 of 62

www.siemic.com.cn

Annex C.ii. EUT OPERATING CONDITIONS

The following is the description of how the EUT is exercised during testing.

Test	Description Of Operation		
Emissions Testing	The EUT was continuously transmitting to stimulate the worst case.		

Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 61 of 62

Annex D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PART **LIST**

Please see attachment

Report No: 13070052-FCC-R2 Issue Date: March 15, 2013 Page: 62 of 62

Annex E. DECLARATION OF SIMILARITY

ABBA INNOVATION S.A.S

To: SIEMIC ,2206 Ringwood Avenue, San Jose, C, USA

Declaration letter

Dear Sir,

We declare that there is no electrical change has been made to the equipment that alters the compliance characteristics. The difference between model 5300, 5130, A1, A2, A3, A5, A7, A6, A8 and original model 5130 in the report 12070199 which was granted by SIEMIC are different logo and color.

Thank you!

Thank you!

Signature:

Printed name/title: Ernesto / Manager

Tel: +86-13823375673 Fax: 0755-83496050

Address: Calle 76 No. 52-40 Local 1, Alto Prado Barranquilla , Colombia