

# INTERTEK TESTING SERVICES

---

## RF Exposure

The equipment under test (EUT) is a Wireless Subwoofer with 2.4GHz function operating in 2402-2481MHz. The EUT is powered by AC 100-240V~50/60Hz. For more detail information pls. refer to the user manual.

### 2.4G:

Modulation Type: GFSK

Antenna Type: Integral antenna

Antenna Gain: 1.7dBi (This information is provided by applicant, and the applicant is responsible for the authenticity of the provided information.)

The nominal radiated output power (e.i.r.p) specified: -1dBm ( Tolerance: +/- 2dB)

The nominal conducted output power specified: -2.7dBm ( Tolerance: +/- 2dB)

According to the KDB 447498 D04 V01:

The maximum peak radiated emission for the EUT is 93.7dB $\mu$ V/m at 3m in the frequency 2481MHz

The EIRP = [(FS\*D) ^2 / 30] mW = -1.53dBm  
which is within the production variation.

The minimum peak radiated emission for the EUT is 93.0dB $\mu$ V/m at 3m in the frequency 2402MHz

The EIRP = [(FS\*D) ^2 / 30] mW = -2.23dBm  
which is within the production variation.

According to FCC Part 2.1091, this unlicensed transmitting devices is categorically excluded from routine environmental evaluation for RF exposure prior to equipment authorization or use, According to the KDB 447498 D04 V01 and OET 65, the simple calculation as below:

The source-based time averaged maximum radiated power = -1dBm+2dB= 1dBm = 1.26mW

The maximum ERP= -1dBm+2dB-2.15dB= -1.15dBm= 0.77mW

At the distance (R) of 20cm to 40cm and in 0.3 GHz to 6 GHz, ERP Exclusion Threshold Level:

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

The ERP Threshold is 3060mW for general population and uncontrolled exposure in the 2.4GHz frequency range according to FCC Part 1.1307. As the maximum ERP at 20cm from the transmitter is lower than the ERP Threshold, the compliance to the ERP Threshold can be ensured by indicating the minimum 20cm separation between the transmitter's radiating structure and body of the user or nearby persons.

The following RF exposure statement or similar sentence is proposed to be included in the user manual:

"FCC RF Radiation Exposure Statement Caution: This Transmitter must be installed to provide a separation distance of at least 20 cm from all persons."