

Testing Report




Customer Name: SHENZHEN SHIXIN ZHONGXIN TECHNOLOGY CO., LTD

Product Name: Antenna

Sample Model: RSR-XZX-2T-5.8G-TX

Reference Standard: GB/T9410-2008; ANSI/IEEE Std 149-1979

Issue Date: 2024.04. 28

Engineer:		Date: 2024.04. 28
Auditor:		Date: 2024.04. 28
Approver:		Date: 2024.04. 28

1. General Information

1.1 General Information of testing institutions


Name	Shenzhen Hetuo Technology Co., Ltd.
Address	Room 1202 B, Building C6, Hengfeng Industrial City, Xixiang, Baoan District, Shenzhen
Tel	18665849001
E-mail	18665849001@163.com
Equipment	Agilent 5071C

1.2 Testing principle


2. Test System

Multi-probe OTA Measurement System


Gain & Efficiency	Gain & Efficiency	SATIMO Agilent 5071C
-------------------	-------------------	-------------------------




Antenna Photo & Length(mm)_ANT1: PCB antenna




Antenna Photo & Lenght(mm)_ANT2:Stainless steel antenna



Antenna Photo & Lenght(mm)_ANT3:Stainless steel antenna



Antenna Photo & Lenght(mm)_ANT4:PCB antenna




1.3 Test equipment

Equipment	Model No.	Serial No.	Manufacturer	Calibration date	Next calibration date
24 probe microwave chamber	4*3*3	NA	SATIMO	2024.03.29	2024.04.29
Network Analyzer	5071C	NA	Agilent	2024.03.29	2024.04.29

1.4 Test environment

Temperature	24 C± 1.5 C
Humidity	45%RH
Pressure	101kPa

1.5 Brief summary of Procedure



1. SATIMO turn on the Upper Computer Software, Name: VeryView99.exe, Version No.: V1.10;
2. VeryView99 via GPIB (General Purpose Interface Bus) to control the shielding room (darkroom)'s SATIMO;
3. Meanwhiel, GPIB control the Agilent 5071C to read the Antenna data by 24 Probe;
4. Agilent 5071C will analyse the data and generate the result;
5. Agilent 5071C will feedback to VeryView99 software to generate the test report.

2. Sample Information


2.1 Client information

Name	SHENZHEN SHIXINZHONGXIN TECHNOLOGY .CO.,LTD
Address	A1 , Shajing Donghuan Industrial Zone , Bao 'an District , Shenzhen
Contacts	Ma Chao
Tel	18218809918
E-mail	machao@c- chip. com. cn


2.2 Description of EUT(S)

Product Name	5.2G/5.8G Antenna
Sample Model	RSR-XZX-2T-5.8G-TX
Antenna Size	ANT1:5.4*7.3mm
	ANT2:12.9*8.1mm
	ANT3:6.0*5.8mm
	ANT4:8.7*5.8mm
Antenna Type	PCB/ Stainless steel antenna
Serial No.	/
Test Item	Antenna Gain, Radiation pattern
Frequency Range	5155-5245MHz 5730-5848MHz
Received Date	2024.04.28
Test Date	2024.04. 28
Remark	The length of the RF cable is 50mm


The test photos




5155.0MHz H+V, Eff: 38.8%




Back View




5200.0MHz H+V, Eff: 30.3%




Back View



5245.0MHz H+V, Eff: 30.3%







Back View







深圳市合拓科技有限公司

[illegible]


5155.0MHz H+V, Eff: 34.5%




Back View




5200.0MHz H+V, Eff: 31.3%




Back View



5245.0MHz H+V, Eff: 27.9%




Back View




[illegible]


5730.0MHz H+V, Eff: 24.4%




Back View




5789.0MHz H+V, Eff: 42.4%




Back View




5848.0MHz H+V, Eff: 31.1%




Back View




5730.0MHz H+V, Eff: 32.3%




Back View




5789.0MHz H+V, Eff: 45.8%



Back View



5848.0MHz H+V, Eff: 37.3%



Back View

